AD



### I HNICA BOOK OF THE

USA-BRDEC-TR // 2513

## Detailed Inventory of Electric Power Consuming Devices Utilized in Tactical Systems I

94-14518

by James P. Lucas

Report Date March 1992



Distribution unlimited; approved for public release.

194 5' 16 027

DITC QUALITY INCRECTED 1



United States Army
Belvoir Research, Development and Engineering Center
Fort Belvoir, Virginia 22030-5586

Destroy this report when it is no longer needed. Do not return it to the originator.

The citation in this report of trade names of commercially available products does not constitute official endorsement or approval of the use of such products.

#### **REPORT DOCUMENTATION PAGE**

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is collected to excress. I hour per response, including the time for reviewing instructions, exceeding data accurace, gathering and excitating the data revoked and excepting and reviewing the collection of information, including augmentures the reviewing this burden, to Washington Headquarters Service, Observice of Information Operations and Reports, 1215 Julieseen Davids Highway, 8xto 1204, Adington, W. 20202-1302, and to the Office of Management and Budget Reduction Project (9704-9140).

Washington, DC 20003.

Headquerters Service, Obestian of Information Oper Washington, DC 20803.	rations and Reports, 121	5 Jallarean Davis Highway, Sulle	lo 1204, Adington, '	W. 20202-4302, and to 1	he Olice of Manage	ment and Budget Reduction Project (6704-6186),
1. AGENCY USE ONLY (Leave blank)		. REPORT DATE		. REPORT TYPE	AND DATES	COVERED
		March 1992	2	Final	Oct	ober 1988 to December 1990
4. TITLE AND SUBTITLE					5. FUNDIN	G NUMBERS
Detailed Inventory of Elec	tric Power Co	ensuming Devices	8			
Utilized in Tactical System	ıs I (U)					
6. AUTHOR(S)						
James P. Lucas						
7. PERFORMING ORGANIZATION NA	• •	• •			8. PERFOR	MING ORGANIZATION T NUMBER
Belvoir Research, Develop Logistics Equipment Direc	ment & Engu tocate	neering Center				
Environmental Control & S Fort Belvoir, VA 22060-56	Systems Supp	ort Division, STR	RBE-FEA			2518
9. SPONSORING/MONITORING AGEN	ICY NAME(8) AN	D ADDRESS(ES)	<del></del>			ORINGAIONITORING
					AGENC	Y REPORT NUMBER
11. SUPPLEMENTARY NOTES		······································	<del></del>			
POC: James P. Lucas, (70	03) 704-1993					
12a. DISTRIBUTION/AYAILABILITY ST	TATEMENT		12b. DISTR	RIBUTION CODE		
750° 4. 74. 44° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4. 48° 4.						
Distribution unlimited; app	proved for pu					
13. ABSTRACT (Meximum 200 words	)	·		·····		
This report presents a listing	of individual	power consumer	rs used in	the 401 Army	y Sets, Kits	, and Outfits (SKOs)
allowing both Table of Orga	nization & Ec	quipment (10&E)	) Develop	ers and Syste	m Develop	ers to identify power needs
of cellocated systems, provi	_		ring powe	r. Also, the e	ffectivenes	s of tactical power provided
to support predecessor equip	oment is now	auditable.				
,						
14. SUBJECT TERMS						15. NUMBER OF PAGES
electric power	power consu	•	wer datab	ase		175
tactical power	tactical syste	ems				16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY OF THIS P	CLASSIFICATION		RITY CLASSIFIC	ATION	29. LIMITATION OF ABSTRACT
Unclassified	Unclass	•••	1	lassified		Unlimited
<u> </u>	L					I

#### Report Number 2518

# Detailed Inventory of Electric Power Consuming Devices Utilized in Tactical Systems I

by

James P. Lucas



US Army Belvoir RD&E Center Fort Belvoir, Virginia 22060-5606

**March 1992** 


Distribution unlimited; approved for public release.

#### **Preface**

able of Organization and Equipment (TO&E) Developers need to identify areas where electric power can be shared. System Developers must evaluate their previously fielded equipment and systems before launching any update programs.

However, equipment power consumption information is sketchy at best. The Belvoir Generator Allocation Program (BGAP) contains tabulated data on 1,110 power consumers including 401 Sets, Kits, and Outfits (SKOs), with multiple power consuming items for which only lump-sum power usage is reported.

Through cooperative effort, many of these SKOs now are being located, inventoried, and analyzed, with first priority on analyzing systems with high power requirements. A detailed power consumption breakout and cross reference data on equipment with major power demand are contained in this report. The report will be revised under the same title as new information becomes available.



#### **Table of Contents**

		age
Section I	Procedure	1
Section II	Results	2
Section III	Discussion	3
Section IV	Conclusions	4
Section V	Plans	4
Appendix	Sets, Kits, and Outfits (SKOs) by Line Item Number	<b>A-1</b>
Tables		
1	Shelter Systems with Environmental Control (by Line Item Number)	9
2	Shelter Systems without Environmental Control (by Line Item Number)	79
3	Tool Sets and Systems without Shelters (by Line Item Number)	107
fleuisi.	•	
# <b>\$128</b>	Histogram: Types of Consumers (Distribution of Shelter Systems)	5
2	Histogram: Types of Consumers (Distribution of Shelters by Consumer)	6
3	Joint Electronics Designation Systems	7
	· · · · · · · · · · · · · · · · · · ·	

#### Section I

#### **Procedure**

he Belvoir RD&E Center's Environmental Control and Systems Support Division, Systems Assessment Team, used the U.S. Army Troop Support Command's Sample Data Collection Program to gather detailed power consumption information on a number of Sets, Kits, and Outfits (SKOs). The Belvoir Generator Allocation Program (BGAP) produced the SKO list (see Appendix). The Sample Data Collection Program at Fort Bragg, NC, inventoried their electrical equipment and reviewed maintenance and operating manuals to confirm the inventory and provide information on unavailable components.

While completing the Fort Bragg inventory, the Program queried other bases involved in the Data Collection project. As each base responds, a physical inventory of additional SKOs will be compiled.

#### Section II

#### **Results**

f the SKOs inventoried, 66 were environmentally controlled shelter systems, 25 were shelter systems without environmental control, and 23 were collections of power consuming tools and equipment not housed within a shelter. Table 1 contains the inventory data on individual power consuming equipment within the environmentally controlled systems. Table 2 has similar data for the tool sets and shelters without environmental control, and Table 3 lists such data for tool sets and systems without shelters. In each case, the systems are listed in order by Line Item Number.

Figure 1 shows a histogram of the types of power consuming equipment found within the SKOs. Two-thirds of these contain 15 or fewer types of power consuming devices. Less than a half dozen systems have over 30 types of power consumer equipment.

Many of these power consuming items are duplicated within a system. Figure 2 shows the number of power consuming items within the inventoried SKOs. Two-thirds of these have 30 or fewer items that consume power. Only a half dozen systems contain more than 70 power consumers. These histograms show that tactical systems can operate effectively with a power supply sized to support the equipment which operates simultaneously.

Figure 3 provides the translation from SKO model number to mission. An example is provided to show how the model number describes the installation, equipment type, and mission purpose of the tactical system.

#### Section III

#### **Discussion**

System designers often assumed their equipment would operate autonomously on the battlefield, without regard to support, housing, feeding, or ancillary equipment. Now, with the Training and Doctrine Command's (TRADOC's) emphasis on power for the total mission—for task forces of collocated troops—new designs need to take advantage of overlapping and non-concurrent electrical power demand.

Optimizing power generation equipment for each task force requires detailed electrical load data. It allows TRADOC to use BGAP with maximum precision and establish the best generator set for each field task force.

System developers now have access to current data when existing components are used in new systems. Developers can determine which equipment's power demands are highest when down-sizing equipment. Operators can better control contingencies which require reduced generator set demand.

#### Section IV

#### **Conclusions**


etermining power consumption by collocated troops requires detailed power data. Only detailed analysis can assure adequate power, identify opportunities for contingency mission operations, provide battle damage and repair assessments, and assure "limp-home" capability. For example, battlefield systems must respond to fuel shortages due to delayed refueling venicles and limited capability to transport extra fuel. By understanding the sensitivity of generator set fuel consumption to power use and knowing the power demands of each equipment item, troops will handle these contingencies more effectively.

#### **Section V**

#### **Plans**

ach of the SKOs with significant power consumption will be inventoried in detail, and each power consumer's requirements will be determined. This information will be entered into a database designed to link each element with its system(s). When queried about an SKO, the database will list its elements. When queried about a power consuming element, the database will list the SKOs that use it.

The database will link to BGAP and access the non-SKO power consumers in BGAP.



25 Shelters have 11 to 20 Consumer Types 30 Shelters have 6 to 10 Consumer Types 7 Shelters have 2 to 5 Consumer Types

Figure 1. Histogram: Type of Consumers (Distribution of Shelter Systems)




Figure 2. Histogram: Power Consumers (Distribution of Shelter by Consumer)

to 30 Consumers

Shelters have 21

25 Shelters have 11 to 20 Consumers

2 Shelters have 2 to 10 Consumers

#### INSTALLATION **EQUIPMENT PURPOSE** A piloted aircraft A invisible light, heat radiation B bombing B underwater mobile C carrier C communication submarine D radiac D direction finding. D pilotless carrier G telegraph teletype reconnaissance, interphone and public address F fixed ground surveillance G general ground use J electromechanical or inertial G fire control K amphibious wire covered H record reproduction M ground mobile K telemetering K computing portable L countermeasure M maintenance test S water M meteorological N navigation aids T ground, transportable N sound in air Q special purpose U general utility P radar R receiving V ground vehicular Q sonar & underwater sound S detect/range W water, surface & R radio bearing, search underwater S special types T transmitting Z piloted & pilotless T telephone (wire) W automatic flight or airborne vehicle V visual & visible light remote control combination X identification & recognition W armament X facsimile or tv Y surveillance & countersurveillance data processing EXAMPLE: AN/TSM-141

AN/ = standard prefix
 T = ground, transportable
 S = special type
 M = maintenance/test
-141 = design number

Figure 3. Joint Electronics Designation System

**Table 1. Shelter Systems with Environmental Control** (by Line Item Number)

#### Notes to Table 1:

- 1. CONTROL NUMBER and SYSTEM CODE at upper left, as well as SYS CODE (first column) and SRCVAL (second to last column) are data handling codes peculiar to the Sample Data Collection Program.
- 2. AMPS (seventh column) and WATTS (eighth column) are totals for each type of power consumer (i.e., individual power requirement multiplied by quantity (last column).

		DATE		90318			OTY	-	~	-	-		-	-	7	7	-
S		OPRS D		4			SRCVAL OTY	S	S	S	S	S	ທ	တ	S	ß	S
SHELT	TYPE S280	5	HIG	z			COOL	•	•	•	,	•	,	•	•	•	36000
	_	PHASE	2	Z		BTU	HEAT	1	•	1	•	•	•	1	•	•	35000
GEN	SYSCD G-60-4	2	٣	>			•										E.
_			ဟ	z			AC/DC	Ş	路	ጀ	ឧ	႘	¥C	ည	<b>Y</b> C	¥C	AC
PRM	MODEL M814		418	>-			WATTS	j	9	1	•		ı	į	210	3307	6448
			240	Z			AMPS W		2.10						1.75	06	8
PRIME	MOVER 5 TON	SE	220				¥		6						ä	15.90	31.
		VOLTAGE	208	>	50		VOLTS	208.0	28.0	270.0	208.0	208.0	120.0	208.0	120.0	208.0	208.0
	-73		0 120	>	ONENT						••	••		•••			
	MODEL AN/TSQ-73		28 11	<b>Z</b>	S			BLE	143-7	BLE	BLE	BLE	BLE	BLE	BLE	237-0	063-8
	<b>z</b> <	•	8	* *	SUB SYSTEM COMPONENTS		NSN	UNAVAILABLE	6240-00-143-7441	MAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	240-00-237-0227	120-01-063-8182
		ZH) X	9	z	SUB		z	Þ	•	9	<b>-</b>	•	₽	9	٠	*	*
	SYS AD	REQUENC	C 50 60	z			넒	73	•	18-3317					INCANDESCENT		
	LATUR	E	<b>1</b>	Z			MODEL			-					-	M56	CH436-1
	NOMENCLATURE GUIDED MSLE SYS AD		MANUFACTURER	¥		,	URE	NSFER U	<b>19</b> DC	ELECTRI	RADAR D	, RADAR	PRINTER	IS CONTR		NATION	TIONER
	NSN 1425-01-023-6141		MANUI	LITTON			NOMENCLATURE	POWER TRA	LIGHT BUI	TEST SET	CONSOLE,	INTERFACE	KEYBOARD PRINTER	ADP STATE	LIGHT		AIR CONDITIONER
	NSN 1425-01-	REFERENCE	DOCUMENT	PLATE			LINE	NONE	MON	NONE	NONE	NONE	MONE	NONE	NONE	H48904	NONE
KBER	LINE A26868	REF					200						AC026				
OL NG			HCT	8800			S	ž	2	ž	ž	ž	ž	ž	2	Z	2
CONTROL NUMBER FU00555 SYSTEM	CODE ACO07		K	7.													

	DATE 91198	
žį.	- •	SRCVAL QTY S S S S S S S S S S S S S S S S S S S
SHELTER TYPE 8250	HI Z	7000 P. P. P
GEN Syscd G-30-6P	PHASE 3 DC	HEAT BYU
	w z	AC C C C C C C C C C C C C C C C C C C
PRM MVR MODEL M900	4 18 N	MATTS 320 200 210 210 3702 864 770 2775 888
	240 N	<b>;</b>
PRIME MOVER 5 TON	10E N N	MPS 2.460 1.60 32.40 1.80 17.80 7.20 6.70 22.20 7.40
	VOLTAGE 0 208 Y	S VOLTS 120.0 208.0 208.0 208.0 1150.0 1120.0 120.0
I	10 12 4	ONENT 768 781 125
MODEL AN/TAM-4	28 1 N	M COM
HARGING	(HZ) 60 400 Y N	SUB SYSTEM COMPONENTS  NSN 6210-00-729-9768 11 4120-00-168-1781 2 UNAVAILABLE 11
NOMENCLATURE BOTTLE CLEANING & CHARGING	FREQUENCY (HZ)  DC 50 60 40  N N Y N	MOBEL 2 LAMPS INCANDESCENT F-18T-2 230 FSG-2
	MANUFACTURER JOINT ELECT	TURE XTURE ITIONER RPRESSOR OR AIR ER NERATOR AIR FLO R DIST RESSOR C
NSN 5855-01-029-8728		LINE NOMENCLATURE  WONE LIGHT FIXTURE  WONE LIGHT  A24455 AIR CONDITIONER  WONE MOTOR COMPRESSOR  WONE COMPRESSOR AIR  WONE FUMP WATER  WONE SOLENOID AIR FLO  WONE SOLENOID AIR FLO  WONE SOLENOID AIR FLO  WONE SOLENOID AIR FLO  WONE BOX POWER DIST  WONE FAN COMPRESSOR C
	reference Document TM9585525212	LINE NONE NONE A24455 NONE NONE NONE NONE NONE
LINE B11795	REF WGT DOC 1920 ING	SYS CODE AA003 AA008 AA008 AA027 BH159 BH159 BH160 BH161 AO008 BH163
SYSTEM CODE BH003	KW 30.	

	SHELTER TYPE 5280	Ì	: OTH 4 90330
	GEN Syscd G-30-6U	Z	X 3
	PRM MVR MODEL M923		X X X
	PRM I MODE M923		240 A1
	PRIME MOVER 5 TON		750 X
		8	X 508
	MODEL AN/TTC-39AV1		28 110 120 N N Y
	nomenclature Central Oppice Telephone	FREQUENCY (HZ)	N N Y N
	NSN 5805-01-121-4395 CENTRAL		MANUFACTURER G.T.E
	NSN 5805-01-	REFERENCE	DOCUMENT 11435HFC01
CONTROL NUMBER PU00592	LINE C17889		WGT DOCU 8885 1143
CONTROL FU00592	SYSTEM CODE BD008A	į	13.

		DATE	91148				Y.	9	~	-	7	-	~	-	-	-	-	-
<b>ب</b>			6				SRCVAL QTY	Ø	S	H	۴	S	۲	۲	۲	H	H	H
SHELTER	S-250	OPRS	-													0		
SH	8-2		E ×	!	<b>!</b>	BTC	100 100	•	•	•	•	•	•	•	•	23000	•	•
		PHASE	გ ≻			ĕ	HEAT	٠	•	٠	ı	1	•	1	18000	ı	•	1
N. S.	STOCE	Σ	m Z				ŀ											
Æ			o z				AC/DC	2	8	2	¥C	岌	¥C	¥C	ပ္က	8	2	<b>V</b> C
PRM MVR	M1037		418 N				WATTS			33	65	•	1	ı	•	•	ı	•
	TON		240 N						0	ø	0	,	,					
RIME	1 1/4	Ħ	220 N				AMP	6.40	1.4	1.89	.50							
P4 3		VOLTAGE	708 N				VOLTS	28.0	28.0	28.0	20.0	28.0	0.80	0.80	28.0	28.0	28.0	208.0
	(V)		120 N		ENTS		Š											••
į	AN/TLQ-17 (V) 3		0TT		SYSTEM COMPONENT			3-74	mi .	2-06	4-36	7-82	0-50	6-30	7-46	1-37	5835-00-311-5491	0-20
\$	AN/TL		× 58		FEM			00-14	MAVAILABLE	9-00	00-43	01-26	01-07	01-07	01-19	01-16	00-33	01-07
		HZ)	0 N		SUB SYSTEM COMPONENTS		NSN	6240-00-143-7441	UNAVA	5820-00-892-0622	5810-	6130-01-267-8242	5865-01-070-2046	5865-	4520-01-197-4674	4120-	5835-	6130-01-070-2027
	Ħ	ت برج	ő z		S										ပ္ထ		Ķ	
	RE SI	EQUEN	S 22						H	24	7	296	07	86	BH24-1000DC		AN/UNH-16A	472
	NCLATURE TERMEASURE SET	£	DC 50 60 40				MODEL	BULB	MOBIL	RT-5	KY-57	5	R-21	T-1386	BH24	NONE	AN/U	PP-7472
	COUNTER		MANUFACTURER RAMIN ENG WK					X	•			ER ER	MTER	<b>1500</b>	HEATER SPACE ELE	MER	PRODU	_
			UFACI IN ED				ATURI	ULB I	X			R S	8	TTER	SPACI	DITIC	REE	UPPL
	5-213		33				NOMENCLATURE	CHT B	SHT B	OIO	SEC	INVERTER POWER	CEIVE	ANSMI	ATER	80	CORDE	POWER SUPPLY
	1-27		410				<u>D</u>	ij	ä	19 R		H	ZE	Ę	H	AI	R	2
į	5865-01-275-2137	ENCE	EMT 86530				LINE	NONE	NONE	R3393	80137	KONE	NONE	NONE	NONE	MONE	NONE	NONE
	2	REFERENCE	DOCUMENT TM32586530410			-	ODE											
MBER	C30675	_					SYS CODE	AA005	A026	M019	<b>1G070</b>	1C042	AC043	AC044	AC045	LK048	AC046	AC047
20 m			MGT 8424				<b>J</b>	7	~	~	~	7	~	~	~	•	~	•
CONTROL NUMBER FUOGE20 SYSTEM	ACO41		Ž															

	DATE	90330			AL OTY	~	~	~		N	<b>co</b>	ed 	•		7		8 54	ຕ : ຜ	rd •	10	~	~	
ğ	OPRS	*			SRCVAL	50	w	<b>U</b> D	<b>U</b> D	<b>w</b>	9	<b>w</b>	ω	wa ·	<b>(</b> (	<b>V</b> 2	w,	w	w	v,	G)	<b>U</b> ,	
SHELTER TYPE 8280		E =	!		7000 2	18000	•	•	•	1	•	•	•	•	ı	•	f	•	•	•	1	•	
GEN G-60-6U	PHASE	3 ×		À	HEAT	'	1	1	•	•	•	1	•	•	•	•	•	ŀ	•	•	•	•	
æ		0 Z			AC/DC	Ş	Ŋ.	ပ္ခ	ğ	ည	Ş	ğ	Ş	Ş	Ş	<b>V</b> C	¥C	¥	Ş,	<b>N</b> C	¥	<b>y</b> C	
PRN MVR MODEL M923			1		MATTE	9568	•	•	•	,	ı	<b>9</b>	2268	•	•	•	•	•	•	200	3000	200	
LIMB OVER TON		7 × 0 × 0			ANTOR		•	•	•	1	1	90.	1.97	•	•	1	ı	•	•	1.70	26.00	4.30	
Z Z w	VOLTAGE	7 X			STITE	•		115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	.4	115.0	
3 (V) ec		120 X	ļ	MENTS	Š	•														11	•	•	
Model An/TYC-39 (V) 5	ľ	N N N		A COMPC		4120-01-076-1753	ABLE	5805-01-120-2928	5805-01-126-9261	5805-01-121-0712	7025-01-125-5767	5830-00-752-5357	5805-01-120-2929	5805-01-120-2919	5810-01-083-1396	5810-01-111-4081	5810-01-082-8403	5810-01-082-8410	5810-01-082-8411	ABLE	4520-00-177-6198	6105-00-234-3504	
_	(Z)	<b>2</b>		SUB SYSTEM COMPONENTS	Non	4120-01	UNAVAILABLE	5805-01	5805-01	5805-01	7025-01	5830-00	5805-01	5805-01	5810-01	5810-01	5810-01	5810-01	5810-01	UNAVAILABLE	4520-00	6105-00	
AUTO SW	ENCK (B	0 2		8					Į.		10	/FI											
TURE CENTER	FREQUENCY (HZ)	% 20 % 20 % 20		i i i i i	Tacom	F-18H-3	OD-169	TT-768	PP-7709/T	RD-49V	AN/UXH-5	LS-147C/FI	PP-7815	CP-1527	HGX-84	KG-83	KG-82	HGX-82	HGX-83	BR2009	P-13		
NOMENCLATURE NESSAGE CENTER AUTO		MANUFACTURER G.T.E		; ; ; ; ;		TTONER		2	PLY	AGNETIC			PLY	COMMUNI						T ICP	: !		
152-3068		G.T.B		 		ATR CONDITTONER	KEYBOARD	TELEPRINTER	POWER SUPPLY	STORAGE MAGNETI	TRANSPORT	INTERCOM	POWER SUPPLY	COMPUTER COMMU	T SEC	LIGHT FIXT ICP	HEATER	BLOWER					
NSN 5805-01-152-3068	REFERENCE	DOCUMENT 11435HPC01		! ! ! ! !		AZALG	•	NONE	MON	NONE	NONE	K94880	NONE		9	E03568		C58726			MONE	NONE	
		MGT DOCU 8500 1143			200	SIS CUDE	BE025	BE026	A0017	BE027	AM028	90	A0016	AD056	AG046	AG047	AG048	AG050	AG049	AA006	AG042	AG041	
CONTROL NUMBER FUGOS87 SYSTEM CODE LINE AX023 C410		21. 85																					

CONTROL FU00595	NUMBER	سر																		
SYSTEM CODE BD017	LINE C60164	*	NSN 5895-01-121-4485	-121-		NOMENCLATURE COMMUNICATIONS CENTRAL	CLATURE	CENTRA	H	MODEL AN/TS	MODEL AN/TSC-99		PRIME MOVER DOLLY	SET	PRM MVR MODEL M-832/U		GEN Syscd St-30-6U	Shelter Type 8280	Ä	
ì		REFERENCE	ENCE	•		1	FREQUENCY (HZ)	JENCY (	HZ)	1	ļ	8	AGE	ľ	ŀ		Z.		OPRS	DATE
30. 2	20870	1741. 35	J5116010		ROCKWELL	OKER	Öz	D9	<b>2</b>		OII N	120 208 Y Y	27 27 28	240 M	4 18 X	w	E ¥	Ē	ø	90330
		•		į																
						!			SUB SYSTEM COMPONENTS	TIEN CO	PONEN	ş						į		
	SYS CODE	DDR	LINE	NOME	NOMENCLATURE	2	MODEL		NSN			VOLTS	AMPS		WATTS	AC/DC	HEAT	1000	SRCVAL	L OTY
	BD018		NONE	PRIN.	PRINTER HIGH SI		RP-265		5815-	5815-01-G35-9002	-9005	120.0				¥C.	•	•	w	7
	BD019		HONE	PROC	PROCESSING SET	SET D	AN/UYK-19	-19	5865-	5865-01-134-7148	-7148	120.0		ı	1	ŞÇ	1	1	83	•
	BD020		NOX I	READ	READER PERFORATO	FORATO	RD-486/U	₽:	5895-	5895-01-122-9916	9766-	120.0			,	ပ္ရွင္	•	1	S)	m (
	BD022		KONTE	PROPERTY	REALDER FUNCTIED PROFITURE TERMS	PAKSWT	EA-2/6/C	5 <del>5</del>	70407	/040-01-122-3445 /035-01-123-00#5	10440	120				ر ا			ט מ	7 ~
	BD023		NONE	RECO	RECORDER REPRODU	EPRODU	RD-485/U	) <u>P</u>	5895-	5895-01-121-9562	-9562	120.0				2	1	,	) VI	חח
	<b>B</b> D024		NONE	COMED	ARATOR	COMPARATOR CORRE	SN-544		5895-	5895-01-121-0522	-0522	120.0				Ş	•	i	w	-
	BD025	_	HOME	COMA	CONVERTER TELES	TELETY	CV-3711/U	1/0	5805-	5805-01-122-3415	-3415	120.0			1	Ŋ,	1	•	W	~
	BD026		NOME	HOMI	MONITOR HF SPECT	SPECT	R-2093		58271	5827-41-038-9118	-9119	120.0		,	•	ğ	•	1	S	-
	BD027			PANE	PANEL MONITOR	TOR	SB-4111	, , ,	5895	5895-01-125-6822	-6822	120.0	_		1	Ų,	•	•	S)	
	80028	- •		RADIC	RADIO RECEIVER	IVER	R-2211/URC	) (JEC	5895	5895-01-122-3488	-3468	120.0			1	Ų.	•	•	S) (	φ.
	W 0000				KECOKDEK KEPKO	KECOKUEK KEPKODO	MD-484/0	25	2000	5835-01-122-3489	V 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	120.0			, .	کا د	• 1	• (	י מי	• •
	AK018		A24017	AIR	AIR CONDITIONER	TOWER	P-18H		4120-1	<b>4120-01-111-3729</b>	-3729	230.0	88.00		20240	ي ر	18000	18000	ט מ	•
	AAOOS	_	KONE	LIGHT	Į.		INCLIDESCENT	ESCENT	UNAVA	UNAVAILABLE		110.0				Ş	1	1	S	12
	AG054	_	HONE	CLEA		COUNT	501		CHAVA	CHAVAILABLE		110.0	_			Š	1	•	S	-
	AA010		MONE	LANTERN		KLECTRIC	2106-7		6230-	6230-00-729-9614	-9614	110.0	•	<b>4</b> 0	09	Ų.	•	•	S	-
	ED031		NOME	PRIN	PRINTER TERMIN	RELIMAL	TT-776/U	9	5895-	5895-01-121-9563	-9563	120.0	_	ı	1	ပ္	1	•	S	-
	8003	_		LIMS	SWITCHMOARD INTE	DINTE	SE-4112	20,000	6110-	6110-01-121-1984	-1984	120.0		1 -		Ų Ç	•	1	י מי	
		_	A A A A	3	CONTRACTOR NAME OF		CWLEAR	130/0K	70000 F F F F F F F F F F F F F F F F F F	5695-151-150-5456 5666-01-150-5656	76.00	126.0		) (	1 (	۽ پ	) (	1 (	0 0	•
	BD039		KONE	AMPL	AMPLIFIER LINE	LINE	1671-112	3	5820-	5820-01-114-22 <b>6</b> 9	-2269	120.0				Į C			מיני	4 ~
	BD041		NOM	OSCI	LLATOR	OSCILLATOR OF TO	1679-9L24	27	6115-	6115-01-148-4562	-4562	120.0	_		1	Ų	•	•	S	-
	<b>BD04</b> 2		NON	RADIO	RADIO RECEIVER	IVER	R-2210/URC	/grc	5895-	5895-01-124-8914	-8914	120.0	_		1	NC NC	٠	•	S	-
	<b>BD04</b> 3		NOM	RADIC	RADIO TRANSMIT	SHITTE	T-1449/URC	/disc	5895-	5895-01-127-4091	- <b>18</b>	120.0				¥C	•	•	တ	*
	BG002		MON	INTE	INTERCOM		LS-633		5830-	5830-01-123-1876	-1876	120.0	_	•	1	Q.	•	•	S	~
	M0027		HOME		POWER SUPPLY		PP-7714/U	<b>1/1</b>	6130	6130-01-125-5988	-5988	120.0	_	•	ı	Ų.	•	•	<b>60</b>	<b>→</b>
	A6028		NON	E O	CONTROL PONTE	SC SC	C-11034/U	P.	6130-	6130-01-123-0083	-0083	120.0		ı		Ų.	•	•	SO (	
	A0029			NO.	POWER SUPPLY	ָ ֡ ֭֭֭֭֭֭֭֡֜	PP-7715/U	2/2	6130-	6130-01-124-8920	-8920	120.0	_			ပ္ခဲ့ရ	•	•	י מי	-
	A0030				POWER SUPPLY	7	PP-7771/UKC	1/ GKC	1430-	6130-01-124-1589 1420-01-123-6808	68CT-	120.6		. (	1 1	ي د	• •	1 1	ט מ	• -
	BD635		NO SEE	SELE	SELECTOR DATA	NTA LLE	SA-2349/U	),u	2895-	5895-01-122-3416	-3416	120.0				įų	•	•	n vs	•
	í		;	ĺ			;			!										

FREQUENCY (H2) C 50 60 400 28 110	PREGU MANUFACTURER DC 5 N Y
2	
N N N SUB SYSTEM CO	
Nen	
4931-00-019-4671	
4931-00-128-1444	
	•
492=UI-UZ-U3	11683-A
067-053-00 4931-00-443-4942	• -
100UUFTO115U 6625-00-987-9060	<b>.</b>
4931-00-914-5183	LRC-201
4931-00-170-1447	
4931-00-178-1051	
6625-00-257-7561	
6625-00-916-5928	
4931-00-115-050/ 6625-00-00-100-000/	ATOB/AT
6006B-106 6110-00-332-2334	Ξ.
4931-00-438-1616	
06/-08K5-00 6695-01-19/-8023 KB-52m 4931-00-435-7662	
, A	-
/2-311	
6625-01-158-2607	
7A 6625-00-450-7593	
RIN-33940 4931-01-160-3832 RIM-506 6625-01-048-8920	
Ī	
107-0	
4931-01-060-0521	38AF-1
/ 350-090-T0-T56F	25AB-2
4931-090-10-1269	33AP-2
4931-01-060-0523	34AP-2
4921-01-040-7278	
Ψ	
T-14	
4931-01-132-7597	
9	
6625-01-112	
7	٠.
001-001 4370-00-00-1730 3 13MD 4310-00-00-01730	

<u>61</u>
Page
9
pane
ঠ

		•			<b>*</b>			-		<b>.</b>	<b>-</b> -	٠.	٠,-		-	7		7	-	_	<b>.</b>	<b>.</b>		٠.	. =	1	-	<b></b> .		•	-	-	_		-	-	<b>-</b> (	~ .	<b>~</b> .	٦.	٠.	٠.	-
_	DATE	90330			AL OF																			_																			
SHELFER TYPE 5 TON EXP	OPRS	•			SRCVAL	ω	S)	S	S	o c	ט מ	a v	מינ	S	S	S	S	S	S	S	S)	S) C	n u	מינ	S	S	S	S C	ט מ	o co	S	S	S	S	S	S	S	n	ທິ	ט מ	3 6	3 6	9 (
SHELTER TYPE 5 TON E		E =			7000	•	1	•	•	1		•	1	•	1	•	1	•	•	•	•	ı	1 1	•	1	•	•	1		ı	•	•	•	ŧ	•	1	•	•	<b>i</b> 1		. (	1 (	1
23	PHASE	2 =			HEAT	•	•	•	1				•	•	•			ı		•	•		. ,	•	1	ı							ŧ	ı	1	ı	•	1			۱ ا	) (	t
SYSCD ST-30-6U	25	m >=			E																																						
<b>§</b> ~		ω <b>z</b>		ļ    - 	AC/DC	NC.	AC.	ÄC	S.	2	۽ د	¥	YC.	YC.	YC Y	<b>y</b> C	AC	¥C	¥Ç.	<b>Y</b> C	Ų.	) (	ָט ט <b>א</b>	Ş	AC	<b>A</b> C	S C	Ų C	٥	Ş	¥C	<b>y</b> C	¥C	¥C	¥C	NC.	ပ္ရွင္	ن د	ب ا	) (	ر م ر	ر م (	۽ ڇ
PRM MVR MODEL M820A2		418 N		!	WATTS	851	464	989	299	414	104 218	264	368	161	172	264	851	379	767	207	414	261	191	241	191	552	138	149		149				460					161	707			
		240 X					.30	. 60	9:	9.9	2 6	30	.20	6	50	.30	<b>\$</b>	30	.30	08	9 6	2 9		9	40	.80	0 9	9.50	90	30	. 60	.60	0	0	90	01.	9.5	9 (	9 5	<b>.</b> .	2 9	2 0	2 9
PRIME MOVER 5 TON	<b>1</b>	750 N			AMPS	7.1	4	8	7	m -	9 6	7			•	~	•	m	4	٠. ا	m			7	H	4	٠		7	-	3.6	4.	4.20	÷	ä	 m	2.	2.70	† · ·	7.10		9 -	• (
	VOLTAGE	208 X			VOLTS	115.0	115.0	115.0	115.0	115.0					115.0	115.0	•	115.0	•	•		115.0	115.0		115.0	1.5.0		115.0	•	ິດ	115.0	'n		ທ່	ທີ່	٠ ا	, 1		115.0	o v			0.611
286		120 N		NENTS	>																										·												
MODEL AN/GSM-286		110 N		SUB SYSTEM COMPONENTS		6695-01-081-9053	4931-00-987-9002	931-00-017-4737	931-01-012-2884	1931-00-40/-2642 6625-00-469-3339	5625-00-439-3213	6625-00-145-2787	6625-01-103-9550	6625-01-083-1725	4931-01-085-4229	4931-01-008-1475	6625-01-008-1480	6625-01-046-3712	6130-01-057-4649	4931-00-008-1478	4931-00-150-7836	5625-01-010-1311 5625-01-003-4396	4931-00-913-299 <b>4</b>	4931-01-039-4040	6625-01-111-1074	6695-01-129-0246	6625-01-085-7707	5625-00-148-8069 5895-01-030-1455	5625-01-030-1439 6625-00-113-2943	4931-01-020-4514	6695-01-154-3085	6625-00-520-5143	6695-01-142-4682	6130-01-130-8049	6695-01-080-6547	6625-00-528-6773	6625-00-595-8762	R687-605-00-07*3	6625-01-092-8915 6695-01-082-5446	6695-U1-U62-5446 6120-00-130-5372	5120-00-130-33 <i>)</i> 5950-00-715-8591	5950-00-/15-6591 6625-00-557-8305	6059-166-00-6398
¥2		Z 58		STEM		-01-0	5-00-1	)-00-1	-01-0	000	00-	-00-	-01-1	-01-0	-01-0	-01-0	-01-0	-01-0	-01-0	00-00-	-00-		5-00-	-01-0	1-01-	-01-1	-01-0	100-	100-	-01-0	-01-1	-00-2	-01-1	-01-1	-01-0	-00-	-00-	200	1011	7 7 7 7	200	200	>
	(HZ)	0 ×		SUB SY	NSN	6699	4931	4931	4931	493	6628	6625	6625	6625	4931	4931	6625	6625	6130	4931	4931	2700	4931	4931	6625	6695	6623	0000	6625	4931	6695	6625	6695	6130	6695	6625	6623	רידכ	0000	4120	100	100	1 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
	ENCY	20 60 Y Y					4	₽9													5					992A		<b>4</b> 7					-R30	00-M3	<b>~</b>		00-5	9	70-6	2			
URE ON SET	FREQUENCY	ပ		i    -  -	ODEL	AK-519	-41-334Y	-90-746A		S/ABAN	32BAP		14B	45	640B	A13N	A48	440	101	S14N	SKD-4850	90B	OTHOD	345A	355A	-87-59992A	27E	-12-432A	523	05A	126M	86503	C-536-C-R30	RE-3-300-M3	100AR-8	9K	67-0655-00	6006B-106	06/-058/-02 035-5039-00	35-503 P-1290	ST-2001	4004	
						<	O	U		<b>0</b> 0	<b>m</b>	1	~	-	∞		ທ : -	in .	I			<b>4</b> a	0 00	. RO	10	<b>×</b> 1		el R	) vo	-	v		ပ	æ.	4	<b>1</b> 0	O 4				4 U		1 6
NOKENCLATURE CALIBRATION		MANUFACTURER		i ! ! !	RE	AMPLIFIER PRECIS	ANALYZER DISTORT	HICH	STANDARD CALIBRA	VOLIMEIAK DIFFE NIVIDER VOLFAGE	STANDARD VOLTAGE	FIXTURE CALIBRAT	GENERATOR PULSE	SIGNAL	SIGNAL	DIFFER	AMPLIFIER DUAL T	OSCILLOSCOPE MAI	ZZ	LAYED	SIMULATOR IGNITI	GRIEGA LAFEDANCE	GENERATOR DETECT	MAIN FRAME MEASU	IN UNIT ELE	DEO A	METEK FREGUENCY WEMED DOMED	T OKEC	OSCILLATOR NONCR	QUART		IT ELE	3	LY	OSCILLATOR PRECI	STANDARD RECEIVE	GNAL	KEGULATUK VOLTAG	A F	TEST LOAD UNIT	POST POST R	VOLTEMENTED DIGITAL	O ALLOW
0960		IANUPA		! ! ! !	NOMENCLATURE	FIER	ZER D	AMPLIFIER HIGH	ARD C	ELEK VO	ARD V	RE CA	ATOR			AMPLIFIER	FIER	OSCI	POWER SUPPLY	SAMPLKK DKLAYED	A C	ATOR	ATOR	FRAME	IN CN	IA NI	METEK FREGUI	GATTNG INTE	LATOR	OSCILLATOR	OSCILLOSCOPE	PLUG IN UNIT		SUPPLY	LATOR	ARD K	PICKOFF SIGNAL	ALCA	STANDARDIZEK C. TRST 10AD INTT	PORME	TRANSPORMER	CALL	
-081-0			1		NOMEN	AMPLI	ANALY	AMPLI	STAND	DIVI	STAND	FIXTU	GENER	GENERATOR	GENERATOR	AMPLI	AMPLI	OSCIL	POWER	SAMPL	DETEC	CRNED	GENER	MAIN	PLUG	PLUG	NST.SK	GATTN	OSCIL	OSCIL	OSCIL	PLUG	POWER	POWER	OSCIL	STAND	PICKO	KEGUL	PEST	TRANS	TRANS	VOT.T	THE PROPERTY OF
NSN 6695-01-081-0960	NCB	DOCUMENT SC6695-92CLA05			LINE	NONE	A57297	A50987	C14192	NONE	NONE	NONE	G41073	NONE	<b>G</b> 54193	NONE	NONE	NONE	NONE	S44405	ANON	NONE	G40856	M60975	C01338	NONE		NONE	NONE	P25531	P44217	KONE	NONE	NONE		R30049	MONE	NONE NONE	NONE	NONE	NONE	NON	a a a a a
	REFERENCE	DOCUMENT SC6695-92	ı	•	CODE	Z	<b>~</b> ·	< (	o e	) Ž	; Z	Ż	G	Z	U	<b>Z</b> :	2 :	z i	Ż (	מ מ	<b>5</b> 2	ž	: ڻ	×	O:	Ż	2 2	t Ž	: <b>Ž</b>	Δí	Å,	ž	ž,	克	Ź,	× i	ž Ż	į	įž	: ž	ž	įŽ	: 3
LINE C72669		WGT D			SYS CO	BH066	BH067	BH068	52009 82070	BH071	BH072	BH073	BH074	BH075	BH076	BH077	BH078	6/0HG		DENOS 1	BHO82	BH084	BH085	BH086	BH087	BH088	PHOS	BH091	BH092	BH093	BH094	BH095	A0022	A0023	960H9	BH097	BH098	O O O O M O	BH100	BH101	BH102	BH103	DATE
<b>E</b> 2		34																																									

-	-	-1	-	-	-	-	-	-	-	-	-	-	-	7	74	-	-		-	-	7
Ø	S	Ø	Ŋ	Ø	S	S	S	S	ß	S	S	w	S	တ	ß	Ø	S	ß	v	Ø	S
•	•	•	•	1	•	•	1	1	•	•	•	i	•	•	•	36000	•	•	1	•	1
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1	•	90009	•	•	•
¥	¥	¥C	¥	¥	¥	YC.	YC	Ų	¥	¥	¥	¥Ç	¥	¥	¥Ç	¥	Š	¥	¥	¥	<b>y</b> C
828	138	345	149	161	384	1440	240	750	241	464	333	379	241	494	840	5830	130	840	1200	448	1448
7.20	1.20	3.00	1.30	4.30	3.20	12.50	2.00	6.50	2.10	4.30	2.90	3.30	2.10	4.30	7.30	28.00	1.10	7.00	10.40	3.90	12.50
115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	208.0	115.0	120.0	115.0	115.0	115.0
7310-00-782-0005	3439-00-930-1638	6130-00-510-8022	6685-01-120-4961	4310-00-578-0406	5130-00-935-7354	4940-00-561-1002	6650-01-101-8431	6695-01-074-7953	3439-00-542-0446	6625-01-081-4902	6625-00-772-6106	6625-01-095-9344	6625-01-010-6783	6695-01-076-8966	6210~00-900-8560	4120-01-063-7573	6730-00-116-1618	4520-00-778-7136	6625-01-048-8920	6695-01-074-7954	6625-01-112-7153
WH-636																	TYPE 1 OR 2	UH-68P	RTM-506	SC-504	DH-501-A
HOT PLATE ELECTR	GUN SOLDERING	POWER SUPPLY	GAUGE VACUUM ELE	PUMP UNIT VACUUM	DRILL ELECTRICAL	HEATER GUN ELECT	MAGNIFIER FLUORE	MODULE MAINFRAME	GUN SOLDERING	TEST SET ELECTRI	TEST SET ELECTRO	TEST SET SEMICON	GENERATOR FUNCTI	POWER SUPPLY DUA	LIGHT FIXT FLUOR	AIR CONDITIONER	VIEWER MICROFICH	-	MAINFRAME POWER	OSCILLOSCOPE DUA	
NONE	L61459	A24763	Y03820	NONE	NONE	NONE	NONE														
BH105	BH106	A0024	BH107	BH108	AH008	AH009	BH109	BH110	AH010	BH111	BH112	BH113	BH114	A0025	AA002	AK014	AG002	AG053	BH052	BH064	BH065

	DATE	90330				E	7	S.	ø	-	-	-	~	7	_
						SRCVAL OTY	S	S	ß	s	Ø	w	S	Ø	ß
SHELTER TYPE 6260	OPRS	0													
SHE	3	E ×	!	!	5	1000 000	9009	•	•	1		•	1	1	1
	PHASE	2×			BTC	HEAT	4000	ŧ	1	•	•	1	•	•	1
GEN SYSCD	, E	m <b>z</b>				l									
8 8		ω >-				AC/DC	ပ္ခ	ပ္ရ	ŭ	Š	Š	ğ	ŭ	ŭ	ğ
PRM MVR MODEL		418 N					1380	7001	150	20	1150	4	250	2000	110
		240 N							0	0	_	~		•	
PRIME MOVER		220 240 418 N N N				AMPS	12.00	8.	1.30	.10	10.00	.03	2.10	26.00	.90
A E -	VOLTAGE	2 208 Z				VOLTS	115.0	15.0	5.0	15.0	115.0	115.0	115.0	115.0	5.0
5		120 Y		ENTS		Ş		•	_	_	_	_	٠.		•
MODEL		110 N		SUB SYSTEM COMPONENTS			1120-00-935-1608	M	3-315	8-312	6130-00-133-5879	M	4-3504	7-6198	5805-01-032-1694
MODEL	È	8 Z		O M			0-93	LABL	0-14	1-00	0-13	LABL	0-23	0-17	1-03
5	2 ~	00 x		SYST		NSN	120-0	MAVAILABLE	240-0	830-0	130-0	NAVAI	105-0	520-0	805-0
NOMOA	A (HZ	09 ×		SUB		Z	•					ם	9	4	S.
ē E	OURNC	DC 50 60 A			•	_	CV-6-5/6-15	6	01/25	7.	24/U				14
TURE		10 z				MODEL	-9-A	BR2009	W-L-101/25AT	LS-14	PP-6224/U			P-13	SB-3614
NOMENCLATURE		MANUFACTURER GICHNER				TURE	TIONER	II ICP	INDESCEN		PLY	DIST			4 SWITCHBOARD TELE S
NSN FROTE-028-8203		MANUFAC	4			NOMENCLAT	AIR CONDI	LIGHT FIX	LAMP INC	INTERCOM	POWER SUI	BOX POWE	BLOWER	HEATER	SWITCHBOA
		DOCUMENT 11435HFC01				LINE	A2366	NONE	NONE	K94880	P40750	NON	NONE	NONE	S82704
NUMBER LINE C70502	REF	WGT DOC 2570 114				SYS CODE	AK007	AA006	AA018	BG001	¥0	A0008	AG041	AG042	BD014
CONTROL NUMBER FU00565 SYSTEM CODE LINE		K. 6. W.													

	DATE	90263			SRCVAL OTY	-	-		7	<b>1</b>	v.	₹ .	н .	-	-
TER	OPRS	<b>m</b>			SRCV	F	₽	[→	<u> </u>	H	H i	H	₽ 1	E→	⊢
SHELTER TYPE S250		H z	!	Bru	1	0009	•	ı	•	•	1	•	•	1	•
GEN SYSCD ST-5-6-3	PHASE	o z		à	HEAT	4000	•	•	1	•	ı	ı	1	•	•
•		ω × 			20/	<b>y</b> c									
PRM MVR MODEL M1028	1	4 18 X					_	_	_	_	100 AC	-	4 AC	75 AC	00 AC
	J	240 N				1380									
PRINE MOVER 1 1/4 TON		220 N	i		AMPS	12.00	10.00	.17	26.00	1.90	.80	6.	.03	.70	1.70
	VOLTAGE	120 208 Y N		 	/OLTS	115.0	115.0	15.0	15.0	115.0	15.0	115.0	115.0	115.0	115.0
41(V);		l		NENTS	Š	•	•	_	-	•		_	_	-	•
MODEL AN/TTC-41(V)2		28 110 N N		COMBO		935-16	133-58	008-31	177-61	032-16	BLE	143-33	BLE	E.E	409-8
	H2)	8 z		SUB SYSTEM COMPONENTS	NSN	4120-00-935-1608	6130-00-133-5879	5830-01-008-3126	4520-00-177-6198	5805-01-032-1694	UNAVAILABLE	6240-00-143-3153	UNAVAILABLE	UNAVAILABLE	4140-00-409-8298
NOMENCIATURE CENTRAL OFFICE TELEPHONE AU	PREQUENCY (HZ)	20 60 Y Y				CV-6-5/6-15	24/11	78		14		W-T-101/25AT		COMPAS II 11	9B5
NTURE OFFIC	PRE	10 z			MODET.	2	pp-62	LS-147F	P=13						
		manupacturer Sacramento		! ! !	MIDE	TOTONED	DDT.V	:		ADD TREE	XIII TOD	NUCESCEN	DIST	COMPON	FAN CENTRIFUGAL
028-8395					NOMBACT AMIDE	NOTIFICATIONED	ALL CONTROL OF	TWEEDOW	HEATER	CHITCHBO	THE PROPERTY.	ONL GME I	AMOG AOB	TENTHONE	FAN CENT
NSN · 5805-01-028-8395	E E E E E E E E E E E E E E E E E E E	DOCUMENT TM11580569312		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1480	NO SECT	D40750	00000	PANCH	202704	ANON	A NON	4 10 10 10 10 10 10 10 10 10 10 10 10 10		NONE
6	0 14 14 14				400	SIS CODE		5	1000	****	* 100		960	900	AD092
15 NG		WGT 2210			į	מ מ	€ -	5 6		Ç Ø	9 4	E ^	5 4	Ç 4	<b>.</b> ≪
CONTROL FU00515 SYSTEN CODE AL002		¥.9													

		S DATE	90330			SRCVAL OT	E+	۴	E	H	E	۲	۲	E	۲
LTER	TYPE S250	OPRS	m				_								,
SHE	TYP S25		E N	!	Đ	1005	9009	•	•	•	•	•	•	•	•
	6-3	PHASE	ပ ပ	İ	BTU	HEAT	0009	1	•	•		•	•	•	•
	SYSCD ST-5-6-3	ā	m Z			ŀ									
			w >-			AC/DC	¥	¥	¥	¥Ç	¥C	¥Ç	¥Ç	¥	<b>V</b> C
PRO	MODEL M1028		418 N			ATTS	1380	3000	110	250	20	1150	100	110	4
	TON		240 N			-				2	12	S	2	.80	.03
PRIME	MOVER 1 1/4 TON	Ħ	220 N			AMPS	12.0	26.00	٠.	2.10	.1.	10.00	-	~	•
14		VOLTAGE	120 208 Y N			LTS	115.0	15.0	115.0	115.0	15.0	15.0	15.0	15.0	115.0
	MODEL AN/TTC-41(V)4	>	120 X	FUTS		Š				_			=		
	TTC-4		110 N	STIP SYSTEM COMPONENTS			4120-00-935-1608	4520-00-177-6198	5805-01-032-1694	14-350	5830-01-008-3126	6130-00-133-5879	ĸ	6240-00-143-3124	<b>M</b> 1
			8 2 7	T MALE	i		00-93	00-17	01-03	00-23	01-00	00-13	UNAVAILABLE	00-14	UNAVAILABLE
	NE AU	(2	0 z	3 SVS		NSN	4120-	4520-	5805-	6105-	5830-	6130-	UNAVA	6240-	UNAVA
	LEPHO	FREQUENCY (HZ)	¥ 60	as	•		15							E	
	CE TE	MENOGE	00 z			H	CV-6-5/6-15		614		47F	PP-6224/U	60	W-L-101/1T	
	ATURE	E	1 <u>0</u> z			MODEL	_	P-13			LS-147F			_	
	NOMENCLATURE CENTRAL OFFICE TELEPHONE AU		GRER	!			AIR CONDITIONER	-	TELE				ئ	SCEN	ST
			MANUFACTURER GICHNER	ļ		ATURE	DITIO		OARD		=	UPPLY	IXI	CANDE	ER DI
	4-886					MENCI	R CON	ATER	LTCHB	ONER	TERCO	MER S	CHT P	NI OF	30X POWER DIST
	11-04					Ø	57 AI	HE	34 SW	Ä	NI OK	50 20	Ĭ	3	8
	NSN 5805-01-044-8869	REFERENCE	DOCUMENT 11435HFC01			LINE	A236	NONE	8827(	NONE	K948£	P407	NONE	NONE	NONE
~	ø.	REPER	11435												
CONTROL NUMBER FU00568 SYSTEM	LINE C78929		WGT 2210			SYS	AK007	AG042	<b>BD014</b>	AG041	BG001	Ø	AAOOG	AA017	A0008
707. 568 77			- 52												
CONT PUO SYST	SODE AL		₹ .												

AN008 C82833 3610-00-344-4706 CAMER	DEPTH STATE	-			, , , , , , , , , , , , , , , , , , , ,		TINE	ANON	NONE TANATIST	ASA455 ATR CONDITTIONER	NONE DEHINITEDIATE	NONE TABLE LIGHT	NOW DENSTRONETER DIG	NONE FIRES	CAMERA
CAME		MANUFACTUR			, , , , , , , , , , , , , , , , , , , ,		TINE	ANON	NONE TANATIST	ASA455 ATR CONDITTIONER	NONE DEHINATOTETE	NONE TABLE LIGHT	NOW DENSTRONETER DIG	NONE FIRES	C81761 CAMERA
CAME		MANUFACTUR					NOMENCI.ATURE	LICHT PIXMIRE	TOTAL BANKE	ATE CONDITTIONER	TENTRAL PARK	FABLE LIGHT	DENST TOMETER DIG	FIXER STATES	CAMERA
CAMER		ACTURER	INTERN				URE	THE							
4									_		-	•	-	1 10	_
SECTION	FREO	ည	z				MODEL	2 LAMPS	4/2	F-18T-2	009		26R	9	1969
ra section reproduction	TENCY (HZ	09 05 0	<b>&gt;</b>		ans							_	כ	Þ	e
	_	00;	z		SVSTR		NSN	210-00-	NAVAIL	120-00-	NAVAIL	NAVAIL	NAVAIL	NAVAIL	610-00-
		011 88	Z		Odkoo			-729-97	ABLE	-168-17	BLE	ABLE	ABLE	ABLE	1610-00-400-7588
	2	120	2		STARK		IOA					12(	12(	12(	
9~L	LTAGE	208 2	<b>.</b>				CTS	0.0	0.0	•					_
Z O									90	6.20	2.80	2.60	1.00	5.00	65.00
15 6E		418	<b>E</b>							3390	345	320	120	900	13533
		W 2	5				AC/DC	Ų	ž	¥	¥Ç	<b>A</b> C	¥	¥	¥C
09-09	PHASI	۵° «۳			;   		ļ	•	•	1200	•	•	•		
					•	BTU	•					•			
10 / 2 mail	OPRS	r	4							8			•		
		90100	7				VAL OTY	S	1	·	S	S	s T	S	S
	1969 - 1016 MOI-G 6961	1969 S-1CN M931 G-00-00 NOLTAGE	1969 5-10N M931 G-00-60 11FE/7510N VOLTAGE OPRS 28 110 120 208 220 240 418 S 3 DC OTH	1969 5-10N M931 G-00-60 11FE/7510N 1969 OPRS 28 110 120 208 220 240 418 S 3 DC OTH N N N N N N N 2	1969 5-10N M931 G-00-60 11FE/7510N 28 110 120 208 220 240 418 S 3 DC OTH N N Y N N 2	1969 5-10N M931 C-00-50 11F26/91OR 28 110 120 208 220 240 418 S 3 DC OTH N N Y N N Y N N Z THE COMPONENTS	1969 5-10N M931 G-00-60 AIFEZ 7310N N Y N N 2 N N Y N N Z TEM CONPONENTS BTU	1969  VOLTAGE  28 110 120 208 220 240 418 S 3 DC OTH  N N Y N N 2  TEM COMPONENTS  BTU  VOLTS AMPS WATTS AC/DC HEAT COOL SRCVA	1969 5-10N M931 G-00-60 AIFEZ/310N  28 110 120 208 220 240 418 S 3 DC OTH  N N Y N N Y  TEM CONPONENTS  970  1969 200 AC  S 20	1969 5-10N M931 G-00-60 LIFEZ/JION  28 110 120 208 220 240 418 S 3 DC OTH  N N N N N N N 2  TEM COMPONENTS  BTU  BTU  COOL 729-9768 120.0 1.66 200 AC  TABLE 120.0 .90 108 AC  TILABLE 120.0 .90 108 AC	1969  VOLTAGE  28 110 120 208 220 240 418 S 3 DC OTH  N N N N N N N N N N N OUTS  TEM COMPONENTS  VOLTS AMPS WATTS AC/DC HEAT COOL SRCVA  O0-729-9768 120.0 1.66 200 AC	1969  VOLTAGE  28 110 120 208 220 240 418 S 3 DC OTH  N N N N N N N N N N N N OUTS  TEM COMPONENTS  VOLTS AMPS WATTS AC/DC HEAT COOL SRCVA  VOLTS AMPS WATTS AC/DC HEAT COOL SRCVA  00-729-9768 120.0 1.66 200 AC	1969  VOLTAGE  28 110 120 208 220 240 418 S 3 DC OTH  N N Y N N N Y N N 2  TEM CONFONENTS  VOLTS AMPS WATTS AC/DC HEAT COOL SRCVA  VOLTS 120.0 1.66 200 AC - T  ILABLE 120.0 2.80 345 AC - S  ILABLE 120.0 2.60 320 AC - S	1969  VOLTAGE  28 110 120 208 220 240 418	1969  VOLTAGE  28 110 120 208 220 240 418 S 3 DC OTH  N N N N N N N N N N N N N N N N N N N

	DATE		90330			QTY	_	4	-	-	~	~	-	-		
			90			SRCVAL QTY	S	s	S	S	s	s	s	s	s	
TER	OPRS		m			SRC										
SHELTER TYPE S250		E	z	!	ā	COOL	9000	•	ı	1	•	•	ı	1	1	
ু <del>ন</del>	PHASE	일 일	z		BTC	HEAT	ı	ı	ı	ı	ı	ı	t	ı	•	
GEN SYSCD ST-3-6-1	/Hd	۳	z			l										
£		တ	<b>&gt;</b>			C/DC	ŊC.	õ	Ş	ñ	Ş	ပူ	Ş	õ	ပ္	
PRM MVR MODEL M1028		418	z				1740 A		_	-	250 7	_	4	-	160 /	
NON		240	Z								0	٥	<u>د</u>	0	σ.	
PRIME MOVER 1 1/4 TON	3	220	z			AMP	15.10	. 69	13.00	.10	2.10	. 50	.03	1.3	1.39	
424	OLTAG	2 208 2	Z			CTS	115.0	15.0	15.0	15.0	115.0	15.0	115.0	5.0	115.0	
	Š	120	<b>&gt;</b>	NTS		0			_	_	_	_	11	11	•	
MODEL AN/TSC-76		110	z	B SYSTEM COMPONENTS			4120-00-679-2669	ea ea	7-6198	8-3126	4-3504	ы	ш	5815-00-553-6061	FF 5-Nn-907-8300	
MODEL AN/TS		28	z	O M			0-67	LABL	0-17	1-00	0-23	LABL	LABL	0-55	06-u	
IG CEN	(Z)	400	z	SUB SYSTEM COMPONENTS		NSN	4120-0	UNAVAI	4520-0	5830-01-008-3126	6105-0	UNAVAILABLE	UNAVAILABLE	5815-0	7.5 S-N	
CHIN	.X	C 50 60 6	>	S												
S PA	QUEN	20	z					6		7.F		DESC		<b>«</b>	/TG	
ICLATURE NICATION	FRE	ည	Z			MODEL	F9000	<b>BR200</b>	P-13	LS-147F		INCANDESCENT		TT-76A	TH-22/TG	
NOMEN		MANUFACTURER	G-R-M CORP			URE	TIONER	er icp					R DIST	WRITER	1 TERMIN	
NSN 5895-00-168-1574		MANUI	G-R-1			NOMENCLA	AIR CONDITIONER	LIGHT FIN	HEATER	INTERCOM	BLOWER	LIGHT	BOX POWE	TELETYPEN	TELEGRAPH TERM	
	REFERENCE	DOCUMENT	35HFC01			LINE	A23907	NONE	NONE	K94880	NONE	NONE	NONE	V36762	V57729	
NUMBER LINE D77886	_	WGT DOC				SYS CODE	AK013	AA006	AG042	BG001	AG041	AA008	A0008	BEOOS	BE003	
CONTROL NUMBER FU00564 SYSTEM CODE LINE BD D7788		KW														

	DATE	90330		SECUAL OFF				8	-	-	7	-	7	-	~	•	*	9	24	m	٦	7	~
rer V van	OPRS	4		2000	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
SHELTER TYPE 5 TON V	OTH	z	•		)	1	1	•	١	ı	•	ı	•	1	ı	1	18000	•	1	1	•	,	•
GEN SYSCD ST-30-6P	PHASE 3 DC	z >		BTO	i '	1	•	1	•	١	ı	•	ı	•	,	•	•	,	ı	•	ı	٠	1
•	s	z		AC/DC	AC.	ပ	Ų	NC NC	Ş,	<b>A</b> C	¥C	¥C	AC	PC PC	. Q	AC	AC	<b>y</b> c	ບ	<b>y</b> c	Ü	U	ပ
PRM MVR MODEL M818	418	z		WATES A		Ž	396 A	•	À I	90 A	425 A		Ř	350 A	Ä	3000 A		_			90 AC	576 AC	432 A
~~~	240	z						۳ -		_							_	_			_		
PRIME MOVER 5 TON	E 220	z		AMPS	•	•	3.30	28.00	•	.80	3.50	•	•	2.90	•	25.00	62.40	75.00	4.00	.80	.80	4.80	3.60
£4 <b>3€</b> 1Ω	VOLTAGE 208	<b>&gt;</b>		VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	20.02	120.0	120.0	120.0	120.0	208.0	120.0	120.0	120.0	120.0	120.0	120.0
_	120	<b>&gt;</b>	ENTS	Š	٠.		•	•										_	ï	7	Ä	_	Ϊ.
MODEL AN/MYQ-4	110	z	OMPO		2-264	Ħ	2-25	2-25	2-52	3-07	2-25	6-83	2-80	9-151	2-586	2-274	9-40	19-6	пí	ьí	гí	ьí	4-00
	28	Z	TEM C		01-09	ILABI	01-0	01-09	01-00	01-15	01-09	01-23	01-23	01-07	01-0	01-09	01-08	00-17	ILABL	ILABI	ILABL	ILABI	01-0
AUTO		Z	SUB SYSTEM COMPONENTS	NSN	5895-01-092-2649	UNAVAILABLE	5895-01-092-2552	5895-01-092-2550	5895-01-092-2549	6675-01-153-0775	5999-01-092-2551	5895-01-236-8963	5895-01-235-8069	7010-01-079-1516	5805-01-092-5894	7025-01-092-2745	4120-01-089-4053	4520-00-177-6198	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	5895-01-094-0081
KSTEM	FREQUENCY (HZ)	<b>&gt;</b>	SU	_		_										•			_	ENT	_	_	
NG S.	SQUEN 50	<b>&gt;</b>			61A		73	0	īῦ	4	6A	PR-336/TYQ-3	MV-857/TYQ-3	۳	92	ស	18000 BTU	MIL-H-52641	ō	INCANDESCENT			171
CCLATURE PROCESSING SYSTEM AUTO	PR S	z	 	MODEL	CV-3661A	S-286	MX10173	TW-430	CP1435	TT-804	R-0526A	PR-33	MV-85	RP-273	MD-1095	MV-705	18000	MIL-H	BR2009	INCAN	¥\×	201	MX-10171
NOMENCLATURE DATA PROCESS	MANUFACTURER		 	URE	FREQUE	LAP ZEN	(EYBOARD	MAGNET	G UNIT	SSEMBLY	H READE	MIT GRO	toup	PRINTER		RY UNIT	TIONER	ACE ELE	T ICP		æ	ACOUN	KEYBOARD
NSN 7010-01-090-6819		HONEYWELL		NOMENCLATURE	CONVERTER FREQU	COMPUTER LAP ZEN	DISPLAY KEYBOARD	TAPE UNIT MAGNET	PROCESSING UNIT	PRINTER ASSEMBL	CARD PUNCH READE	PRINTER UNIT GRO	MODULE GROUP	TERMINAL PRINTER	MODEM UNIT	DISK MEMORY UN	AIR CONDITIONER	HEATER SPACE EL	LIGHT FIXT ICP	IGHT	HUMIDIFIER	LEANER VACUUM	DISPLAY
iN 10-01-0	NCE	IMII/01030210			•	_	_	•		_	_			-		_	Š	_	_		_	•	NONE
	REFERENCE	)/IIW	•		Z	<b>Z</b>	<b>Z</b> :	Z.	Z ;	<b>~</b> }	~ ;	<b>Z</b> :	<b>~</b> 1	<b>Z</b> ;	æ ;	Z.	<; ∶	Z 1	Z :	Ζ,	Z :	Ξ;	Z
CONTROL NUMBER FU00588 SYSTEM CODE LINE BD062 D78075		T 05187		SYS CODE	BD056	BD063	BD051	BD046	BD045	80025	BD050	80065	BD066	BD067	89008	BD048	AK001	BD054	AA006	AA008	BD069	AG054	BD064
CONTROL FU00588 SYSTEM CODE BD062	KK																						

	DATE	90292			SRCVAL OTY		~	-	9	٦ :		M 	<b>-</b>		m 	~ <b>·</b>		24	•	~	7		,,	7
SHELTER TYPE 5 TON VAN	OPRS	4			SRCV	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
SHELTER TYPE 5 TON V.	Ē	E z	:	į	1000 019	•	•	1	•	•	1	•	•	•	1	1	1	•	18000	•	•	•	•	ı
GEN SYSCD G-60-6P	PHASE	3 =	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ì	HEAT	•	1	•	1	•	•	ı	•	•	•	•	•	•	1	1	•	•	•	•
		) Z			AC/DC																			
PRM MVR MODEL M931		0 2						- AC	O AC	- AC			- AC	- AC			- AC			- AC				
PRM I MODEI M931	040				WATTS		3360		9009		425	1188			4500	90		720	13004					
PRIME MOVER 5 TON	220		1 1 1		AMPS	1	28.00	1	50.00	•	3.50	9.90	1	1	37.50	.80	•	6.00	62.40	1	•	1	1	1
à X I	Š	80.7 0	1	ស	VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	208.0	120.0	120.0	120.0	120.0	120.0
MODEL AN/MYQ-4A	011	X		SUB SYSTEM COMPONENTS		2-2549	2-2550	7-0646	2-2745	6-4147	2-2551	2-2552	Ħ	щ	7-6198	3-0775	2-2649	щ	9-4053	Г	щ	阿	ស្ម	ы
		5	1	YSTEM C		5895-01-092-2549	5895-01-092-2550	7010-01-177-0646	7025-01-092-2745	7045-01-016-4147	5999-01-092-2551	5895-01-092-2552	UNAVAILABLE	UNAVAILABLE	4520-00-177-6198	6675-01-153-0775	5895-01-092-2649	UNAVAILABLE	4120-01-089-4053	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	JNAVAILABLE
D DATA	Y (HZ)	2 ×	1	SUB S	NSN	589	589	701	702	704	299	589	CNA	CNA		667	589		412	CNA	UNA	<b>VND</b>	CNA	CNA
NCLATURE ESSOR AUTOMATED DATA	FREQUENCY (HZ)	20 ×			MODEL	CP1435	TW-430	RP-309	MV-705	MX-10172	R-0526A	F.X10173	MV857	6066N10	MIL-H-52641	TT-804	CV-3661A	INCANDESCENT	18000 BTU	CV-3787	MD-1149	CV-3788	MD-1150	N/A
NOMENC	dadimo salinen	HONEYWELL			NOMENCLATURE	PROCESSING UNIT	TAPE UNIT MAGNET	PRINTER LINE	3	CLEANER MAGNET I	CARD PUNCH READE	DISPLAY KEYBOARD	DRIVE DUEL DISKE	HUMIDIFIER	HEATER SPACE ELE	PRINTER ASSEMBLY	CONVERTER FREQUE	LIGHT	AIR CONDITIONER	CONVERTER	MODEM	CONVERTER	MODEM	ISOLATOR UNIT
NSN 7010-01-158-5397	REFERENCE	DOCOMEN 1 TM117016205101			LINE	NONE	NONE	NONE		_	NONE	A24455	NONE		NONE	NONE	NONE							
CONTROL NUMBER FU00541 SYSTEM CODE LINE BD044 D78325	REFERENCE NOTINEERS	28850			SYS CODE	BD045	BD046	BD047	BD048	BD049	BD050	BD051	BD052	BD053	BD054	BD055	BD056	AA008	AK001	BD057	BD058	BD059	BD060	BD061
OFROR																								

		DATE		90330				SRCVAL OTY		•			~	ı KO	~	7	<b>-</b>	m	· ~	~
TER		OPRS		т				SPCV	S	€	· E-	· E-	E-	•	-	H	€	۲	<b>E</b>	· [-
SHELTER	TYPE S250		OTH	Z		!	BTU	COOL	0009	1	•	١	•	1	•	ı	•	•	1	•
	<b>7</b> -9-	PHASE	ا ک	z			æ	HEAT	'	•	1	•	•	•	ı	ı	ı	ı	1	٠
CEN	SYSCD ST-10-6-4	ď	m	Z				ŀ												
ρĸ	_	i	S	<b>&gt;</b>				AC/D	YC.	¥	Y	Ş	YC.	AC	¥C	¥C	¥	¥	Ş	Š
PRM MVR	MODEL M1028		418			 		ATTS	1380	150	4	70	300	100	9	250	1500	480	1800	24
	TON		240			} !						.17	9	.80	.50	10	00	10	9	.80
PRIME	MOVER 1 1/4 TON	3E	220					AMPS	12.00	1.30	•	•	2.60	~	-:	2.10	13.00	4.10	15.60	7.
	_	8	208	z				VOLTS	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0
	30		120	<b>×</b>		NENTS		Š			-	_	Ξ.	-	-	_	_	_	_	_
į	MODEL AN/TGC-30	l	110	Z	I	SUB SYSTEM COMPONENTS			4120-00-935-1608	5805-00-985-9088	3	5830-01-008-3126	5815-00-553-6061	LE	LE	6105-00-234-3504	4520-00-177-6198	5805-00-907-8300	5815-01-062-8194	5810-01-080-5613
\$		,	<b>58</b>	Z		STEM			6-00-	6-00-	MAVAILABLE	-010-	-00-	MAVAILABLE	UNAVAILABLE	-00-	-00-	6-00-	-01-0	-01-0
	PEWRI	HZ)	400	Z		UB SY		NSN	4120	5805	CNAV	5830	5815	CNAV	CNAV	6105	4520	5805	5815	5810
	ELETY	Ş	9 :	<b>&gt;</b>	1	S			-15						CENT				4 A (V	
g	ICE T	REQUE	ရှိ	Z	1			EL	CV-6-5/6-15	CV-425/V		LS-147F	TT-76A	<b>BR2009</b>	INCANDESCENT		e	TH-22/TG	AN/UGC-74A(V	5
	L OFF			Z				MODEL					Ė	BR2	UNI					KW-7D
	NOMENCLATURE CENTRAL OFFICE TELETYPENRIT		MANUFACTURER		1			贸	A23667 AIR CONDITIONER	ELEPH	IST		TER	ICP				V57729 TELEGRAPH TERMIN	YPEWR	
			INUFAC	CKAIG				NOMENCLATURE	NDITI	TER 1	WER D	X.	PEWRI	FIXT	LIGHT			APH T	TELET	
	5815-00-156-4365	3						OMENO	IIR Q	ONVER	ጀ ጀ	INTERCOM	ELETY	IGHT	IGHT	LOWER	HEATER	ELEGI	ADIO	SEC
	5-00-1	<b>E</b> .		30114				2	1667	615	2	K94880 ]	762 7				H	729 1	146 F	300 1
202	5815	REFERENCE	DOCUMENT	IMILIDELIDIGELLA	į				A23	F04	Ž Ž	<b>X</b>	<b>436</b>	NONE	NONE	2	NONE	V57	V36	H02
	D80116	REI	Ž	W.				SYS CODE	701	90	808	101	202	90	80	7	42	503	201	4
¥	38	5	3 6	1617				SYS	AK007	BEC	300	BG001	BEC	*	Y	AGC	Yes	BEC	AXC	AGO
CONTROL NUMBER FU00577 SYSTEM CODE	BE029	Š	¥ <	;																

	DATE		90330		QTY	~	-	-	-	<b>-</b>	<b>-</b>	<b>-</b>	7	~	-	17	~	
ä	OPRS DA		ع 9		SRCVAL QTY	۲	1	H	₽	<b>(</b> -	[→	H	<b>[-</b> - :	[-	۴	H	۴	
Shelter Type S280		H	Z		1000 C00I	•	١	ı	•	•	i	ı	1	ı	•	•	9006	
GEN SYSCD ST-10-6D-1		2	Z		HEAT	1	•	•	ı	ı	1	1	ı	ı	ı	•	•	
•	Δ.	S	Z >		Ac/Dc	٠.,	••		•	•	•	•	•	•	•	•	O	
PRM MVR MODEL M3582		418	Z		WATTS AC		159 AC	440 AC	800 AC	460 AC	•	620 AC	80 AC	500 AC	385 AC	340 AC	1705 AC	
PRIME MOVER 2 1/2 TON		220 240	×		AMPS W			38.00	69:	4.00	5.00	5.30	.60	4.30	3.30	2.90	14.80	
PRIME MOVER 2 1/2	VOLTAGE	208 2			/OLTS	•		•		115.0	115.0	115.0	115.0	115.0	115.0	115.0	_	
MODEL An/TSQ-84		110 120	Z	SUB SYSTEM COMPONENTS	5	4520-00-177-6198		_	_		6625-00-464-1702 1		_				-4645	
	(112)		. –	SUB SYSTEM	NUN	4520-00-	5805-00-	5815-00-	5805-00-	6130-00-	6625-00-			6105-00-	5805-00-	INAVATIARI.E	4120-00-	
LATURE CAL CONTROL COMO CTN	VONSTIGUT	Transference Transference	N N N N	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MODEL	P-13	T-13	TH-119/PC	TT-119/10	DD-3940	AN / GGM-15V	AN/FISM-181/A	LS-147C/FI		WAL 248 /B	0/047-VI	BKC7504	
NOMENC			MAGLINE	; L		NOMENCLATURE	S. S. MODELL	TELEGRAFA LENGTH	IIPEWALIEA	DOWED CITIDALY	CET CET	meen cen netrono	MODE TENERAL	502	DER DAMON DINCIN	GATOR ALBERT	AID CONDITIONED	CONDITIONS
NSN 5895-01-007-4788							E NEATER	VALUE CC.	1/3 TELE	V3/636 KEFE	DE POMES SO	TOTE OCK	MODEL CON	STATE OF STA	ţ			מוש וחה
7		KEFEKENCE	DOCUMENT 11-5895-799-14	!			N CONTRACTOR	707							•	٠.	_	•
LINE E60197	•		WGT D 5250 1			SYS CODE	AGOAZ	BEOOS	BE012	BE013	A0012	DE014	BEOLD	9	AG041	BEOIP	AA006	AROOP
FU00580 SYSTEM CODE AWO02		į	<b>3</b> . α															

			DATE		90330			OT.	_		~		-	-	-	-	-	7	7	-	7	-	10
9	<b>§</b>		OPRS D		ō m			SRCVAL OTY	S	S	E	s	S	တ	ß	E	S	S	S	S	S	×	တ
den tano	TYPE	2280	0	E	z		ם	7000 C000		1	•	•	٠	•		18000	•	•	•	1	•	•	•
	0	7-4-CT-LC	PHASE	<u>ရ</u>	z		BTU	HEAT	•	•	•		•	ı	ı	14300	ı	ı	ı	ı	•	,	ı
7 <u>4</u>	SYSCD	7 - 12	_	<u>س</u> ا	>			ا د															
٤	4		I	S)	Z			AC/D	ည	ည	<b>V</b> C	2	ይ	8	AC	¥Ç	Ճ	8	Ճ	ይ	2	¥Ç	ይ
Q/M MQQ	MODEL	V . V E		418	z			WATTS	177	1	31	56	224	٣	166	3307	S	3924	7	224	112	65	13
				240	Z			_	.85	,	53	93	2	=	0	2	80	2	4	8	8	.24	9
ARLOG	MOVER	201	35	220	Z			AMPS	~		``	.69	8.0	7	.80	15.90	. 38	14.00	.24	8.00	4.00	``	•
-	-		VOLTAGE	208	<b>&gt;</b>			VOLTS	208.0	0.8	135.0	28.0	28.0	28.0	208.0	208.0	12.0	28.0	28.0	28.0	28.0	270.0	28.0
	71-25	1		120	Z	ENTS		×				N		N	7		_						N
	MODEL OT-488/CSC-10/W	9/00*		110	<b>z</b> .	OMPONENTS			2-033	3-092	2-530	ы	3-092	es.	7-022	1-373	w	4-167	3-743	2-970	3-638	4-167	ம
	MODEL	3		28	z	O M			11-04	11-04	11-04	[LABL	11-04	LABL	00-23	30-41	LABL	11-04	00-22	11-04	11-04	11-04	LABL
	ADWV		(2)	<b>4</b> 00	<b>&gt;</b>	SUB SYSTEM COMPONENTS		NSN	7010-01-042-0331	7025-01-043-0926	7035-01-042-5308	UNAVAILABLE	5895-01-043-0925	UNAVAILABLE	4240-00-237-022	4120-00-411-3731	UNAVAILABLE	5985-01-044-1677	5820-00-223-7433	5895-01-042-9709	5895-01-043-6388	6625-01-044-1676	UNAVAILABLE
	WITE O	4	FREQUENCY (HZ)	9	z	SC			-10													œ	
	אָל אַל		EQUEN	20	Z.			ے	OU-41/GSG-10	93/G	619	822	01-70/GSG	_		H-4	MX-9842/G	44	AN/VRC-46	01/6	363	AN/GSM-208	
	CLATURE DIBECTION CRNTED ABOV	1179	F.	ပ္တဲ့	z			MODEL	00-4-	PT/493/G	C-10679	CP-1822	2-2	KG-31	<b>M</b> 56	F-18H-4	6-XX	RO-344	AN/VI	C-9901/G	CV-2863	AN/G	ပ္က
	NOMENCLATURE FIRE DIBECTI			MANUFACTURER	z.			URE	GROUP	LOTTER	AGNETIC	ROCESSO	RTILLER	, KEYIN	NATION	TIONER	EMOTE C	LECTRON		SSY COM	DATA	EST	
	NSN 7010-01-017-7040			MANUE	NOLLITON			NOMENCLATURE	CONVERTER GROUP	IGITAL PLOTTE	CONTROL MAGNETIC	ENTRAL P	CONSOLE ARTILL	SENERATOR, KEYIN	DECONTAMINATION	AIR CONDITIONES	MONITOR REMOTE	PRINTER ELECTRON	RADIO SET	CONTROL ASSY COM	CONVERTER DATA	<b>fODULE, TEST</b>	LIGHT
	01-0	;		•		•		_	•	_	Ŭ	•	•	Ŭ	_		_	_	=	•	Ü	_	3
	NSN 7010-	) 	REFERENCE	DOCUMENT	IMETER			LINE	NONE	NONE	NONE	NONE	NONE	NONE	H48904	A24575	NONE	NONE	<b>Q53001</b>	NONE	NONE	NONE	NONE
g	LINE F55750	)	REF	200	20			SYS CODE	<u>س</u>	ŭ	-	4	4	Ñ	و	4	,	m		7	0	•	o
NUMBI	LINE F557	,	!	WGT	7/84			SXS	AD079	AD093	AD081	AD094	AD074	AD095	AD09	AK024	AD09	AD07	Ę	AD077	AD080	AD090	AA019
CONTROL NUMBER FU00584 SYSTEM	CODE AD098	!	į	X .	.17																		

	DATE	91172			SRCVAL QTY		<b>~</b>	~ ~	rd ·	-d -	~ ·	~ ·			rd .		S			s 1	s 10
<b>83</b>	OPRS	m			SRC	V)	V.	V.	ν,	<b>0</b> 1	<b>U</b> ,	ν,	" •	•,	•,	٠.	•-	••	••	••	••
SHELTER TYPE S280		E z			7000	•	1	•	1	1	•	1	18000	•	•	1	1	1	•	•	•
GEN SYSCD ST-15-4-2	PHASE	× 3	1 1 1 1	ě	HEAT	•	•	•	1	•	•	•	•	1	•	•	•	1	1		•
•		w z	į		AC/DC	٠							•	٠.		•.	,,	٠.	• •	,,	•
PRM MVR Model M923		418 N				8	<u>8</u>	2	8	8	2	<b>¥</b>	¥ .	2	2	2	2	2	2	5 AC	<u>ک</u> ا
PRM M MODEL M923					WATTS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	65	•
		240 N	į		AMPS	ı	•	•	•	•	•	•	1	1	•	•	1	1	•	.24	1
PRIME MOVER 5 TON	e S	220 N			2																
	VOLTAGE	208 Y			VOLTS	•	•	•	•	1	1	1	•	1	•	•	•	ì	ı	70.0	28.0
MODEL OA-8389/GSG-10V		120 Y		ENTS	Š		9	8		52		7.	11		7.7	23	60				
EL 8389/		110 M		OMPO		2-033	3-092	2-530	M	3-092	M	7-022	1-37	M	4-167	3-74	2-97	(A)	P.	4-16	ស្ន
MODEL OA-83		8 z		O Ma		11-04	1-04	11-04	LABL	11-04	LABL	30-23	00-41	LABL	11-04	00-22	31-04	LABL	LABI	01-04	LABL
	HZ)	N N W K		SUB SYSTEM COMPONENTS	NSN	7010-01-042-0331	7025-01-043-0926	7035-01-042-5308	UNAVAILABLE	5895-01-043-0925	UNAVAILABLE	4240-00-237-0227	4120-00-411-3731	UNAVAILABLE	5985-01-044-1677	5820-00-223-7433	5895-01-042-9709	UNAVAILABLE	UNAVAILABLE	6625-01-044-1676	UNAVAILABLE
RTY	NCY (	νz				6-10				ñ				ō		9				808	
ION A	REGUE	in 22			ET.	OU-41/GSG-10	PT/493/G	C-10679	CP-1822	OJ-70/GSG	31,		F-18H-4	MX-9842/G	RO-344	NN/VRC-46	C-9901/G	•		AN / GSM-208	
ICLATURE DIRECTION ARTY	•	10 z			MODEL	ho	Y.	t	<u>-</u>	S	KG-31	M56	F-1	EX-	80-	AN.	6-0			/NA	2
NSN 7010-01-017-7039 FIRE DIRECTI		MANUFACTURER LITTON		1 4 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	a attite to namon	CONVERTER GROUP	DIGITAL PLOTTER	CONTROL MAGNETIC		CONSOLE ARTILLER	GENERATOR KEYING	DECONTAMINATION	AIR CONDITIONER	REMOTE COMM MONI	PRINTER ELECTRON	RADIO SEN	COMMUNICATIONS CO	-	DATA TERMINAL DI	•	LIGHT
-01-0	<u>pi</u>	ar.			_	. ~			_		_	- 40		_		-	!		2	1 12	E
NSN 7010	REFERENCE	DOCUMENT DATA PLATE		į	7	NON	NONE	NONE	NON	NONE	NONE	H48	A24	NONE	NONE	053	NONE	NON	NON	NON	NONE
MBER Line F83626	REF	D 1			מעט פאס		· M	-	4	. 4	· Ñ	ي	4			,	ב	. =	2		6
2		WGT 6100			200	AD079	AD09	AD081	AD094	AD074	AD095	AD09	AK024	AD097	AD073	AM	AD077	ADIO	ADIOS	AD090	AA019
CONTROL NUMBER FUG0624 SYSTEM CODE LINE AT F836		KW 15.																			

	DATE	91217			OTY	12	~	~	-		-	~	-	~
TRI.	OPRS D	6 E			SRCVAL OTY	S	ŵ	S	w	S	S	Ø	တ	ဟ
SHELTER TYPE 5 TON TRL	Ī	N N		-	7000	•	18000	•	•	3	•	•	•	•
50-2	PHASE	2 z		BTC	HEAT		12000	1	•	•	•	ı	•	ı
GEN SYSCD ST-60-6U-2	PHI	m >			Ì		15							
		o z			AC/DC	ပ္ရ	Š	Ų	¥C	٩ç	¥C	¥	YC	٧c
PRM MVR MODEL M931		4 2 2 3					0009	880	009	720	360	172	140	<b>+</b>
		240 N								•		4		<del>د</del>
PRIME MOVER 5 TON	ы	220 N			AMPS	8.00	28.80	104.00	5.00	ō.	3.00	4.	9.50	.03
<b>2, 2</b> €	VOLTAGE	120 208 2 Y Y			OLTS	0.0	208.0	0.0	0.0	0.0	0.0	120.0	0.0	120.0
6	>	120 Y	ENTS		-	٠.	•••	•••	٠.	• •	٠.			12
MODEL AN/ASM-189		110 N	NOMMO			9-6-6	7-693	4-734	006-6	M	3-525	0-092	ej.	ьj
		8 Z	O MEET			00-72	01-07	01-06	88-00	ILABL	00-75	16-00	MAVAILABLE	NAVAILABLE
AILER	(2	0 z	SUB SYSTEM COMPONENTS		NSN	6210-	4120-01-077-6931	6130-	5130-	UNAVA	7910-	4140-	UNAVA	UNAVA
emitr	CY (H	C 50 60 4	us	1										
HOP S	EQUEN	0 Z			ij	LAMPS	TM18K1202083	462	-D-661		121	_		
ATURE NIC S	F	10 z			MODEL	2	TW18	PP-7462	4	2T30	5-1021	PV-83	RK5	
NOMENCLATURE ELECTRONIC SHOP SEMITRAILER		MANUFACTURER J-E-C	1		TURE	CTURE	AIR CONDITIONER	POWER SUPPLY CHR	RTABLE	ERGENCY	LEANER	ILATION	TTIONER	BOX POWER DIST
-6114		MANU J-E-			ENCLA	HT FT	COND	ER SU	LL PO	HT EN	COMM	VENT	COND	POWE
0-234		614			NOM	1.16	8 AIR		DRI	LIG	VAC	FAN	AIR	Ô
NSN 4940-00-234-6114	REFERENCE	DOCUMENT TM11494024614			LINE	NON	A24318	NONE	NONE	NONE	NONE	NONE	NONE	NONE
5	REFE	DOCUI TM11			CODE				•	ي د	ı ıcı	•	7	. 00
) 4		WGT 16080			SYS CODE	AAOO	AK021	AD08	BD12,	AAOZ	BD12	BD12	BD12	A0008
CONTROL FU00631 SYSTEM CODE BD123		KW 60.												

			DATE	90191				SRCVAL OT'S					_			
TER		S-280-B/G	OPRS	71				SRC	S	H	S	L	۲	E O	S	S
SHEL	TYPE	S-28		H N				1000 000	•	•	•	•	•	9000	•	•
		-0 <u>2</u>	PHASE	 ႘=	* * * *	Ž	בי פונס	HEAT	•	ŧ	1	•	,	ı	•	ŧ
GEN	SYSCD	-10-	PH	m <b>z</b>			1									
		ស		ω >-				C/DC	¥Ç	ŭ	ပ္	ŭ	ŭ	ŭ	ŭ	ŭ
PRM MVR	TODEL	M35A2		418 N						_	2400 A	_	_	3565 A	760 A	193 A
-	_	TON		240 N												
ZIME	MOVER	2 1/2 1	643	220 N				AMPS	26.00	1.70	20.00	.03	1.39	31.00	24.00	6.90
ā	X	~	VOLTAGE	28 110 120 208 220 240 418			į	TS	0.9	0.0	0.0	0.	0.9	0.0	0.9	115.0
		<b>168</b>	×	120 X		ENTS				116	120	115	115			
	MODEL	NSM-14		110 N		SUB SYSTEM COMPONENTS			1520-00-177-6198	6-7	63	6.3	6-3	2-464	-638	UNAVAILABLE
	MODI	N/N		. 3 <b>8</b>		S E			771-00	NAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	0-592	00-542	LABLE
			2	o z		SYS		NSN	1520-0	<b>INAVA</b>	<b>INAVA</b>	<b>MAVA</b>	INAVA	120-0	130-0	MAVAI
		F:	X (H2	X K 60		SOF	•	~	•	_	۰	ر				
		ELEC	SQUENC	20 X							ELTA		6	AKC7504	04C/G	•
	TURE	Avco	FRI	)     			1	MODE	P-13		WYE-DELTA		BR200	AKC7	PP-11	
	NOMENCLATURE	SHELTER AVCON ELECT		TURER				2.4		IIR	ISOL	ST	G)	NER	•	CLEANER VACUUM
				MANUFACTURER DEKALB			į	ATUR		SOR A	RMER	ER DI	IXI	DITIO	UPPLY	VACU
		5-776						NOMENCLATURE	ATER	MPRES	ANSFO	N POE	GHT F	R CON	WER S	EANER
		00-43		38141	. I			2	HE	ខ	Ę	2	IJ	07 AI	18 PO	
	NSN	4940-	REFERENCE	DOCUMENT TM114940238141			1	LINE	NONE	NONE	NONE	NONE	NONE	A239	P372	NONE
í	LINE		REFE	DOCU TM11				ŎE								7
J00502 /STEM	LIN	H01		WGT 4228				SYS CODE	AG04	A003	A003	A000A	AAOO	AK00	A000A	A0037
FU00502 SYSTEM	ea Leg	16		_												
FUO	CODE	ВНО		KW 12.												

	DATE	91148				OTY	-	-	-	-	ß	~
		91				SRCVAL OTY	S	S	S	S	S	ß
SHELTER TYPE S-250	OPRS	-										
SHELT TYPE S-250		E z	•	. i		1000	•	1	1	0006	١	1
	PHASE	Z		7	BTU	HEAT	•	•	ŧ	0009	1	1
GEN SYSCD	<u> </u>	Z								•		
œ		o >-				C/DC	ဗ	ပ္	X	ပ္	ပ္	ŭ
PRM MVR MODEL M1037		Z				WATTS AC/DC	33	46	700	•	100	7 09
TON	6	Z						0	0		9	
PRIME MOVER 1 1/4 TON	ai	N Z				AMP	1.89	. 50	25.00		.86	.50
H 2 -	VOLTAGE 220 240 418	Ž				OLTS	28.0	115.0	28.0	15.0	15.0	115.0
96		<b>X</b>		ENTS		_		_		_		-
MODEL AN/GSM-236	.	Z		OMPO			2-06	5-789	7-769	5-16	ы	ы
MOD AN/	9	9 Z		O WH			0-89	86-0	0-93	0-93	LABL	LABL
	'Y (HZ)	z		SUB SYSTEM COMPONENTS		NSN	5820-00-892-0622	6130-0	5820-00-937-7690	4120-0	UNAVAILABLE	UNAVAILABLE
ORT	E) X	<b>&gt;</b>		ร						15		ENT
ANSP	FREQUENCY (HZ)	2					4	53/U	63	-9/9	ō	DESC
LATURE SHOP TRANSPORT	FRE	3 z				MODEL	RT-524	PP-2953/U	PP-4763	CV-9-5/6-15	BR2009	INCANDESCENT
NOMENCLATURE ELECT SHOP TI	ê	r L									_	•
NOME	9	GICHNER				RE		Ľ	ĭĭ	TONE	ICP	
716	M	ICHNI				CLATT		SUPI	SUP	LIQNO	FIX	
12-3	3	Ē O				OMEN	ADIO	OWER	OWER	IRC	IGHT	IGHT
-01-0	63	<u> </u>				<b>Z</b> .	39 R	888 P	45 P	138 A	1	
NSN 4940-01-012-3716	REFERENCE	DATA PLATE				LIN	R339	P38	P407	A238	NON	NONE LIGHT
73	REFE	DATA				CODE	_	_	_			
NUMBER LINE HO2173	Ę	970				SYS	<b>AM015</b>	A0003	A0008	AK047	AA006	AA008
CONTROL NUMBER FU00618 SYSTEM CODE LINE ACO40 H021	3											

	DATE	90283		OTY	e	٣	7	-	7	7	1	7	-	7	-	-	-
		6		SRCVAL OTY	U	υ	U	U	υ	U	ပ	S	ß	U	υ	ß	O
SHELTER Type S250	OPRS	_										0					
SHEL/ TYPE S250	HILL	z	<u> </u>	COOL	•	•	•	•	•	•	•	0006	•	•	•	•	•
SYSCD ST-10-6D-2	PHASE	2		HEAT	•	•	•	•	•	•	•	7000	•	•	•	•	•
GEN SYSCD ST-10	"	Z		-0													
-	o.	×		AC/DC	ŊC.	<b>A</b> C	AC	¥C	YC.	<b>A</b> C	¥C	YC.	¥Ç	AC	YC.	YC YC	Ac
PRM MVR MODEL M1037	418	Z		WATTS		90	<b>+</b>	4	15	15	10	3960	26	100	90	•	80
TON	240	Z		_		5	<u>س</u>	4	0	0	,	0	9	9	9	,	,
PRIME MOVER 1 1/4	;E			AMPS	.50	.7	õ.	ε.	1.00	3.19		33.00	₹.	99.	.83		
<b>M2</b> (1	VOLTAGE	Z		/OLTS	20.0	120.0	20.0	120.0	120.0	15.0	115.0	120.0	120.0	120.0	120.0	120.0	120.0
45	120	<b>?</b> >	ENTS	>	-	_	-			_	_			-			•
MODEL AN/TSQ-154	91	Z	SMPO.		ш	E)	E	2-535	7-784	ea	ш	6-221	9-682	ы	4-623	3-026	2-972
MODEL AN/TS	80	2	N N		LABL	LABL	LABL	0-75	1-18	LABL	LABL	1-13	1-24	LABL	1-51	1-22	1-25
	2)	Z	SUB SYSTEM COMPONENTS	NSN	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	5830-00-752-5357	5815-01-187-7844	UNAVAILABLE	UNAVAILABLE	4120-01-136-2214	5805-01-246-6826	UNAVAILABLE	5815-01-214-6237	6130-01-223-0267	6130-01-252-9724
£	¥ (н	>	SU			Į,				7					2		
GEMEN.	FREQUENCY (HZ)	z		. 1	e e	NCANDESCENT		LS-147C/FI	(C-7	2 FL-171-42	000	<b>H9KH-115P</b>	FA-1035/U	EXT. MOBILE	AN/UGC-74B(V	PP-6224/U	PP-8190/G
TURE	FR	z		MODEL	1 BULB	INCAN		LS-14	AN/UXC-7	2 FL	<b>ASP1000</b>	нэкн-	TA-1(	EXT.	AN/UC	PP-6.	PP-8]
NOMENCLATURE FACILITY MANAGEMENT	MANIFACTURER			URE	TURE		DIST			ZENITH		FIONER	DIGITA		TIONS T	PLY	ATTERY
7-0963	MANIE	GTE		NOMENCLATURE	SHT FIXT	LIGHT	K POWER	INTERCOM	FACSIMILE	MPUTER 2	INTER	AIR CONDITIONER	TELEPHONE DIGI	LIGHT	COMMUNICATIONS	POWER SUPPLY	CHARGER BATTER
1-24						Ĭ	BO	NIO	4 FA	ទូ	PR	B AII	B TE	Ĭ	<u>S</u>		£
NSN 5895-01-247-0963	REFERENCE DOCUMENT	DATA PLATE		LINE	NONE	NONE	NONE	K9488	Te196	NONE	NONE	A23828	T4540	NONE	V3614	P40750	NONE
89	REFERENC	DATA		SYS CODE	34	98	98		25	14	53	34	8	25	34	57	7.0
NUMBER LINE MO42	WGT	2382		SXS	AA024	AA008	A0008	BG	AE0	AD04	AEO	AK034	AEO	AAO.	AX0	AL057	ABOC
CONTROL NUMBER FUO0533 SYSTEM CODE LINE BEO44 M042	XX	•															

	DATE	91204		OTY		-		~	C4	-	-	~4	7	~	~	7		~	-	-	~	7	<b>-</b>	-	-	-		-	-	-		-4	-	~	-	-
ដ	OPRS D	8		SRCVAL	×	×	X:	×	æ:	×	I	I	X.	X:	×	<b>X</b>	Œ:	<b>X</b>	<b>X</b> :	X	æ :	X.	<b>X</b> :	<b>E</b> :	×	Σ	Œ	Σ	Œ	Σ		Σ	X	X	Œ	Σ
SHELTER TYPE S-661		E z		1000	•	36000	•	•	ı	1	ı	ı	1	•	ı	1	ı	•	•	•	•	1	•	•	•	ŧ	t	1	١	•		1	1	1	1	1
		) z		HEAT	•	32000	ı	•	•	•		•	6	•				ŧ		ŀ		•	•	1	ı	ı	1	,	•			ı			•	•
GEN SYSCD G-30-4	PHASE	~ >-		H		32(																														
æ		n z		AC/DC	NC.	¥C	¥C	٧	¥Ç	¥C	¥	႘	<b>Y</b> C	¥C	¥C	Ų.	¥Ç	¥C	¥C	¥	YC.	¥C	YC.	AC	¥Ç	N <sub>C</sub>	YC YC	٦ ک	AC	¥C	<b>3</b> C	NC NC	¥C	¥Ç	¥C	<b>y</b> C
PRM MVR Model M1015		2 7 7		WATTS	300	1	3307		ı	•	112	65	•	•	ı	•	1	•		•	ı	1	ı	•	65	•		•	•	1	ı	t		ı	ı	ı
U K		2 Z						,	í		7	g	,			í	,	,	,	,	,	,	,	,	o	,	,	,	,	,	,	,	J	,	,	1
PRIME MOVER CARRIER	E)	770 N		AMPS	2.50		15.80				.97	1.16													. 50											
AXU	VOLTAGE	802 X		VOLTS	120.0	208.0	208.0	120.0	120.0	120.0	120.0	28.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	208.0	208.0	208.0	120.0	120.0	120.0	208.0	120.0	120.0
38	>	120 ¥	ENTS	8	12		••		12	•	-				•				• •									8			17	12	•	•	12	12
MODEL AN/TSQ-138		S z	OMPON		Ħ	4-799	7-022	9-168	M	M	6-326	3-743	5-041	3-446	5-745	2-709	5-746	0-443	3-985	5-740	5-017	9-167	4-998	rā	4-364	0-907	9-168	Ħ	4-998	5-915	E)	E)	4-998	9-340	Ħ	ej
MODEL AN/TS	ļ	8 N Z	TEM C		ILABL	4120-01-164-7995	4240-00-237-0227	5865-01-109-1683	UNAVAILABLE	ILABL	5810-01-146-3260	5820-00-223-7433	5811-01-165-0413	00-53	01-10	01-12	01-10	01-07	00-03	5811-01-165-7405	01-15	5865-01-109-1679	5811-01-164-9984	UNAVAILABLE	5810-00-434-3644	5820-01-140-9070	5865-01-109-1689	UNAVAILABLE	5963-01-164-9987	5865-01-115-9152	UNAVAILABLE	UNAVAILABLE	5811-01-164-9983	6130-00-059-3404	UNAVAILABLE	UNAVAILABLE
	(2	9 *	SUB SYSTEM COMPONENTS	NSN	UNAVAILABLE	4120-	4240-	5865-	SVAVA	UNAVAILABLE	5810-	5820-	5811-	7035-00-533-4464	5815-01-165-7457	5821-01-122-7094	5895-01-165-7460	5821-01-070-4433	5831-00-933-9822	5811-	7025-01-155-0172	5865-	5811-	UNAVA	5810-	5820-	5865-	UNAVA	5963-	5865-	UNAVA	UNAVA	5811-	6130-	UNAVA	UNAVA
64	CY (H	o z	SU						-	3																								•		
ol se	PREQUENCY (HZ)	o z		ت.	INCANDESCENT	4-25		935	S.	AN/UXK-64 (V)	•	AN/VRC-46	<b>œ</b>	AN/UYQ-10	91	288A	0508	547	11	25	9/89	97	233	ın.	7	2 <b>,</b>	0214		893A	293A			<b>V</b> 6	28VS200Y-9		19 <b>A</b>
ATURE	F. 6	Z		MODEL	INCA	F36T4-2S	M26	C-10935	TC-DSM	N/N	KG-84	5/NZ	57958	SN/C	KY-891	RT-1288A	MX-10508	C-10547	C-1611	F-1552	MU-768/G	R-2197	MD-1233	KG-45	KY-57	R-442A	MX-1021		PP-7893A	PP-7293A			10509A	28VS		UYK-19A
NOMENCLATURE MASTER CONTROL SET		MANUFACTURER J-E-C		RE	)	FIONER	MATION	CONTROLLER DISPL	RECORDE	ESSING	KEY		LION		IL NASMI	TRANSMI	DIPLEXER TUNABLE		TERCOM	AABLE N	RY UNIT		TONICAT			RADIO	PROCESSOR SIGNAL	POWER DISTRIBUTI	PLY	PLY	61	COMPUTER BOX FAN	SIGNAL PROCESSOR	PLY	DETECTI	SIS
-7408		J-E-C		NOMENCLATURE	Ħ	AIR CONDITIONER	DECONTAMINATION	TROLLE	CASSETTE RECORD	DATA PROCESSING	GENERATOR KEY	RADIO SET	PANEL CAUTION	PLASMA DISPLAY		RECEIVER 1	LEXER 1	CONTROL RADIO	CONTROL INTERCO	FILTER TUNABLE	DISK MEMORY UNI	RECEIVER SET	MODEM COMMUNICA	S N	SEC	RECEIVER RADIO	CESSOR	ER DIS	ER SUPPLY	POWER SUPPLY	MAST DRIVE	PUTER I	NAL PRO	POWER SUPPLY	CHEMICAL DETECT	I.O. CHASSIS
1-165		E)		MON	LIGHT	-		8	CAS	_	_	_	PAN	PLA	KEY	REC	DIP	800	Ž O	FIL	DIS	REC	ON I	H	-	REC	PRO	POE	POWER	POE	MAS	S	SIG	POW	CHE	I.0
NSN 5811-01-165-7408	REFERENCE	DOCUMENT DATA PLATE		LINE	NONE	NONE	H48904	NON NO	NONE	NONE	E03028	<b>Q53001</b>	NONE	NON	NONE	S01373	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE									
& &	REFE	DATA		SYS CODE	8	õ	9	C .	۳ :	7	7		3	9 !	7	æ :	5	စ္က	<u>.</u>	22	23	¥.	ر در	۰	0	37	38	8	39	2	Ξ.	2	33	7	35	96
IL NU		37200		SXS	AAOOB	AK050	AD096	BD072	BD073	BD074	AE054	Ž	BD075	BD076	BD077	BD078	BD079	BD080	BD081	BD082	BD083	BD084	BD085	98008	AG070	BD087	BD088	A0008	BD089	BD090	BD091	BD092	BD093	BD094	BD095	BD096
CONTROL FU00627 SYSTEM CODE BD071	ŝ	30.																																		

	DATE	90330				Z.	7	٠,	7	-	7	7	-	-	7	-	-	7	-	7	-	-	-	-	~	4	16	-	~	38	7
2 ER	OPRS [	4				SRCVAL	S.	s o	ω ·	S	S	S	S	S	S	ß	ß	S	S	S	S	S	S	S	S	S	S	S	S	S	S
SHELTER TYPE M373A2		E				2000	•	ı	ı		ŧ	•	,	ı	•	,	•	ı	•	1	ı	,		•	18000	•	1	•	ł		•
				! !	BTU	Ö																			18						
GEN SYSCD ST-60-6U-2	PHA	Z				HEAT	1	•	ı	•	•	1	•	•	1	•	•	•	١	1	1	•	•	í	ſ	14000	1	1	1	1	•
GEN SYSCD ST-60	ſ	n >-		)       	ļ	ဋ																									
PRM MVR Model M52A2		o >-										ပ္	ပ္								¥			AC		AC	AC	AC	AC		
PRM M MODEL M52A2		7 Z				WATTS	392	724	4.1	151	224	•	1	112	150	405	405	257	270	9800	'	108	22880	•	3000	150	400	١	'	760	130
<b>E &amp; S</b>	- 1	7 ×				AMPS	14.00	9.00	07.7	5.40	00.	•	ı	.00	. 50	. 50	. 50	90	1.00	350.00	ı	90	104.00	•	14.40	12.50	3.30	•	ı	6.30	1.09
PRIME MOVER 5 TON	AGE						-				ω -	_	_	4		-	-				_								_		
	VOLTAGE			Ş		VOLTS	28.0	28.0	20.00	28.0	28.0	28.0	28.0	28.0	270.0	270.0	270.0	270.0	270.0	28.0	120.0	120.0	220.0	270.0	208.0	120.0	120.0	•	120.0	120.0	120.0
-143	000	>		ONENT			.677	276		1961	100	435	1331	388	308	329	1328	1943	1326	915			342	919	1931	1502	1153	1932			618
MODEL AN/TS>~14:	9	, Z		COME			_44-1	-045-	, in the	-017	-042-5	-051-6	-045-0	-043−€	-042-5	-042-0	-045-0	-051-3	-042-0	-926-	BLE	BLE	-064-7	-044-1	-077-6	-915-3	143-3	-302-	BLE	BLE	116-1
	IS	<u>,                                     </u>		SUB SYSTEM COMPONENTS		•	5985-01 - 44~1677	3633-01-043-0923		1010-01-01/-6967	5895-01-042-9709	6130-01-051-9435	7010-01-042-0331	5895-01-043-6388	7035-01-042-5308	7021-01-042-0329	5962-01-042-0328	5895-01-051-3943	5895-01-042-0326	6125-00-958-6915	UNAVAILABLE	UNAVAILABLE	6130-01-064-7342	6625-01-044-1676	4120-01-077-6931	4520-00-912-3502	6240-00-143-3153	2330-00-705-8932	UNAVAILABLE	UNAVAILABLE	6730-00-116-1618
F FAC	(HZ)	;		SUB	:	ZOZ	200	0 E	2 6	) i	28			586	70.	70.	28	586	583	61;	NS S	25	61:	99		45		23.	Z C	NO	67
MAIN	UENCY	) 					Ç	ָ פַּפָּ	001	Ç	ن	-100	3SG-1(	<b>~</b>	•	_	0		-100	<b>4</b>			~1	-208	20208		1/25A				OR 2
NOMENCLATURE ELECTRONIC EQP MAINT FACILI	FREQUENCY (HZ)	Z			i	HODEL	RO-344	00-10/636	TOC / 00 L	200	5/1066-2	591058-100	OU-41/GSG-10	CV-2863	C-10679	MX-8951	MX-8950	MX-619	586941-100	PU-545/A	PH-610	K/N	PP-7462	AN/GSM-208	TM18K1202083	P-15	W-L-101/25AT	M373A2	501	BR2009	TYPE 1
NOMENCLATURE ELECTRONIC E			1			_			•	3			_	•	ပ္	_	_	ຶ	н	_	_	z	Δ.	Ī	~		_	ER			÷
NOME	MANIIFACTIIRER	ANA				OKE	PKINTER ELECTRON	AND STVMIDS AT	DENTE LIAMONE AUTOR	RIABL	CONTROL ASSY COM	PLY	CONVERTER GROUP	CONVERTER DATA	CONTROL MAGNETI	CONTROL UNIT IN	CENTRAL PROCESSO	MEMORY UNIT MAS	PLOTTER MAP DIG	MOTOR GENERATOR	COMPRESSOR AIR	ST	PLY	ST	AIR CONDITIONE	ECT	LAMP INCANDESCEN	VAN SEMI TRAILER	CLEANER VACUUM	LIGHT FIXT ICP	VIEWER MICROFIC
8342	MANIIF	TOBYHANA	1			NOMENCLATUKE	HALL HALL	4 5	מינים בי	לו מילי	KOL A	POWER SUPPLY	ERTER	ERTER	ROL M	ROL U	RAL P	RY GN	TER M	R GEN	RESSO	FAN EXHAUST	POWER SUPPLY	MODULE TEST	CONDI	HEATER ELECT	INCA	SEMI	NER V	T FIX	ER MI
-082-		14				S	PKIN	TAME			CONT	POWE	CON	CON	CONT	CONT	CENT	MEMO			COMIC	FAN	POWE	_		HEAT	_	-	CLEA	LIGH	-
NSN 4940-01-082-8342	SNCE	TM11494048114	1		4	TIL	NONE	NO N	MESSES S	107.007 1011E	NON E	NONE	M72298	NONE	NONE	NONE	NONE	A24318	NONE	NONE	574353	NONE	NONE	103820							
	REFERENCE DOCUMENT	rM1149	•								٠, ،	<b>~</b> ,	_	<b>~</b> .	<b>~</b> ;	۷,	~	~	~	2.	٠,	<u>۔</u> ,	<b>Z</b> ,	2	~	2	2	0,	Z	2	_
NUMBER LINE M96554	MGT I	-			3000	מונים בי	2004	A 000 A	AD076	2000	200	ADO / B	AD079	AD080	AD081	AD082	AD083	AD084	AD085	AD086	AD087	AD088	AD089	AD090	AK021	AG013	AA018	AD091	AG054	AA006	AG002
<b>년</b> 4	3	19020			ų	•	• •	, 4	, 4	. "	• '	• •	~		~	~4,	~	~4,	~4,	~~,	•	~;	Æ,	~	~;	~	~	~~;	Æ.	~	~
CONTROL FU00594 SYSTEM CODE AD072	KW	20.																													

Column   C	_	DATE	1	90226				SRCVAL OTY			,,		17	10	,- M	,,	<b>~</b>
Columbia	LTER E ON VAN	OPRS	•	s S					S	S	S	S	v.	S	S	S	vs
Columber	SHEI TYPI		E	Z	!	}		1000	18000	•	1	•	1	•	•	1	•
SECONDE   LINE   NSH	00 CD	PHASE	) 20 10	Z ×			Ā	HEAT	ı	1	•	•	1	•	1	•	•
NOTE   NEW   NOMENCLATURE   NODEL	ρú		S	z				C/DC	'n	ũ	ပ္	Ş	ũ	Ş	Š	ŭ	Ç.
Columbia	PRM MV MODEL M931		1	z		 				_	_	_	_	_	-	*	250
LINE   NSN	PKZ		0 240	z						.20	.30	.80	.90	. 50	.50	.03	00.
LINE   NSN	PRIM MOVE 5-TO	TAGE	22 80	z ×		! ! ! !			•	0							
LINE   NSN	ιo.	IOA	120	>		ENTS		VOL	208		_	_	_			•	
LINE   NSN	DEL 1/MSC-2		110	z		COMPON			J.E	85-908	907-830	715-617	900-856	3LE	177-619	J.E	234-350
LINE   NSN						SYSTEM		2	AVAILA	05-00-5	05-00-6	05-00-	10-00-6	AVAILA	20-00-	AVAILA	02-00-
NOTE NUMBER  M. LINE NSN NOMEN  REFERENCE  WGT DOCUMENT HANUPACTURE  13000 DATA PLATES MILLER  AK031 NONE AIR CONDITIONEE  BE005 F04615 CONVENTER TELES  BE003 V57729 TELEGRAPH TERMI  BD016 V81707 SMITCHBOARD  AA008 NONE HEATER  AG041 NONE BLOWER	CATION	V (HZ)	60 4	_ ⊁		SUB	)   	X	5	80	Š	80	62		•	5	61
NOTE NUMBER  M. LINE NSN NOMEN  REFERENCE  WGT DOCUMENT HANUPACTURE  13000 DATA PLATES MILLER  AK031 NONE AIR CONDITIONEE  BE005 F04615 CONVENTER TELES  BE003 V57729 TELEGRAPH TERMI  BD016 V81707 SMITCHBOARD  AA008 NONE HEATER  AG041 NONE BLOWER	COMMUNI	POTENC	50	<b>&gt;</b>				12	}	425/V	22 /TG	22A/PT	AMP	ANDESCE	-	,	
NOTE NUMBER  M. LINE NSN NOMEN  REFERENCE  WGT DOCUMENT HANUPACTURE  13000 DATA PLATES MILLER  AK031 NONE AIR CONDITIONEE  BE005 F04615 CONVENTER TELES  BE003 V57729 TELEGRAPH TERMI  BD016 V81707 SMITCHBOARD  AA008 NONE HEATER  AG041 NONE BLOWER	LATUR) NTER (	Ē	ш	z				MOD		_		•	•	<b>H</b>	4	•	
NOTE NUMBER  MA LINE NSN  LINE NSN  REFERENCE  MGT DOCUMENT  13000 DATA PLATES  13000 DATA PLATES  AR031 NONE  AR031 NONE  AR003 V87729  BD016 V81707  AA008 NONE  AG042 NONE  AG041 NONE  AG041 NONE	NOMENC OPS CE		PACTURER	æ				MIRE	TTTONER	P TELEGE	H TERMIN	ARD	XT FILLOR			TSTO	
NOTE NUMBER  MA LINE NSN  LINE NSN  REFERENCE  MGT DOCUMENT  13000 DATA PLATES  13000 DATA PLATES  AR031 NONE  AR031 NONE  AR003 V87729  BD016 V81707  AA008 NONE  AG042 NONE  AG041 NONE  AG041 NONE	1-2088		MANUI	MILL				MENCLE	CNO	NVERTE	ELEGRAP	TTCHBO	LCHU FT	FRU	SATED	X DOME	LOWER
NOL NUMBER  NO E	5-00-02	<b>a</b>	1 1	ATES				JN AN.	N. A.	4615 0	7729 TI	1207	1459	T AN	H	NE P	NE B
MAT LINE N199 NGT 13000 SYS C AK031 BE006 BE006 AA002 AA004		Magaaa	CUMEN	DATA PL													
CONTROL TOOSOS NOOS KW 7. 1	NUMBER LINE N199	-						מאמ	AKOAL	RECOR	RECOR	אנסתת	A B 0 0 2	SOOK K	AC042	a cook	AG041
0 E 0 U <	CONTROL FU00508 SYSTEM CODE ANO03		2									•					

	DATE	90284			SRCVAL OTY	3	S 1	٦ د	C 5	c c	S 1	c C	s 1	ر د	c 1	s 1	c J	s 1	r 0	7 C	C	c C	C 1
TER	OPRS	7			SRC																		
SHELTER TYPE S250	E S	z	1	1	)000 D.	•	•	1	•	1	•	,	1	1	•	ı	1	10000	1	•	•	ı	1
gen Syscd ST-10-6D-2	PHASE 3 DC	z			BTU	1	1	1	1	1	1	•	•	•	1	•	•	7000	1	•	•	•	1
	v	> >-			AC/DC	်ပ	ÄČ	AC	AC	AC AC	¥C	U	<b>A</b> C	S S	U	AC.	U	U	AC	U	<b>A</b> C	U	ပ
PRM MVR MODEL M1037	418	Z			WATTE		30 A	4	30 A	80	26 A	¥ 06	Ī	35 A	40 A	Ä I	40 A		150 A	30		515 A	
PRIME MOVER 1 1/4 TON	240				AMPS WA		.25	.03	1	•	.46	.83	•	ı	.34	ı		33.00 3	1.40	ı	3.33	ı	•
PRIME MOVER 1 1/4	VGE				2		•	•			•							33	H		m		
94	VOLTAGE			S	VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0
/TTC-	120			ONENT					767	724	<b>826</b>	237	443	333	357		498	214		116			499
MODEL OL-412/TTC-46	28 110			M COMP		ABLE	ABLE	ABLE	-125-5	-222-	-246-6	-214-6	-252-5	-254-0	-752-5	ABLE	-245-6	-136-2	ABLE	-247-9	ABLE	ABLE	-130-1
	00	z		SUB SYSTEM COMPONENTS	NSN	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	7025-01-125-5767	6130-01-252-9724	5805-01-246-6826	5815-01-214-6237	7025-01-252-5443	5805-01-254-0333	5830-00-752-5357	UNAVAILABLE	5805-01-242-6498	4120-01-136-2214	UNAVAILABLE	5820-01-247-9116	<b>NAVAILABLE</b>	NAVAILABLE	5805-01-130-1499
	Y (HZ	S >-		SUE	2	ر	_		-	•		ح	•			٠		4	_		_	٦	υ,
ROUP	FREQUENCY (HZ)	Z			1	T.B	INCANDESCENT		AN/UXH-5	PP-8190/G	TA-1035/U	AN/UGC-74B(V	.54/G	C-11878/T	LS-147C/FI		SM-D-817230	H9KH-115P		AN/GRC-224	186		CV-3734T
ATURE	F 10	z			MODEL	1 BULB	INC		AN/C	PP-6	TA-1	AN/L	IR-1	C-11	LS-1		SM-I	H9K		AN/	OL-386		CG CG
NOMENCLATURE OPERATIONS GROUP	MANUFACTURER				URE	TURE		DIST	TAPE	ATTERY		TIONS T		NIT ORD		LARM PA	L SERVI	LIONER	UST	ECEIVER	TRAL PR	ZG.	
NSN 5805-01-245-9059	MANUE	GTE			NOMENCLATURE	LIGHT FIXTURE	LIGHT	BOX POWER DIST	TRANSPORT TAPE	CHARGER BATTERY	TELEPHONE DIGI	COMMUNICATIONS	KEYBOARD	CONTROL UNIT ORD	INTERCOM	CONTROL ALARM	NEL CAL	AIR CONDITIONER	FAN, EXHAUST	CONTROL RECEIV	GROUP CENTRAL	BAY ROUTING	CONVERTER
01-24		ы			-						08 TE	46 CO			2						_	_	-
NSN 5805-	REFERENCE DOCUMENT	DATA PLATE			LINE	NONE	NONE	NONE	NONE	NON	T45408	V361	NONE	NONE	K94880	NONE	NON	A23828	NONE	NONE	NONE	NONE	NOME
MBER LINE PO5439	REFI	DAT			SYS CODE	24	96	80	28	07	20	34	53	55		53	54	34	00	50	51	22	50
2	WGT	2575			SYS	AA024	AA008	A0008	AM028	AB007	AE060	AX034	AM029	AM055	BG	AM053	AM054	AK034	AD100	AM050	AM051	AM052	BE020
CONTROL FU00539 SYSTEM CODE BE049	ΚM																						

	DATE	90187		Sport tongs	; •	· ~	~	~	~	ŝ	-	-	7	-	-	S	-	~	~	-
SHELTER TYPE S-280 B/G	OPRS	m		(Dege	-	E	۲	E	۴	E	E	₽	F	۲	H	۲	<b>E</b> 4	₽	۲	E
SHELTER TYPE S-280 B		E z	! ;	BTO	3 '	•	ı	•	•	i	1	1	1	1	•	1	•	9000	•	•
GEN SYSCD G-15-6U	PHASE	z 20 × 3		Butan	i '	1	•	•	•	1	1	•	•	•	•	1	00009	1	•	•
g		w z		04/04	֝֝֝֝֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֡֓֓֡֓֓֓֓֡֓֡֓֡֓֡	Ş	AC	AC	¥C	AC.	<b>y</b> C	AC AC	AC	AC	¥C	¥C	<b>A</b> C	NC NC	AC	Ac
PRM MVR Model M35A2	ı	4 4 8 8		Marine.	202	242	200	300	20	75	550	550	4500	1955	100	300	770	3410	216	1000
5 TON	- 1	240 N		M SQM		2.20	1.80	2.70	.45	.68	5.00	5.00	40.90	17.70	90	2.70	7.00	.60	1.96	00.
PRIME MOVER 2 1/2	8	208 220 Y N								٥.			•							
	8	120 X	ENTS	1011	110.0	110.0	_		_	•	110.0	110	110.0				-	5 115.0	110.0	
MODEL ES-82A	I	110 N	COMPON		ILE	37	20-514	120-514	89-155	120-513	X.E	I.E	I.E	120-514	100-263	143-307	114-105	92-464	ILE E	42-304
	·	400 28 N N N	SUB SYSTEM COMPONENTS	Non	UNAVATLABLE	UNAVAILABLE	6740-00-420-5146	6740-00-420-5140	6645-00-089-1556	6740-00-420-5139	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	6740-00-420-5148	6740-00-400-2634	6240-00-143-3071	4520-00-114-1055	4120-00-592-4645	UNAVAILABLE	4520-00-242-3049
HIC TI	(HZ)	, 09 ×	SUB	Ä	5	5	9	9	ĕ	9	5	5	5	.9	6			₹	5	4
NOMENCLATURE DARKROOM PHOTOGRAPHIC TRANS	8	N N		14007	LS-586/U	KSR6-SS	EH-91A	EN-105A	FN-5	FM-188A		3/4 HP	15GPH	FH-19A	EH-92-A	W-L-101/37	UH-68-F	AKC7504	N/A	FW-13
NOMENCLATURE DARKROOM PHO		MANUFACTURER KELLET		a que		ATOR	PROCESSI	PROJECTI		NTING SA	FIER	FER PUMP	R HEATER	TROL UNI	IG KIT	ANDESCEN		TIONER	JST	MERSION
NSN 6780-00-400-2641				STATE LUCKSON	INTERCOM	REFRIGERATOR	MACHINE PROCESSI	PRINTER PROJECT	TIMER	LITE PRINTING	DEHUMIDIFIER	MOTOR WAT	HOT WATER HEATER	TEMP CONTROL UNI	PROCESSING KIT	LAMP INCANDESCI	HEATER	AIR CONDITIONER	FAN EXHAUST	HEATER IMMERSIC
NSN 6780-00	REFERENCE	DOCUMENT TM11678022512		TINE		NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	A23907	NONE	NONE
NUMBER LINE N86514		WGT DOC		avs con	BG003	AG068	AG057	AG058	AG059	AG060	AG061	AG062	AG063	AG064	AG065	AA015	AG066	AK006	AD088	AG067
CONTROL I FUO0501 SYSTEM CODE AG069		14. 4																		

	DATE	90296			OTY	<b>-</b>	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	æ
gs.	OPRS D	4			SRCVAL OTY	×	E	E	E	¥	×	×	I	I	I	×	X	X	H	¥	Œ	×
SHELTER TYPE M390	10 11 11 10	z			COOT		•	•	•	•	•	•		1	•	1	•	•	•	•	1	•
GEN SYSCD ST-60-4	PHASE	} <b>z</b>		ě	HEAT	22000	•	1	,	,	,	,	,	,	,	,	,	ı	ı	•	,	,
• • • • • • • • • • • • • • • • • • • •	U	2			AC/DC	Ď	ر ک	Ş	Ş	Ş	ပ္	ပ္	ğ	¥C	Ş	Ų	¥C	ပ္ခ	AC AC	¥C	AC AC	ŭ
PRM MVR MODEL M35A2	418	<b>?</b> >			WATTS	•	166	124	120	120	120 7	·	79			79	79	79	7	-	1747 2	160
TON	240	Z					.80	2	.29	.29	.29	.29	.19	.19	.19	.19	.19	.19	33			
PRIME MOVER 2 1/2	GE				AMPS	20.00	٠.	•	``	```	``	``	7	7.	7	7	7.	•	.03	.80	4.20	1.39
	8	2		10	VOLTS	208.0	208.0	416.0	116.0	116.0	416.0	416.0	416.0	116.0	416.0	416.0	116.0	416.0	416.0	416.0	416.0	115.0
-20	130			ONENTS		•		•		•	•	-	•	•	•	•			•	•	•	,
MODEL AN/MSW-20	110			COMP		072-6	237-0	BLE	165-1	350-5	141-3	167-7	BLE	BLE	144-6	070-5	054-9	BLE	BLE	BLE	184-6	BLE
	ļģ.	<b>3</b> > 1	1 1 1 1 1 1 1	SUB SYSTEM COMPONENTS	NSN	4120-01-072-6388	4240-00-237-0227	UNAVAILABLE	5895-00-165-1185	5895-00-350-5346	5895-00-141-3606	5895-00-167-7939	UNAVAILABLE	UNAVAILABLE	5820-01-144-6007	5820-01-070-5555	5810-00-054-9110	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	1430-01-184-6768	UNAVAILABLE
NOMENCLATURE PLATOON COMMAND POST	NCY	N N		S	MODEL	F-36T4-2	. W26			TPX-46	C-8738	CP-925		TD-660A/G	AN/GRC-103	AN/GRC-103	KG-27	CV-1548A/G	•		AN/MPQ-62	BR2009
NSN NOMENCLATURE 1430-01-180-5318 PLATOON COMM	GAGILLE	RAYTHEON		•	NOMENCLATURE	AIR CONDITIONER	DECONTAMINATION	PROCESSOR RADAR	RADIO TRANSMITTE	SYNCHRONIZER ELE	CONTROLLER ANTEN	PROCESSOR SIGNAL	CONTROLLER INDIC	MULTIPLEXER	RECEIVER RADIO	TRANSMITTER RADI	GENERATOR, KEY	CONVERTER TELEPH	BOX POWER DIST	DISPLAY TACTICAL	RADAR SET	LIGHT FIXT ICP
NSN 1430-01-	REFERENCE	VOLT METER			LINE	A24934	H48904	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	L22987	NONE	NONE	NONE	<b>C66602</b>	NONE
NUMBER LINE PO6103	REFERENCE WOLLD PROCESSES				SYS CODE	AK030	AD096	AT012	AT013	AT014	AT015	AT016	AT017	AT018	AT019	AT020	AE051	AT021	A0008	AT022	AT023	<b>AA</b> 006
CONTROL FU00542 SYSTEM CODE AT011	3	7.																				

	EMI	S DATE	91253			SRCVAL OTY	s S	S	s 1	S	S	s 2	s 1	<u>ب</u>	<b>.</b>	s I	S	•
SHELTER TYPE	5 TON SEMI	OPRS	E.															
SHELT	υ H	.	OTH N	!	! ;	1000	•	٠	t	•	18000	٠	1	ı	ŀ	1	١	
_	09	PHASE	ပ္က 🗷			HEAT	•	1	•	•	14000	1	•	•	•	•	•	
GEN	3-30-6U		ო ≯			l					-							
		l	o z			AC/DC	ŊC.	¥C	<b>A</b> C	¥C	AC	AC	YC	¥C	Ä	¥ς	<b>A</b> C	
PRM MVR Model	M931		4 1 8 N			TTS	720	150	108	•	328	5990	22	11936	373	187	9	
			240 N						0				<b>&amp;</b>	•	0	0	0	
PRIME MOVER	5 TON	ப	220 N			AMPS	6.00	1.25	.90		16.00	28.80	. 18	54.20	3.20	1.60	.50	
a z	ĸ	VOLTAGE	208 Y			VOLTS	120.0	120.0	0.0	0.0	208.0	8.0	120.0	220.0	5.0	5.0	120.0	
		Š	120 Y		ENTS	O <sub>A</sub>	•	12	12	12					11	1		
占	.21		110 N		SYSTEM COMPONEN		-976	•••	6.3		-062		-961	-124			-975	
MODEL	TSS-21		7 8 8		O ME		0-729	LABLE	LABLE	LABLE	1-122	LABLE	0-477	1-214	LABLE	LABLE	0-901	
	ıc	_	0 X		SUB SYSTEM COMPONENTS	NSN	6210-00-729-9768	NAVAILABLE	NAVAILABLE	NAVAILABLE	120-01-122-0626	MAVAILABLE	5650-00-477-9613	1510-01-214-1245	MAVAILABLE	NAVAILABLE	6230-00-901-9755	
	GRAPH	FREQUENCY (HZ)	¥ 60		SUB	Z	9	-	9	Þ	4	Þ	9	~	•	ם	9	
	TOPO	DUENC	N 20				S	DESCE			-3A	140					21	
ATURE	PRESS SECTION TOPOGRAPHIC	FRE	° ≥			MODEL	2 LAMPS	INCANDESCENT	63		F-18H-	LWA-2440	LUXO	SOR	PC4M	PC2M	W-L-661	
NOMENCLATURE	ESS S		URER				ы			IST	NER		GHT	SS	RY		ION	
			MANUFACTUR ADCOR			TURE	XTUR		IAUST	IER D	OLLIO		R LI	PRE	CILIA	×	CTENS	
	-1744		MANUF			ENCL	LIGHT FIXTURE	HT	EXI	ğ	CONI	TER	NIFIE	NTIN	IP AU	IP MA	LIGHT EXTENSION	
•	1-105			· .		MON	LIG	LIG	FAN	BOX	AIR	HEA	MAG	PRI	54	5	LIG	
N.S.	3610-01-105-1744	ENCE	DOCUMENT DATA PLATE			LINE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	
	4	REFERENCE	DOCUMENT DATA PLA					_	_	_	_	_	_		_	_	_	
MBER	P50154					SYS CODE	A003	A008	AD088	8000	K011	W022	A022	W023	W024	W025	H016	
2			WGT 25125			S	<	<	~	æ	<	~	<	~	⋖	⋖	<	
CONTROL NUMBER FU00636 SYSTEM CODE LINE	AW021		30.															

	DATE	90201				OTY.	18	~	~	7	-	7	-	-
SHELTER TYPE EXP 2-SIDE	OPRS [	4				SRCVAI	S 18	တ	S	S	တ	S	s	w
SHEL	Ę	z			_	1000 C00I	1	24000	•		•	•	•	•
GEN SYSCD ST-60-6U-2	PHASE				BTO	HEAT	•	23600	•	1		ı	t	•
GEN SYSCD ST-60-	<u> </u>	<b>&gt;</b>						7						
	U	Z	į			C/DC	¥	Ų	Ų	Ų	Ų	Ų	ړن	٩c
PRM MVR MODEL 5-TON	110	z				TTS A	720 A	6656 A	22 A	420 A		_	8900 A	•
13	240	Z								_	_		_	
PRIME MOVER M1022DOLL	VOLTAGE	Z				AMPS	9.00	32.00	.18	3.50	.30	1.40	30.00	1.60
W A A	OLTAG	<b>?</b> >-		ı		LTS	0.0	208.0	0.0	0.0	0.0	5.0	0.0	0.0
	2	2	 	NTS		9						11	23	12
13	9	z	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	SUB SYSTEM COMPONENTS			6210-00-729-9768	4120-01-279-5659	7-9613	ri i	7-6394	F	Ħ	ы́
MODEL	12	Z		Ä			0-72	11-27	00-47	LABI	00-13	LABI	LABI	[LABI
	(2)	Z		B SYST		NSN	6210-0	4120-0	9650-0	UNAVAJ	6230-0	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE
	٠. در	>		S										
	FREQUENCY (HZ)	Z	į				(PS	HPA-					•	112
ATURE	¥ '5	Z				MODEL	2 LAMPS	~				360	GTOZP	HUBBELL
NOMENCIATURE PRESS SECTION	dia di merio e a	TOOELE		:		FURE	KTURE	ITIONER	R LIGHT	r WATER	MERGENCY	ΛX	RINTING	LIGHT
4582	MAN MIT	TOOE	į			NCLA	T FI	COND	IFIE	Ä		<u>8</u>	S, P	E
-238-				! 		NOME	LIGH	AIR	MAGN	SINK	LIGH	PUMP	PRES	LIGH
NSN 3610-01-238-4582	REFERENCE	DATA PLATES						NONE						
-	REFER	DATA				ODE								
MBER LINE P50291		_				YS C	A003	AK026	A022	B004	A020	B005	B006	A021
J. 80	3	16140				S	<	<	<	<	<	<	<	⋖
CONTROL NUMBER FU00506 SYSTEM CODE LINE AWOO6 P5029	2	15.												

		DATE	90284			SECVAL OFY		m	<b>-</b>	-	-	7	-	7	-	-		<b>.</b>	-	-	-	-	٦	-	-
9		OPRS	8			SRCV	ပ	U	S	O	ပ	ပ	S	ပ	O	O	U	S	U	ပ	S	O	O	ပ	Ü
QAE 1470	TYPE \$250		E ×	:	· .	1000	•	1	10000	ì	1	•	•	•	•	1	•	•	1	•	1	•	1	•	1
,	SYSCD ST-10-6D-2	PHASE	) z		2	HEAT	•	١	7000	•	•	•	1	1	•	•	•	•	•	1	•	•	ı	•	1
9			w >-			AC/DC	NC.	YC YC	¥C	AC	<b>A</b> C	2	ŭ	<b>Y</b> C	ပ္ခ	ပ္ခ	ပ္ခ	¥C	Ų.	¥C	ŭ	ပ္	ğ	ပ္	¥C
AGO.	MODEL M1037		A E E			WATTE	•	06	3960	*	08	30	26	30	400		415	1	0	32		06	65		04
	TON	- 1	N A			AMPS W		.75		.03		ı	.46	1	3.33				•		•	.83		1.40	.34
00 FX	MOVER 1 1/4	NGE	N Z			Ā	•	•	33.00	•			•		ë.							•		ij	•
	-47	8	120 208 Y N		Ş.	VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0
	MODEL OL-413/TTC-47		N N		SUB SYSTEM COMPONENTS				-2214		-9724	-5767	-6826	-9116	••	-1499		••	-6498	-0333	-5443	-6237	-3644		-5357
	MODEL OL-41		Š N Z		TEN CO		UNAVAILABLE	UNAVAILABLE	4120-01-136-221	UNAVAILABLE	6130-01-252-972	7025-01-125-5767	5805-01-246-6826	5820-01-247-9116	UNAVAILABLE	5805-01-130-1499	UNAVAILABLE	UNAVAILABLE	5805-01-242-6498	5805-01-254-0333	7025-01-252-5443	5815-01-214-6237	5810-00-434-3644	UNAVAILABLE	5830-00-752-5357
		HZ)	<b>Z</b>		UB SYS	NSN	UNAVA	UNAVA	4120-	UNAVA	6130-	7025-	5805-	5820-	UNAVA	5805-	UNAVA	UNAVA	5805-	5805-	7025-	5815-	5810-	UNAVA	5830-
	ICLATURE ITIONS GROUP	FREQUENCY (HZ)	N N N		v)	MODEL	1 BULB	INCANDESCENT	H9KH-115P		PP-8190/G	AN/UYH-5	TA-1035/U	AN/GRC-224	OL-386	CV-3734T			SM-D-817230	C-11878/T	IR-154/G	AN/UGC-74B(V	KY-57		LS-147C/FI
	NSN 5805-01-244-4259 OPERATION		MANUFACTURER GTE			NOMENCLATURE	LIGHT FIXTURE	LIGHT		BOX POWER DIST	CHARGER BATTERY	-			GROUP CENTRAL PR	CONVERTER	BAY ROUTING	CONTROL ALARM PA	PANEL CALL SERVI	CONTROL UNIT ORD	KEYBOARD	COMMUNICATIONS T	T SEC	FAN, EXHAUST	
	NSN 5805-01	REFERENCE	DOCUMENT DATA PLATE			LINE	NONE	NONE	A23828	NONE	NONE	NONE	T45408	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	V36146	S01373	NONE	K94880
CONTROL NUMBER FU00536 SYSTEM	LINE P70292		A. 2615 DATA			SYS CODE	AA024	AA008	AK034	A0008	AB007	AM028	AE060	AM050	AM051	BE020	AM052	AM053	AM054	AM055	AM029	AX034	AG070	AD100	BG
0 7 %	CODE BE047	•	- <b>-</b>																						

	DATE	90330		L OTY	-	-	-	-	-	8	~	-	~	-	-	7
ğ	OPRS	m		SRCVAL OTY	S	۲	۲	H	۴	۲	H	۲	H	<b>-</b>	۲	H
SHELTER TYPE 5250	HATO	<b>*</b>	. 2	1000	0009	•	•	•	•	•	•	•	•	•	•	•
gen Syscd St-5-6-3	PHASE_	N.	BTU	HEAT	4000	ı	ł	•	i	ı	•	•	•	1	•	•
•	S	>		_ 	<b>V</b> C	ပ	ပ	Ų.	ບ	ပ	ပ	ပ	<b>Y</b> O	ပ	Ų	2
PRM MVR MODEL M1028	418	Z			3100 A	700 D	_	_	-	1200 A	-	_	-	1500 A	_	_
TON	240	Z.								•		04.	.97	•	2.10	
PRIME MOVER I 1/4 TON	AGE 8 220			AMPS	26.90	25.00	37.	1.30	ij	10.40				_		
υ	VOLTAGE 120 208		TS	VOLTS	115.0	28.0	28.0	115.0	28.0	115.0	28.0	28.0	115.0	115.0	115.0	28.0
MODEL AN/GRC-122C	110 1	<b>&gt;</b>	SUB SYSTEM COMPONENTS		-9952	-7690	-7548	-6061	-5277	-8194	-1435	-5613	-3260	-6198	-3504	-7441
MODEL AN/GR	28	<b>&gt;</b>	TEM CO		4120-00-045-9952	5820-00-937-7690	00-223	5815-00-553-6061	5815-00-999-5277	5815-01-062-8194	00-617	5810-01-080-5613	5810-01-146-3260	00-177	6105-00-234-3504	6240-00-143-7441
	HZ)	z	UB SYS	NSN	4120-	5820-	5820-	5815-					5810-	4520-	6105-	6240-
RITER	FREQUENCY (HZ)	<b>&gt;</b>	ca		0		106A			74A (V	יט					
CLATURE TELETYPEWRITER	FREQUE	×		MODEL	CE-6A-60	PP-4763	AN/GRC-	TT-76A	MD-522	AN/UGC-74A(V	PU-724/	KW-7D	KG-84	P-13		BULB
NOMENCL RADIO T	MANUFACTURER	GENERAL DYNA		URE	TIONER	PLY	INSMITTE	RITER	MODEM TELETYPEWR	ETYPEWR	MOTOR G		Z, KEY			B DC
NSN 5815-01-095-1211	MANU			NOMENCLATURE	AIR CONDITIONER	POWER SUPPLY	RADIO TRANSMITT	TELETYPEWRITER	DEM TEI	RADIO TELETYPEW	INVERTER MOTOR	T SEC	GENERATOR, KEY	HEATER	BLOWER	LIGHT BULB DC
5-01-09	8 L	-334-12			3701 AI	P40745 PC	Q32756 RA		3822 MC	V36146 RA	E IN	H02300 T	3028 GE	E HE		
	REFERENCE DOCUMENT	11-5815-334-12	İ	DE LINE		P40	032	<b>V36</b>	MSE	V36	Ó	H02	E03	NONE	NONE	NONE
NUMBER LINE Q90100	WGT DO	1962 11		SYS CODE	AK010	A0009	AM014	BEOOS	BE008	AX007	A0010	AG044	<b>AE</b> 054	AG042	AG041	AA005
CONTROL NUMBER FU00579 SYSTEM CODE LINE BEOO7 Q9010	ЖX															

	DATE	91205			SPCVAL OTY		-	T X	 	 	s 1	T	T T		 	Ω <b>X</b>	 	s e	s S	~ *	T T	S	<b>X</b>	×	S 1
TER	OPRS	-			SP																				
SHELTER TYPE S-661	AT N	Z		! i	BT0	'	•	1	36000	•	1	1	1	•	•	•	1	•	•	•	1	•	•	1	•
Я	PHASE	Z			HEAT	'	•		32000	1	1	1	•	•	•	1	•	•	•	1	•	1	•	•	•
GEN		_			و	)																			
PRM MVR Model M1015	100	-			AC/DC			AC	¥	Ž	¥	¥	¥	¥	¥	Ş	¥	AC	¥	¥	AC	¥	¥C	AC	AC
	418				WATTE	150	65	3307	•	•	•	•	•	•	ı	•	•	,	•	•	•	1	•	•	ı
PRIME MOVER CARRIER, C	240				AMPS		1.16	15.80	i	ı	•	•	•	•	ı	1	ŧ	١	1	•	•	ı	•	ı	•
PRIME MOVER CARRI	GE 220				2	! નં	Ä	15.																	
	VOLTAGE 208				VOLTS	120.0	28.0	208.0	208.0	120.0	120.0	20.0	120.0	120.0	120.0	208.0	120.0	208.0	208.0	208.0	120.0	120.0	120.0	208.0	120.0
<b>#</b>	120	>	-	ENTS	>	-		N				7				•		•	• •	~	7	-		•	-
MODEL AN/MLQ-34	110	Z		OMPO		ស្	3-743	7-022	4-799	9-1-6	9-16	9-16	9-16	9-16	9-16	9-17(	9-16	9-17(	9-16	ej	ьŝ	Ħ	9-39	9-16	Ħ
MODEL AN/MIA	28	z		N N		LABL	00-22	30-23	11-10	01-10	01-10	01-10	01-10	01-10	01-10	01-10	01-10	01-10	01-10	ILABL	ILABI.	ILABL	01-10	01-10	ILABI
easure	HZ)	<b>&gt;</b>		SUB SYSTEM COMPONENTS	NSN	UNAVAILABLE	5820-00-223-7433	4240-00-237-0227	4120-01-164-7995	5865-01-109-1687	5865-01-109-1690	5865-01-109-1689	5865-01-109-1686	5865-01-109-1697	5865-01-109-1683	5865-01-109-1701	5865-01-109-1691	5865-01-109-1702	5865-01-109-1692	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	5865-01-109-3983	5865-01-109-1680	UNAVAILABLE
TERM	CX CX	Z		S		ENT																<b>~</b>			
N TOO TOO	FREQUENCY (HZ)	z	1		<u>د</u>	INCANDESCENT	AN/VRC-46		4-2S	001	996	0214	000	97	935	39	334	967	01		5.K	AN/UYK-19B	965	680	051
ATURE R SET	E D	z			MODET.	INCA	AN/V	<b>X</b> 56	F36T4-2S	C-11001	C-10966	MX-10214	C-11000	R-2197	C-10935	T-1439	SA-2334	C-10967	0-1801		TC-D5M	AN/U	C-10965	HD-1089	C42-051
NOMENCLATURE RECEIVER SET COUNTERMEASURE	MANUFACTURER				URE		•.	NATION	TIONER	ICNAL I	ADIO FR	SIGNAL	ER DATA	SET	R DISPL	ER		MPLIFIE		T BOX	RECORDE		INDICATO	IANGER	
NSN 5865-01-008-6629	MANUI	J-E-C		•	NOMENCLATURE	LIGHT	RADIO SET	DECONTAMINATION	AIR CONDITIONER	CONTROL SIGNAL	CONTROL RADIO FR	PROCESSOR SIGNA	CONTROLLER DATA	RECEIVER SET	CONTROLLER DISPL	TRANSMITTER	SWITCHING UNIT	CONTROL AMPLIFI	EXCITER	POWER DIST BOX	CASSETTE RECORD	COMPUTER	CONTROL INDICATO	HEAT EXCHANGER	RECEIVER
NSN 5865-01-	REFERENCE	DATA PLACE			LINE	NONE	953001	H48904	NONE             NONE	NONE	NONE	NONE	NONE												
73	REFERENC	DATA			CODE	æ		v	c	en.	•	œ	c	_	~	~	_	<b>4</b> 0	<b>ک</b>	en.	3	v	7	ge.	•
CONTROL NUMBER FUJO628 SYSTEM CODE LINE BD097 R40073	MGT	27500			SYS CODE	AA008	¥	AD096	AK050	BD098	BD099	BD088	BD100	BD101	BD072	BD102	BD103	BD104	BD105	<b>N</b> 0008	BD073	BD106	BD107	BD108	BD109
CONTROL FUO0628 SYSTEM CODE BD097	K	.09																							

BELVOIR RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

NSN						<b>式</b>	WER (	SING	INVE	POWER USING INVENTORY REPORT	REPORT	e.								
FREQUENCY (HZ)	LINE N S25447 5	SN 805-01-2	44-4257	NOMENCLA SMALL EX	VIURE CI. NO	Ö			MODE AN/T	TC-48	(V) 1	PR.	ME /ER /	2 2 2	RM MVR ODEL 1037	GEN SYS	CD 10-6D-2		ILTER 0	
GTE N N N N N N N N N N N N N N N N N N N	M 5	RENCE			FRE	QUENC	ZH) X:	)   			ION SC.	TAGE			)°		PHASE	1	OPRS	DATE
	Ĕ	PLATE	GTE	ACI URER	Z z	2	2 ×	g z		Z	, V Y	Šz		) * Z	2 Z	o ~	) Z	E z	7	90283
							SUB	SYST	EM CC	SUB SYSTEM COMPONENTS	STA						STRANCOMOC WALSON BITS			

	OTY	m	٣	-	-	-	-	-	н	-	7	н	~	-
	SRCVAL	U	U	U	υ	S	S	υ	U	U	U	ပ	U	ပ
	1000	1	•	•	ŀ	1	0006	•	ı	ı	ı	ı	ı	1
BTU	HEAT	1	1	•			7000	•			•			ı
	AC/DC	ΥC	<b>y</b> c	<b>y</b> c	<b>y</b> C	AC	<b>y</b> C	AC	AC	AC	AC	<b>y</b> c	AC	<b>V</b> C
	WATTS	9	06	4	80	56	3930	100	20	40	35	65	160	150
	AMPS	.50	.75	.03	1	.46	33.00	.80	.16	1	1	1	1	1.40
	VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0
	NSN	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	6130-01-252-9724	5805-01-246-6826	4120-01-136-2214	UNAVAILABLE	5810-01-213-8200	UNAVAILABLE	5805-01-254-0333	5810-00-434-3644	5805-01-253-6148	UNAVAILABLE
	MODEL	1 BULB	H		_	TA-1035/U				MD-1231(P)/T			SB-4303(P)/G	
	NOMENCLATURE	LIGHT FIXTURE	LIGHT	BOX POWER DIST	CHARGER BATTERY	TELEPHONE DIGITA	AIR CONDITIONER	MODULE LOGIC GRO	T SEC	MODEM, GROUP POW	CONTROL UNIT ORD	T SEC	SWITCHBOARD TELE	FAN, EXHAUST
	LINE	NONE	NONE	NONE	NONE	T45408	A23828	NONE	T08971	NONE	NONE	S01373	NONE	NONE
	SYS CODE	AA024	AA008	A0008	<b>AB</b> 007	AE060	AK034	AM058	AG071	AB008	AM055	AG070	AE061	<b>A</b> D100

	DATE	90330			8	1 2 2 2	' 7	7	7	~	-	-	-	-	-	-	~	4	~	7	~	-	~
ğ	OPRS	m				S SILVAL WIT	S	S	S	S	S	w	တ	S	S	တ	S	S	S	S	S	လ	S
SHELTER TYPE S280		E N	!	! }		300	1	1	•	1	1	1	•	1	•	1	1	1	•	•	ı	1	ı
GEN SYSCD ST-10-6D-2	PHASE	~ Z			BTO	TEAT	•		•		,	1	•	•	•	,	,	,	,	1	,	,	,
		w >-			6	) () ()	ίÕ	ŭ	<b>A</b> C	¥C	<b>Y</b> C	کر ا	ũ	AC	ŭ	Ac	ŭ	AC	ŭ	Q	¥C	AC.	<b>A</b> C
PRM MVR Model M35A2	ļ	418 X				1705	158	125 A		Ī	•	•	1	1		-	1			1500 2			1
TON	- 1	240 N			-	AMPS WA		1.00	.26	1.00	ı	•	ı	ı			1	1.30			4.30	•	
PRIME MOVER 2 1/2	AGE	270 N				Ī	•			-	_	_	_	_	_	_	_			_		_	_
	S	120 208 Y N		TS	101	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0
MODEL AN/TSC-93A	- 1	110 N		MPONEN		-4645	-9110	-8425	-8364	-8795	-2722	-5908	-2195	1-6476	-3421	-6401	-1980	-9768		-6198	-3504	-6229	-0155
	ļ	8 2 2		TEM CO		NSN 4120-00-592-4645	5810-00-054-9110	6805-01-028-8425	5805-01-028-8364	5805-00-069-8795	5820-01-200-2722	5815-01-114-5908	5895-01-112-2195	5820-01-043-6476	5895-01-042-3421	5895-01-109-6401	5895-01-101-1980	6210-00-729-9768	JNAVAILABLE	4520-00-177-6198	6105-00-234-3504	5895-01-109-6579	5805-00-000-0155
IAL SAT	(HZ)	0 z		SUB SYSTEM COMPONENTS		NUN A 1 2 0	5810-	6805-	5805	5805-	5820-	5815-	5895-	5820-	5895-	5895-	5895-	6210-	UNAVA	4520-	6105-	5895-	5805-
TERMIN	JENCY (	7 × 60		<b>3</b>				•	5A/G	9/8					_	_	~	ຜ	ESCENT			8.	7/TSC
ATURE CATIONS	FREQU	N N K N N N N N N N N N N N N N N N N N			18.00	MUDEL AKC7504	KG-27	TD-1069	TD-1065A/G	CV-1548/G		F-1516		MD-945	AM-6701	BZ-236A	C-10273	2 LAMPS	INCANDESCENT	P-13		CV-3198A	RT-1287/TSC
NOMENCIATURE COMMUNICATIONS TERMINAL SAT		TURER				TURE	R, KEY	XER	ATA	R TELEPH	OR CONTR	NIT BAND	NIT BAND	GITAL DA	R RADIO	ALARM	AL CAPAB	FIXTURE				R FREQ	TRANSMI
NSN 5895-01-113-5344		MANUFACGICHNER			. NORMANIA P	ATP CONDITTONE	GENERATOR, KEY		BUFFER DATA	CONVERTER TELE	TRANSLATOR CONT	FILTER UNIT BA	FILTER UNIT BA	MODEM DIGITAL	AMPLIFIER RADI	MONITOR ALARM	SERVO DUAL CAPI	LIGHT FI	LIGHT	HEATER	BLOWER	CONVERTER FREQ	RECEIVER TRANS
NSN 5895-01-	REFERENCE	DOCUMENT 11435HFC01	1		924	A23907	L22987	T21130	H35599	F05376	NONE	NONE	NONE	NONE	NONE	NONE							
63	REFE				9000	SIS CODE	AE051	AE056	AE055	BD015	AM033	AM023	AM034	BE018	AM022	AM024	AM026	AA003	AA008	AG042	AG041	BE017	AM035
1 0 T		MGT 3460			Š	AKC	AEC	AEC	AE(	BD	Ā	AMC	¥	BE(	<b>Z</b>	Ž	AM	¥	¥¥	AG	ĄĞ	BE	Æ
CONTROL NUMBER FU00586 SYSTEM CODE LINE AXOO3 S349	i	× ′																					

	DATE		90323				L OTY	-	20	7	7	~	-	-	
	OPRS		4				SRCVA	S	S	S	S	S	S	S	
TYPE S280		HIO	z	1	!	P	1000 2001	0006	•	1	•	1	١	•	
<u>.</u>	IASE	႘	z			BI	IEAT	000	•	1	•	•	ı	ı	
3.4.8CD	ā	٦	*				ł								
		ဟ	<b>&gt;</b>				AC/DC	Ų	Ş	<b>Y</b> C	AC	YC	YC YC	<b>y</b> c	
MODEL M35A2		418	Z				TTS	432	800	500				4	
		240	z				S. WA	0	0	0				e.	
1/2	ĸ	220	×				AMP	16.5	6.9	4.3	۳.	26.0	ĸ.	•	
<b>E</b> 0	OLTAG	208	*									5.0	5.0	5.0	
	>	120	>		ENTS								11	11	
EL 39-6	•	110	Z		MPON			3-499	9-616	1-350	2-535	7-619	6-3	60	
MOD S-6					Č X			01-10	30-72	30-23	30-75	00-17	LABL	LABL	
RONIC	(HZ)	60 400	×		SUB SYS		NSN	4120-(	6210-(	6105-(	5830-(	4520-(	UNAVA	UNAVA	
ELECT	UENCY	20	z					326	S		C/FI				
ATURE	FREQ	ည	Z				MODEL	ECU9HC	2 LAMP		LS-147	P-13			
NOMENC		FACTURER	NER				TURE	ITIONER	KTURE				VACUUM	R DIST	
-6853		MANU	GICH				ZNCLA!	COND	IT FIX	ER	RCOM	TER TER	NER	POWE	
-127-		•	8				NOM	AIR	LIG	BLO	INT	HEAT	CLE	BOX	
	ERENCE	UMENT	E11415HF												
NE 5169	REF	Ω Δ	2				CODE	60	33	1		2	2	8	
LII S4		WGI	3790				SXS	AKO	AAOC	AGO	BG	AGO	AGO	AOO	
CODE BH012		KW	10.												
	CLATURE MODEL MOVER SHELFER ELECTRONIC S-639-G 2 1/2 TON	LINE NSN NOMENCLATURE MODEL MODEL SYSCD TYPE S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G 2 1/2 TON M35A2 G-30-6U 5280 REFERENCE PREQUENCY (HZ) VOLTAGE OPRS	LINE NSN NOMENCLATURE MODEL MODEL SYSCD TYPE S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G 2 1/2 TON M35A2 G-30-6U S280 REFERENCE FREQUENCY (H2) WGT DOCUMENT MANUFACTURER DC 50 60 400 28 110 120 208 220 240 418 S 3 DC OTH	LINE NSN NOMENCLATURE MODEL MODEL SYSCD TYPE S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G 2 1/2 TON M35A2 G-30-6U S280  REFERENCE WGT DOCUMENT MANUFACTURER DC 50 60 400 28 110 120 208 220 240 418 S 3 DC OTH 3790 TO&E11415HFCO4 GICHNER N N Y N N N Y Y N N N Y Y N N N 4	LINE NSN  LINE NSN  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  REFERENCE  WGT DOCUMENT  MANUFACTURER  N Y Y N N N N N N N N N N N N N N N N	LINE NSN  LINE NSN  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  REFERENCE  WGT DOCUMENT  MANUFACTURER  N N N N N N N N N N N N N N N N N N N	LINE NSN  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  REFERENCE  WGT DOCUMENT  MANUFACTURER  NOVELTAGE  VOLTAGE  VO	LINE NSN  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  2 1/2 TON M35A2 G-30-6U  S280  REFERENCE  WGT DOCUMENT  MANUFACTURER  DC 50 60 400 28 110 120 208 220 240 418 S 3 DC OTH  3790 TO&E11415HFCO4 GICHNER  N Y N N N Y N N A  SUB SYSTEM COMPONENTS  BTU  SUS SYSTEM COMPONENTS  BTU  SCVA	LINE NSN  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  REFERENCE  WGT DOCUMENT  MANUFACTURER  N Y N N Y N N N Y N N N Y N N N Y N N N Y N N N Y N N N Y N N N N N N N N N N N N N N N N N N N N	LINE NSN  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  S45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC S-639-G  REFERENCE  WGT DOCUMENT  MANUFACTURER  WGT DOCUMENT  MANUFACTURER  N N N N N N N N N N N N N N N N N N N	LINE NSN  NOMENCIATURE  \$45169 5411-01-127-6853 MAINT SHELTER ELECTRONIC  \$5-639-G  \$2 1/2 TON M35A2  \$280  \$280  REFERENCE  WGT  DOCUMENT  MANUFACTURER  MANUFACTURER  N  N  N  N  N  N  N  N  N  N  N  N  N	LINE NSN   NOMENCIATURE   MODEL   MODEL   MODEL   SYSCD   TYPE	LINE   NSN	LINE NSN	LINE   NSN

FUODS	CONTROL NUMBER FU00528	æ																		
SYSTEM	1											PR	IME	PRM	PRM MTR	GEN		SHEL	SHELTER	
CODE		<u> </u>	NSN		NOMENCLA	TURE				EL		S.	VER	MOD	EĽ	SYSCI	^	TYPE		
BD070		S74490	2330-00-	2330-00-772-5273	VAN SEMI TRAILER EXPANDABLE	TRAIL	ER EX	ANDABLI	M313	ღ		Ś	S TON	M931	-	G-30-6U	.eu	5-T0	5-TON EXP	
		REFE	REFENENCE			FREO	UENCY	(HZ)			8	LTAGE				_	PHASE		OPRS	DATE
KM	WGT	D000	ENT	MANUE	MANUFACTURER	ည	20	400		110	120	208	220 2	40 41	180	3	DC OTH	PITO		
6	73	TM92	TM923302384	BOYERTOWN	LOWN	z	z	N Y N		z	>	>	z	N N X X N N	Z	*	Z	z	e	90276
							-													
			1											1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	1	1 1 1 1 1 1 1	;		
								SUB SYSTEM COMPONENTS	STEM C	OMPONI	ENTS									
													•				m	BIG		
	SXS	SYS CODE	LINE	NOMENCLAT	URE	MODEL		NSN			IOA		AMPS	WATTS	AC/	ł	HEAT	COOL		SRCVAL QTY
	AK02	33	A24900	AIR CONDI	TIONER	CB-36-08-360	08-36		-00-	5-5348	3 208		16.50	3432	YC.			36000		-
	AA008A	)8A	NONE	NONE LIGHT INCANDESCE	ANDESCE			UNAV	<b>VILABL</b>	ьñ	120		11.20	1350	¥		•	1	ß	18
	AG056	99	K26301	HEATER SP	ACE	UH-68F		4520	-01-05	4520-01-050-5628	3 120	120.0	14.00	1680 AC	AC	_	00009	1	w	~

	DATE	0000				SRCVAL OTY	8	•	4	4	7	8	N	~	S	-	-	S	4	9	*	~	•	8	9	8	<b>-</b>
TER	OPRS	~	,			SRCV	Š	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
SHELTER TYPE S280		HTO H	:	!	BTU	COOL	9000	•	ι	•	t	ı	ŧ	•	t	ı	ı	ı	١	1	1	ı	•	l	•	1	ŧ
GEN SYSCD ST-15-6U	PHASE	က က	4	 	Ä	HEAT	•	•	•	•	•	•	1	•	•	•	•	•	1	•	1	•	•	ı	•	1	ı
		s z	:			AC/DC	AC.	AC	YC V	AC	AC	NC.	ບ	<b>V</b> C	ບ	AC	AC AC	ပ	<b>V</b> C	AC	AC	AC	AC	AC	ပ	AC	<b>A</b> C
PRM MVR MODEL M35A2		4 18 v	:			WATTS A	3410 A	316 A	180 A	500 A	Ä	-	< ·	-	-	Æ I	Ā I	- ×	< .	× .	241 A	120 A	480 A				
TON		24 0 4	:	i !								ı	1		•			1	,					~			.30
PRIME MOVER 2 1/2	E	220 20	:			AMPS	29.60	2.70	1.50	4.30											2.10	1.00	4.17	26.00	2.00	٦.	ς.
	8	0 208 *	•	S		VOLTS	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0
7-85A	1	110 120 N N		ONENT			1645	110				5279	1434							580	1402		1795			1071	357
MODEL AN/TSC-85A		28 N		COM			1-265-	-054-	-826-	-028-	-112-	-109-	-156-	-045-	-114-	-109-	-196-	-043-	-101-	-109-	-109-	-028-	3-690-	1-177-	1-729-9	-143-	-752-
СОМИ	(ZH)	60 4 00 N	:	SUB SYSTEM COMPONENTS		NSN	4120-00-592-4645	5810-00-054-9110	5820-00-928-3382	6805-01-028-8425	7025-01-112-6311	5895-01-109-6579	6130-01-156-0434	5895-01-042-3421	5815-01-114-5908	5895-01-109-6401	5820-01-196-7377	5820-01-043-6476	5895-01-101-1980	5895-01-109-6580	5895-01-109-6402	5805-01-028-8364	5805-00-069-8795	4520-00-177-6198	6210-00-729-9768	6240-00-143-3071	5830-00-752-5357
VCLATURE INAL SATELLITE COMM	FREQUENCY (HZ)	N 20	•	 		MODEL	AKC7504	KG-27	TD-660/BG	TD-1069	TD-1337	CV-3198A	PP-7712V2	AM-6701	F-1516	BZ-236A	C-11109	MD-945	C-10273	CV-3201A	MX-965A	TD-1065A/G	CV-1548/G	P-13	2 LAMPS	W-L-101/37	LS-147C/FI
NOMENC		GICHNER				NOMENCLATURE		GENERATOR, KEY		_		යු	POWER SUPPLY		AND			MODEM DIGITAL DA		回	ЕСНО	-	TER TELEPH			ANDESCEN	INTERCOM
NSN 5895-01-113-5343	REFERENCE	TOLE 11435HFC01					-	_	_	_ 0	_	_		•		_				NONE		_	9	,i.,	_	~	K94880 I
LINE S78466	REFE					SYS CODE	AK006	AE051	AE050	AE056	AE057	BE017	A0013	AM022	AM023	AM024	AM025	BE018	AM026	BE019	AM027	AE055	BD015	AG042	AA003	AA015	BG
FU00590 SYSTEM CODE AX002	3	7.																									

	DATE	91257				ALO J	ν.	*	-	-	-	-	-	7	-	-		7	-	-	~	-	7	-
SHELTER TYPE 5 TON SEMI	OPRS	4				SRCVAL QTY	ο (	S)	S	တ	S	S	S	တ	S	S	တ	တ	S	S	တ	S	S	w
SHELTER TYPE 5 TON S	E	Z			J	1000 000	•	1	•	•	18000	1	•	1	•	1	1	•	•	i	•	ı	1	•
<b>.</b> 9	PHASE	<b>2</b>	1	i	BIO	HEAT	1	ı	1	1	14000	ł	•	ı	ı	1	•	•	•	•	1	ı	ı	•
gen Syscd G-60-6u	ר"	n >=			ı						٦													
HVR T		0 Z				AC/DC	٧ •	¥	¥	Ä	¥C	<b>A</b> C	¥Ç	<b>A</b> C	AC	¥	¥C	¥C	¥C	AC	YC.	¥Ç	AC	AC
PRM MVR MODEL M931	7.10					WATTS	1260	120	108	•	3328	1	•	•	ŧ	ı	•	ı	480	•	•	•	•	90
N & **	270					_	10.50	1.00	96.	•	16.00	ı	1	•	•	í	•	•	4.17	•	1	ſ	•	.75
PRIME MOVER 5 TON	GE					2	0.	ij	•		16.								4					•
	VOLTAGE			ro.		VOLTS	120.0	120.0	120.0	120.0	208.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	115.0	120.0	120.0	120.0	120.0	120.0
3-12	130			NENT				•••	•	•						-			•	•			•	394
MODEL ADC-TSS-12		2		COMP			6210-00-900-8560	3LE		BLE	4120-01-122-0626	1260-01-061-7081	3610-01-123-7782	6740-00-165-7267	BLE	9LE	BLE	7025-01-121-4099	7910-00-205-3400	6675-01-180-3869	6740-00-797-7361	BLE	BLE	6230-00-137-6394
24	10			YSTEM			-00-0	UNAVATLABLE		MAVALLABLE	0-01-	0-01-	0-01-	-00-0	MAVAILABLE	MAVAILABLE	NAVAILABLE	5-01-	-00-0	5-01-	-00-0	UNAVAILABLE	UNAVAILABLE	-00-0
SET	(HZ)	2	j 1	SUB SYSTEM COMPONENTS		NSK	621	Y 5		CNA	412	126	361	674	CNA	AND.	CNA	702	791	667	674	NA CNA	ZN5	623
NOMENCLATURE TOPOGRAPHIC SUPPORT SET	FREQUENCY (HZ)	0 ×						SCENT			~	48	Œ	00		10								
RE C SUP	FREQU	n <b>z</b> .	1			MODEL	LAMP	INCANDESCENT			F-18H-3A	AN/UYK-48	185-FL-M	MIM335100	LQ-2550	QMS-PS810	BC-200B	9872-C	MU-11	910563	AR120A	F-486	BC-750A	
CLATU RAPHT			1			_	,					_		_	Š	Ö	Ä		Š	91(	_	_	m	
NOMENCLATURE TOPOGRAPHIC	MANITER CONTIDER		1			일	LTCO		ī	DIST	IONER	HOTOGI	ON SE	E LIG		NE.	걸	RAPHIC	ANER		PRETE	YSTEM	OWER	LIGHT EMERGENCY
	ANTIER	ADCOR	1			CLATO	FIXT		XHAUS	POWER	DIDIO	FIC P	DUCTI	STAG	뚔	MACHI	SUPP	ER, G	M CLE	SCAN	INTER	TER S	COMPUTER POWER	EMER
105-5	7	<b>: &lt;</b>	 			NOMENCLATURE	LIGHT FIXT FLUOR	LIGHT	<b>FAN, EXHAUST</b>	BOX, POWER DIST	AIR CONDITIONER	ANALYTIC PHOTOGR	REPRODUCTION SET	SPLIT STAGE LIGH	PRINTER	COPY MACHINE	POWER SUPPLY	PLOTTER, GRAPH	VACUUM CLEANER	MICROSCAN	PHOTOINTERPRETER	COMPUTER SYSTEM	COMPU	LIGHT
NSN 6675-01-105-5761	ω E	ATE					ý			NONE		NONE	4	NONE		NONE		NONE	E33083	NONE	NONE	NONE	NONE	NONE
	REFERENCE	DATA PLATE	;				3	2	2	2	2	2	88	2	2	2	2	2	E3	Š	2	2	2	2
MBER LINE T01973						SYS CODE	AAOOZ	AA008	AD088	A0008	AK011	AW010	AW011	AW012	AW013	AW014	AW015	AW016	BD148	AW017	AW018	AW019	AW020	AA020
J. S.	1	28015				S.	₹:	\$	¥0	8	AK	AK	AM	AK	AW	AK	AW	AM	B	AW	AK	AK	AW	¥
CONTROL NUMBER FU00635 SYSTEM CODE LINE AW009 T019	32																							

			DATE	01263				L OTY	Φ	4	-	-	~	7	1	-	-	1	
rg.		5 TON SEMI	OPRS	•	•			SRCVAL QTY	S	S	တ	S	S	S	တ	S	ຜ	S	
SHELTER	TYPE	S TON	J	H.TO	•		9	T000	•	1	1	•	18000	1	1	ı	•	•	
		Ð	PHASE	ပ္က	4		BTU	HEAT	١	ı	•	•	14000	ı	1	•	•	•	
GEN	SYSCD	G-60-6U	ā.	m >	•			J					ĭ						
	٠.			w 2	4			AC/D	AC	<b>A</b> C	AC	<b>A</b> C	AC	AC	AC	¥	AC A	<b>y</b> C	
PRM MVR	MODEL	M931		418 N	4			ATTS	1260	120	108	1	9568	1540	621	299	3749	90	
•		_		240	•			AMPS W		00.1	.90	,	00	7.00	5.40	5.80	6.30	75	
PRIME	MOVER	S TON	GE	120 208 220	4	!		¥	10.	<u>-</u>	٠		46.00	7.	ທີ	'n	16.	•	
			VOLTAGE	208 208	•			VOLTS	120.0	120.0	120.0	120.0	208.0	220.0	115.0	115.0	230.0	120.0	
		3-16		120	•	ONENT				• •	•	_						394	
	MODEL	ADC-TSS-16		28 11 N	4	SUB SYSTEM COMPONENTS			6210-00-900-8560	BLE	BLE	BLE	076-1	3615-01-171-3309	7610-00-030-2032	174-1	3610-01-236-9998	6230-00-137-6394	
					<b>.</b>	YSTEM		_	-00-0	NAVAILABLE	NAVAILABLE	NAVAILABLE	0-01-	15-01-	-00-07	-00-0	0-01-	-00-01	
		TION	(HZ)	00 400	4	SUB S		NSN	621	<b>-</b>	SNS	NO	412	361	761	761	361	623	
		TOPOGRAPHIC REPRODUCTION SE	UENCY	DC 50 60 4	E	į.				NCANDESCENT			<u>د</u>						
	URE	IC RE	FREO	ည် ကို	•			MODEL	LAMP	NCAND	3		F-18H-3	8	ᄕ	AK	92CS		
	NOMENCLATURE	GRAPH			-				m	H	9				ט	7		<b>.</b>	
	NOME	TOPO		MANUFACTURER		 		URE	T FLU		UST	R DIS	TIONE	EDDER	ΓĽ	CHER	TER	RGENC	
		6443		MANUE				SNCLAT	IT FIX	£	EXHA	POWE	CONDI	SR SHR	R DRI	STIT	ZR CUT	LIGHT EMERGENCY	
		1-105-			•			NOM	9 LIG	LIG	FAN,	BOX	3 AIR	PAPI	PAPI	WIR!	PAPI	LIG	
	NSN	3610-01-105-6443	ENCE	DOCUMENT DATA DIATE				LINE	L6145	NONE	NONE	NONE	A2446	NONE	NONE	U4070	NONE	NONE	
	Z	45 3	REFERENCE	DOCUM															
CONTROL NUMBER FUO0637 SYSTEM	LINE	T022						SYS C	AA002	AA008	AD088	A0008	<b>AK012</b>	AW027	AW028	AW029	AW030	AA020	
FROL N 3637 FEM	61	92		Ċ															
CONTROL FUO0637 SYSTEM	CODE	AW026		MX C	3														

	DATE		91253				COTY	9	4	-	-	~	-	-	-
SHELTER TYPE 5 TON SEMI	OPRS		7				SRCVAL OTY	S	S	တ	S	w	S	S	S
SHELTER TYPE 5 TON S		E	z			7	C001	1	•	1	ı	18000	•	•	t
Ð	PHASE	2	z			BTC	HEAT	•	•	•	•	14000	•	•	
GEN SYSCD G-60-6U	¥	۳	*				l								
œ		S	Z				AC/DC	ŊÇ.	ŊC V	¥	¥C	YC.	YC Y	Ş	<b>Y</b> C
PRM MVR MODEL M931		418	z				TTS	840	120		•		1950	90	480
		240	z							0	,	•	•	z,	_
PRIME MOVER 5 TON	e	220	z				AMP	7.00	1.0	.90		16.00	22.50	.7	4.17
A ≇ W	VOLTAGE	110 120 208 220 240 418	X				OLTS	0.0	0.0	120.0	0.0	0.8	0.0	0.0	115.0
	>	120	>		ENTS		8		12	12	12				
MODEL ADC-TSS-3		110	z		OMPON			6210-00-900-8560	ы	m	ы	120-01-122-0626	1-731	7-639	5-340
ADC		28	z		TEM			06-00	NAVAILABLE	NAVAILABLE	MAVAILABLE	01-12	01-20	00-13	00-50
Ęų.	(2	100	z		SUB SYSTEM COMPONENTS		NSN	6210-	UNAVA	UNAVA	UNAVA	4120-	3615-	6230-	7910-00-205-3400
RT SE	E) 25	9	>-		S				ENT						
SUPPOI	EQUEN	50 60 4	Z					Š	NCANDESCENT			F-18H-3A			<b>ب</b>
ATURE PHIC	E	ğ	z				MODEL	3 LAMP	H	9			-		MU-11
NOMENCLATURE TOPOGRAPHIC SUPPORT SET		ACTURER	ADCOR				URE	T FLUOR		UST	R, DIST	TIONER		RGENCY	EANER
NSN 6675-01-105-5753		MANUE	ADCOR	•			NOMENCLAT	LIGHT FIX	LIGHT	FAN, EXHA	BOX, POWE	AIR CONDI	SHREDDER	LIGHT EME	VACUUM CLEANER
NSN 6675-01-:	REFERENCE	MENT	DATA PLATE				LINE	L61459	NONE	NONE	NONE	NONE	NONE	NONE	E33083
s S	REF						SYS CODE	AA002	AA008	AD088	A0008	AK011	AW032	AA020	BD148
CONTROL NUMBER FUO0638 SYSTEM CODE LINE AW031 T0316			60. 30535												

			DATE		91253			QTY	σ	4	-	-	7	-	7	~	-	-	-
es		SEAL	OPRS D		4			SRCVAL QTY	S	Ø	S	Ø	Ø	တ	Ø	တ	ß	S	ß
SHELTER	TYPE	NOL C	_					2000	•	ı	ı	•	00	•	1	1	,	1	
83	<b>E</b> + (	n		OTH	z	<b>;</b>	BTU	8					18000						
	į	20	PHASE	2	z		80	HEAT	ı	•	•	•	14000	•	•	t	ı	ı	1
GEN	SYSCD	G-30-60	Δ.	۳	<b>&gt;</b>			l					•						
		_		S	2			AC/D	AC	¥C	AC	AC	<b>A</b> C	ÄC	¥	<b>A</b> C	¥Ç	<b>y</b> C	AC
PRM 1	MODEL	M931	ļ	418	Z			ITTS	1260	120	108	1	1328	ı	22	•	•	ı	90
				240							٥		0	;	80				Īυ
PRIME	MOVER	Į.	M	220	z			AMPS	10.50	1.00	.90		16.00		.18				.75
ρ.	Σ	ro.	VOLTAGE	208	>-			OLTS	120.0	0.0	120.0	120.0	208.0	120.0	120.0	120.0	120.0	20.0	120.0
		o.	>	120	>	ENTS		8		12	12		•••					_	
	EL	ADC-TSS-9		110	z	NOMNO			0-856	E)	E	ea ea	2-062	1-708	7-961	3-104	3-775	1-409	7-639
	MODEL	ADC		28	z	FEE			06-00	<b>JNAVAILABLE</b>	ILABL	LABL	01-12	01-06	00-47	01-20	01-03	01-12	00-13
		_	(2	100	2	SUB SYSTEM COMPONENTS		NSN	6210-00-900-8560	JNAVA	UNAVAILABLE	UNAVAILABLE	4120-01-122-0626	1260-01-061-7081	6650-00-477-9613	6675-01-203-1049	6675-01-033-7750	7025-	6230-00-137-6394
		TOPOGRAPHIC SUPPORT SET	FREQUENCY (HZ)	9	×	SU		_	•	INI	_	_	•	•	Ī	•	Ī	•	
		oddn:	QUENC	20	Z	<u>i</u> !			e.	INCANDESCENT			I-3A	AN/UYK-48			-0210	ပု	
	TURE	HIC	FRI	ည	z			MODEL	3 LAMP	INCAN	63		F-18H-3A	S/NY	LUXO		C-72-0210	9872-	
	NOMENCLATURE	OGRAF							UOR			IST	ER	OGR	H		SC0	ICS	ζ
				MANUFACTURER	œ			TURE	XI FL		AUST	ER, D	ITION	PHOT	R LIG	BLE	TEREO	GRAPH	ERGEN
		-5759		MANU	ADCOR			ENCLA	LIGHT FIXT FLUOR	H	EXH,	POW.	AIR CONDITIONER	LYTIC	NIFIE	HT TA	/IEWER STEREOSCO	TTER	LIGHT EMERGENCY
	,	1-105						NOM	PIT 6	LIG	FAN	BOX	AIR	5 ANA	MAG	LIG	VIE	Pľ	LIG
	NSN	575-0	ENCE	ENT	PLATE			LINE	L61459 1	CONE	VONE	NONE	NONE	15483	NONE	NONE	NONE	NONE	NONE
			REFERENCE	DOCUMENT	DATA PLATE	•											_	_	_
MBER	LINE	T0574	-	_	_			XS CC	A002	A008	D088	8000	AK011	WOIO	A022	W034	AW035	AW016	A020
CONTROL NUMBER FU00639 SYSTEM				MCT	27125			S	æ	~	~	~	~	~	~	Æ	<b>Æ</b>	~	~
CONTROL FU00639 SYSTEM	CODE	AW033		K	30.														

SHELTER TYPE 5-Ton Cont	OPRS DATE 4 90197			SRCVAL QTY	1 0	٠.	va i	- ·	s ·	S	8	S ·	. I		SO I	S	S .		S		
SHELTER TYPE 5-TON C	o H.N	!	Brd	1000	00001	ı	•	i	ı	1	•	ı	•		1	ı	•	•	•	•	1
GEN SYSCD G-60-6U	PHASE 3 DC Y N		à	HEAT	74300	•	•	•	1	•	•	•	ı	•	•	•	•	•	1	•	•
ğ	w z			AC/DC	ر ا	YC.	ပ္ရ	¥Ç	<b>y</b> C	YC.	¥	AC	<b>Y</b> C	¥Ç	¥Ç	<b>Y</b> C	¥	S S	AC	¥	¥C
PRM MVR MODEL M931	0 418 N			WATTS	8966	40	9	650	1000	9	120	200	400	3200	1035	984	360	320	1932	200	115
PRIME MOVER 5-TON	220 240 N N			AMPS	46.00	.30	. 50	•	8.30	.50	1.00	1.80	3.30	ı	9.00	8.20	3.00	2.60	16.80	1.70	1.00
<u>g</u> 35 iv	VOLTAGE 0 208 Y	Ñ		VOLTS	208.0	120.0	115.0	120.0	120.0	120.0	120.0	110.0	120.0	120.0	115.0	120.0	120.0	120.0	115.0	115.0	115.0
MODEL ADC-TSS-8	28 110 120 N N Y	SUB SYSTEM COMPONENTS			4120-01-076-1753	UNAVAILABLE	4940-00-195-7251	7910-00-205-3400				-2728	6740-01-016-4527	6740-01-118-5406	4320-01-098-0156	6675-00-526-6542	6740-01-058-7423	6675-00-221-7121	6740-00-291-9391	6210-00-729-9768	UNAVAILABLE
r set rec	K (HZ) 60 400 Y N	SUB SYS		NSN	4120-	UNAVA	4940-	7910-	UNAVA	UNAVA	UNAVA	4940-	6740-	6740-	4320-	6675-	6740-	6675-	6740-	6210-	UNAVA
NOMENCLATURE TOPOGRAPHIC SUPPORT SET REC	FREQUENCY (HZ)  R DC 50 60 40  N Y Y N	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		MODEL	F-18H-3		PEN ULTRA	CL-18000			DLV-20	M-25	_		_		KODAK		יו יי		CP25
NSN NOMENCLATURE 6675-01-105-5758 TOPOGRAPHIC	MANUFACTURES ADCOR			NOMENCLATURE	AIR CONDITIONER	SAFELIGHT	CLEANER ULTRASON	CLEANER VACUUM	DRIER PRINT PHOT	TICHE EMBERSANCE	UNISHIA CHULL	MIXER LIGHTD	PRINTER PHOTOGRA	MACHINE PROCESSI	PINE INTE CENTRI	PROTETER PROJEC	SAFET.TCHT DARKED	BOADS TOACTING II.	CINK DDOCESSING	TICHT PINTIPE	TIMER
NSN 6675-01-	REFERENCE DOCUMENT TM5667531914			LINE	A24463	NONE	ANCN	E33083	NONF	ANON PARTY	ANON	W54973	P90938	NON		~	ANON				NONE
NUMBER LINE TO8625	REFERENC WGT DOCUMENT 27285 TN566753			S. × CODE	AK012	BH142	RH143	BULAA	BUIAR	27 LDQ	OFTIG	ATUG DAIY6	RH149	BHIRD	DU151	PULLS	20110	CTUG	#01110	COUNT	AA003 BH156
CONTROL FU00505 SYSTEM CODE AW007	KW 12.																				

		DATE		91247			LOTY	•	~	-	~	-			-	-	-	~	-		7	~	-	-	-	-	-	-	-	-		-	
ă	EXP	OPRS		~			SRCVAL OTY	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	Ø
SHELTER	TYPE 5 TON		E	Z	!	F	1000	•	•	36000	•	1	ı	•	•	•	•	1	•	•	1	•	•	•	•	•	•	1	•	1	•	1	•
	SYSCD G-10-6	PHASE	2			RTI	HEAT	•	1	1	00009	•	•	ı		•	•	•	ı	1	1	•	•	•	•	1	1	ı	•	•	•	•	•
NA S			S	z			AC/DC	NC.	ပ္	· U	Š	¥	ည္	ပ္ခ	NC NC	ĄÇ	¥C	ÄČ	AC AC	ğ	¥	ŭ	ğ	¥C	¥C	¥C	¥C	¥C	AC AC	<b>A</b> C	Ŋ.	¥C	υ
PRW MVR	MODEL M931		418	z			WATTE				_	٧ -	۲ -	480 A	692 A	-	373 A	200 A	100 A	345 A	۲ -	۲,	<b>≺</b> -	·		Ī	۲ ،	۲ .	<b>۲</b>		160 A	۲,	187 A
-	-		240	z			_																						1				
PRIME	MOVER 5 TON	3	220	Z	!		AMPS	6.00	50	16.00	14.00			4.17	6.00	6.00	3.20	1.70	.86	3.00				1.20	1.30	2.60				10.00	1.30		1.60
ш.	an Ko	8	~	<b>&gt;</b>			VOLTS	120.0	120.0	208.0	120.0	120.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	120.0	115.0	120.0	15.0	115.0
			120	<b>&gt;</b>		N EW I D	Š			•			•	•		•	•			7													
	MODEL S/EQ		8 1	z	ounanyunyo namono atto			6210-00-900-8560	LABLE	4120-01-122-0629	520-00-778-7136	5895-01-099-8220	6130-00-699-6659	7910-00-205-3400	5130-00-142-5325	5130-00-889-9004	3415-00-517-7754	6230-00-901-9755	6230-00-268-9246	LABLE	6625-00-999-6282	5625-00-649-9284	5950-00-987-5601	3439~00-930-1638	3439-00-585-6057	3439-00-223-2528	6680-00-799-7616	6625-00-238-1460	5950-00-987-9301	4940-00-152-2107	6625-00-498-9984	6625-00-238-1460	1940-00-204-0319
		(HZ)	4	z		1616 90	NSN	6210-0	UNAVAILABLE	4120-0	4520-0	5895-0	6130-0	7910-0	5130-0	5130-0	3415-0	6230-0	6230-0	UNAVAILABLE	6625-0	6625-0	5950-0	3439-0	3439-0	3439-0	0-0899	6625-0	5950-0	4940-0	6625-0	6625-0	4940-0
	REP		09			9			CENT	80-9									20		05C									21			
	CLATURE EQUIP, ELECT REP	ZE O	20				MODEL	3 LAMP	INCANDESCENT	UAC40-5/6-08	UH-68F	PA-250A		MU-11	BD-320	BD-160	MODE7M	W-L-661	MIL-L-4020	RCD-10	AN/URM-105C	305DMM	PUC50-2	450K4	SP-120	8	<b>TS-805</b>		W5MT3A	BDL-812121	2200S	_	2M037
	clature Equip, e	1	2	Z			MO			S	5	PA-							MII	<b>2</b>	ž	30	PU	450	SP-	W300	•	XI	_		220	BIM	2MC
	SHOP		MANUFACTURER		: !		TURE	XT FLUOR		ITIONER	PACE	R POWER	BATTERY	LEANER	ECTRICAL	ECTRICAL	GRINDING	TENSION	EXTENSION	OR OR	ä	COPE	PPLY	DERING	SOLDERING	SOLDERING	OPE TACH	ARMATUR	MER VARI	ND ROTAR	PENN	ARMATUR	TER ARMA
	NSN 4940-01-096-4475		MAND	XX S			NOMENCLATURE	LIGHT FIXT FLUOR	LIGHT	AIR CONDITIONER	HEATER SPACE	AMPLIFIER POWER	CHARGER, BATTERY	VACUUM CLEANER	DRILL EL	DRILL ELECTRICAL	MACHINE	LIGHT EXTENSION	LIGHT EX	OSCILLATOR	MULTIMETER	OSCILLOSCOPE	POWER SUPPLY	GUN, SOLDERING		IRON, SO	STROBOSCOPE TACH	TEST SET ARMATUR	TRANSFORMER VARI	TEST STAND ROTAR	RECORDER PENN	TEST SET ARMATUI	UNDERCUTTER ARM
	NSN 4940-01-	REFERENCE	DOCUMENT	DATA PLATE	1		LINE	L61459	NONE	A24900	NONE	NONE	NONE	E33083		NONE	389168	NONE	NONE	NONE	M80002	NONE	X85791										
VUMBER	LINE T10275			20045 DATA			SYS CODE	AA002	AA008	AK017	AG053	BD146	BD147	BD148	BD149	BD150	AH004	AH016	AH025	BD151	BD152	BD153	BD154	BH106	AH039	BD155	BD156	BD157	BD158	BD159	BD160	BD161	BD162
CONTROL NUMBER FU00634 SYSTEM	CODE BD145		. ;	10. 200																													

		DATE		90263				SRCVAL OTY	;	۱	1 0	•
Į	SHELTER TYPE S280B/G	OPRS		e						· E-	-	F
į	TYPE S280		EES	z		<u>!</u>	BTC	1000 000	•	•	18000	1
	SYSCD ST-30-6U	PHASE	S 3 DC OTH	X		 	20	HEAT	1	•	12000	•
			တ	z				C/DC	ن.	ري	Ų	Ş
3	MODEL M35A2C		28 110 120 208 220 240 418	z				TTS A	399	399	6552 AC	80
	TON		240	z				SC	9	900	50	0
2	FAIRE MOVER 2 1/2 TON	23	220	z				Z	55.	55.	31.50	•
-		VOLTA	208	<b>&gt;</b>				OLTS	15.0	15.0	208.0	10.0
	115B		120	>	į	NEWTS						H
	MODEL AN/TSM-115B		110	z		COMPO			16-93	28-98	26-95	걸
					1	STEM			-01-2	6625-01-128-9878	4120-00-926-9567	UNAVAILABLE
	NOMENCLATURE SHELTER VULCAN AIR DEFENSE	HZ)	C 50 60 400	Z		SUB SYSTEM COMPONENTS		NSN	6625	6625	4120	UNAV
	IR DE	NCY (	9	<b>&gt;</b>		60			00B	~	-208	
	CANA	REQUE	20	Z	.			Z	AN/TSM-100B	AN/TSM-22	CE20/AL4-208	BR2009
	LATUR R VUL			Z				_	•		_	
	NOMENCLATURE SHELTER VULC		MANUFACTURER	MECH				zj i	ECTRO	DAR	AIR CONDITIONER	ICP
			NUFAC	ECTRO	# 1			TY.	E E	E E	NDITI	FIXT
	212-6							CHEN	EST S	TEST S	IIR CC	IGHT
	NSN 4940-01-212-6575	M	; 	9-4940-554-13P	1		:	<u> </u>	<b>3</b>	ij	A24592 1	1 1
	NSN 494	REFERENCE	DOCUMENT	940-:	į							
4	LINE T10429			-			2		60	010	AK015	906
		!	MGI	0086				i i	AT	ATC	AK	Ž
FU00516 SYSTEM	CODE BH021	į	X (	30.								

	DATE 90276		017 12 12 11
TER B/G	OPRS DA		SRCVAL QTY S 12 S 12 S 2 S 3
SHELTER TYPE 52808/G	H z	,	18000 18000
GEN SYSCD ST-60-4	PHASE 3 DC Y N	 	BTU HEAT 12000
SYS	ωz		20/
PRM NVR MODEL M36A2	118 X		WATTS AC/DC 3240 AC 360 AC 500 AC 1500 AC 14174 AC
	240 N		WATTS 3240 360 500 1500 14174
PRIME MOVER 2 1/2TON	250 N	 	AMPS 15.50 3.27 4.50 7.20 68.10
E Z N	VOLTAGE 28 110 120 208 220 240 418 N Y N Y N N		VOLTS 208.0 110.0 110.0 208.0
<b>7</b> 6	120 N	NENTS	
MODEL AN/TSM-94	110 Y	COMPO	52-11 34-35 43-49
		SUB SYSTEM COMPONENTS	4120-00-152-1150 UNAVAILABLE 6105-00-234-3504 UNAVAILABLE 835-00-443-4914
) MIS	(HZ) X	S ans	412 412 UNA 610 UNA 483
GUIDE	FREQUENCY (HZ)  SC 50 60 400  N N Y		860 SCENT
CLATURE RQUIPMENT GUIDED MISSI	FREQU DC 5	! !	MODEL 1321559860 INCANDESCENT RW800 C-1208
NOMEN SHOP	MANUFACTURER RCA	! ! ! !	RE TONER CT URGING
NSN 4935-00-930-7251			NOMENCLATURE AIR CONDITIONER LIGHT BLOWER HEATER ELECT NITROGEN PURGING
00-93	54-24		NO PELLIN
NSN 4935-	REFERENCE DOCUMENT TM94935-554-24		A24592 AND AND AND AND AND AND AND AND AND AND
LINE T14485	REFE DOCU TM94		SYS CODE AK004 AA008 AG041 AG012 BH026
	WGT 7500		SYS CV AK004 AA008 AG041 AG012 BH026
SYSTEM CODE BH022	KW 24.		

		DATE	90330		Ę	_	_	_	_	_	_	_	4	•	_		-	_	_		_	_	_	_	-	-
	z		8		SRCVAL OTY	S	S	s	S	S	ß	ß	ß	S	S	ໝ	S	S	S	S	S	S	S	S	S	S
SHELTER	5 TON VAN	OPRS	-					_																		_
SHEL	2	H	z			•	•	•	,	•	1	•	1	•	•	•	•	•	1	١	•	•	•	•	•	10000
	•	PHASE	Z		HEAT	•	•	•	•	•		1	•	•	1	•	•	•	1	•	•		•	ŧ	ı	7000
GEN	G-5-6D	~ [~	>																							•
8		ď	>		AC/DC	ŊĊ.	AC	AC	<b>y</b> C	YC	AC	<b>y</b> C	YC	<b>y</b> c	ÄC	¥Ç	٩c	Ϋ́С	<b>y</b> c	Ac	¥Ç	2	<b>Y</b> C	¥Ç	Ş V	¥C
PRM MVR MODEL	M931	414	Z		WATTS	2880	1492	373	373	460	1440	828	960	240	9	138	ı	•	100	140	632	100	150	•	•	3432
		240	Z		-			0	0			0	0	0	٥	0			0	0	٥	٥	0			
PRIME	5 TON	220	Z		AMPS	24.00	7.10	3.20	3.20	5.00	12.50	7.20	8.30	2.00	.50	1.20	•	•	6.	1.20	5.50	3.60	1.30	•	•	16.50
₽4 <b>X</b>	, ונח	VOLTAGE			VOLTS	120.0	208.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	120.0	•	115.0	115.0	15.0	28.0	115.0	120.0	120.0	208.0
		120	?~	ENTS	>					•	•		-	•		•	•	o.					_	•	•	
<u>د</u>		9	z	PON		-818	-456	-899	-796	-775	-116	-000		-307	-375	-280	-130	-570	-202	-039	-876	-376	-605	966-	-634	-499
KODET	C-2	80		SUB SYSTEM COMPONENTS		6130-00-985-8185	4310-00-542-4563	6130-00-889-8994	3413-01-045-7965	3415-00-517-7754	4940-00-785-1162	7310-00-782-0005	UNAVAILABLE	6240-00-143-3071	6230-00-240-3759	3611-00-204-2809	6130-00-504-1301	2330-00-542-5709	3439-00-892-2026	3439-00-542-0396	3439-00-853-8760	3439-00-640-3760	3439-00-585-6057	4920-00-967-9969	1920-00-508-6345	4120-01-193-4998
		(2)	Z	B SYS	NSN	6130-0	4310-(	6130-(	3413-(	3415-(	4940-(	7310-(	UNAVA	6240-(	6230-(	3611-(	6130-(	2330-(	3439-(	3439-	3439-(	3439-(	3439-	4920-(	4920-	4120-(
		E) X	3 >	S			4		<b>&amp;</b>																	
	S/MT	FREQUENCY (HZ)	) z	! !		5/6	1387	<u>, , , , , , , , , , , , , , , , , , , </u>	8003	_	0		_	11/37			336			0				1-6		326
188 188 188	H	FREG	) z	 	MODEL	PP-1659/G	MIL-C-13874	W-D-661	MIL-D-80038	MODE7M	LFT 500	WH-636	BR2009	W-L-101/37			MIL-R6336	H-447	3439	WG-1400	TC-552			PN-7199-1		<b>ECU9HC326</b>
CTAT	SET	9	INC		^			CAL		NG )	_		_		_	•	_	ER I	•	-	•	M	퍼	RCR I	ධු	
NOMENCLATURE	SHOP	A CTITO	2		8	TERY	UNIT	RICA	ITI			HOT PLATE ELECTR	ICP	LAMP INCANDESCEN	ISION	KING	×		ING	NG	SING	SING	ZING	AIR	ELEC	AIR CONDITIONER
2		MANITERACTION	CONVERTO		NOMENCLATURE	CHARGER BATTER	COMPRESSOR UN	DRILL ELECTRIC	MACHINE DRILL	MACHINE GRIND	TER	TE 1	LIGHT FIXT ICH	ICANI	LIGHT EXTENSIO	MACHINE MARKIN	POWER SUPPLY	VAN SEMI TRAI	SOLDERING	GUN SOLDERING	SOLDERING	SOLDERING	SOLDERING	STAND TEST AL	STAND TEST EL	DIT
	-204	24	ខ្ល		ENCI	RGER	PRES	LL	HINE	HINE	GUN HEATER	PL	H	NI d	HT	HINE	ER S	S		IOS	SC	SC	SC	LON	LON	Š
	-621	•	20		NON	-					55	HOT	LIG	Š	LIG	MAC	Š.	Z	<b>15</b> 5	50	IRON	IRON	IRON			
X X	4920-00-621-2040	REFERENCE	SC518099CLA05	+ 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	LINE	<b>D99025</b>	NONE	<b>G55686</b>	NONE	<b>J89168</b>	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	V99650	V99911	A23955
2		REFERENC	1021		DE																					
MBER	T22331				SYS CODE	AH030	AH012	AH013	AH014	AH004	AH015	BH105	AA006	AA015	AH032	AH033	AH034	AH018	AH035	AH036	AH037	AH038	AH039	AH040	AH041	AK009
NON .	H	3	20080		SY	AH	¥	¥	AH	¥	AH	BH	2	2	¥	¥	Z	Z	7	Z	Ŧ	Z	Z	¥	¥	Ā
CONTROL NUMBER FU00591 SYSTEM CODE LINE	AH029	3																								

NSN	-
NSM	Ø
NSN	1
NSN	•
NSN	
NSN	¥ς
NSN	•
NSN	
NSN	
NSN	2.0
NSN	
NSN  REFERENCE DOCUMENT  REFERENCE DOCUMENT  DOCUMENT  DOCUMENT  DOCUMENT  DOCUMENT  NONE  LINE NONE  LIGHT EXTENSION  HA1132 PEN INSP UNIT FL  RREQUENCY  NONE  LIGHT FIXT ICP  RREQUENCY  NONE  LIGHT FIXT ICP  RREQUENCY  NO Y  REQUENCY  NO Y  REQUENCY  NO Y  NO Y  REQUENCY  NO Y  NO Y  REQUENCY  NO Y  RECU9HC326  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2197  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2197  NONE  LIGHT FIXT ICP	2-570
NSN  REFERENCE DOCUMENT  REFERENCE DOCUMENT  DOCUMENT  DOCUMENT  DOCUMENT  DOCUMENT  NONE  LINE NONE  LIGHT EXTENSION  HA1132 PEN INSP UNIT FL  RREQUENCY  NONE  LIGHT FIXT ICP  RREQUENCY  NONE  LIGHT FIXT ICP  RREQUENCY  NO Y  REQUENCY  NO Y  REQUENCY  NO Y  NO Y  REQUENCY  NO Y  NO Y  REQUENCY  NO Y  RECU9HC326  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2197  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2197  NONE  LIGHT FIXT ICP	2330-00-542-5709
NSN  REFERENCE DOCUMENT  REFERENCE DOCUMENT  DOCUMENT  DOCUMENT  DOCUMENT  DOCUMENT  NONE  LINE NONE  LIGHT EXTENSION  HA1132 PEN INSP UNIT FL  RREQUENCY  NONE  LIGHT FIXT ICP  RREQUENCY  NONE  LIGHT FIXT ICP  RREQUENCY  NO Y  REQUENCY  NO Y  REQUENCY  NO Y  NO Y  REQUENCY  NO Y  NO Y  REQUENCY  NO Y  RECU9HC326  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2197  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2196  NONE  LIGHT FIXT ICP  RR2197  NONE  LIGHT FIXT ICP	2330-(
NSN REFERENCE DOCUMENT SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC49209CLA37	
NSN REFERENCE DOCUMENT SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC492099CLA37 SC49209CLA37	_
NSN REFERENCE DOCUMENT SC492099CLA37 SC492099CLA37 SC492099CLA37 SC49209PCLA37 SC49209PCLA37 SC49209PCLA37 SC49209PCLA37 SC49209PCLA37 SC49209PCLA37 SC49209PCLA37 SC49209PCCATURE NONE LIGHT EXTENSION P94633 PUMP CENTRIFUGA H81132 PEN INSP UNIT F K87165 MAGNETIC INSP K A23955 AIR CONDITIONER NONE LIGHT FIXT ICP	
NSN 68 4920-00-621-2041 REFERENCE DOCUMENT SC492099CLA37 SC492099CLA37 NONE LINGH EXTE P94633 PUMP CENTR H81132 PEN INSP UI K87165 MAGNETIC I A23955 AIR CONDIT NONE LIGHT FIXT	GILER
NSN 68 4920-00 REFERENCE DOCUMENT SC492099CLA SC492099CLA SC492099CLA HR1132 HR1132 HR1132 KR7165 A23955 NONE NONE NONE NONE NONE NONE NONE	ar Twa
NSN 68 4920-00 REFERENCE DOCUMENT SC492099CLA SC492099CLA SC492099CLA HR1132 HR1132 HR1132 KR7165 A23955 NONE NONE NONE NONE NONE NONE NONE	VAN V
REFE SC49	4
UMBER 1724 1724 1724 1724 1726 1726 1726 1727 1727 1727 1727 1727	•
Z	OTAIN
CONTROL NUMBER FU00563 SYSTEM CODE AH024 T224 T224 30. 30. AH025 AH025 AH025 AH025 AH025 AH025 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH026 AH027	

	DATE	90330			L OTY	-	-	-	-	-	-	1	7	<b>4</b>	∢	-	<b>-</b>
Z Z		_			SRCVAL OTY	S	Ø	S	S	ဖ	S	တ	S	S	S	w	w
SHELTER TYPE 5 TON VAN		E ×		. 5	100 100 100	ı	ı	ı	1	•	ı	1	0006	•	•	•	•
19-	PHASE	 8≈		DTG	HEAT	•	•	•	•		•	1	0009	•	•	•	•
GEN SYSCD		× 3			! ይ												
ž,		א מו			AC/DC	Ų	Š	¥	Š	¥	ž	ž	ž	ğ	¥	YC	¥
PRM MVR Model Moggi		418 N			ATTS	373	373	5000	460	570	475	0069	3432	720	240	373	1
		240 X						_	_	_	_	_	_	_	_	_	
PRIME MOVER 5 TON	, M	220 N			AMPS	3.20	3.20	21.70	5.00	4.90	4.10	30.0	16.50	6.2	2.00	3.20	•
A 25 C	VOLTAGE	208 X			OLTS	115.0	15.0	230.0	15.0	15.0	115.0	230.0	208.0	115.0	115,0	115.0	ı
		120 Y		ENTS	>			•		•				_		•	<b>.</b>
EL		110 N		OMPON		7006-61	5-413	3-974	7-775	900-6	0-884	1-141	3-499	M	3-307	7-852	12-570
MODEL	,	2 28 2 28		E E		9-88	0-16	0-24	0-51	0-40	0-0	59-0	1-19	LABI	0-14	9-0	0-54
	(2	0 Z		SUB SYSTEM COMPONENTS	NSN	3730-00-889-9004	3413-00-165-4136	3424-00-243-9746	3415-0	3405-00-409-0063	3439-00-020-8847	3431-00-691-1415	4120-01-193-4998	UNAVAILABLE	6240-00-143-3071	5130-00-857-8528	2330-00-542-5709
	Ë	, V V		SC								_	•	_			
Ę	FREQUENCY (HZ)	20 X					ROCKWELL 15					MIL-W-80027	92		/37		
ຸນ ກູ	nog n	io z			ដូ		CWEL	W-F-785	E7.H	390		8-M-	<b>ECU9HC326</b>	600	W-L-101/37	06-S-00	17
CLATURE		12 z			MODEL		ROCI	W-F-	MODE7M	28-390		MIL	ECUS	<b>BR2009</b>	W-L	00	M-447
NOMENCLA SUOD SET		MANUFACTURER	-1			-	13	SAT TRE	LINDING	SAW, BAND	NIT C	SLDING	TIONER	r ICP	AMP INCANDESCEN	×	VAN SEMI TRAILER
6	5	(ANUF)			NOMENCLATURE	DRILL ELECTRIC	PRESS DRILL	ACE HE	INE GE	BAND	JLATOF	INE WE	LIGNO	r FIXT	INCA	ER DIS	SEMI 1
					OME	RIL	RES	'CRN	IACH:	AW,	IRC	INCH.	IR (	HOL	AR	MAD	N.
9	3	LA38				56 D	99 F	124	E 89	<b>(</b> )	O	18 M	55 2	_	_	0,1	
NSN 4920-00-621-2043	REFERENCE	DOCUMENT SC492099CLA38			LINE	G570	G62899	NONE	3891	NONE	NONE	Y481	A23955	NONE	NONE	NONE	NONE
~§	REFI	DOCI SC45			ODE	_		_			٠.		_			_	_
NUMBER LINE T22742	•	WGT			SYS CODE	AH007	AH006	AH020	AH004	AH021	AH022	AH023	AK005	AA006	AA015	AH017	AH018
CONTROL NUMBER FU00581 SYSTEM CODE LINE		KW 19.															

	6	315	90330				L OTY	~	-	-	~	-	7	-	7	48	4	-	
S.	S TON VAN		-				SRCVAL OTY	S	တ	S	တ	S	S	S	S	S	S	S	
SHELTER	ğ.	E	z	ı	)	Þ	COOL	•	•	•	1	•	•	1	0006	1	1	•	
	, i	100	Z			BTU	HEAT	•	•	•	ı	1	•	•	0009	•	•	1	
GEN	3-5-6	֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	>												•				
		U	>	1			AC/DG	<b>A</b> C	¥	<b>Y</b> C	¥	¥Ç	¥	¥	¥	¥	¥	<b>V</b> C	
PRM MVR MODEL	<b>M8</b> 31	418	Z				ATTS	1492	373	373	460	1440	200	373	3432	960	240	•	
		240	2				-			20	8	20	70	20	50	30	2.00	1	
PRIME MOVER	S TON	200	2				¥	7.	ë	e,	5.00	12.	ij	'n	16.50	80	7		
		?	2				VOLTS	208.0	115.0	115.0	15.0	115.0	115.0	15.0	208.0	115.0	115.0	•	
		120			NENTS		>			•	_		••	•	•	-		60	
MODEL	on.	110			COME			42-45	89-89	45-79	17-71	85-11	01-97	57-85	93-49	LE	43-30	42-57	
2	ပ်	a c	2 2		STEM			4310-00-542-4563	8-00-	3413-01-045-7965	3415-00-517-775	4940-00-785-1162	6230-00-901-9755	5130-00-857-8528	4120-01-193-4998	UNAVAILABLE	6240-00-143-3071	2330-00-542-5709	
	Í	400	Z		SUB SYSTEM COMPONENTS		NSN	4310	6130	3413	3415	4940	6230	5130	4120	UNAV	6240	2330	
!	֓֞֞֞֜֞֞֞֞֜֞֞֞֞֞֞֞֜֞֞֞֞֞֞֞֞֞֞֜֞֞֞֞֞֞֓֓֞֞֞֞֞֞	בינג גינג	>+		S			374		338					10		37		
63	T S/I	FREQUENCY (RA)	Z				H	(IL-C-13874	-D-661	IL-D-80038	H/S	FT 500	4-L-661	06-S-00	<b>ECU9HC326</b>	600	W-L-101/37		
CLATURE	SET ACFT S/MT	د ۱۲	ž				MODEL	MIL	Š	MIL	MODE7M	_	-	_	_	_	_	_	
	SHOP SE	MANIFACTIBER					URE	R UNIT	CTRICAL	RILLING	RINDING	œ	ENSION	SK	TIONER	T ICP	NDESCEN	TRAILER	
MBER LINE NSN	49-6509	MANITE					NOMENCLATURE	COMPRESSOR UNIT	RILL ELE	MACHINE DRILLING	ACHINE G	UN HEATE	IGHT EXT	ANDER DI	IR CONDI	IGHT FIX	AMP INCA	VAN SEMI TRAILER	
	9-00-	<b>4</b> _	SC492099CLA45				_	Ī	686 D	NONE M	ĕ			E S	ິດ	回口	E		
NSN	90 <b>4</b> 920-	DOCTORENT	92099				LINE	NONE	655	NON	389	NONE	NONE	NON	A23	NON N	NON	NONE	
UNBER	T23290	WGT DOC					SYS CODE	AH012	AH013	AH014	AH004	AH015	AH016	AH017	AK009	AA006	AA015	AH018	
CONTROL NUMBER FU00574 SYSTEM CODE LINE	AH011	3						,	7	7	. •	7	7	7	7	. 7	7	•	

	DATE	90330				SRCVAL QTY	~	-	20	-	-	7	~	=======================================	<b>.</b>	-	
TER	OPRS	m				SRCV	E	E	E	H	H	H	F	E	e	H	
SHELTER TYPE S280		HIO	:	!	BTU	COOL	,	,	•	10000	•	,	ı	ı	J	1	
n9	PHASE	 မှ =	•		Ø	HEAT	•	•	•	7000	ı	ı	ŧ	3	1	1	
GEN Syscd G-30-6U	Δ,	۳ <b>&gt;</b>	•			1											
•		ω >	•			AC/D	¥Ç	Ä	¥	¥C	¥Ç	¥Ç	Ä	¥Ç	ÄC	¥Ç	
PRM MVR MODEL M35A2		418 N	4			TTS	000	250	400	3432	40	1200	112	1650	1760	9	
TON		240	•							•				•	•	0	
PRIME MOVER 2 1/2 TON	M	220	•			AMPS	26.00	2.10	3.4	16.50	۳.	13.04	90	14.3	15.30	ų.	
E Z N	VOLTAGE	208	•			VOLTS	115.0	5.0	5.0	208.0	5.0	5.0	5.0	5.0	2.0	2.0	
<b>*</b>	Š	120	4	ENTS		8	-		11							11	
MODEL AN/MGC-19A		110	<b>E</b>	MPON			7-619	4-350	ea ea	3-499	2-535	2-819	8-776	3-606	7-830	ω	
		8 2	5	S MA			00-17	00-23	LABL	91-10	30-75	31-06	01-11	30-55	06-00	LABL	
NOMENCIATURE TELETYPEWRITER OPPS CENTRAL	HZ)	602	£	SUB SYSTEM COMPONENTS		NSN	4520-00-177-6198	6105-00-234-3504	UNAVAILABLE	4120-01-193-4998	5830-00-752-5357	5815-01-062-8194	5810-01-118-7766	5815-00-553-6061	5805-00-907-8300	UNAVAILABLE	
PPS C	FREGUENCY (HZ)	9,	<b>+</b>							9	FI	4A (V	•		•		
E TER 0	REOUF	20	H			EL	6	,	BR2009	ECU9HC326	LS-147C/FI	N/UGC-74A(V	KG-84A	FT-76A	TH-22/TG	•	
LATUR PEWRI	(a.	10 2	<b>E</b>			MODEL	P-13	,	BR2	ECU		~	_	Ė	•		
		MANUFACTURER	TOBIANAMA D	!		NOMENCLATURE	!		IXT ICP	AIR CONDITIONER	*	RADIO TELETYPEWR	LOOP ECCENTRIC D	TELETYPEWRITER	TELEGRAPH TERMIN	CLEANER VACUUM	
1-510		MAN	2			KENCI	HEATER	SLOWER	THT F	CON	LERCO	DIO T	OP EC	LETYP	LEGRA	EANER	
1-04]		9	3	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					LT	55 AI	NI OF	16 RA	31 82	52 TE	29 TE		
NSN 5815-01-041-5104	REFERENCE	TENT	ioeelietonroo			LINE	NONE	NONE	NONE	A23955	K9488	V36146	E030;	V36762	V57729	NONE	
88	REFE	DOCUMENT				ODE				. ~			_			. ~	
CONTROL NUMBER FU00570 SYSTEM CODE LINE AX026 V39228		WGT	0976			SYS CODE	AG042	AG04	AAOO	AK009	98	AX007	BD01	BEOOS	BEOO3	AG043	
CONTROL FU0057C SYSTEM CODE AX026		K.															

	DATE	5 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
ZE R	PRS 1	SRCVAL QTX T T 8 T T 6 T T 1 2 T T 2 2
SHELTER TYPE	S280 OTH	70006
GEN	PHASE  PHASE  DO  N  N	BTU PEAT
Ex.	\sigma 2	AC AC AC AC AC AC AC AC AC AC AC AC AC A
PRM MVR MODEL		WATTS 1748 1280 600 900 3000 112
PRIME	2 1/2 TON M GE 220 240 N N	AMPS W 1.20 1.10 5.20 5.20 6.00 3.10
PRIME	2 1/2 NGE 3 220 N	AMPS 11.10 5.20 7.80 7.80 26.00 30 90
	AN/TSC-58A 2 1 VOLTAGE 28 110 120 208 2 N Y N	S VOLTS 115.0 115.0 115.0 115.0 115.0
	-58A 10 12	00NENT 1645 1300 1194 1061 1198 1357 766
MODEL	AN/150	A COME -592-4 -907-8 -062-8 -553-6 -177-6
	/ (HZ) 60 400 Y N	SUB SYSTE NSN 4120-00 5 5805-00 74A(V 5815-01 4520-00 7FI 5830-00
ATURE	I I N	MODEL MODEL ARC7504 TH-22/TG AN/UGC-7- TT-76A P-13 LS-147C/I KG-84A
NOMENCLATURE 10_6287 TEDMINAL METAGRADIE	MANUFA	LINE NOMENCLATURE A23907 AIR CONDITIONER V57729 TELEGRAPH TERMIN V36762 TELETYPEWRITER NONE HEATER K94880 INTERCOM E03028 LOOP ECCENTRIC D
NSN 5805-010-018287	医口口	
CONTROL NUMBER FU00569 SYSTEM LINE BD003 V57504	RE WGT DO 5430 TO	SYS CODE AKO06 BE003 AXO07 BE005 AG042 BG BG
CONTROL FU00569 SYSTEM CODE BD003	κκ •	

	DATE	90302			SRCVAL QTY S S S S S S S S S S S S S S S S S S S
SHELTER TYPE 5 TON BOX	OPRS	4			SRCY S S S S S
SHELTER TYPE 5 TON B		e z	!	₽	COOT
<b>~</b>	ASE	2 × 2 ×	! ! ! !	BIG	HEAT
EN YSCD T-60-	F	بد عا			1
e G w w		w z			AC / DC AC AC AC AC AC
PRM MVR GEN MODEL SYSCD M55A2 ST-60-4		418 N			AMPS WATTS 12.10 240 17.20 1500 1
		240 N			\$ . 0001110
PRIME MOVER 5 TON	ë	28 110 120 208 220 240 418 N Y N Y N N N			AMPS 2.10 7.20 7.20 -
ра да ч	VOLTAC	7 × ×			VOLTS 1110.0 208.0 208.0 208.0 208.0
5		120 N	VENTS		•
MODEL AN/TSM-93		110 Y	OMPO		17 – 94 77 – 94 77 – 95
		2 ×	Maj		FLABI FLABI 20-17 00-17 01-12
ICLATURE STATION GUIDED MISSILE	H2.)	ic 50 60 400	SUB SYSTEM COMPONENTS		NSN UNAVAILABLE UNAVAILABLE 4935-00-177-9498 4935-00-177-9502 4935-00-109-3365
ж Д	2	9 z	S		ENT
GUID	FOTIEN	N SO		•	10DEL NCANDESCENT 20800 10K-1165 10K-1155 10K-1638
ICLATURE STATION	Ġ	N N	į		
NOMENCLA TEST STA		TURER IP			LINE NOMENCLATURE NONE LIGHT NONE HEATER ELECT U59250 TEST STATION GUI U59255 TEST STATION GUI U59424 TEST STATION GUI A24592 AIR CONDITIONER
2 F		MANUFACTUR RCA CORP			ELEC FATIC TATIC TATIC NDITI
0-72!		•			MENC GHT ATER ST S ST S ST S
0-93		0-10			NO HE
NSN 4935-00-930-7250	acnagaaag	REFERENCE DOCUMENT TM91425-550-10	*		LINE NONE NONE U5925 U5945
0	0000	DOCU TM91			CODE 2 6 6 7 7
NUMBER LINI WOOL		WGT 8660			SYS CODE AA008 AG012 AT006 AT007 AT008
CONTROL NUMBER FU00544 SYSTEM CODE LINE BH025 W0086		KW 26.			

CONTROL NUMBER   FUNDER   FU			DATE	90318		7
NOLINE NSN  LINE NSN  LINE NSN  REFERENCE  MCDEL  X17831 5820-00-089-7887 TRANSHITTER RADIO SET  X17831 5820-00-089-7887 TRANSHITTER RADIO SET  MGDEL  X17831 5820-00-089-7887 TRANSHITTER RADIO SET  MGDEL  ANJTRT-22  2 1/2 TON M35A2  2 2/2 TON M35A2  PHASE  PHASE  PHASE  RECTIFIER PRWH MVR GEW  MODEL  NN Y N N N N N N N N N N N N N N N N N		TER O		ъ		SRCVAL OTY T T 1 T T 1 T T 1 T T 1
NOTIVE NSN    TINE   NSN		SHEI TYPE S280	E CO		:	, m
STATE   NOTE	į	SYSCD 3-200-6P	PHASE 3 DC	>-		HEAT
NOTE SET AND STATE STATE AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND SET AND S		œ.	ြတ	z		ACC DC ACC DC ACC DC ACC DC ACC ACC ACC
LINE   NSN		MODEI M35A2	1	>		1775 1640 1
LINE   NSN		NOI	240	<b>&gt;</b>		8 5 H
LINE   NSN		MOVER 2 1/2	3E 220	Z		AME 80.0
LINE   NSN	•	''	OLTAC 208	Z		0.0000000000000000000000000000000000000
1.1NE NSN  LINE REFERENCE  WGT DOCUMENT  AANUFACTURE  AANUFACTURE  FREQUENCY  MGT DOCUMENT  AANUFACTURE  FREQUENCY  FREQUENCY  BC36  M11-5820-543. i SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  FREQUENCY  NO SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  ANOBE  STUDIO TRANSMITTE  C-6025  BE040  NONE  RADIO TRANSMITTE  T-938  BE041  NONE  RECTIVER MODULATO  MODEL  ANOBE  BE042  NONE  RECTIVER MODULATO  ANITRE-18		25	120	Z	ENTS	2000000100
1.1NE NSN  LINE REFERENCE  WGT DOCUMENT  AANUFACTURE  AANUFACTURE  FREQUENCY  MGT DOCUMENT  AANUFACTURE  FREQUENCY  FREQUENCY  BC36  M11-5820-543. i SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  FREQUENCY  NO SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  ANOBE  STUDIO TRANSMITTE  C-6025  BE040  NONE  RADIO TRANSMITTE  T-938  BE041  NONE  RECTIVER MODULATO  MODEL  ANOBE  BE042  NONE  RECTIVER MODULATO  ANITRE-18		DEL /TRT-:	110	Z	OMPO	55 - 12 55 - 12 55 - 12 55 - 12 55 - 12 56 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57 - 12 57
1.1NE NSN  LINE REFERENCE  WGT DOCUMENT  AANUFACTURE  AANUFACTURE  FREQUENCY  MGT DOCUMENT  AANUFACTURE  FREQUENCY  FREQUENCY  BC36  M11-5820-543. i SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  FREQUENCY  NO SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  ANOBE  STUDIO TRANSMITTE  C-6025  BE040  NONE  RADIO TRANSMITTE  T-938  BE041  NONE  RECTIVER MODULATO  MODEL  ANOBE  BE042  NONE  RECTIVER MODULATO  ANITRE-18		MO! AN,		z	STEM (	00-15 00-16 00-16 00-16 00-15 00-16
1.1NE NSN  LINE REFERENCE  WGT DOCUMENT  AANUFACTURE  AANUFACTURE  FREQUENCY  MGT DOCUMENT  AANUFACTURE  FREQUENCY  FREQUENCY  BC36  M11-5820-543. i SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  FREQUENCY  NO SAC ARMY DEP  NO WENTER RADIO SE  FREQUENCY  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  MODEL  AANUFACTURE  AANUFACTURE  MODEL  AANUFACTURE  ANOBE  STUDIO TRANSMITTE  C-6025  BE040  NONE  RADIO TRANSMITTE  T-938  BE041  NONE  RECTIVER MODULATO  MODEL  ANOBE  BE042  NONE  RECTIVER MODULATO  ANITRE-18			42) 400	Z	JB SYS	NSN 5820- 5820- 5820- 5820- 5820-
LINE NSN  LINE REFERENCE  WGT DOCUMENT  A.1636 M11-5820-543. i SAC ARMY DEP N  SYS CODE LINE NOMENCLATURE PP  ACO26 NONE RECTIFIER POWER PP  ACO26 NONE STUDIO TRANSMITT C-  BEO39 NONE STUDIO TRANSMITT C-  BEO40 NONE TRANSMITTER CONT C-  BEO40 NONE TRANSMITTER CONT C-  BEO40 NONE GROUP ANTENNA TU QA  BEO42 NONE SHELTER MODULATO ND  BEO42 NONE SHELTER MODULATO ND  ACO33 R38868 RECEIVER RADIO AN AN		) SET	VCY (1	<b>&gt;</b>	S	80
LINE NSN  LINE REFERENCE  WGT DOCUMENT  A.1636 M11-5820-543. i SAC ARMY DEP N  SYS CODE LINE NOMENCLATURE PP  ACO26 NONE RECTIFIER POWER PP  ACO26 NONE STUDIO TRANSMITT C-  BEO39 NONE STUDIO TRANSMITT C-  BEO40 NONE TRANSMITTER CONT C-  BEO40 NONE TRANSMITTER CONT C-  BEO40 NONE GROUP ANTENNA TU QA  BEO42 NONE SHELTER MODULATO ND  BEO42 NONE SHELTER MODULATO ND  ACO33 R38868 RECEIVER RADIO AN AN		RADI	REQUE	2		21 1922 10-5/6 1168 123 125 1495 1495 188/TR
S53  ELINE NSN  LINE NSN  REFERENCE  WGT DOCUMENT  41636 M11-5820-543 i SAC AR  SYS CODE LINE NOMENCLATU  ACO17 A24900 AIR CONDIT  ACO17 NONE STUDIO TRAI  BEO39 NONE STUDIO TRAI  BEO41 NONE GROUP ANTER  BEO42 NONE SHELTER NOI  BEO42 NONE SHELTER NOI  ACO13 R38868 RECEIVER R		LATUR	10 2	2,		MOD UAC UAC C-6( C-6( C-6( C-6( MD-5
S53  ELINE NSN  LINE NSN  REFERENCE  WGT DOCUMENT  41636 M11-5820-543 i SAC AR  SYS CODE LINE NOMENCLATU  ACO17 A24900 AIR CONDIT  ACO17 NONE STUDIO TRAI  BEO39 NONE STUDIO TRAI  BEO41 NONE GROUP ANTER  BEO42 NONE SHELTER NOI  BEO42 NONE SHELTER NOI  ACO13 R38868 RECEIVER R		NOMENC	CTURER	120		RE FOWER TONER TONER SMITT SMITTE NNA TU NULATO
TINE NSN  LINE NSN  LINE NSN  REFERENCE  WGT DOCUMENT  41636 M11-5820-543.i.  SYS CODE LINE NOME  AC017 A24900 AIR  AC017 A24900 AIR  AC017 A24900 AIR  AC017 A24900 AIR  BE038 NONE STUD  BE038 NONE STUD  BE040 NONE TRAN  BE041 NONE GROUP  BE041 NONE GROUP  BE041 NONE GROUP  BE042 NONE SHELL			ANUFA			CLATUI FIER I ONDIT: O RAD: O TRANS TRANS ANTER MOI
353 2M LINE NSN LINE S20-00- 1 X17831 5820-00- REFERENCE WGT DOCUMENT 41636 M11-5820-54; SYS CODE LINE AC026 NONE AC032 NONE BE038 NONE BE038 NONE BE038 NONE BE040 NONE BE040 NONE BE041 NONE BE041 NONE BE041 NONE BE042 NONE BE042 NONE BE042 NONE BE043 NONE BE043 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE BE044 NONE		7-680			) 	NOMEN RECTI AIR C STUDI STUDI TRANSI RADIO SRELTI
353 3M LINE 1 X17831 1 X17831 41636 M11-41636 M11- 825 CODE ACO26 ACO17 ACO26 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17 ACO17		-00-0	CE T 0-543			0 8
353 3M LINE LINE MGT 41636 AK017 AK012 BE038 BE038 BE038 BE039 BE041 BE041 BE041 BE042			FEREN CUMEN 1-582			
35.3 MG 416.3 MG AND AND AND AND AND AND AND AND AND AND	BER	INE 17831				S COD 026 017 032 038 039 040 041
CONTRO FU0055 SYSTEM CODE AX031 KW 134.	L NUM	ч×	WGT 11636			SY: AO: AX( BEC BEC BEC BEC BEC BEC BEC BEC BEC BEC
	CONTRO FUO055	AX031				

		DATE	90304				SRCVAL OTY		-	۰ ۸	-	-	_	-	-	· ~	e	-
	SHELTER TYPE S250	OPRS	٣				SRCV	٤٠	H	-	-	₽	E	<b>E</b>	F	H	E	F
			E ×		!	BTU	1000	1	1	•	•	•	•	ı	ı	10000	1	1
3	GEN SYSCD G-10-6D	PHASE	Z D			à	HEAT	١	•	ı		4	ŧ	•	ı	7000	•	1
			M >4	1			ا 20											
	MODEL M1037	¢	2 X					o Ac								8 AC		o AC
		- 1	* ×				WATTS	80	80	16	Õ				Ñ	1518	18	9
	FRIME MOVER 1 1/4 TON	000	) Z	1	SUB SYSTEM COMPONENTS		AMPS	. 70	.70	1.40	10.70	.70	.70	7.00	.40	7.30	1.60	5.20
		8	80.7 X				OLTS	15.0	15.0	15.0	28.0	15.0	115.0	115.0	115.0	208.0	15.0	115.0
	.(a)09-		×				×	H	H	H	••	7					•	•
	MODEL AN/TSC-60(V)7	11,	Y Z					BLE	BLE	<b>NBLE</b>	BLE	BLE	BLE	UNAVAILABLE	UNAVAILABLE	4120-01-088-3791	-143-30	-062-81
		S	2				NSN	UNAVAILABLE	MAVAILABLE	UNAVAILABLE	JNAVAILABLE	JNAVAILABLE	UNAVAILABLE				6240-00-143-3071	5815-01-062-8194
	FRAL	CY (HZ	<b>2</b> ×					5	5	5	5	5	5		5			
	NOMENCLATURE COMMUNICATION CENTRAL	FREQUENCY (HZ)	<b>2</b> > -	1			EL	222	53	VFT1290	_	106A-1	HF-8023	HF-8032	_	F-9000H-3	W-L-101/37	: AN/UGC-74A(V
	NOMENCLATURE COMMUNICATIO	IC	) z	į			MODEL	<b>E</b>	•					HF-	1280		_	
	NOMENC	MANUFACTURER	TI				NOMENCLATURE	IVER	SMITTE		HIGH	POWER SUPPLY	POWER SUPPLY	្ន		IONER	DESCEN	TYPEWR
	-1827	MANITE	ROCKWELL					ADIO RECEIVER	VADIO TRANSMITT	FT SYSTEM	NTERFACE HIGH			POWER SUPP		AIR CONDITIONER	LAMP INCANDESCEN	ALET O
DEK	NSN 5895-01-129-1827		18513					RAD	RAD	VFT	INI					5 AIR		
	NSN 5895-(	REFERENCE DOCUMENT	FM115895118513				LINE	NON	NONE	NONE	NONE	NON	NON	NONE	NONE	A23955	NONE	V30140
	LINE 216333						SYS CODE	G1045	946	047	048	032	A0033	A0034	AM049	AK022	AA015	AX007
CONTROL NUMBER FU00545 SYSTEM		WGT	765				SY	5	Ž.	Ž	Į,	į						
FU00545 SYSTEM	CODE AM044	K	œ															

_
69
<b>U</b>
- 64
•
_
_
- 5
0
75
盂
X
7
.5
끝
_Q
C

	DATE	90330			O.T.		7	7	ri .		٠,	- ،	· ~	-	1	-	-	58	-	7	-	7	-	-	⊶ ,	ı,	ì -	٠.	-	7	<b>ન</b>	<b></b> ,	<b>⊣</b> -	٦,	4 10	) (	۱ ۸	-	н	-	<b>-</b>	<b>-</b> 4 •	~ .	4	
V.V.V	OPRS [				SRCVAL	S	s	S	S (	י מי	ט מ	o co	S CO	S	ß	S	S	S	တ	S	ß	S	w	တ	S) (	ກເ	ט מ	o co	S	S	S	s i	S C	ט מ	ט ני	ט ני	S	S	S	S	S	တ (	in i	o	
SHELTER TYPE STON VAN	0	E ×		. =	1000		00009	1	ı	1 4		ı	1	1	1	1	1	ı	•	ı	•	ı	1	•	1	<b>t</b> 4			1	•	1	ı	1	<b>!</b> 1		ı	ı	•	1	1	•	•	1	I	
GEN SYSCD ST-60-6U-3	PHASE	2 ×			HEAT	'	47000	•	ı	1 (	•	,	1		1	•	1	•	•	•	•	1	ı	ı	ı	<b>å</b> 1	ı <b>ı</b>	ı	ı	•	ı	•	B 4	) (		ı	•	•	1	1	•	ı	1 (	ì	
ğ		s z			AC/DC	AC	ΑĊ	YC.	<b>Y Y</b>	) C	2 4	NC O	¥C	AC	<b>A</b> C	Ac	AC	Ac	AC	AC	ΥÇ	AC	AC.	AC	A C	ָבָי בי	ے پر	S C	AC	٩c	Ų.	Q (	) (	ر د د	ر د ه	ט מ	Ş	AC	AC	٧ç	<b>9</b>	ပ္	Ų Ç	ړ	
PRM MVR MODEL M931		0 418 N			WATTS		-	•		7 1 2					·	57	-			-			-		750	•			099		•	•	C 611					-			-		006		
PRIME MOVER 5 TON	8.3	220 240 N N			AMPS		64.00	.34	90.	3 6	2.00	.20	3.00	2.00	.50	.50	•	20.10	. 34	2.40	12.00	64.00	10.00	٠	6.50	•	•	25.00		1.50	18.00	•	2.5		25.00	) C	18.00	25.00	.40	. 20	3.00	•	5.4	<b>;</b>	
	8	0 208 Y		S	VOLTS	•	208.0	115.0	120.0		120.0	115.0	115.0	120.0	。	115.0	1	115.0			208.0	208.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	208.0	208.0	115.0	120.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	240.0	2	•
MODEL OQ-290 (V) 2MSM		28 110 120 N N Y		SUB SYSTEM COMPONENTS	-			-5357		BI.E	BLE	-1461		6625-00-500-6525	-1459				-5357													2													
		00 N		JB SYSTE	NSN	2330-01	4120-01	5830-00-752	UNAVALLABLE INAVATI ABI E	INAVATLABLE	UNAVAILABLE	6625-01-	UNAVAILABLE	6625-00-	6625-01-	UNAVAILABLE	2330-01-	6210-00-	5830-00	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVALLABLE	UNAVAILABLE	TINAVATLABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVALLABLE	TCD-TD-CZQQ	TWAVATTABLE	UNAVAILABLE	UNAVALLABLE	OND TOTAL								
NOMENCLATURE TEST FACILITY ELECTRONIC EQ	REQUENCY	DC 50 60	1	15	MODEL	XM991E1	CV-60-5/6-08	LS-14/C/F1	7 A	460-1A	I-250	92-BD	RT-20A	8640B	82AD	SC-1	XM1065	2 LAMPS	LS-147C/FI	TT-768	CB-154-3	H-120	NOVA-3	001-0	€ A	4/N	0009	LK-351FM	6005	DAP3-AF-8-33	153B	503A	800BF1 HR-1515	615R	N/A	LK-344A	LK-343A	LK-351FM	BHK500-0-4	BHK1000-0-2	3330B	5200A	4 /2 2 /2	4	- 120
		MANUFACTURER RCA			_	œ	ITIONER	CCCCCAMPT	_	POWE							LER						EXPANSIO			ICAL	SS			வ		POWER SOURCE AC	HONELLY A	OR VIDEO	ຍ			REG			ည္က	AC	MALSA		
NSN 6625-01-235-5480		RCA			NOMENCLATURE			_	LIGHT	METER LASER	ILLUMINATOR	METER F			METER A	CONTROL	VAN SEN			PRINTER LINE	CONVERT	WINCH	CHASSIS	DANET	DRIVE DISK	FAN ELE	CONTROL	POWER S	INTERFA	DECODER	POWER	POWER OF	MONTTOD	GENERAT	STATION	POWER S	POWER S			POWER S	CALIBKA	CALIBRATOR	HUMINITE		
NSN 6625-0	REFERENCE	DOCUMENT DATA PLATE	6 6 7			NONE	A25860 K94990	NONE	NONE	NONE	NONE	NONE	NONE	548119	NONE	NON	NONE	NONE	104880	NONE	NONE	NONE	NON	MON	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NON ENCIN	NON	NONE	NO NO	i : :									
LINE 225240		58120 DAT			SYS CODE	AL054	ARUZU BG	AT.004	AL005	AL006	AL007	AL008	AL009	AL010	ALOII	ALOIZ	ALUSS	AA003	20.5	AL013	ALO14	AL015	AL016	ALOIA	AL019	AL020	AL021	AL022	AL023	AL024	ALUZO	AL020	A1.028	AL029	AL030	AL031	AL032	AL022	AL034	AL035	AL036	ALU3/	AL036		
SYSTEM CODE ALOO3		94.5																																											

_
ທ ທ
1 1
NG C
1393
6.70
•
0.808
7 (4
UNAVAILABLE
UNAVAILABLE
R5325A UNAVAILABLE
R5325A UNAVAILABLE
R5325A UNAVAILABLE
R5325A UNAVAILABLE
AIR COMPRESSOR R5325A UNAVAILABLE
R5325A UNAVAILABLE
AIR COMPRESSOR R5325A UNAVAILABLE

		DATE	90330				SRCVAL OTY	-	-	m	-	-	-	-	~	-	æ	7	-	1	
JER JER	TYPE XM-991E2	OPRS	~				SRCVA	S	S	S	S	S	S	S	S	S	S	S	S	w	
SHELTER	TYPE XM-99	ļ	E Z			ם	1000 CO	1	•	•	1	•	1	1	•	60000	•	•	90009	•	
7	SYSCD ST-100-6U-1	PHASE	X DC			BTU	HEAT		٠	•	•	,	•	1	1	47000	•		47000	1	
TVR GEN		ļ	თ <b>&gt;</b>				AC/DC	AC.	Ş	<b>A</b> C	AC	<b>y</b> C	¥	¥C	AC	<b>V</b> C	Ϋ́С	AC	¥c	AC	
PRM MVR	MODEL M931		0 4 18 N				WATTS	1	•	345	200	•	•	1	•	3328	280	120	3328	ı	
PRIME	MOVER 5 TON		220 240 Y Y		! ! !		AMPS	•	•	3.00	4.30	1	•	•	•	16.00	2.43	1.00	16.90	ŧ	
ä	Z w	~	0 Z08		S		VOLTS	208.0	208.0	115.0	115.0	208.0	208.0	208.0	208.0	208.0	115.0	115.0	208.0	•	
	ដូត		N Y		SUB SYSTEM COMPONENTS			6ů	6a	6a	6a	ы	ы	63	61	5-5416	0-8560	3-3071	3-5980	1-1707	
	MODEL MYQ-5		8 z		YSTEM C			UNAVAILABLE	JNAVAILABLE	UNAVAILABLE	<b>NAVAILABLE</b>	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	4120-00-935-5416	6210-00-900-8560	6240-00-143-3071	4120-01-213-5980	2330-01-151-1707	
	NTRAL	K (HZ)	2 ×		SUBS		NSN	UNA	UNA	UNA	UNA	UNA	CNA	CINA	UNA	412				233(	
	YCLATURE ESSOR GROUP CENTRAL	FREQUENCY (HZ)	N C				MODEL	3811	3211	1600	SEARS	3505	3525	370580	3278	4AC6V60	LAMP	-L-101/37	CV-60-5/6-08	XM-991E2	
	NOMENCLATURE PROCESSOR GR	MANITERCENT	GTE				MOMENCLATURE	F PRINTER CON	RINTER	EHUMIDIFIER	IUMIDIFIER	ARD READER	PUNCH	CONTROLLER COMMU	MONITOR COMPUTED	CONDITION	LIGHT FIXT F	P INCANDE:	AIR CONDITIONE	VAN SEMI TRAILER	
	NSN UNAVAILABLE	ы	DP					_	Д,	<b>:</b>	_	•									
į		REFERENCE	PRINTOUT	į			E LINE	NON	NON	NON	NON	NONE		NO.	NO.	A25E	1014	NONE	A25860	SC	
) Z	Z25526	MGT DO				1	SYS CODE	AD065	AD066	ADOOL	AD062	AD067	AD068	AD069	AD070	AKOTS	AAOUZ	AAOIS	AK020	AD0/1	
FU00576 SYSTEM	AD064	K																			

	DATE	90318			SRCVAL OTY	e 	4		7	<b>60</b>	7	8		~
Shelter Type XM-995E2	OPRS	*			SRC	Ψ,	0,	٠,	<b>U</b> ,	٠,	٠,	٠,	•,	υ,
		Z		Þ	1000 COOI	•	•	•	60000	,	•	•	,	•
-60-1	PHASE	3 <b>z</b>		BTC	HEAT	•	١	١	47000	1	1	١	1	1
GEN SYSCD ST-100-6U-1	# 	n >+			!				47					
	le	n >-			AC/DC	Ş	AC A	YC	YC V	<b>y</b> C	¥C	ÄĈ	¥C	¥C
PRM MVR MODEL M931		Z			WATTS	•	•	•	929	280	120	345	200	•
		N N												
PRIME MOVER 5 TON		Z			AMPS	Ī		Ĭ	16.0	2.43	1.00	3.00	4.30	
<u>r</u> ¥ v	OLTAG	N N N X X N			LTS	8.0	9.0	8.0	208.0	115.0	115.0	115.0	5.0	ł
	<b>^</b>	X X	ENTS		8	20	20	20			_		11	y
, II O		Z	NOAWO			E	M	EL)	3-598	0-856	3-307	딸	ы	1-170
MODEL		ő Z	O WEL			MAVAILABLE	ILABL	ILABL	01-21	06-00	00-14	UNAVAILABLE	<b>JNAVAILABLE</b>	01-15
	(2)	ž Ž	SUB SYSTEM COMPONENTS		NSN	UNAVA	UNAVAILABLE	UNAVAILABLE	4120-	6210-00-900-8560	6240-	UNAVA	UNAVA	2330-01-151-1706
₽.	. H.	⊋ >-	SU											
PORAG	FREQUENCY (HZ)	S Z			د				CV-60-5/6-08	<b>Q</b>	W-L-101/37		ຜ	XM-995E2
ICLATURE MASS STORAGE	F .	Zz			MODEL	٠.	m	3803	_	• •	_		SEARS	XX-9
NOMENCLA GROUP M		MANUFACTORER GTE			NOMENCLATURE	RAGE DISK ACC	I TAPE MAGNET	CONTROL TAP	CONDITIONER	LIGHT FIXT FLUOR	P INCANDESCEN	MIDIFIER	IDIFIER	VAN SEMI TRAILER
ABLE		A E				STO	CIND	CIND	AIR	LIGI	LAM	DEH	HOM	VAN
NSN UNAVAILABLE	REFERENCE	PRINTOUT DAT P			LINE	NONE	NONE	NONE	A25860	L61459	NONE	NONE	NONE	NONE
37					S CODE	0058	9059	0900	X020	4002	1015	1900	2062	AD063
5		WGT 21910			S	AL	AL	AL	7	3	2	A	¥	AL
CONTROL NUMBER FU00552 SYSTEM CODE LINE AD057 Z629	Š	31.												

		DATE	90324			AL OTY		<b>ત</b>	-	<b>.</b>	-	~		<b>-4</b> •	<b></b>	~	<b></b> .	<b></b> ,	rd (	rd (	<b></b> .	<b></b>	٠,	٠.	-	<b></b>	м			rd :	rd :	m ,	۹,	
i ir		OPRS	-			SRCVAL	S	S	S	w	S	S)	S	S)	S)	S)	S) (	י מי	י מי	ינט	ינט	ימי	ימ	ימ	ימי	ינט	U)	(C)	<b>0</b> ,	<b>.</b>	<b>.</b>	S) (	<i>7</i> 3 '	V)
SHELTER TYPE S250/M	•		E N	!	! ;	1000	•	1	•	•	•	•	ı	ı	•	•	•	•	,	ı	•	•	•	1	•	1	ı	•	1	•	•	•	1	36000
	1	PHASE	Z		1	HEAT	1	•	•	•	ı	•	•	•	•	ŀ	t	•	•	•	ì	•	•	•	•		•	٠	•	•	١	•	•	31000
GEN			m≯			1																												
g		ļ	s z	i		AC/DC	AC.	AC	Y <sub>C</sub>	<b>y</b> C	¥Ç	<b>A</b> C	YC	¥	ŊÇ	¥Ç	YC.	<b>Y</b> C	¥Ç	<b>Y</b> C	¥C	Y V	Ų.	Ų.	Ş	¥Ç	Š	Ä	¥Ç	YC	¥	NC.	Ų	¥
PRH MVR MODEL CUCV			4 18 8 X			WATTS	1	•	•	ı	1	•	•	ı	•	t	ŧ	•	•	1	•	•	ı	•		•	ı	•	1500	•	20	20	₹	5824
TON			24 2 X						1				1		•			1	ı		ı	ı		ı		ı	•	ı	20		.17	.16	.03	00
PRIME HOVER 1 1/4		إيم	7 7 8			AMPS																							12.50		•	•	•	28.00
6 至 4		VOLTAGE	208 Y		 	VOLTES	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	208.0
ın			120 Y		ENTS	Š	7	1	ä	ä	ä	ä	ä	Ä	ä	ä	ä	ä	H	ä	H	ä	ä	ਜ	Ä	7	Ä	-	• •	-	•	-	-	-
HODEL AN/MSC-75			110 N		MPON		ß.	ы	64	e e	ы	س	63	ea ea	ы	ш	ف	ED	ы	ш ш	œ	ᇤ	œ	Œ	E	回	E	e e	7-619	띰	8-312	티	eg.	2-06
MODEL AN/MS			8 8 8		SUB SYSTEM COMPONENTS		UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	JNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	JNAVAILABLE	4520-00-177-6198	UNAVAILABLE	5830-01-008-3126	UNAVAILABLE	UNAVAILABLE	4120-01-122-0628
			4 N N		SYS	NSN	INAVA	MAVA	MAVA	MAVA	JNAVA	JNAVA	JNAVA	JNAVA	JNAVA	JNAVA	MANA	JNAVA	JNAVA	UNAVA	JNAVA	UNAVA	UNAVA	UNAVA	UNAVA	UNAVA	UNAVA	UNAVA	4520-	UNAVA	5830-	UNAVA	UNAVA	4120-
TRAL		Х (H2	0 7		SUE	_	. –		_	7		_	_	_	_	_	~	_	_	_	_	_	_	_	_	_		_	•	_				8
CEN		FREQUENCY (HZ)	¥ 20				88	9-0	)		χΩ									0-13	0-11			1-96				0-82			7.	ď		CH40-5/6-08
NOMENCLATURE COMMUNICATIONS CENTRAL		FRE	ŭ z			MON	SKECTAS	F-1100-G			OMNIMUX							TCC-10		F-5100-13	F-5100-11			F-3151-96				F-5100-82	P-13		LS-147F	1 BULB		CH40-
NOMENCLATURE COMMUNICATIO			RER				T.M.		8 M	2	ER	S	PA	4	PAT			ECO	LE	LE	)   			TOR			TRA	SPE				F-3	E	TER
NON NON NO			manufacturer Tobyhanna			2017	TOURE MED O	ASS	DEVIC	TRACK	IPLEX	ATION	GITAL	IGITA	ITAL		SY	R TEL	R MSE	CONSC	ONSOL			OPERA			R CEN	HIGH		ER		XTURE	R DI	ITIO
			MANU			agrae Longach	DANET, DOMER	RIOWER ASSY	ARCHIVE DEVIC 8M	DRIVE 9 TRACK MA	F/O MULTIPLEXER	COMMUNICATIONS	PANEL DIGITAL P	MODULE DIGITAL P	UNIT DIGITAL PA	VF PATCH	MODEM ASSY	CONVERTER TELECO	CONVERTER MSE LE	PRINTER CONSOLE	SYSTEM CONSOLE	KEYBOARD	DISPLAY	CONSOLE OPERATOR	KEYBOARD	DISPLAY	PROCESSOR CENTRA	PRINTER HIGH SP	HEATER	HUMIDIFIER	INTERCOM	LIGHT FIXTURE	BOX POWER DIST	AIR CONDITIONER
ABLE						2	NAG	Q I	ARCI	DRI	F/0	O	PAN	S S	INS	VF	MOD	CON	SON	PRI	SXS	KEY	DIS	CON	KEY	DIS	PRO	PRI	HEA	HOM		_	BOX	
NSN UNAVAILABLE		REFERENCE	DOCUMENT DATA PLATE			1	NON	NON	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	K94880	NONE	NONE	A24763
		REFE	DOCUMENT DATA PLA			300	300.	٠.		. ~	. ~						,,,	_	~				۲.	~	_				. ~	. ~	٠ -		œ	
NUMBER LINE NONE			WGT			1000	AKO AK	AX037	AXO38	AX039	AX040	AX041	AX042	AX043	AX044	AX045	AX046	AX047	AX048	AX049	AX050	AX051	AX052	AX053	AX054	AX055	AXOSE	AX057	AG042	AXOSB	BG001	AA024	AOOOR	AK037
CONTROL FU00559 SYSTEM CODE AX035			ΚM																															

	DATE	90324				OTY	~	7.	80	-	-	-	-	S	7	-	-	-	m	-	п
ă x	OPRS D	1 9				SRCVAL QTY	ß	S	ß	S	တ	S	တ	S	S	S	S	S	S	တ	S
SHELTER TYPE S250/M		H z			5	1000 C000	•	•	•	ı	•	ı	ı	ı	•	1	ı	ı	ı	•	36000
ь	PHASE	2 z			BTU	HEAT	•	•	1	ı	•	ı	1	1	1	1	•	•	•		31000
GEN		· · ·				AC/DC															
PRM MVR MODEL CUCV	,  -	o, <u>z.</u>						Y	¥C.	¥C.	¥C.	¥C.	Ž	YC.	¥C	YC.	YC.	YC	¥C	¥C	¥
	- 1	0 _ 418 N				WATTS	٠	•	'	'	•	•	•	•	•	4	•	1500	9	50	5824
RIME OVER 1/4 TON	ľ	0 240 N				AMPS	ı		!	•	1	•	•	•	ı	.03	ı	13.00	6.50	.17	28.00
PRIME MOVER 1 1/4	AGE	8 7 8				<													9		
	8	7 × ×		S		VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	208.0
122		120 Y		SUB SYSTEM COMPONENTS			•	-		•	•	-,-				•	••	86			•
MODEL AN/MSQ-122	- 1	OZ.		SOME			LE	E E	LE	LE	LE	LE	I.E	LE	LE	LE	LE	520-00-177-6198	I.E	5830-01-008-3126	4120-01-122-0628
N N	·	8 7 8		STEM			UNAVAILABLE	MAVAILABLE	MAVAILABLE	<b>INAVAILABLE</b>	MAVAILABLE	UNAVAILABLE	<b>NAVAILABLE</b>	UNAVAILABLE	<b>MAVAILABLE</b>	<b>NAVAILABLE</b>	UNAVAILABLE	-00-	UNAVAILABLE	-010-	-01-1
7	HZ)	4 0 0 0		UB SY		NSN	UNAV	UNAV	UNAV	UNAV	UNAV	UNAV	CNAV	UNAV	CNAV	<b>CNAV</b>	CNAV	4520	SNAV	5830	4120
) IGIT	FREQUENCY (HZ)	% X		S								_									-08
TEM I	anoa:	¥ 20				H.	F-1100-G			MUX		F-4596-00						_	Ţ.	LS-147F	CH40-5/6-08
ATURE R SYS		ŭ z				MODEL	F-11			OMINIMO		F-45						P-13	1 BULB	LS-1	CH40
NOMENCLATURE COMPUTER SYSTEM DIGITAL		MANUFACTURER TOBYHANNA				NOMENCLATURE	BLOWER ASSY	DRIVE DISK	CONTROLLER CLUST	F/O MULTIPLEXER	UNISYS 5000/95	POWER SUPPLY COM	IIVE DEVIC 8M	MAC OPENET	MAC MUX5000	POWER DIST	HUMIDIFIER	TER	LIGHT FIXTURE	INTERCOM	AIR CONDITIONER
ABLE			į			NOM	BLO	DRIV	CONT	F/0	CNIS	POW	ARCE	MAC	MAC	BOX	HOM	HEATER			AIR
nsn Unavailable	REFERENCE	DOCUMENT DATA PLATE	\$   			LINE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	K94880	A24763
ឌ ស្ន	REFE	DOC				CODE	7	6	0	0	1	~	80	<u>س</u>	4	80	80	C)	4	_	7
NUMBER LINE NONE		1 J				SYS CODE	AX037	AX059	AX060	AX040	AX061	AX062	AX038	AX06.	AX064	A0008	AX058	AC042	AA024	BG001	AK037
CONTROL NUMBER FU00560 SYSTEM CODE LINE AXO65 NONE	•	N.																			

COURTEL NUMBER  FULLINE NSN  SYSTEM  CODE  LINE NSN  NOME 4240-00-Z02-001 PACILITY COMM ELECTRONIC AN/ASM-684  NOME 4240-00-Z02-001 PACILITY COMM ELECTRONIC AN/ASM-684  NOME 4240-00-Z02-001 PACILITY COMM ELECTRONIC AN/ASM-684  NOME A240-00-Z02-001 PACILITY COMM ELECTRONIC AN/ASM-684  NOME A240-00-Z02-001 PACILITY COMM ELECTRONIC AN/ASM-684  NOME REFERENCE  NAMO19 NOME PALATE  SUB SYSTEM COMPONENTS  SYS CODE LINE NOMENCLATURE  NOME ROADS  NOME ROA	<b>→</b> ↔
NEN	n va
NSN	18000
NSN	12000
NSN	12
PRIME FRM MODEL  4240-00-Z02-001 FACILITY COMM ELECTRONIC AN/ASM-684 11/4 TON M1028  EFERENCE  OCUMENT  ATA PLATE TOBYHANA N Y Y N N N Y Y N N N N N N N N N N	۲۵
NSN	
NSN	
NSN	16.2
NSN	208.0
NSN	
NSN	3-178
NSN	00-16
NSN 4240-00-Z02-001 FACILITY COMM ELECTRON EFERENCE OCUMENT HANUFACTURER DC 50 60 ATA PLATE TOBYHANA N Y Y AY NONE FAN, EXHAUST NONE BOX FOWER DIST NONE BOX FOWER DIST NONE COMPRESSOR AIR THOMAS F40745 POWER SUPPLY PP-4763A/GRC K33939 LIGHT FIXT PLUOR 3 LAMP NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST NONE FAN, EXHAUST	4120-00-168-1781
NSN 4240-00-Z02-001 FACII EFERENCE OCUMENT MANUFACTURE ATA PLATE TOBYHANA TA PLATE TOBYHANA TOBYHANA DE LINE NOMENCLATURE NONE FAN, EXHAUST NONE FAN, EXHAUST NONE COMPRESSOR AIR P40745 POWER SUPPLY R33393 RABIO L61459 LIGHT FIXT FLUO NONE FAN, EXHAUST	. •
NSN 4240-00-Z02-001 FACII EFERENCE OCUMENT MANUFACTURE ATA PLATE TOBYHANA TA PLATE TOBYHANA TOBYHANA DE LINE NOMENCLATURE NONE FAN, EXHAUST NONE FAN, EXHAUST NONE COMPRESSOR AIR P40745 POWER SUPPLY R33393 RABIO L61459 LIGHT FIXT FLUO NONE FAN, EXHAUST	7
NSN 4240-00-Z02-001 FACII EFERENCE OCUMENT MANUFACTURE ATA PLATE TOBYHANA TA PLATE TOBYHANA TOBYHANA DE LINE NOMENCLATURE NONE FAN, EXHAUST NONE FAN, EXHAUST NONE COMPRESSOR AIR P40745 POWER SUPPLY R33393 RABIO L61459 LIGHT FIXT FLUO NONE FAN, EXHAUST	F-18T-2
NSN 4240-00-Z02- CCUMENT ATA PLATE CCUMENT ATA PLATE COUNENT NONE FAN, NONE FAN, NONE BOX NONE COMP P40745 POWE R33939 RADI L6145 FAN, NONE FAN,	NDITIONER
NSN 4240-00 4240-00 CUMENT ATA PLATE ATA PLATE COUNE C	8
LINE NOMBER LINE NONE WGT DOCU 9470 DATA SYS CODE BG AD099 AD099 AD002 AD002 AD002 AD002	A24455
LIIN NOW WGT NOW NOW NOW NOW NOW NOW NOW NOW NOW NOW	2
. 3 ~	AK02
CONTROL CONTEN SYSTEM CODE AWOO5 KW 8.	

	DATE			Ę	֓֞֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֓֓֓֓֓֓	•	- •		-	-	-	~	~	-	7	~	7	-	-	_	~	-
<b>5</b>	OPRS [	1			אריאה עוו ה	3 0	a (	S	S	S)	S	S	κ	S	S	ß	S	ຜ	w	S	ß	S
SHELTER TYPE S-250	O HTO	:		1500		1 1	•	•	0006	ı	•	•	•	ı	ı	ı	ı	•	i	•	•	•
GEN SYSCD ST-10-6D-1	PHASE 3 DC		i	Bro	near.	1	•	•	,	1	•	•	ŀ	ı	1	1	•	•	•	•	•	•
	w z			6	20/20 20/20	، ر	Ų	Ų	AC	<b>A</b> C	ပ္ရ	AC	<b>V</b> C	AC	AC AC	Ų	Ų	¥C	Ų	¥C	ŭ	<b>A</b> C
PRM MVR MODEL M1037	418	:				7 001	1500	٠	<b>ب</b>	<b>«</b> 1	<b>د</b> ۱	<b>ا</b>	۷ ،	<b>«</b>	<b>«</b> ۱	<b>د</b> ۱	<b>د</b> ۱	-	-	<b>ح</b> ۱	-	112 A
PRIME MOVER 1 1/4 TON	220 240	4				9.40	12.50	1	1	1	1	•	•	•	•	ŧ	•	•	1	ı	•	.97
	VOLTAGE	4			VOLTS		_	208.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0
MODEL 0A-9375/TSQ-164	120	•	ONENTS	•	•			N	<b>ન</b>				-		7				-	-		•
MODEL OA-937	28 110	4 4	SUB SYSTEM COMPONENTS			6240-00-143-744T	520-00-912-3502	UNAVAILABLE	UNAVAILABLE	5820-01-292-2969	MAVAILABLE	025-01-292-2965	MAVAILABLE	5820-01-292-2880	UNAVAILABLE	7021-01-285-4347	5895-01-292-0948	NAVAILABLE	MAVAILABLE	MAVAILABLE	1025-01-292-2976	
œ	H2) 400		UB SYST		NSN	0-0479	4520-0	UNAVAI	UNAVAI	5820-0	UNAVAI	7025-0	UNAVAI	5820-0	UNAVAI	7021-0	5895-0	UNAVA	UNAVA	UNAVA	7025-	
FINDE	ENCY (		S										_				5					
rure Rection	FREQUENCY (HZ)		; ! ! !		MODEL	anna Pore	P-15	0006		PTS-040	200	IP-1594	R-2307/U	TD-1444	R-3021	CP-1947	MD-1261/U	CU-1382H	SD-1	1280A	CP-1949	
NOMENCLATURE GROUP DIRECTION FINDER	TURER	TINC	 	!	E G	2	<b>LTARY</b>	CONER	LTCHIN	R ELEC	NTROL	£	JAL	œ	œ	IGITAL	œ	UPLER	DER		GITAL	
NSN 5895-01-292-0940	MANUFACTURER				NOMENCLATURE	LIGHT BULB DC	HEATER MILITAR	AIR CONDITIONER	ANTENNA SWITCHIN	SYNTHESIZE	CHANNEL CONTROL	DISPLAY UNIT	RECEIVER DUAL	MULTIPLEXER	DF RECEIVER	COMPUTER DIGIT	DEMODULATOR	ANTENNA COUPLER	TAPE RECORDER	FSK MODEM	CONSOLE DIGITAL	T-SEC
NSN 5895-01	REFERENCE DOCUMENT	DAIA PLAIE	# 		LINE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	
					SYS CODE	AA005	AG013	AK049	AC060	AC061	AC062	AC063	AC064	AC065	AC066	AC067	AC068	AC069	AC070	AC071	AC072	
CONTROL NUMBER FU00622 SYSTEM CODE LINE AC059 NONE	KW WGT						~**			~	7	~		7	•							

	DATE	91164				AL OTY	9	-	<b>-</b>	7	-	-	7	-	-	7	<b>ત</b>	-	<b>-</b>	<b>m</b>	7	-	<b>-</b>	m	-
O TER	OPRS	7				SRCVAL	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
SHELTER TYPE S-250	i i	z		!	BTU	COOL	•	•	0006	1	•	•	•	•	•	•	•	•	•	•	•	•	t	1	•
GEN SYSCD ST-10-6D-1	PHASE	2 z			B	HEAT	1	•	•	ı	1	•	•	•	1	•	•	•	1	í	•	•	•	•	•
	u	) Z				AC/DC	Q	ű	Ų	Ŏ	ú	Ş	ğ	¥C	ŭ	ပ္	<b>Y</b> C	ပ္ခ	ပ္ခ	¥C	<u>ک</u>	¥	AC.	¥C	ŭ
PRM MVR MODEL M1037	81.4	ž				-	180 D	200 Y	-	130 D	•		<b>ح</b>	1	٠	•	<b>ح</b> ا	•	-	۲	<b>ح</b>	٠ ۱	•	•	1
TON	240	<b>2</b> ×				3							ı		,		ı		ı		1		1		
PRIME MOVER 1 1/4	35					AMPS	6.40	12.50		2.32															
	8	Ž				VOLTS	28.0	115.0	208.0	28.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0
TSQ-1	100			NENTS		>			~		-		-	-	•		<b>-</b>	_	•	_			-	_	_
MODEL OK-583/TSQ-164	011 80	•	-	SUB SYSTEM COMPONENTS			6240-00-143-7441	4520-00-912-3502	BLE	5820-00-223-7433	BLE	5820-01-292-2958	BLE	BLE	5895-01-294-1167	BLE	BLE	5820-01-292-2969	7021-01-292-2974	BLE	7025-01-292-2976	5820-01-292-2880	BLE	5810-01-146-3260	5810-00-434-3644
	18	2		SYSTE		z	40-00-	20-00-	UNAVAILABLE	20-00-	UNAVAILABLE	20-01-	UNAVAILABLE	UNAVAILABLE	95-01-	UNAVAILABLE	UNAVAILABLE	20-01-	21-01-	UNAVAILABLE	25-01-	20-01-	UNAVAILABLE	10-01	10-00-
TROL	(HZ)			SUB		NSN	62	45	5	28	5	58	5	5	28	5	5	28	20	5	70	28	5	28	28
ET CO	FREQUENCY (HZ)	) z								C-46	59	05	7		14	1/0	02	40	37		49	44			
LATURE RADIO SET CONTROL	FRE	d z				MODEL	BULB	P-15	0006	AN/VRC-46	PP-8259	RT-1605	R-2307	325LA	C-12014	F-1611/U	SCU-302	PTS-040	CP-1937	1280A	CP-1949	TD-1444	GFE	KG-84	KY-57
NOMENCLATURE GROUP RADIO	9491	INC					ō	ARY	NER			NSMI	-7	TER	UENC	INS	IVER	ELEC	ITAL		TAL		INK	<b>&gt;</b>	
	STIE & CALL	SCI COMM INC				LATURE	SULB D	MILIT	*DITIO	SET	SUPPLY	ER TRA	ER DUA	MPLIF	FREG	SUTION	RECE	SIZER	ER DIG	E C	3 DIGI	EXER	S JET	FOF. KE	
60-26	K	SC				NOMENCLATURE	LIGHT BULB DC	HEATER MILITARY	AIR CONDITIONER	RADIO SET	POWER SUPPLY	RECEIVER TRANSMI	RECEIVER DUAL	POWER AMPLIFIER	CONTROL FREQUENC	ISTRI	COUNDE	YNTHE	OMPUTI	FSK MODEM	CONSOLE DIGITAL	MULTIPLEXER	PRINTER JET INK	GENERATOR KEY	T-SEC
NSN 5895-01-292-0942	9 0 E	ATE				LINE	,		NONE A	253001 R		_									_			82	
NSN 589	REFERENCE	DATA PLATE		•			NONE	NONE	02	0	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	EO	SO
MBER LINE NONE						SYS CODE	AA005	AG013	AK049	Ť.	AC074	AC075	AC076	AC077	AC078	AC079	AC080	AC061	AC081	AC071	AC072	AC065	AC082	AE054	AG070
23 NG	£73	2800				SY	\$	AG	Ž	AM	¥	AC	AC	AC	AC	¥	¥	¥	AC	AC	AC	AC	¥	AE	¥e
CONTROL NUMBER FUGO623 SYSTEM CODE AC073 NONE	2	10.																							

	DATE	90284				L OTY	m	~	-	-	-	-	-	-	<b>~</b>	-	7	-	-	-	-	
ğ	OPRS I	~				SRCVAL QTY	ပ	U	ပ	ပ	U	ပ	တ	ပ	ပ	S.	ບ	ပ	ပ	ပ	ပ	S
SHELTER TYPE S250		O N				COOL	1	•	ı	•	•	•	ı	ı	ı	1	1	ı	•	1		10000
	PHASE	O Z	1		BTO	HEAT	١	•	1	•	ı	•	1	1	•	•	t	•	•		•	7000
GEN SYSCD	품	m Z																				
8	ļ	s ×				AC/DC	AC	¥C	<b>A</b> C	¥C	<b>y</b> c	¥Ç	<b>A</b> C	¥C	<b>A</b> C	¥C	¥Ç	¥	¥	<b>y</b> C	Y V	<b>A</b> C
PRM MVR MODEL M1037	ļ	0 418 N				WATTS	9	9	4	80	84	41	26	115	207	1	35	22	22	49	32	3960
PRIME MOVER 1 1/4 TON		0 240 N				AMPS	.50	<u>ن</u>	.03	Į.	•	ı	.46	1	•	•	1	1		ι	•	33.00
PRIM MOVE 1 1/	AGE	8 230 N					_	_	_	_	_	_	_	_	_	_	_			0	0	
	VOLTAGE	120 208 Y N		Sī		VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0
í-182		0		ONEN						9724			5826								6160	2214
MODEL An/TSM-182		28 N		COM			ABLE	ABLE	ABLE	-252-	ABLE	ABLE	-246-	ABLE	ABLE	ABLE	ABLE	ABLE	ABLE	ABLE	-133-	-136-
	(Z)	0 z		SUB SYSTEM COMPONENTS		NSN	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	6130-01-252-9724	UNAVAILABLE	UNAVAILABLE	5805-01-246-6826	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	6625-01-133-6160	4120-01-136-2214
	CY (F	60 ×		S				ENT		()			5								<b>=</b>	ο Δ.
E LTY	FREQUENCY (HZ)	50 N				EL	BULB	INCANDESCENT		PP-8190/G	-		TA-1035/U		2M		~	. 0	8840A/AF	5A	SG-1171/U	н9КH-115P
LATURE	E					MODEL	1 13	INC		PP-	1				8642M		1992	4200	884	6255A	-	_
NOMENCLATURE MAINT FACILI		TURER				<b>3</b>	RE	!	IST	TERY		3	IGITA	CONTROL UNIT TAP	GENERATOR SIGNAL	DEVICE INTERCONN	Q	WATT		Ŋ,	CENERATOR STENAL	ONER
		MANUFACTUR! GTE				TATUE	FIXT		WER	R BAT	T.I.ER	OSCO	ONE	[ND ]	ATOR S	TALL	FR	MTCR	FETER	SIPPI	dOT.	TION
266-59		MAN				NOMENCI.ATURE	LIGHT FIXTURE	TRHI	BOX POWER DIST	CHARGER BATTER	CONTROLLER	OSCILLOSCOPE	FELEP	CONTER	ENER	DEVICE	COUNTER FRED	METER MICROWAT	MIT T METER	POWER STIPPLY	LENED	AIR CONDITIONER
NSN 4910-01-266-5978	<u> </u>	ATE				_	_		_			_	80	1				-	_		-	
NSN 491(	REPERENCE	DOCUMENT DATA PLATE		•		E LINE		NONE	NONE	NONE	FINON	NONE	74	NONE	NONE	NONE	NONE	NONE	2	Z	9	¥2
MBER LINE NONE	RE					SVS CODE	AA024	AA008	80008	AB007	MORE	AMO67	AE060	AM068	AM069	AM070	AMO71	AMO 7.2	AMO 7.3	AMO74	AMO75	AK034
NO NO NO NO NO NO NO NO NO NO NO NO NO N		WGT 2428				λ.	Ä	Ä	Š	A	Ä	A	AR	A	AM	A	A	MA	MA	A	2	ž ž
CONTROL NUMBER FU00540 SYSTEM CODE LINE BE050 NONE		жw 5.																				

	DATE		90324			VTC	, -	• -	4	~	-
m m	OPRS D		1 9			SRCVAL OFF	<i>V</i> :	ט	)	S	s
SHELTER TYPE S250/M	0	HIS	z			C001.	1	1	I	ŧ	0006
	PHASE		Z		BTU	HEAT	. <b>.</b>	ı		•	0007
GEN	盂	ľ	×								_
Æ		S	z			AC/DO	Ų	4	)	ပ္	AC.
PRM MVR MODEL CUCV	VOLTAGE	418	z			WATTS AC/DC	•	٩	-	40	3432
TON	ļ	240	z			S	,	~	•	m	
PRIME MOVER 1 1/4 TON	9	220	z			AMPS		C	•	'n	16.50
<b>M A</b> 1	VOLTAG	208	×			OLTS	120.0	20.0		20.02	0.80
		120	*	ENTS		Š	-	-	۱,		
MODEL AN/MYM-1		110	z	MPON			ы	G.	1 1	5-1	3-499
MOD)	ļ	<b>58</b>	z	SUB SYSTEM COMPONENTS			JI:AVAILABLE	LIABLI		ONAVAILABLE	1120-01-193-4998
	REQUENCY (HZ)	400	z	B SYS		NSN	U.:AVA	UNAVA	****	UNAVA	4120-
	.E.,	9	×	ns S							
ER	QUENC	20	>						p	9	<b>C326</b>
ATURE SHELT	FRE	ပ္	z			MODEL			1110	720	ECU9:4C326
NOMENCLATURE SUPPORT SHELTER		MANUFACTURER	TOBYHANNA	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		NOMENCLATURE	DIFIER	POWER DIST	T PTV TIDE	LIVIONE	CONDITIONER
ABLE	•	_	•			NOME	HOMI	BOX	TITEM	110	AIR
NSN UNAVAILABLE	REFERENCE	TUT	PLATE			LINE	NONE	NONE	NONE	NOW P	A23955
	REFE		DATA			ODE					
LINE		Į,	ı		1	SYS CODE	AX058	A0008	AAO24	7 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	AKOOA
SYSTEM CODE AX066	3	44									

**Table 2. Shelter Systems without Environmental Control** 

## Notes to Table 2:

- 1. CONTROL NUMBER and SYSTEM CODE at upper left, as well as SYS CODE (first column) and SRCVAL (second to last column) are data handling codes peculiar to the Sample Data Collection Program.
- 2. AMPS (seventh column) and WATTS (eighth column) are totals for each type of power consumer (i.e., individual power requirement multiplied by quantity (last column).

		DATE	91134				SRCVAL OTY	2	-	۳ د	٦ د	- -	r .		~ L	- -	ri 1	٦ 1	ri Fi
TER	o o	OPRS	~				SRC	-	•	-	-	r	-	-	-	•	-	_	
SHELTER	S-25-0		E z	:	1	BTU	COOL	•	•	•	•	•	ı	•	1	•	•	•	•
		PHASE	႘ႜႍ			M	HEAT	1	ı	•	•	ı	•	1	1	1	•	•	•
GEN	G-60-4	盂	<b>د ک</b>			į	ı												
	-		w z				AC/DC	ည	ğ	¥C	¥C	٩c	AC	¥Ç	¥	ပ္ရ	ÄC	AC	<b>y</b> C
PRM MVR	13000		418 N					130	65	ı	1	1500	ı	ı	ı	172	32	•	<b>Q</b>
	•		240 N					~	٠.							0	7		0
PRIME	5 TON	6	220 N				AMPS	2.32	ij.		•	13.00				1.50	.27		1.20
E	Ėυ	VOLTAGE	7 X				VOLTS	24.0	5.0	115.0	208.0	115.0	208.0	5.0	9.0	5.0	115.0	8.0	115.0
	7(V)1	Š	120 . Y		ENTS		8		11	_ _	"	11	20		20	11	11	٠	11
ŧ	AN/TPQ-37(V)1		011 N		MODIN			1-743	1-364	3-548	2-563	64	63	5-484		60	ы	0-384	Est.
20	AN/TPC	ı	2 Z	!	E C			0-22	10-43	11-07	1-08	LABLI	LABL	1-08	[LABL]	(LABL)	LABL	11-07	[LABL]
			¥ 00		SUB SYSTEM COMPONENTS		NSN	5820-00-223-7433	5810-00-434-364	5840-01-073-5483	5840-01-082-5633	UNAVAILABLE	UNAVAILABLE	7025-01-086-4849	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	5840-01-070-3848	UNAVAILABLE
		X (H2	0 z		SUE		_	•,	ψ,		•,	_	_	•	_	_	_	-	_
		FREQUENCY (HZ)	20 N		 		•	C-46		4	64		9	80	03			(V)	
9	SET	FRE	o Z		! ! !		MODEL	AN/VR	KY-57	RO-524	IP-13		OL-293	RD-45	1635903			0X-72	BR2009
	IR SET		ES ER				_												
	RADAR		MANUFACTURER ELLIS&WATTS		1 1 1 1 1 1		URE			LINE	PANC		OCES	MAG!	PLY	IST	ST	'RANS	T IC
	4258		MANUF				NOMENCLATURE	OSET	T-SEC	PRINTER, LINE	CATO	IEATER	SIGNAL PROCESSOR	SPORT	POWER SUPPLY	EXHA	FAN EXHAUST	NTENNA TRANSCEI	LIGHT FIXT ICP
	-043-		101	•	! ! !		NOME		T-SE		INDI	HEAT	SIGN	TRAN	POWE	FAN	FAN	ANTE	LIGH
	nsn 5840-01-043-4258	CE	DOCUMENT FM115840355101		1		LINE	53001	501373	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
5		REFERENCE	DOCUMENT TM115840		i				ι ŏ	ž	ž	ž	ž	ž	ž	ž	ž	ž	ž
BER	LINE A41666	RE					SYS CODE		070	033	034	AC035	036	037	038	100	AD099	950	AA006
ž.	1 ~		WGT 20920				SX	AM	7	YC.	V	V	V	Y	V	AD.	8	Ä	2
CONTROL NUMBER FUGO617 SYSTEM	AC032		30.																

~		OPRS DATE		90276			SRCVAL OTY	7	7 1	1	°
HELTER	TYPE S280B/G			•			S TOOS		1		
v:	ıΕα		e l	Z	ł	Britis	2				
	09	PHASE	ည	Z		8	HEAT	1	1	•	1
N.	SYSCD G-60-6U	д	<u>ا</u>	z							
2	J W		တ	<b>&gt;</b>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		AC/D	ŊĊ.	YC.	YC.	•
PRM	MODEL M35A2		28 110 120 208 220 240 418	z	į		ATTS	500 AC	3000	40	360
	MOVER 2 1/2 TON		240	z	į		M Sa	30	20	30	· C
DETME	OVER 1/2	E C	220	z	į		Z	4.30	26.	•	,
_		OLTA	208	z	į		LTS	115.0	15.0	15.0	2
	<b>V</b> 0	>	120	>-	į	ENTS	Š				
	MODEL AN/GSQ-80A		110	z		OMPON		4-350	7-619	2-535	940-0
	MOD AN/		28	z	1	TEM C		00-23	00-17	00-75	00-72
		(2	400	z		SUB SYSTEM COMPONENTS	NSN	6105-00-234-3504	4520-00-177-6198	5830-	6210-
		CY (H	DC 50 60 400	<b>×</b>		SU					
	g	SOUEN	20	<b>&gt;</b>	į		. 7			17C/F	2
	TURE CENT	FR	ည	z	1		MODEL		P-13	LS-147C/FI	O T.M.
	NOMENCLATURE S MESSAGE CENTER		MANUFACTURER	YHANNA			NOMENCLATURE	BLOWER			
	8-679				1		MENCI	OWER	ATER	TERCC	CHU
	00-01			HFC04	† 1 1 1 1 1		2	BI	H	80 IN	1.1
	NSN 9999-00-018-6795	RENCE	DOCUMENT	11415				NONE			
Ł	-	REFE	DOCO	TORE			CODE	-	~		, •
NORDE	LIN D78		WGT	825			SYS	AG041	AG04:	BG	AAO
FUOD530 SYSTEM	CODE AX009		KW								

FUOD534 SYSTEM	CONTROL NUMBER FU00534 SYSTEM COOR LINE	NUM			£		•	1		PRIME	<b>2</b>	PRM MVR	Æ	CEN		SHELTER	ž.	
BE045	L69510		5820-01-247-0980	RADIO TERMINAL	TOKE			AN/TRC-190(V) 4	90(V)4	1 1/4 1	4 TON	MODEL M1037		SYSCD ST-5-6D-2	2-0	TYPE S250		
Ž	REF WGT DOC	REFERENCE	MANUFACTII	CTIRER	FREQUENCY (HZ)	CK (H)	(Z)	28 110	VOI.	VOLTAGE	- 1	l'	c	E (			OPRS	DATE
તં		DATA PLATE	-		Z	8 >	Z	N		0 N	2	Ž	<b>n</b> >-	7 Z	3 =	5 z	8	90283
					1													
						SU	SYSTE	SUB SYSTEM COMPONENTS	ENTS									
	SYS CODE		-	RE	MODEL	-	NSN		VOLTS		AMPS	S THE C	70/20	ı	BTU	1000	VII. 1472000	2
	AA024	NONE		URE	1 BULB	_	UNAVAILABLE	ABLE	120.0	•		9	) V		į '	}	ל נייני נייני	; ~
	AA008	NONE			INCANDESCENT	ENT	NAVAILABLE	ABLE	120.	0	.75	06	Ş,		ı	1	·	
	AM056	NONE	RECEIVER TRANSMI	RANSMI	AN/GRC-226 (V		5820-01	5820-01-248-4767	7 120.0	0	ı	46	Ş		•	•	Ü	-
	AM050	NONE	-	CEIVER	AN/GRC-224	-	5820-01	5820-01-247-9116		0	•	30	Ş		•	•	U	' ~
	AG013	NONE			P-15	•	1520-00	1520-00-912-3502			12.50	1600	NC.		ı	ı	U	ı <b>~</b>
	AM057	NONE	RECEIVER TRANSMI	RANSMI	AN/GRC-226 (V		5820-01	5820-01-249-0356		0	•	9/	AC		•	•	· U	-
	AG070	S0137.			KY-57		5810-00	5810-00-434-3644	4 120.0	0	•	65	¥C			•	U	-
	AM055	NONE	CONTROL UNIT	IT UND	C-11878/T		5805-01	-254-033		0	•	35	Ş		•	1	U	-
	AB008	NONE	MODEM, GRO	UP POW	MD-1231(P	)/T (	NAVAILABLE	ABLE	120.0	0		9	YC.			•		-
	AB007	NONE	CHARGER BA	TTERY	PP-8190/G	v	5130-01	130-01-252-9724	4 120.0	0		80	Ş		1	•	Ú	-
	A0008	NONE	BOX POWER DIST	DIST		٠	MAVAILABLE	ABLE	120.	0	.03	4	Ş			•	U	-
	AD100	NONE	FAN, EXHAU	ST		_	MAVAILABLE	ABLE	120.0		2.87	300	AC			•	ပ	7

	DATE	90276				7	3 ^		• ~
SHELTER TYPE S280B/G	OPRS	4				SKCVAL QII	• E-	· E-	·
	E C	Z	!		D.	3 '	•	•	•
GEN SYSCD ST-10-6D-1	PHASE OTH	Z			BTU		•	•	•
ρĸ	102	_	1		00/04	800 AC	Ş	Ş	¥C
PRH HV HODEL H35A2	0 418	2			S dab & M	800	200	3000	20
PRIME MOVER 2 1/2 TON	20 24	z			AMDS	6.90	4.30	6.00	.17
PRI MOV 2 1	VOLTAGE 28 110 120 208 220 240 418	z	į			115,0			
31	120	<b>&gt;</b>		NENTS	Ô				
MODEL AN/MSC-31	28 110	z	1	M COMPO		6210-00-729-9768	-234-35	-177-61	5830-01-008-3126
	(HZ) 60 400	X X		SUB SYSTEM COMPONENTS	NSN	6210-00	6105-00	4520-00-177-6198	5830-01
NOMENCLATURE OPERATIONS CENT COMMO	FREQUENCY (HZ) DC 50 60 400	z			MODEL	2 LAMPS		P-13	LS-147F
NOMENCLA 11 OPERATIC	MANUFACTURER	HNER				LIGHT FIXTURE			
-167-793					NOMENCE	LIGHT F	BLOWER	HEATER	INTERCOM
NSN 5895-00-167-7931	REFERENCE DOCUMENT	TO&E11415HFC04			LINE	NONE	NONE	NONE	K94880
10		-			S CODE	AA003	041	042	100
	WGT	3140			SY	Ž	ğ	ž (	5
CONTROL NUMBER FU00529 SYSTEM CODE LINE	KK.	ำ							

	DATE	90330				SRCVAL OTY	80	~	~	8	-	Ю	1	8	-	-	-
TER	OPRS	•				SRCV	۲	H	H	۲	H	۲	H	H	H	H	H
SHELTER TYPE S280	H	z	!	ł	BTU	COOL	•	•	•	•	1	•	ı	•	•	•	1
GEN SYSCD G-30-6U	PHASE 3 DC	Z			à	HEAT	•	•	•	1	•	ı	1	•	•	1	•
	1	<b>&gt;</b>				AC/DC	¥C.	¥C	¥C	¥C	AC	¥C	AC	¥C	<b>y</b> C	AC.	AC
PRM MVR MODEL M35A2						WATTS							150			4	46
PRIME MOVER 2 1/2 TON	220 240						2.78	.50	. 60	26.00	.34	4.69	1.30	.70	.80	.03	.40
PRIME MOVER 2 1/2	VOLTAGE 208 22	z						0.				-			0.	0.	o.
8	VO 120	*		ENTS		VOLTS		115.0					0 115.0		_	115	•
MODEL AN/MSC-32	110	z		COMPON			29-976	LE	34-350	77-619	52-535	46-873	03-276	.98-443	23-743	I.E	85-789
¥₹	28	z z		SUB SYSTEM COMPONENTS		z	6210-00-729-9768	UNAVAILABLE	6105-00-234-3504	4520-00-177-6198	5830-00-752-5357	5805-00-246-8734	5815-00-503-2760	5815-00-198-4438	5820-00-223-7434	UNAVAILABLE	6130-00-985-7899
	Y (HZ)	<b>&gt;</b>	 	SUB		NSN		_	61							5	61
NCLATURE ATIONS CENTER	FREQUENCY (HZ)	z				MODEL	2 LAMPS	INCANDESCENT		P-13	LS-147C/FI	TH-5/TG	TT-76/GGC	TT-4/TG	AN/VRC-47		PP-2953/U
NOME	MANUFACTURER	GICHNER	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9			NOMENCLATURE	IGHT FIXTURE		œ	œ	WO:	TELEGRAPH TERMIN	Teletypewriter	Teletypewriter	SET	BOX POWER DIST	POWER SUPPLY
NSN 5895-00-021-2090	Z	U	1			NOMEN	LIGHT	LIGHT	BLOWE	-						_	
NSN 5895-0	REFERENCE DOCUMENT	11435HFC01	j			LINE	NONE	NON	NONE	NONE	K94880	V57709	V36762	V36214	054174	NONE	P38588
23		••				SYS CODE	AA003	800	041	042	,	BE022	BE023	024	AM032	800	NO003
2	WGT	2500				SY	2	2	<b>∑</b>	Ž	8	BE	9 2	BE	Ž	Ž	Ō.
CONTROL FU0057: SYSTEM CODE AWOO1	X	÷															

NETTINE   NETTINE   NETTINE   NOMENCLATURE   NODEL   SYSCD   TYPE		DATE	90330				SRCVAL OTY	•	7	~	-	-	-	-		7	-	-	1	1
LINE NGN	E .	OPRS	m				SRCVI	۲	F	۲	۲	H	۲	F	H	H	۲	H	E	H
LINE NSN   NOMENCLATURE   NODEL   NODEL   NODEL   SYSCD	SHEL TYPE S280		E ×	!	ļ.	5	1	•	١	•	•	•	1	•	•	ı	•	•	١	•
LINE NSN	.0-6-3	PHASE	2 Z			E	HEAT	•	•	ı	1	•	•	•	1	•	•	•	•	•
LINE NSN	GEN SYSC ST-1		m z				' ည													
LINE   NSN	MVR EL A2	1	∞ ≻				•	-	¥C	¥	¥	¥	¥Ç	AC	¥Ç	AC	¥	AC	YC.	YC.
LINE   NSN			4 4 2				WATTS	180	500	3000	40	180	160	160	385	220	4	100	100	•
LINE NSN	TON NO.									00	34	26	39	30	30	06	03	80	80	60
LINE NSN	PRIME MOVES 2 1/2						2	4	4	26.	•	4	ä	ä	ë	4	•	•	•	•
LINE NSN   NOMENCLATURE   MODEL		VOLTA					OLTS	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
LINE NSN   NOMENCLATURE	ASC				NENTS		>	-	4			_	_		•			-	-	-
LINE NSN   NOMENCLATURE	DEL -675/i		110 N		COMBO			冒	34-35	77-61	08-31	46-87	07-83	98-44	03-14	15-61	44-30	벌	띰	멸
LINE NSN   NOMENCLATURE			% % %		STEM			<b>VILAB</b>	-00-	-00-1	-01-0	-00-	6-00-	-00-	-00-	-00-	-00-	AILAB	<b>NILAB</b>	MAVAILABLE
LINE NSN   NOMENCLATURE	ICATIÇ	HZ)	4 0 0		UB SYS		NSN	UNAV	6105-	4520-	5830-	5805-	5805-	5815-	5805-	5805	6625-	UNAV	UNAV	UNAV
LINE NSN  LINE REFERENCE  MCT DOCUMENT  2644 114354FC01 TOBYHA  2644 114354FC01 TOBYHA  AA006 NONE BLOWER  AG041 NONE BLOWER  AG042 NONE BLOWER  AG042 NONE BLOWER  BE003 V57709 TELEGRAPH  BE003 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE017 NONE OSCILLOSCO	OMENCIA	NCY (	9 ⊁		S											E	81C			
LINE NSN  LINE REFERENCE  MCT DOCUMENT  2644 114354FC01 TOBYHA  2644 114354FC01 TOBYHA  AA006 NONE BLOWER  AG041 NONE BLOWER  AG042 NONE BLOWER  AG042 NONE BLOWER  BE003 V57709 TELEGRAPH  BE003 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE017 NONE OSCILLOSCO	S LNG CNG	REQUE	e z				13	600		_	147F	5/TG	22/TG	t/TG	248/A	22A/P	USM-1	ın		
LINE NSN  LINE REFERENCE  MCT DOCUMENT  2644 114354FC01 TOBYHA  2644 114354FC01 TOBYHA  AA006 NONE BLOWER  AG041 NONE BLOWER  AG042 NONE BLOWER  AG042 NONE BLOWER  BE003 V57709 TELEGRAPH  BE003 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE017 NONE OSCILLOSCO	LATUR	E	ğ z				MOD	BR2		P-1:	LS.	TH-	TH	Ĺ	TA-	SB-	AN/	223	475	
LINE NSN  LINE REFERENCE  MCT DOCUMENT  2644 114354FC01 TOBYHA  2644 114354FC01 TOBYHA  AA006 NONE BLOWER  AG041 NONE BLOWER  AG042 NONE BLOWER  AG042 NONE BLOWER  BE003 V57709 TELEGRAPH  BE003 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE016 V57729 TELEGRAPH  BE017 NONE OSCILLOSCO	OMENC!		<u> </u>				60	S S					ERMIN	ĒR			LEPHO	62	ω	IST
### LINE NSN   NS9898 5805-00-   NS9898 5805-00-   REFERENCE   NGT DOCUMENT   S44 114354FC01   S44 114354FC01   S4042   NONE   S6042   NONE   S6042   NONE   S6042   NONE   S6042   NGT09   S6043   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6032   NONE   S60322   NONE   S60			TUPAC	!			ATURI	TXI			×	LPH T	LP HO	EWRI'	OR R	SOARD	T TE	SCOPI	SCOPI	E D
### LINE NSN   NS9898 5805-00-   NS9898 5805-00-   REFERENCE   NGT DOCUMENT   S44 114354FC01   S44 114354FC01   S4042   NONE   S6042   NONE   S6042   NONE   S6042   NONE   S6042   NGT09   S6043   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6030   NONE   S6032   NONE   S60322   NONE   S60	57-78		<b>3</b> 2				MENCI	GHT	OWER	CATER	TERC	LEGR	LEGR	<b>LETY1</b>	NERA	ITCHI	ST SI	CILLA	SCILL	× Z
S82 LINE LINE LINE REFE WGT DOCU 2644 1143 AA006 AG041 AG042 BG001 BG001 BE024 BE016 BE016 BE016 BE016 BE016 BE016	00-16		<b>.</b>				_	_	_	_	-,	•	•	•	•	٠.	•	٠	٠	_
### LINB   N5988   N6T   N67	NSN 5805-	RENCE	MENT				LINE	NON	NON	NON	K948	V577	V577	V362	3352	V817	NON	NON	NON	NONE
2	8	REFE	1143				CODE	9	-	~	-	~	ú	4	9	ø	•	-	7	ω,
1 E82.2	LIN NS9		#GT 644				SXS	AAOO	AG04	AG04	BG00	BE02	BEOO	BE02	BE01	BD01	BE03	BE03	BE03	A0008
SYSST CODE BDOO A KA A KA	FU00582 SYSTEM CODE BD001																			

		TE ST	90330				OF.	-	-	-	<del>ا</del>	8	-	1 7	~	-	m
		DATE	90;				SRCVAL OTY	F	E	H	H		E		H	۲	-
8	វី ស 🤈	OPRS	m														-
2	TYPE S250	į	E z	ļ	!	Đ	1000	1	1		1	1	1	1	ı	1	•
	ñ	PHASE	Z Z	1		BTU	HEAT	•	ı	•	1	•	ı	•	ı	1	1
š	SYSCD ST-5-6-3	₹	r z				1										
	4	,	n >-				20/20	<b>,</b>	×	Q	ŭ	×	Ų	Ų	ပ္	Q	ပ္က
<b>300</b>	MODEL M1028		e T						1045 D	_	•	_	2009		•	•	_
	NOT		Z														
DOTAG		23	Z				AHP.	1.3	37.30	1.40	14.4	15.2	5.20	.80	4.3	13.00	3.20
Ď	i <b>z</b> a	VOLTAGE	N X				LTS	5.0	0.8	8.0	5.0	8.0	115.0	8.0	5.0	5.0	28.0
	42D	7	7 X		ENTS												
	MODEL AN/GRC-142D	:	N X		OMPON			3-606	3-754	9-480	3-976	7-914	2-819	0-561	4-350	7-619	3-744
	MOD/NN/	0	o Z	į	O HOL			00-55	00-22	00-91	11-00	01-24	90-10	01-08	00-23	00-17	00-14
	•	2	Z		SUB SYSTEM COMPONENTS		NSN	5815-00-553-6061	5820-00-223-7548	5815-00-919-4800	5820-(	5130-(	5815-01-062-8194	5810-(	6105-00-234-3504	4520-00-177-6198	6240-00-143-7441
	뛾	X (H)	<b>2</b> ×	i	53		_	•				Ī			•	•	•
	SWRIT	FREQUENCY (HZ)	2						3-106	K	3A/G		3-74A				
	CLATURE TELETYPEWRITER	F. 7	ď z	 			MODEL	TT-76A	AN/GRC-106A	MD-522A	PP-4763A/GRC	P-724A	AN/UGC-74A(V	KW-7D		P-13	BULB
	U	040	ECH	1				~		ELE			EWR				
	NOMEN	MANITEA	ELECTRO MECH				TURE	WRITE	F	DIO T	PPLY		LETYP				20 FB
	-7264	MANIT	ELEC				MCLA	STYPE	IO SE	er Ra	SR SU	TRTER	RADIO TELETYPEWR	ပ္က	ir Er	ĒR	LIGHT BULB DC
	-104		14	i			E O N	TEL	RAD.	<u> </u>	POW	IN	RAD!	T		HEATER	LIG
	NSN 5815-01-104-7264	REFERENCE	TM11581533414				LINE	V36762	932756	M58822	P40745	NONE	V36146 1	H02300	NONE	NONE	NONE
	0	REFER	TM11:				ODE										
NUMBER	LINE 290120	HGT.	1335				SYS CODE	BE005	AM014	BE010	A0004	A0011	AX007	AG044	AG041	AG042	AA005
CONTROL NUMBER FU00571 SYSTEM	CODE BE009		6.														

		DATE		90330				L OTY	~	7	~	~	~	7	7	-	~	7	18
TE X		OPRS		М				SRCVAL QTY	F	H	E	H	۲	F	F	F	E	H	H
SHELTER	TYPE S280	Ū	HIO	z		!		COOL	•	1	•	1	•	1	•	1	•	ı	•
	6D-1	PHASE	2	Z			BTU	HEAT	1	t	1	•	•	1	1	ŧ	1	,	•
ZEN	SYSCD ST-5-6D-1	ጁ	٣	z				ı											
			S	<b>&gt;</b>				AC/DC	¥	¥Ç	¥C	¥C	Ş V	¥C	¥	¥C	¥	Ş	<b>Y</b> C
PRM MVR	MODEL M35A2		418	z				ITS	158	80	9	240	740	70	9	40	200	3000	720
	NOL		240	z							0	9	5	0	0	0	0	9	0
PRIME	MOVER 2 1/2 TON	M	220	z				AMPS	1.37	69.	.50	2.00	6.43	9.	.50	.30	4.30	26.00	6.20
Δ.	<b>X</b> (4)	VOLTAGE	208	z				70LTS	115.0	5.0	115.0	115.0	115.0	5.0	115.0	5.0	115.0	5.0	115.0
	51V	>	120	>		ENTS		8	•	_	_	_	Ξ.	_	_		•		
	MODEL AN/TRC-151V		110	z		NOGWC			4-911	8-338	8-836	9-879	5-493	0-807	4-217	2-535	4-350	7-619	9-6-6
	MODEL AN/TRO		78	z		S M			30-00	30-92	01-02	90-00	00-93	30-93	99-00	00-75	00-23	00-17	00-72
		3	100	*		SUB SYSTEM COMPONENTS		NSN	5810-00-054-9110	5820-00-928-3382	5805-01-028-8364	5805-00-069-8795	5820-00-935-4931	5805-00-930-8079	5805-00-884-2176	5830-(	6105-00-234-3504	4520-00-177-6198	6210-00-729-9768
	. •	FREQUENCY (HZ)	9	×		SUE		~	•,						٠,			•	
	MINAI	OUENC	20	×				_		0/BG	65A/0	48/6	AN/GRC-103V	4/6		LS-147C/FI	•		IPS
	TURE	FRE	12	z				MODEL	KG-27	TD-66	TD-10	CV-1548/G	AN/GE	TD-75	TD-202	LS-14		P-13	2 LAMPS
	NOMENCLATURE RADIO SET TERMINAL		ACTURER					JRE	, KEY										LURE
	NSN 5820-00-006-8843		MANUFACTUR	•				NOMENCLATURE	GENERATOR, KEY	MULTIPLEXER	UFFER DA	CONVERTER TELEPH	PADIO SET	MULTIPLEXER	MULTIPLEXER	INTERCOM	BLOWER	EATER	LIGHT FIXTURE
	-00-	Ħ	٠.	1969					2			F05376 (			1579	K94880	<u> </u>		_
	NSN 5820	REFERENCE	DOCUMENT	TM11589569614	Ī	İ		LINE		M84	H35	FO	037	NONE	M8	K94	Õ	NONE	NONE
<b>E</b>	LINE Q92899	REF	8	TMI				SYS CODE	51	50	55	15	21	52	53		41	42	8
NCMB	38		WGT	1380				SXS	AE051	AE050	AEO	BDO	AMO	AEO	AE053	ä	AGO	AGO	AA003
CONTROL NUMBER FU00572 SYSTEM	CODE AX029		KM	٠. د.															

	DATE	91157			C OTY	~	~	-	-	-	~	7	7	-	-	-	-	-
S	OPRS	~			SRCVAL OTY	۲	₽	۲	۲	H	w	H	64	H	H	H	۲	E
SHELTER TYPE S-250	ō				000 000	•	,	•	•	,		,		•	,	,	•	•
				3TC	•													
9	PHASE	<b>*</b>			HEAT	•	•	•	•	•	•	•	•	•	•	•	•	•
GEN SYSCD G-10-4D		ייכר			' 路													
PRM MVR MODEL M1037	ju ju	0 Z			AC/DC		¥	¥C	¥	¥	¥	¥	Ճ		YC.	Ž	¥Ç	<b>V</b> C
	-	, z			WATTS	130	65	•	1	•	ı	40	9	80	1500	1	١	32
PRIME MOVER 1 1/4 TON	240				AMPS	2.32	.50	•	ı	ı	ŧ	.34	2.10	.70	13.00	•	•	.27
PRIME MOVER 1 1/4	GE				2	ď	•					•	N		13			
	VOLTAGE				VOLTS	28.0	15.0	208.0	15.0	15.0	115.0	15.0	15.0	15.0	115.0	0.80	0.80	115.0
36 (V)	150	7 ×	NENTS		>	33	_		83 1	_	-			-	_			-
MODEL AN/TPQ-36(V)1	-	Z	COMPO			23-74	34-36	82-56	73-54	86-48	ZE EE	LE	43-74	Ę	LE	LE	E	LE
A W	o C	N Z	STEM			5820-00-223-7433	5810-00-434-3644	5840-01-082-5633	5840-01-073-5483	7025-01-086-4849	MAVAILABLE	MAVAILABLE	6240-00-143-7441	NAVAILABLE	NAVAILABLE	NAVAILABLE	NAVAILABLE	NAVAILABLE
	HZ)	<b>2</b> ×	SUB SYSTEM COMPONENTS		NSN	5820	5810	5840	5840	7025	CNAV	CNAV	6240	UNAV	UNAV	UNAV	CNAV	CNAV
	FREQUENCY (HZ)	Z	S			١.												
M	EQUE	Z			닖	AN/VRC-46	7.	FP-1364	524	28	7	600	•			1635903	893	
ATURE	E (	z			MODEL	AN/	KY-57	IP-I	RO-6	RD-458	-X0	<b>BR2009</b>	BULB			163	OL-293	
NOMENCLATURE RADAR SET	0401	N N			•			NORA	••	GNET	IVER	E IC	õ				SSOR	
	dita Antiga	HUGHES			ATURE	닯		OR PA	LINE	RT MA	RECE	IXTUR	ULB C			UPPLY	PROCE	AUST
NSN 5840-01-043-4257	7	-			NOMENCLATURE	RADIO SET	SEC	INDICATOR PANO	PRINTER LINE	TRANSPORT MAGN	ANTENNA RECEIV	GHT F	LIGHT BULB DC	z	HEATER	POWER SUPPLY	GNAL	FAN EXHAUST
01-04		54101			2	01 RA	73 T	Z	PR									
NSN 5840-	REFERENCE	TM115840354101			LINE	253001	5013	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
8	REFERENC	11111			CODE		_		_	_	_	٠,		_	٠,	~	••	•
NUMBER LINE R14148	E CA	4440			SXS	Æ	AG070	AC034	AC03.	AC037	AC05.	AAOO	AA00	AC058	AC03	AC038	AC03(	AD099
CONTROL NUMBER FU00621 SYSTEM CODE LINE AC002 R141	35	-																

	DATE	90283			AT. OTV	۳ ا	C	7	-	-	-	-	٦	<b>œ</b>	-	-	-	-		-	-
Ä	OPRS	8			SECUAL	ပ	O	U	U	U	U	O	U	U	S	S	S	Ü	S	O	U
SHELTER TYPE S250	E	Z	ļ	ļ	BTU	1	1	•	•	•	•	•	٠	1	1	•	•	•	1	ı	•
GEN SYSCD ST-5~6D-2	PHASE	Z			HEAT		•	•	•	•	•	1	٠	1	1	•	•	•	•	•	1
	U	>			JU/J	) V	<b>Y</b> C	¥Ç	YC.	¥	VC	¥C	¥	¥	¥C	¥Ç	¥C	¥C	¥Ç	<b>A</b> C	<b>V</b> C
PRM MVR MODEL M1037	418	•			Subdist	9	90	300	1600	4	32	100	40	270	1	1	•	80	26	65	20
PRIME MOVER 1 1/4 TON	220 240				AMPS		57.	2.87	12.50	.03	ı	.80	ı	ı	•	•	•	•	.46	•	.16
ä. X →	VOLTAGE	Z		S S	S#TOV	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0
MODEL AN/TRC-191	110 1	z		SUB SYSTEM COMPONENTS		BLE	BLE	BLE	520-00-912-3502	BLE	805-01-254-0333	BLE	BLE	820-01-247-9118	5985-01-247-9115	5820-01-252-9770	BLE	252-9724	5805-01-246-6826	5810-00-434-3644	5810-01-213-8200
**	18	z		UB SYSTEM	NSN	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	4520-00-	UNAVAILABLE	5805-01-	UNAVAILABLE	UNAVAILABLE	5820-01-	5985-01-	5820-01-	UNAVAILABLE	6130-01-252-9724	5805-01-	5810-00-	5810-01-
NOMENCLATURE RADIO ACCESS UNIT	FREQUENCY (HZ)	Z		S	MODET.	1 BULB	INCANDESCENT		P-15		C-11878/T	TD-1426(P)/T	MD-1231(P)/T	RT-1539	CV-2391	C-11865	K-022	PP-8190/G	TA-1035/U	KY-57	KG-94A
	MANIFACTURER	GTE			NOMENCI. A TITRE	LIGHT FIXTURE	LIGHT	FAN, EXHAUST	HEATER MILITARY	BOX POWER DIST	CONTROL UNIT ORD	MODULE LOGIC GRO	MODEM, GROUP POW	RECEIVER TRANSMI	MULTICOUPLER ANT	CONTROLLER RECEI	CONTROL UNIT RAD	CHARGER BATTERY	TELEPHONE DIGITA	T SEC	T SEC
NSN 5820-01-247-5731	REFERENCE DOCUMENT	DATA PLATE			LINE	NONE	NONE	NONE	NONE		NONE										.L089J
NUMBER Line R33351	REFE WGT DOCU	_			SYS CODE	AA024	AA008	AD100	AG013	A0008	AM055	AM058	AB008	AM059	AM060	AM061	AM062	AB007	AE060	AG070	AG071
CONTROL NUMBER FU00535 SYSTEM CCUE LINE BEO46 R333	K	2.																			

	9	91065			OTY	~	~	N	~	~	<b>-</b> 4 :	7	-	7	٦	~	-	H	7	-		٦	-	-	-1	-	-	Ħ	-	~		-1	-	-
	DATE	91			SRCVAL	Ü	ر ن	U ·	U ·	C)	o i	U	U	ပ	ပ	U	U	υ	Ü	U	Ü	Ü	Ü	υ	U	Ü	U	U	U	υ	رن	ú	ú	ບ
TER 7B/G	OPRS	~			SRC																										-	_	_	
SHELTER TYPE S-457B/G		E z	,		COOL	•	1	•	1	١	ı	1	1	1	ı	•	1	ı	1	•	•	i	1	1	•	í	í	í	•	ı	f 1	4	1	1
	PHASE	₹ ≈		T The	HEAT	•	ı	•	ı	1	ŀ	ı	•	ı	١	•	ı	ŧ	ı	1	ı	ı	ı	ı	1	ı	ı	ı	ı	ŧ	1 1	ı	1	•
GEN	E (	n >+	i		Ì																													
ğ	le	n z	1		AC/DC	YC.	<b>A</b> C	Ų.	٧ç	YC YC	¥C	¥Ç	YC	AC AC	AC	ည္က	AC	AC	AC	ည္ရ	AC	AC	AC	ည္က	AC	AC	AC.	AC	AC	YC.	S V	Ö	S	ည
PRM MVR MODEL M1037	- 1	Ž Z	1		WATTS	ı	30	•	120	ı	32	ı	•	1	142	9	1	1	•	ß	•	ı	•	33	1	ı	1	ŀ			30			
TON	3	ę z				,	9		4	ı	0				m	0				0	1	1		6	i		ı	ı	ı	0	v <sub>e</sub>			. 0
PRIME MOVER 1 1/4	a,	N			AMPS		. 26		1.04		.30				1.23	2.50				.20				1.89						2.00	186	. 20	. 62	1.00
	8	80 X			VOLTS	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	24.0	115.0	115.0	115.0	24.0	115.0	115.0	115.0	24.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	24.0	24.0	24.0
2 (V)		X X		ENTS	>																		_											
MODEL AN/TRQ-32(V)1	:	N X	1	COMPON		5811-01-165-0409	5895-01-165-6225	5895-01-166-6958	7025-01-257-0177	5930-01-258-8009	6110-01-165-0405	5895-01-166-6949	5895-01-115-9154	1680-00-903-4378	5895-01-266-8236	5835-01-023-4332	7025-01-168-0084	5821-01-070-4433	5820-00-892-0624	5810-00-434-3640	5915-01-165-6223	5915-01-165-6224	5810-01-068-3693	5820-00-892-0622	7025-01-263-6049	7045-01-260-4984	5810-01-063-2875	6130-01-259-3074	5895-01-262-1191	5821-01-122-7094	5865-01-084-0421			5985-01-274-8934
MOI	ļ	» ×		WE		01-10	01-10	01-10	01-2	01-2	01-10	01-10	01-1	6-00	01-2	01-0	01-10	0-10	9-00	00-4	01-10	01-10	01-0	8-00	01-2	01-2	01-0	01-2	01-2	01-13	01-0	TABI	LABI	1-2
	HZ)			SUB SYSTEM COMPONENTS	NSN	5811-(	5895-	5895(	7025-(	2930-(	6110-(	5895-	5895-(	1680-(	5895-(	5835-(	7025-(	5821-(	5820-(	5810-(	5915-(	5915-(	5810-(	5820-(	7025-(	7045-(	5810-(	6130-(	5895-(	5821-(	5865-	UNAVAILABLE	INAVATLABLE	5985-(
OI.	FREQUENCY (HZ)	S >		, co		10		R-	<b>20</b>	<b>1</b> 20-	80	<b>18</b>	ğ	50	<b>20-</b>	4		C-1	Ö		٠ ب	Ļ			'RQ-	Ņ	RC RC	<b>70</b>	<b>180</b> -	ARC	SS C			
RAD	OUEN	) () <b>%</b>				A/QT	570	83/T	24/1	165	44/1	49/1	02/C	100-	45/T	H-17	5/6	7/A	A/VE	7	-925	525-	Ē1	4	44/T	838-	71/	79/1	44/T	88A/	1965			
NOMENCLATURE RECEIVING SET RADIO	FRE	ďΖ			MODEL	C-1611D/A1C	MX-10570	C-11383/TRR-	CP-1824/TRQ-	SA-2559/TRQ-	SA-2444/TRQ-	ID-2349/TRR-	C-11002/USQ	4408-100-29	C-11845/TRQ	AN/UNH-17A	RP-272/G	C10547/ARC-1	R-442A/VRC	KY65E-1	65110526-1	65110525-1	KG-84E1	RT-524	C-11844/TRQ-	C5139838-2	SA-2171/VRC	PP-8179/TRQ-	C-11844/TRQ-	RT-1288A/ARC	CV-3579/TSO MX-10526/TRO			
NOMENCL		OREK				RCOM	CLI		A PR		m̃.	8	DIRECTION CONTRO	FUNC	CONTROL RECEIVER	RECORDER REPRODU	MAT		oi		FILTER BAND PASS	PASS	×		HIN	E	FRE		CONTROL PROCESSO	NSMI	CONVERTER MAGNET	BLY	) X	ROL
N N		AVOX			TURE	INTE	DIRE	INDI	DAT	SSY	LION	BOAR	ο Σ	TI.	RECE	REP	AUTO	RADIO	RAD		AND	NO	X GE		VE G	CARTRIDGE	CIGN	PPLY	PROC	TRA	Žζ Ž	SSEM	SSEM	LNO
7655		MAGNAVOX	į		NCLA	ROL	CONTROL DIRECT	ZOL L	INAL	SWITCH ASSY	RIBU	ž	ÖLLO	L FA	ROL	RDER	rer	ROL	IVER	ບ	ER B	ER B	r KE	0	DRI	CAR	CH A	R SU	ROL	RECEIVER TRANSMI	FRIE	ER A	Y	AN.
167-	_				NOMENCLATURE	CONTROL INTERCOM	CONT	CONT	TERMINAL DATA	SWIT	DIST	DISPLAY BOARD	DIRE	PANEL FAULT FUNC	CONT	RECO	PRINTER AUTOMAT	CONTROL RADIO	RECEIVER RADIO	T SEC	FILL	FILTER BAND PASS	ELECT KEY GEN 1	RADIO	DISK DRIVE UNIT	DISK	SWITCH AUDIO FRE	POWER SUPPLY	CONT	RECE	00NO 10NO 10NO	DRIVER ASSEMBLY	SWITTCH ASSEMBLY	ANTENNA CONTROL
-01-	E	0701	1			98	_ 四	_	-	ы		_			_				R25600					 6			-		Ē					
NSN 5895-01-167-7655	REFERENCE	TM32589507010	Ì		LINE	E90	NON	NONE	NONE	NONE	NON	NONE	R25	NONE	NONE	NONE	NONE	R33	NONE	NONE	NON	NONE												
	REFE	TM32			ODE		_	_									_	_		_	_			_				_	_					
NUMBER LINE R36854	£53	2966			SYS CODE	AX068	AX069	AX070	AX071	AX072	AX073	AX074	AX075	AX076	AX077	AX078	AX079	AX080	AX081	AX082	AX083	AX084	AX085	AM019	AX086	AX087	AX088	AX089	AX090	AX091	AX092	AX094	AX095	AX096
CONTROL PUOCEOS SYSTEM CODE		5. 2																																

		DATE	90300				T. OTV	4		-		-		-	17	80	~
	TEK	OPRS	٣				SPCU	F	-	· E-	•	₽	•	H		F	H
	SMELTER TYPE S280		Z		!	P	1000	1	1	•	1	•	•	1	1	•	1
	•	PHASE	Z		1 5 6 1 1	BTU	HEAT	'	1	•	1	1	1	ı	•	ŧ	•
į	SYSCD G-5-6D	ā,	2				١										
	¥	lu	>				AC/DC	Ş	AC.	S V	AC	Ճ	Š	¥C	¥C	¥Ç	AC
2	MODEL M35A2	418					ATTS	1350	3000	9	46	53	200	75	340	240	4
6	MOVER 2 1/2 TON	240	Z				AMPS W		26.00		.40	1.89	4.30	.60	2.90	2.00	.03
0074	MOVER 2 1/2	AGE 220	Z				2	_					4			~	
		VOLTAGE	X		Ø		VOLTS	115.0	115.0	115.0	115.0	28.0	115.0	115.0	115.0	115.0	115.0
	-138	- 1			ONENT			356	198	357	899	622	504	980			
	MODEL AN/TRC-138	28 110	2		SUB SYSTEM COMPONENTS			5820-00-926-7356	4520-00-177-6198	5830-00-752-5357	-985-7	-865-0	-234-3	-985-	ABLE	ME	ABLE
		(2 400 (1)		i 1 1	SYSTE		z	20-00	20-00	30-00	30-00	20-00	02-00	02-00	MAVAILABLE	NAVAILABLE	MAVAILABLE
		(HZ) 60 4	<b>&gt;</b>	1	SUB		NSN	58	45	58	61	28	61	28	_	_	5
	α.	FREQUENCY (HZ)	z					7-144		C/FI	33/U			×	_	INCANDESCENT	
	TURE PEATE	FRE	z				MODEL	AN/GRC-144	P-13	LS-147C/FI	PP-29	RT-52		CV-425/V	BR2009	INCANI	
	NOMENCLATURE RADIO REPEATER	ACTURER	GICHNER	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			URE	•					BLOWER	TELEGR	T ICP		BOX POWER DIST
	-8841						ENCLA	RADIO SET	IER	ERCOM	ER SUF	ဝ	E S	VERTER	EL EL	H	POWER
	0-133		3-15				NON NON	RAD	HEA	O INT	80 POW	9 RAD	BIO	200	LIG	FIG	
	NSN 5820-00-133-8841	REFERENCE DOCUMENT	820-77				LINE	NONE	NONE	K9488	P3858	R3393	NONE	F0461	NONE	NONE	NONE
g	8	REFE	11-5				SYS CODE	<b>-</b> , (	<b>.</b>	,	<u>m</u> (	، نو	٠,	۰ م	، م	20 (	<b>20</b>
NUMBI	LIN R78	WGT	4465				212	BEOIL	AG04	8	AOOC	AMOI	AG04	BEOC	AAOC	AAOC	Acco
CONTROL NUMBER FU00567 SYSTEM	CODE AX013	KW	ທີ														

	DATE		90323				QTY	m	٣	٣	-4	7	~	18
æ	OPRS D		6				SRCVAL OTY	ß	S	S	ß	ß	ß	Ŋ
SHELTER TYPE S280	OP		••										í	
SH TYI S2		Ę	z			Þ	1000 000							
d	PHASE	ا ا	z		1 1 1 1 1 1 1	BTU	HEAT	ı	•		•	•	,	,
gen Syscd ST-5-6D-1	太	٣	z				1							
E a a		ß	×				2/00	ပ္ခ	ŭ	ŭ	ŭ	ŭ	٧c	ŭ
PRM NVR MODEL M35A2		418	z				TTS 1	110 7	105	06	0		0000	
		240	Z								_		٠,	
PRIME MOVER 2 1/2 TON	60	220	z				AMPS	9.60	.90	. 78	.30	2.60	26.00	6.90
Z¥∾	OLTAG	208	x				LTS	5.0	5.0	5.0	5.0	5.0	115.0	5.0
Ŋ	>	120	>		MTS		8							
2 -13	1	110 120	z		PON			-4931	-8075	-2176	-5357	-3504	-6198	
MODEL AN/TRC-152		28	z		8			976-0	0-630	0-884	0-752	0-234	0-177	LABLE
	3	400	z	i	SUB SYSTEM COMPONENTS		NSN	5820-00-935-4931	5805-0	5805-0	5830-00-752-5357	5105-0	4520-00-177-6198	MAVAI
	(H)	9	*		SU					_		Ĭ	•	
NOMENCLATURE RADIO REPEATER	FREQUENCY (HZ)	20	z				ODEL	N/GRC-103	TD-754/G	D-202	LS-147C/FI		-13	2 LAMP
CLAT			<b>X</b>				Ï	*	E	H	7		Δ,	N
NOMEN		MANUFACTURER	G SYSTE				NOMENCLATURE	H	XER	XER				1000
1832		MANU	CRIT.				NCLA	OSE	IPLE	IPLE	RCOM	気	ă	E,
-900-			Š				NOME	RADI	MOLT	MOLT	INTE	BLOW	HEAT	LIGH
NSN 5820-00-006-1832	ENCE	DOCUMENT	1415HF				LINE	032687	NONE	M84579	K94880	NONE	NONE	NONE
	REFERENCE		06E1	•										
LINE R78067		WGT	•				SYS CODE	AM021	AE052	AE053	BG	AG041	AG042	<b>AA</b> 009
FU00557 SYSTEM CODE AX018		Ž	•											

	DATE 90311	\$200H400
E C	3 91	SRCVAL QTV T 2 T 1 2 T T 1 1
Shelter Type S250	•	100 D
2-5	PHASE 3 DC OTH Y N N	Bru
GEN Syscd St-3-6-2	E   ~ ~	į l
gs.	w z	999999
PRM MVR MODEL M561	4 16 N	WATTS AC/DC 3000 AC 500 AC 40 AC 80 AC 1110 AC
	N N	
PRIME MOVER 1 1/4 TON	VOLTAGE 28 110 120 208 220 240 418 N N Y N N N N	AMPS 26.00 4.30 .30 .69
	VOLTAG 208 N	S VOLTS 115.0 115.0 115.0
MODEL AN/TRC-113(V)1	120 Y	20 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
EL TRC-	110 N	20MPO 17-61 14-35 12-53 15-83 35-49
MOD NN/	8 Z	158 0 00-17 00-2 11AB 00-9
•	REQUENCY (HZ) ; 50 60 400 ; N Y N	SUB SYSTEM COMPONENTS  NSN  4520-00-177-6198 11 6105-00-234-3504 11 5830-00-752-5357 11 UNAVAILABLE 5820-00-935-4931 111 5805-00-930-8079 11
	X (F	<b>!</b> >
SET	O E	C/FI
LATURE REPEATER SET	PRED	MODEL P-13 LS-147C/FI BR2009 AN/GRC-103V TD-754/G
NOMENCLATURE RADIO REPEATI	MANUFACTURER CRAIG SYSTEM	URE II ICP
NSN 5820-00-813-6359		LINE NOMENCLATURE NONE HEATER NONE BLOWER K94880 INTERCOM NONE LIGHT FIXT ICP Q32687 RADIO SET NONE MULTIPLEXER
0-81	2-14	SHEUJER RELIGIEN
NSN 5820-0	REFERENCE DOCUMENT 11-5820-562-14	LINE NONE NONE NONE NONE NONE
9	XEFE 30CU 11-5	ODE
LINE R78130	WGT 1	SYS CODE AG041 AG041 BG AA006 AM021
FU00547 SYSTEM CODE AX008	• KW	

	DATE 90330		Ę,	<b>V</b>	N 1	N	N	N (	7	N	<b>-</b>	₹ (	Ω,	~
	-		SRCVAL OTY	<b>:</b> • (	H	<b>H</b> (	<del>[</del> 4 (	H	H	F I	H	<b>F</b> (	<b>:</b>	F
Shelter Type S250	OPRS 3													
SHEL/ TYPE S250	H N	Bru	1000	•	•	•	•	•		•	•	•	•	•
7	PHASE DC		HEAT	í	•	ŧ	•	•	•	ŧ	•	,	,	ı
gen Syscd St-3-6-2	E Z		1											
•	S >-		AC/DC	ຍ	ບ	ပ	ບ	ບ	ğ	ບ	ပ	U	ပ္ရ	U
PRM MVR Model M1028	( <del>0</del> ) ×						•	Ž 0	-	-	-			Z T
	•		WATTS	300	Š	24	80	7	158	74	9	120	10	
TON	240 N	}				_	69.	9.	37	6.43	30	1.00	.80	.03
PRINE MOVER 1 1/4 TON	220 N		AMPS	26.	4	2.00	•	•	ä	ø	•	<del>ب</del>	•	•
A Z A	VOLTAGE 208 N		VOLTS	115.0	5.0	115.0	5.0	115.0	115.0	115.0	5.0	5.0	5.0	115.0
<b>8</b>	× 20 ×	NTS	8				•						11	11
Model An/Trc145bv	2 7	PONE		-6198	-3504	-8795	-3382	-8079	-9110	-4931	-5357			
MODEL AN/TRO	80 20	8		-177-	-234	-0690	-928-	930	-054	-935	-752	ABLE	ABLE	ABLE
	10	SUB SYSTEM COMPONENTS	_	1520-00-177-6198	6105-00-234-3504	5-00	5820-00-928-3382	5805-00-930-8079	5810-00-054-9110	820-00-935-4931	5830-00-752-5357	NAVAILABLE	NAVATLABLE	MAVAILABLE
	HZ) 400 N	S an	NSX	452	610	800	582	580	583	582	8	25	(NE)	5
	FREQUENCY (HZ) C 50 60 4 Y Y					,,				330		ENT		
4	200 ×	İ	د			W-1548/G	60 / BK	54/5	,	NN/GRC-103V	.8-147C/FT	NCANDESCENT	ő	}
TURE	10 ×	İ	MODE	2-13	}	2-7	13-61	Ē	KG-27	U/NY	1.8-1	TNCA	RD2009	
nomenclature Radio Terminal	NA.					70							^	. <b>e.</b>
NOME	Manufactur Gichner		200	1		TAG	į	í£	, i				1	DIS
847	MANUFAC	į	E-4.10		4 0	7	72.10	7	400	100	1 2	5	7	OWER
NSN 5820-01-104-4748			STATE OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY OF THE PARTY	4444	DICTOR	CONTRDUCTO FFT.FOH	MIT TIDE EYED		Ceves for	DANTO SEE		1		BOX POWER DIST
01-1	5314		2			9 0		5 Z	. C	7 0	, r	7 F	4 6	4 M
NSN 5820-	REFERENCE DOCUMENT TH11589545314		7 7 20			NONE					7			NONE
9	REPER DOCUM		å	9										
MBER LINE R92996			2000	֓֞֝֞֝֞֜֞֜֞֜֞֜֞֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	7000	1 0	CTOO	000	2007	1003	A021	2		A0008
5 NG	WGT 2560		ē	0 2	ć	Ċ	Ö Á	¢ ?	< €	¢ 7	¢ ŝ	0 4	Ç 4	< <
CONTROL NUMBER FU00575 SYSTEM CODE LINE AXO06A R929	KW													

			DATE		90330					L OTY	2	۰ ۸		• ^		. ~	۱ ۸	-	'n	4	-	7	
	ğ		OPRS		m					SRCVAL OTY	E	. 6-	· E-	• E	• E-	• E-	• 6-	•	H	•	•	H	
	SHELTER	\$250	Ü	H	z				Þ	1000	1	1	١	•	١	•	١	•	1	•	•	•	
		6-2	PHASE	 임	z				BTC	HEAT	•	ı	•	•	•	•	,	•	•	•	٠	ı	
	SVSC	ST-3-6-2	<u>C</u> 4	٣	Z		1 1 1			ì													
				တ	*					AC/DC	Y	Y	V	Ž	V	¥	¥	V	¥	Y	¥	<b>y</b> C	
	PRM MVR MODIFI	M1028		418	z					ATTS	200	740	70	80	9	120	000	0	100	120	•	158	
		TON		240	Z										0	9	9	0	9	2	33	7	
	PRIME	1 1/4	ä	220	z					AMPS	4.30	9			.50	1.00	26.00	.30	.80	1.00	.03	7.3	
,			VOLTAGE	208	z					VOLTS	115.0	15.0	15.0	5.0	115.0	5.0	115.0	115.0	5.0	2.0	115.0	115.0	
		45BV1	>	120	×			ENTS		Š	_	_	_	_	-	_	_	_	11	11	11		
	EL	AN/TRC-145BV1		110	×			OMBON			4-350	5-493	0-807	8-338	8-836	9-879	7-619	2-535	M	M	E	4-911	
	Q	NN/		<b>58</b>	Z			TER			6105-00-234-3504	5820-00-935-4931	5805-00-930-8079	820-00-928-3382	01-02	90-00	520-00-177-6198	00-75	NAVAILABLE	NAVAILABLE	MAVAILABLE	5810-00-054-9110	
			(2	400	z	-	***************************************	SUB SYSTEM COMPONENTS		NSK	6105-	5820-	5805-	5820-	5805-	5805-00-069-8795	4520-	5830-00-752-5357	UNAVA	UNAVA	UNAVA	5810-	
			Ή (H	9	<b>&gt;</b>		-	SU				2					•		_	Ė	_		
		7	FREQUENCY (HZ)	20	<b>&gt;</b>		-			. 1		AN/GRC-103V	5/4	0 / BG	TD-1065A/G	CV-1548/G		LS-147C/PI	9	INCANDESCENT			
	NOMENCLATURE	RADIO TERMINAL	E	ပ္ထ	Z					MODEL		-	•	-	-	_	_	_	<b>BR2009</b>	•••		KG-27	
	MENCL	DIO T		URER			1									LEPH			<b>6</b> 5		ST	7 GENERATOR, KEY	
				MANUFACTURER	GICHNER		1 1 1			ATURE		E	EXER	EXER	DATA	ER TE		<b>=</b>	i ti		ER DI	OR, K	
		1-336		3	GIC					NOMENCLATURE	BLOWER	DIO SI	CTIPL	LTIPL	FFER	WERT	LER	PERCO	THE	탪	NOW Y	VERAT	
		0-19			314					2	Ä	17 RAI	5	28 M	IDE 6	(S)	H	EI O	ĭ	ĭ	8	7 GE	
	NSN	5820-00-791-3365	REFERENCE	DOCUMENT	58954					LINE	NONE	<b>Q32687</b>	NONE	<b>M846</b> 0	H3555	F0537	NONE	K9488	NON	NONE	NONE	L2298	
e E	M	R92996	REF	2	TW.					SYS CODE	-	-	ņ	o	j.	S	~		φ	<b>∞</b>	80	<b>-</b>	
NOMB	LINE	R92		M C.	0					SXS	AG04	AM02	AE05	AE05	AE05	BD01	AG042	8	AA006	NA NO	A0008	AE05	
CONTROL NUMBER FU00578 SVSTEM	CODE	AX028		M L																			

	DATE	90330		T. OTY		•	-	-		-	~	-	-	-	~	~	~	~	-	7	-	-	-	4
	OPRS	n		SRCVAL	S	S	S	S	S	S	S	S	တ	S	S	S	S	S	S	S	S	S	S	S
SHELTER TYPE \$250	122	z	!	BTU COOT.	•	•	•	1	•	1	•	ı	•	•	•	•	1	1	•	1	•	•	1	•
GEN SYSCD ST-10-6D-1	PHASE 3 DC	<b>z</b>		HEAT	•	•	1	1	•	ŧ	•	ł	ł	•	•	•	1	1	1	•	•	•	1	•
• 44 44	S	z		AC/DC	Š	NC VC	Ş	ŠČ	Ş	¥C	Ų	ğ	NC NC	¥Ç	ပ္	¥C	¥Ç	ğ	¥C	¥Ç	AC.	YC VC	¥C	<b>A</b> C
PRM MVR MODEL H35A2	418	z		WATTS		_	1500	1	•	1	•	•	•	•		•	•	-	•	1	1	•	•	•
7 7 70N	7	z		AMPS W			12.50	1	•	•	•	ı	1	•	•	•	•	•	•	ı	•	•	1	•
PRIME MOVER 2 1/2	VOLTAGE 208 220	*						•	0.	0.	0.	•	•	۰.	0.	0.	•	0.	0.	•	0.	0.	0.	•
70V3	120 VO	<b>&gt;</b>	ENTS	VOLTS		120.0	120.0	_	1 120.0	9 120.0	•		_			_	_	0 120.0	8 120.0	1 120.0	4 120.0	7 120.0	7 120.0	3 120.0
MODEL AN/TRC-170V3	1	z	COMPONENTS		234-350	BLE	BLE	156-594	141-816	142-374	146-773	142-083	142-083	143-959	055-004	156-674	142-816	145-246	145-494	145-246	143-694	142-800	142-662	143-7-8
	10	<b>z</b>	SUB SYSTEM COMPONENTS	NSN	6105-00-234-3504	UNAVAILABLE	UNAVAILABLE	5820-01-156-5947	5820-01-141-8161	5820-01-142-3749	5820-01-146-7736	5820-01-142-0838	5820-01-142-0839	5820-01-143-9598	5810-01-055-0048	5820-01-156-6740	5870-01-142-8169	5820-01-145-2460	5820-01-145-4948	5820-01-145-2461	5820-01-143-6944	5820-01-142-8607	5820-01-142-6627	5805-01-143-7483
	CY (HZ	<b>&gt;</b>	SUB	Z	. •	Þ	ם					_,	-		S	S	S	E	U				S	ις.
LATURE	FREQUENCY (HZ)	> Z	. 1	MODET.			RW800	AM7221-TRC-1	AM-7027-TRC	SN-553-TRC-1	AM-7026TRC-1	DM-71-TRC-17	DM-71-TRC-17	TP-7905TRC-1	KG-81	M-5	PP-7904	TD-1235(P)	MD-1026(P)	TD-1236-G	BZ-250-TRC-1	C106102TRC-1		
NOMENCLATURE RADIO TERMIN	URER		1				_	Ī	-		Ť	턴	<	•	×	_		_	_ ≪	•		_	AC TO	ANALO
18-3976	MANUFA	Raytheon	*	VOMENCT.ATURE	BLOWER	LIGHT BULB	HEATER ELECT	MPLIFIER RADIO	PLIFIER	SYNTHESIZER ELEC	AMPLIFIER CONVER	MODEM TX TRANSP		POWER SUPPLY	T-SEC	PANEL TEST INTER	POWER SUPPLY	<b>CULTIPLEXER</b>	MODEM DIGITAL I	<b>WLTIPLEXER</b>	MONITOR ALARM	CONTROL UNIT ORD	CONVERTER AC TO	ORDER WIRE ANALO
NSN 5820-01-148-3976	ENCE	1158209341324		LINE NO	_	_	NONE HI	•	•	NONE SY	•	NONE MC			E03123 T-	_	_	_	NONE MC	NONE M	NONE MC	NONE CC	NONE CC	NONE OF
 	REFERENCE DOCUMENT	11582		SYS CODE	<b>41</b>	07	12	36	37	38	39	33	34	18	51	35	13	58	36	29	40	41	37	42
5 e	WGT	5850		SYS	AG041	AA007	AG012	AM036	AM037	AM038	AM039	BE033	BE034	A0018	AG051	BE035	A0019	AE058	BE036	AE059	AM040	AM041	BE037	AM042
CONTROL FU00589 SYSTEM CODE AX030	K																							

	DATE		90284			QTY	7	-	-	-	~	m	~	m	7	7	-	-	-	-
œ	OPRS D		Б			SRCVAL OTY	ပ	ပ	U	U	ပ	U	ပ	ပ	U	ပ	U	U	U	ပ
SHELTER TYPE \$250	ď	E ;	Z			700 000	•	1	•	1	•	•	•	1	1	•	ı	•	•	
GEN SYSCD ST-10-6D-2	PHASE	8:	Z		BTU	HEAT	•	1	ı	1	•	ı	•	1	1	•	1	•	ı	ı
GEN SYSCD ST-10		: ا	Z.			ા પ્ર														
PRM MVR MODEL M1037		w :	*			AC/E	<b>Y</b> C	¥C	¥	Š	AC	¥	¥	AC	¥C	AC	¥	¥	¥C	¥C
		418	z			WATTS	42	30	4	1600	200	9	300	1700	200	40	m	100	100	80
PRIME MOVER 1 1/4 TON		240	Z.			AMPS &	25	25	.03	50	•	.50	2.87	10		.34	ı	ı	1	•
PRIME MOVER 1 1/4	ខ	220	Z			2	•	•	•	12.50		•	~	14.10		•				
	VOLTAGE	208	i	<b>~</b>		70LTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0
MODEL ON-305/TTC-46		120	Z	SUB SYSTEM COMPONENTS		_	_	_	_										-	
MODEL ON-305/		110	Z.	COMPO			LE	LE	I.E	4520-00-912-3502	5810-01-212-8128	5810-01-213-8200	I'E	5805-01-120-2929	5805-01-120-2982	5830-00-752-5357	5999-01-218-3901	LE	I.E	6130-01-252-9724
N O		æ :	2	STEM			UNAVAILABLE	UNAVAILABLE	NAVAILABLE	6-00-	-01-2	-01-2	UNAVAILABLE	-01-1	-01-1	-00-7	-01-2	UNAVAILABLE	UNAVAILABLE	-01-2
•	HZ)	<b>4</b>	z	UB SY		NSN	UNAV	UNAV	UNAV	4520	5810	5810	CNAV	5805	5805	5830	5999	<b>SNAV</b>	UNAV	6130
	FREQUENCY (HZ)	9 :	×	S				CENT								FI				C)
g SOUP	REQUE	20	z			12	BULB	INCANDESCENT		<b>ا</b>	-93	94 <b>7</b>		PP-7815	PP-7711	LS-147C/FI	838			PP-8190/G
ATURI	E	ည်း	2.			MODEL	1 B(	INC		P-15	KGX-93	KG-94A		PP-	PP-	LS-	0-1838			PP-
NOMENCLATURE9053 SWITCHING GROUP		MANUFACTURER	315			HOMENCLATURE	LIGHT FIXTURE	CIGHT	BOX POWER DIST	HEATER MILITARY	28	) <u>B</u> C	FAN, EXHAUST	POWER SUPPLY	ER SUPPLY	Intercom	OSCILLATOR FREQ		SWITCHING GRP TI	CHARGER BATTERY
1-245						NON	LIG		BÖ	HEA	4 T SEC	1 T S	FA	Š Š			OSO	SWI	SWI	S
NSN 5805-01-245-9053	REPERENCE	DOCUMENT				LINE	NONE	NONE	NONE	NONE	K2321	T0897	NON	NON	NONE	K94880	NONE	NONE	NONE	NONE
20	REPE	DOCUMENT	DATA			SYS CODE	4	ë	<u>م</u>	٣	64	_	ō	9	S		9	*	ίč	7
Ž		WGT	8 / C 7			SXS	AA024	AA008	<b>N</b> 000	AG01	AG07	AG07	AD10	A0016	A001	2	AMO6	AM06	AM065	AB007
CONTROL NUMBER FU00538 SYSTEM CODE LINE BE048 S247		X.																		

		•			<u>~</u>	m	<b>~</b>	_	-	-	<u>ر</u> ي	N (	m	~	-	-	~	
	DATE	90284			2						_							
S.	OPRS I	0			SRCVAL OTY	U	ပ	ပ	U	U	ပ	C)	U	U	ပ	ပ	ပ	
Shelter Type S250		E 22			COOL	1	í	•	•	•	ſ	•	•	•	ŧ	•	٠	
6D-2	PHASE			B	HEAT		ŧ	ı		•	•	,	ı	,	,	,	,	
GEN SYSCD ST-10-6D-2	₹,	<b>7 Z</b>																
<b>§</b>	ŀ	∞ >-	į		AC/DC	¥	Ų	Š	ğ	Ž	Ž	ŭ	Ų	¥	¥	¥	Ş	
PRN MVR MODEL M1037	- 1	Z Z	3		WATTS	9	90	*	80	<b>•</b>	300	200	1700	200	1600	٣	300	,
JON		240 N			_	.50	5	.03	ı	.34	õ	92	2	,	20	ı	87	
PRIME MOVER 1 1/4	35	220 N			AMPS	•:	•	٠.		٠:	2.50	1.66	14.10		12.50		2.87	i I
	8	0 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8		ø	VOLTS	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	120.0	,
Model DN-306/TTC-47		120 X		NENT					24	57	8	28	53	82	05	10	)	
EL 306/	}	110 x		OFF		NJ.	N	N	2-97	2-53	3-82	2-81	0-29	0-29	2-35	8-39	, 1	į
MODEL ON-30		2 7 8		STEM C		MAVAILABLE	MAVAILABLE	MAVAILABLE	6130-01-252-972	5830-00-752-5357	-01-21	5810-01-212-8128	-01-12	5805-01-120-2982	520-00-912-3502	5999-01-218-3901	TANAVATTARI.E	-
•	H2)	<b>4</b> 0 <b>z</b>	1	SUB SYSTEM COMPONENTS	NSN	UNAV	UNAV	UNAV	6130	5830	5810	5810	5805	5805	4520	5000	TWAV	2000
	2	9 ×		63			ENT			H	,							
ŝ	FREQUENCY (HZ)	S Z				ď	DESC		9/06	70/1		m	12	11	<b>:</b>	œ	2	
NOMENCLATURE SWITCHING GROUP	FRE	S S			MODEL	1 BULB	TACANDESCENT		PP-8190/G	1.S-147C/FI	KG-94A	KGX-93	PP-7815	PP-771	P-15	0-1838	,	
MENCL		Manupacturer Gte		} : : : :	6	. 2	•	E.S.	, a	İ				. >		0404	, , , ,	·-
		JFAC			i eli mi	N.		9	į		•		Tool	TOOL		9	110	200
NSN 5805-01-245-9054		MAN			OMENCE	TOTAL P	TOTAL PARTY.	TO ACT	CHADGED BATTERY	COMM	OEC.	N C	CHAP	S GAMO	PATER			AN, EA
01-2		N			2		1 -	2 0	9 (	4 (	1 E	1 4 1	• P		4 3		) P	<b>4</b>
NSN 5805-	ERENCE	DOCUMENT DATA PLATE		! !					ANON									
LINE 524818	REF	DAT			400	200 F	r a		0 6		-	• •	, u	<b>.</b>	) r	, ,	, c	ō
		WGT 2832			CVC	200			ACCO.		<b>2007</b>	AG07		1004		100	0000	ADIO
FU00537 SYSTEM CODE BE051		ž <b>;</b>																

	DATE	90311				Ş	20	•	-	-	۲ ۲	-
E E	OPRS D	4				SRCVAL	T 20	F	-	-	•	H
SHELTER TYPE S280	_					1000	ı	•	1	•	1	•
97 6- 97	Ē	5		<b>!</b>	BTU	ช						
<b>n9</b>	PHASE	3		 	B	HEAT	•	ł	1	1	ı	•
GEN SYSCD G-30-6U	<u>"</u>	<b>&gt;</b>			١							
\$	lu	>-				AC/DA	<b>y</b> C	¥C	¥C	¥C	YC.	<b>A</b> C
PRM MVR MODEL M35A2	418	NNNNNN				TTS	800	200	40	4	3000	9
PRIME MOVER 2 1/2 TON	240	Z				S	0		0	5		
RIME OVER 1/2	220	2	1			Ž	6.90	4.30	۳.	.03	26.00	.50
D. E. O.	VOLTAGE	*				LTS	5.0	5.0	115.0	5.0	5.0	2.0
	120 V	Z		ENTS	;							11
MODEL S-640-G	110	z		MPON			9-61	1-350	2-535	6.1	1-619	M
MODEL S-640-	28	z		O WE			0-72	0-234	0-752	LABLI	0-177	LABL
	Y (HZ) 60 400	Z		SUB SYSTEM COMPONENTS		NO.	6210-0	6105-0	5830-00-752-5357	UNAVAI	4520-00-177-6198	UNAVAILABLE
LECT	CY (H	*	1	S								
PER E	FREQUENCY (HZ)	z	1			֓֞֜֜֜֜֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֜֜֜֓֓֡֓֜֡֓֡֓֜֜֡֓֓֡֓֡֡֜֜֡֓֡֓֜֡֓֡֡֜֜֡֓֡֡֜֜֡֡֡֡֜֜֡֡֡֜֜֡֓֜֡֡֜֜֜֡֡	IPS		LS-147C/FI			
VTURE SHEL	, N	z	į			Tagor	2 LAMPS		LS-14		P-13	
NOMENCLATURE STORAGE SHELTER ELECT	URER		į		•		<b>1</b> 23		!	ST		<b>5</b>
	MANUFACTURER	GICHNER				TOTE	XIOR					NYCE NYCE
7-685	MAN	GIG	į		L		HI	WER	INTERCOM	2	TER	ANER
1-127					2		3	BIC	INI	Ô	HE	S
NSN 5411-01-127-6854	REFERENCE DOCUMENT	5HFC01							K94880			
<b></b>	REFE	1143			200	,	<b>.</b>	<b>-</b>	9	<b>.</b>	<b>.</b>	<b>~</b>
NUMBE LIN S45	WGT	810			SVS			4004	3		AG04	AG04
CONTROL NUMBER FUODS SYSTEM CODE LINE BH013 S4510:	KW	m m										
0 E 0 0 E												

												_	_		
	DATE	90323			Ę	<b>D</b> (	9 (	<b>.</b>	•	~	<b>~</b> (	<b>*</b>	1		
		9			SRCVAL OTY	י מי	n ·	<b>S</b>	S I	י מע	ימי	S)	מי	ທ	
TER	OPRS	Ю			SR										
Shelter Type S280		Ę ×	!	p	1000	•	•	1	•	•	•	•	•	•	
	38	<b>≥</b>		Brrd	HEAT	•	•	ı	ı	•	ı	•	•	•	
GEN SYSCD G-5-6D	PHASE	m >+	į		至										
			İ		AC/DC										
PRM MVR MODEL M35A2		leo ==													
PRM MY MODEL M35A2		418 N	į		ATTS	960	320	632	140	3000	9	240	340	*	
NO		240 X													
PRINE MOVER 2 1/2 TON		220 N			A	8	2.7	5.4	1.2	26.00	.30	2.0	2.90	.03	
PR 2	VOLTAGE				ဖွ	0	0	0	0	0		0		0	•
	-	28 110 120 208 N N Y N		ŝ	VOLTS	115	115.	115.0	115.	115	115	115		115.0	
MODEL AN/TCC-73V1		12		NEW		80	6	2	270	80	167				
13 17 17		110		OFFE		19-87		7	9-0	77-6	5.0		1 :	3 5	4
MODEL		Z 28		SYSTEM COMPONENTS		0						TT A D			
		lộ z		SYS	NUN	5805-00-069-8795	C825-809-00-008	5820-00-0E6 500E	1	4520-00-332-00:3	0 0	TANK TANKAT	4	NAVALLABLE	4 2 4 2
	(60)	FKEQUENCY (B2)		SUB	Ž	, Œ	, ú	) W	'nú	7	- 4		•	ם כ	•
2	1 2					ç	2 2	2	,	3		7 2 7	NCANDESCENT		
S SHOW:		j in z g			5	100eu	0401	FD-00-01	,	TD-/34/6	2 .	12/2/47/27	ANDE	BR2009	
TUR		E OZ			Š		2	2 5	) 4	9.	7	3		BRZ	
NOMENCLATURE MPDMIMAL TRIEDHONE		NC RE					EYE	;	<b>.</b>					ا بم	H
MON	3	ACTU				S I	TEL	EK.	X	X				E E	SIG
3	5	MANUFACTURER WAGLINE INC			1	CLAT	RTER	PLEX	A TOR	PLEX	æ	Ž O O		L	
	i e						ONO	OLT	ENE	ULTI	EAT	KIEK	EEST	EEST	×
	1	8514			;	Z,	76 0	800	87 6	<b>.</b> .	 	80	- -	, M	63
NSN	P805-00-134-3404	reference Document Tm115005585142				LINI	F053	<b>X8</b> 4	L229	NON		K948	NON	NONE LIGHT FIXT ICP	Z
		EFER OCUM													
LINE	5889					SYS CODE	3015	3050	1021	3052	3042	,,	1008	AA006	3008
Í		¥67 5300				S	표	7	7	7	×	ል	2	2	¥
FUODSSS SYSTEM LINE	AX027	χ ν													

	DATE		90318			SRCVAL OTY	•	*	*	~	~	4	7	•
TER	OPRS	,	7			SRCVA	H	H	H	H	E	E	H	H
SHELTER TYPE S250	-	E :	ž.	)	P	S0	1	ı	•	•	1	•	•	•
-	PHASE	ე ლ :	Z		BTO	HEAT	•	1	1	i	1	ı	i	ı
GEN SYSCD ST-3-6-1	ď	m ;	<b>Z</b> ,			ı								
g	İ	s:	<b>,</b>			AC/DC	YC.	¥C	¥C	V V	¥C	¥	AC	<b>A</b> C
PRM MVR MODEL M1037	ļ	418	Z.				160		140	0001	200	80	40	316
		240	Z,							"		<b>6</b>	٥	0
PRIME MOVER 1 1/4 TON	60	220	Z,			AMP	1.39	4.17	1.20	26.00	4.30	9	ñ	2.70
Z¥-	VOLTAGE	28 110 120 208 220 240 418	z			OLTS	115.0	2.0	2.0	115.0	115.0	5.0	115.0	2.0
10	×	120	<b>,</b>	ENTS		ÖΛ	-							•
MODEL AN/TCC-65		011	z,	MPON			1-3382	-879	-8075	-6198	-3504		-5357	-9110
MODE AN/1		28	z	S			0-928	590-0	0-930	0-177	0-234	LABLE	0-752	0-054
•		400	z z	SUB SYSTEM COMPONENTS		NSN	5820-00-928-3382	5805-00-069-8795	805-0	4520-00-177-6198	6105-00-234-3504	NAVAI	5830-00-752-5357	5810-00-054-9110
	ZH) X	9 :	×	SOS		Z	S.	LO.	r.	4	Ψ	ם	_•	
HINAL	FREQUENCY (HZ)	50	z				0/BG	48/G	4/6			ø	7C/FI	
NOMENCLATURE TELEPHONE TERMINAL	FRE	ပ္ :	z			MODEL		CV-15	TD-75	P-13		BR2009		KG-27
ENCLA		RER	T KI					EPH				<u>بم</u>		L22987 GENFRATOR, KEY
		MANUFACTURER	2 X 2			TURE	XER	R TEL	XER			XI IC		R, KE
NSN 5805-00-156-4368		MAND	CKAL			ENCLA	TIPLE	VERTE	TIPLE	TER	KER	HT FI	ERCOM	FRATO
)-156			<b>-14</b>			NOM	S MOL	SCON	101	HEA	BLO	LIG	TWI	7 GEN
NSN 5805-06	SNCE	DOCUMENT	75-37			LINE	184601	<b>P0537</b>	ONE	ONE	FONE	ONE	(9488)	75298
	REFERENCE		) 6-1:				_	_			~	_	-	_
LINE V28144		MGT.				SYS CODE	AE050	BD015	AE052	AG042	AG041	<b>AA</b> 006	BG	AE051
SYSTEM CODE AX010		¥.	÷											

	DATE			L QTY	œ	<b>œ</b>	<b>œ</b>	4	7	-	~	∞	-	17
ä	OPRS I	,		SRCVAL QTY	H	H	H	<b>6</b> -	H	E	H	F	H	H
SHELTER TYPE S280	o HIO	: !	P	COOL	•	•	•		•		•		,	•
Q Q	PHASE	:	BTU	HEAT	•	ı	1	ı	1	ı	•	•	1	•
GEN SYSCD G-5-6D	m >	-    -  -  -		ا ک										
PRM MVR Model M35A2	(co 2			AC/DC		S.	_	_	_	_	_		-	-
	0 418			WATTS	960	320	632	140	3000	40	500	240	4	340
PRIME MOVER 2 1/2 TON	220 240				8.30	2.78		1.20			4.30		.03	2.90
PRIME MOVER 2 1/2	AGE 22	E							•					
	VOLTAGE 0 208		S	VOLTS	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0	115.0
-73V2	0 120	•	ONENT	•	795	382	110	079	198	357	504			768
MODEL AN/TCC-73V2	28 11	ž,	COME		5805-00-069-8795	5820-00-928-3382	054-9	5805-00-930-8079	177-6	5830-00-752-5357	6105-00-234-3504	BLE	BLE	6210-00-729-9768
	,,,,,	2	YSTEM		5-00-	-00-0	-00-0	5-00-	-00-0	-00-0	5-00-	MAVAILABLE	NAVAILABLE	-00-0
	(HZ)	X Z	SUB SYSTEM COMPONENTS	NSN	580	582	581	580	452	583	610	9	0	621
NAL	ENCY 0	<b>H</b>			9/	<b>.</b>		U		/FI		SCENT		
re Termi	PREQUENCY (HZ)	Z,		TODEL	-1548	TD-660/BG	KG-27	FD-754/G	P-13	LS-147C/PI		INCANDESCENT		2 LAMPS
CLATU	1 <u>0</u> 2	Z		MOM	PH C			•	_	_		•		
NOMENCLATURE 404 TELEPHONE TERMINAL	MANUFACTURER	MAGLINE INC		NOMENCLATURE	P	PLEXER	ATOR, KEY	PLEXER	œ	COM	œ		OWER DIST	LIGHT FIXTURE
-134-5	Z :	E.		NOMEN	CONVE	MULTI	GENER	MULTI	HEATE	INTER	BLOWE	LIGHT	BOX P	LIGHT
NSN 5805-00-134-5404	REFERENCE DOCUMENT	Shr CO4				M84608	L22987	NONE	NONE	K94880	NONE	NONE	NONE	NONE
MDER LINE V31452	REF	411		SYS CODE	15	20	51	52	42		41	80	80	03
LII V	WGT	0056		SXS	BDO	AEO	AEO	AEO	AGO	8	AGO	AAO	900	AA003
CONTROL NORDER FU00566 SYSTEM CODE LINE BD006 V3145	XX 4	ń												

	DATE	90330			QTY	m	7	-	20	-	æ	12	<b>6</b> 0
es	OPRS DA	9			SRCVAL QTY	۲	H	۲	۴	۲	۲	E	H
SHELTER TYPE 5280		æ			S TOOO	•	•	•	1	•		1	,
_		E ×	!	BTU	P								
1-09-	PHASE	2 2	1 1 1 1	·M	HEAT	١	1	•	•	1	١	1	•
GEN SYSCD ST-10-60-1	<u>a</u>	m Z			1								
	,	ω ≯			AC/DC	¥	ğ	Ş	ပ္	ပ္ရ	Š	ပ္ရ	ပ္
PRM MVR MODEL M35A2	' 1	418 N			ATTS 1	1800	2000	26	400	40	200	1920	1200 1
NO		2 % 2 %			_			0	0	0	0		
PRIME MOVER 2 1/2 TON		220 240 N N			AMPS	19.50	26.00	.40	3.40	.30	1.70	16.60	10.40
2 ₹ ∾	VOLTAGE	0 208 2			VOLTS	115.0	115.0	5.0	115.0	115.0	5.0	115.0	15.0
4	>	120 Y		CLAS	8		_			•	• •	•	
MODEL AN/MSC-29A		28 110 120 N Y Y		NO.		-8194	-6198	-3260	-9768	-5357	-908	-8300	-6061
MODEL		<b>x</b> 8		3 <b>5</b>		1-062	0-177	1-146	0-729	0-752	0-985	0-907	0-553
	(2)	60 400 Y N		SUB SISTEM COMPONENTS	NSN	5815-01-062-8194	4520-00-177-6198	5810-01-146-3260	6210-00-729-9768	5830-00-752-5357	5805-00-985-9088	5805-00-907-8300	5815-00-553-6061
a.	<b>34</b>	¥ 60		20		2				_			
E LEPHON1	FREQUENCY (HZ)	V 20			諨	AN/UGC-74A(V	_	34	2 LAMPS	LS-147C/FI	CV-425/V	TH-22/TG	76A
ATUR!		Z			MODEL	NN/	P-13	KG-84	E %	-81	Ş	TH-	TT-76A
NOMENCLATURE TERMINAL, TELEPHONE	1	MANUPACTURER GENERAL ELEC			LINE NOMENCLATURE	LETYPEWR		R, KEY	XTURE	K94880 INTERCOM	P. TELEGR	H TERMIN	V36762 TELETYPEWRITER
1-6762		-			TENCIA	OIC TE	LTER	TERATO	THT FI	PERCOM	WERTE	EGRAP	ETYPE
0-943	; ,	FC01			ON	6 RAL	HEA	8 GEN	116	IMI 0	S	9 TEL	2 TEL
NSN 5805-00-943-6762	REFERENCE	DOCUMENT TO&E11435HFC01	, ,		LINE	V3614	NONE	E0302	NONE	K9488	F0461	V5772	V3676.
40		DOCUMENT TOEE1143			ODE								
NUMBER LINE V57504		MGT 5600			SYS CODE	AX007	AG042	AE054	AAOOB	BG	BE006	BE003	BE005
CONTROL NUMBER FU00562 SYSTEM CODE BE004 V5756	i	7											

		DATE		90268			L OTY	20	-	~	-
rer		OPRS		7			SRCVAL OTY	H	H	۲	F
SHEL	TYPE S280		HIO	z	ı	, 5	1000 C00I	1	•	•	ı
	SYSCD ST-10-6-3	PHASE	l	Z *	ı	BITU	HEAT	1	•	1	•
CEN	SYS( ST-1		S	*			, 	ีย	ပ	ບ	ບ
PRM MVI	MODEL N/A		418	Z			TTS A	400 AC	30	500 A	500 A
			240	z		 	S WA	3.60	.27	20	50 1
PRIME	MOVER SKID MOUN	3 3	220	2		}   	AM	3.6	``	4	13.60
		VOLTA	0 208	Z		S	VOLTS	110.0	110.0	110.0	110.0
	1-167		28 110 120 208 220 240 418	2		PONENT		9768		3504	3502
	MODEL AN/GSM-167		28 1	×		MOD MI		0-729-	NAVAILABLE	0-234-	0-912-
	ORTAB	2	100	z		SUB SYSTEM COMPONENTS	NSN	6210-00-729-9768	UNAVAI	6105-00	4520-00-912-3502
	FRANSP	VCY (H	9	*		SU			CENT	ı	
	NOMENCLATURE ELECTRONIC SHOP TRANSPORTAB	FRECUE	5c 50	N Y N		; ; ; ;	MODEL	LAMPS	NCANDESCENT		P-15
	TRONI		ZER	Ę			_	N	Н		
	NOM 3 ELEC		JPACTUI	ELECTRO MECH		! ! !	ATURE	EXTURE			KILITA
	NSN 4940-00-999-1793		MANI	ELE		# 	NOMENCL	LIGHT F	LIGHT	BLOWER	HEATER MILITARY
	3N 40-00-	INCE		LATE				NONE			
		REFERI	DOCUM	DATA PLATE	•	•					
	LINE			3700			SYS	AA003	AA008	AG041	AG013
PU00526 SYSTEM	CODE BH024			2. 3							

**Table 3. Tool Sets and Systems** without Shelters

# Notes to Table 3:

- 1. CONTROL NUMBER and SYSTEM CODE at upper left, as well as SYS CODE (first column) and SRCVAL (second to last column) are data handling codes peculiar to the Sample Data Collection Program.
- 2. AMPS (seventh column) and WATTS (eighth column) are totals for each type of power consumer (i.e., individual power requirement multiplied by quantity (last column).

		DATE		90263			L OTY	~	-	m	m
ă		OPRS		SO.			SRCVAL OTY	E	H	E	H
SHEL	TYPE N/A	-	E			. 5	1000	•	1	•	ı
	19-	HASE	E OCT			UT-8	HEAT	•	ı	•	1
ZZ C	SYSCD G-30-6U	***	٣	<b>&gt;</b>			1				
MVR	MODEL M35A2		iw Im	Z			AC/I	¥	¥	¥C	¥
		VOLTAGE	416	Z			MATTS	186 AC	8206	3600	3357
	MOVER 2 1/2 TON		240	<b>&gt;</b>			IPS V	69	0	30	16.10
PRIME	MOVER 2 1/2	GE	220	*			2	H	39.	16.	16.
		VOLTA	208	*			OLTS	110.0	08.0	20.0	08.0
			120	Z		NENTS					
	MODEL M-1945		110	Z		CONTO		21-23	80-87	35-66	7310-00-903-5402
	<b>S</b> 7			_		STEM		-00-	-00-	6-00-	6-00-
		HZ)	20 60 400	z		SUB SYSTEM COMPONENTS	NSN	7320	7320	7320	7310
		NCY (	60	<b>&gt;</b>		S)				23	
	<b>#</b> >	REQUE	20	Z		)   	ij	PE-20	M-BP-68	2-PB-30623	533-235
	ICLATURE BAKERY	Ρ.,	ıΔ	Z		 	MODEL	(C)	H	Ŭ	533
	NOMENC		TURER	BAKER, PERKIN		1	64	INE P	GH, O	GH PR	
			NUFAC	KER, P			LATUR	KACH	, <b>20</b>	F 000	AKERY
	10-07						OMENC	I PTER	IXING	ABINE	OVEN BAKERY
	NSN 7360-01-010-0787	842	DOCUMENT	20110		1	Ž	93 8	261 M	100 C	B18373 O
	NSN 7360	REFERENCE	UNENT	07360	•						
ea Ea	LINE B18648	REF	0	TMI			CODE	2	2	*	BI005
NOMB	BE		¥G¥	37858			SXS	BIO	BIO	BIO	BIO
CONTROL NUMBER FU00517 SYSTEM	CODE BIO01			37. 37							

	DATE	91008		2 OT 8
Shelter Type Unshelter	OPRS	'n		SRCVAL QTY S S 3 S
SHEL		E z		1000
) -6P	PHASE	_ 2 ≥	1	HEAT - - -
gen Syscd G-100-6P		m >×		ا و
PRH HVR MODEL	l	o z		AC/DC AC AC AC
PRM		418 X		WATTS 29150 9240 26928
		7 7		8000
PRINE MOVER 5 TON	핅	28 110 120 208 220 240 418 N N Y Y N		AMPS 132.50 42.00 122.40
	OLTA	7 Z		VOLTS 220.0 220.0 220.0
		120 N	ENTS	2222
MODEL 75 TPH		) N	OMPON	<b>M M M</b>
MOD 75	ļ	» X	S MAI	ILABL TLABL
	FREQUENCY (HZ)	Z	SUB SYSTEM COMPONENTS	NSN UNAVAILABLE UNAVAILABLE UNAVAILABLE
ANT	CK	9 ×	S	
EN EN	EQUEN	0 2		ت
ATURE	E	Ζ×	 	MODEL 10HP 5HP 15HP
NOMENCLATURE CRUSH & SCREEN PLANT		EAGLE	1	# # # # #
NSN 3820-00-725-6462		EAGLE		NOMENCIATURE MOTOR ELECT MOTOR ELECT MOTOR ELECT
NSN 3820-00-	REFERENCE	A PLATE		LINE NONE NONE
LINE F49399	REF			SYS CODE AZ018 AZ019 AZ020
FU00600 SYSTEM CODE AZ017	2	65.		

		DATE		9100				5	!				
Shelter Type	ELTER	OPRS		9				SRCVAL OF	w	t)	Ø	•	o
SHEL	CNSH		E	Z				1000 000	•	1	•		)
	d.	PHASE	2				BIE	HEAT	•	1	•	,	)
GEN	-100-	PH	m	>									
<u> </u>	Ġ		ဖ	z				C/DC	<b>V</b> C	ũ	ပ္	9	ړ
PRM MVR MODEL			418	<b>&gt;</b>				WATTS 1					
			240	z									
PRIME MOVER	TON	es.	220	X				ARP	77.5	81.60	88.00	K K	
Z X	S)	OLTAG	208	z	!			VOLTS	0.0	0.0	0.0	•	?
		Ž	120	Z		ENTS		8	7	22(	22(	777	
MODEL	121		110	Z		MODIC			80	M	64		
MOD	225	į	28	z		PER C			ILABL	<b>LIABL</b>	MAVAILABLE	MAVATIABLE	
	LANT	(2	400	Z		SUB SYSTEM COMPONENTS		NS.	UNAVAILABLE	UKAVA	UNAVA	INAVA	
	IASH P	FREQUENCY (HZ)	9	<b>&gt;</b> -		S							
	3 4 2	BOUEN	20	z				ı	Δ,		۵.	Δ	
ATURE	SCREE	E	ဋ	Z				MODEL	125H	15EP	7.58	100H	
NOMENCLATURE	KOSH,	:	URER										
N.	ر 1		MANUFACTURER	1				ATURE		LECT	LECT	LECT	
NSN	:7-857		3	ENC	# 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9			NOMENCLATURE	10k	TOR R	TOR E	FOR	
;	-00-52	•		LEO4									
NSN	3820-	REFERENCE	MENT	SC382098CLE04	į			LINE					
LINE	9673	REF	S S	SC3			1	SYS CODE	2	2	<u></u>	*	
5	Ž	ļ	<b>1</b> 2	,				SYS	V20	VZQV	AZ02	AZ02	1
FU00601 SYSTEM CODE LINE	AZ021	į	NA.	91.									

	DATE 90268		I OTY
SHELTER TYPE N/A	OPRS 1		SRCVA
SHEI TYPY	E 3	•	1000 .
GEN SYSCD G-10-6D	PHASE S 3 DC OTH Y N N N		AMPS WATTS AC/DC HEAT COOL SRCVAL QTY
			, 50/50
PRM MVR MODEL	N N		7500 J
PRIME MOVER N/A	220 24 N N		AMPS 1
P. N.	VOLTAGE 5 208 Y		
HODEL MST HTD	VOLTAGE 28 110 120 208 220 240 418 N N N Y N N N	SUB SYSTEM COMPONENTS	NSN 6240-00-143-3138 208.0
NOMENCLATURE PLOODLIGHT SET ELECTRIC	FREQUENCY (HZ) DC 50 60 400 N N Y N	SUB SYSTEM COMPONEN	
NCLATURE DLIGHT S			MODEL CEN 750WT
NOME 19-5642 FLOO	MANUFACTURER HIGH LITE		NOMENCLATURE LAMP INCANDESC
LINE NSN H79221 6230-00-299-5642	REFERENCE DOCUMENT SC623097CLEO3H	! ! ! !	LINE
	REF WGT DOC 500 SC6		SYS CODE
FU00524 SYSTEM CODE AA011	χи 7.		

8	OPRS DATE	1 90296		SRCVAL QTY N 3
SHELTER TYPE N/A	_	Z	ł	BTU COOL
GEN Syscd St-60-4	PHASE	} <b>z</b>		HEAT
PRH MVR G MODEL S			# 	WATTS AC/DC 1347 AC
	240	z		ANPS WATT 23.40 134
PRINE MOVER N/A	OLTAGE	Z		VOLTS AN 416.0 23.
NODEL AN/MPQ-61	VOLTAGE 250 240 418	×	SUB SYSTEM COMPONENTS	NSN VO: 1440-00-805-3012 410 UNAVAILABLE
2.5			SUB SYSTEM COM	NSN 1440-00- UNAVAILA
NTURE ET	FREQUENCY (HZ)	Z	: t t t t t t t t t t t t t t t t t t t	MODEL XM-19211
NOMENCLATURE 8780 RADAR SET	MANUPACTURER	RAYTHEON		NOMENCLATURE LAUNCHER ZL TRANSHITTER RADA
. NSN	REFERENCE DOCUMENT	, METER		LINE L45757 NONE
LINE H8667	<b>A</b>	9500 VOLT		SYS CODE AC013 AC015
FU00543 SYSTEM CODE AC014		23. 9		

			DATE		9114				5	l							
ă	i	NSHELTER	OPRS I		-				SRCVAL OT	S	S	S	s	S	w	w	Ø
SHELT	TYPE	UNSHI	Ü	HIO	z				1000 0000		1	•	•	•	1	1	ı
			6.1	ļ	_			BTC	•								
	_		PHASE	ا کا					HEAT	•	•	•	•	•	•	•	
ŽŽ.	SYSCD		_	3	z				ا ن								
ž				တ	z	!			AC/D	ည်	2	8	2	2	8	2	2
PRM M	MODEL	M1037		418	z				AMPS WATTS	•	1	•	•	•	•	•	•
				240	z				<b>XX</b>								
. 20	VER	1 1/4 TON		220	z				AMP	•	•	•	·	·	٠	•	•
Z.		-	LTAGE	208	z				OLTS	0	28.0	0	0	0	0	0	28.0
		(V) 1	8	28 110 120 208 220 240	z		NTS		TOA	28	28	28	28	28	78	28	28
		AN/ULQ-19(V)1		110	z	1	MPONE										
	MODE	AN/U		28	<b>&gt;</b>		SUB SYSTEM COMPONENTS			MAVAILABLE	MAVAILABLE	NAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	NAVAILABLE
•			_	400	z		SYST		NSN	NAVAI	NAVAI	HAVAI	NAVAI	NAVAI	NAVAI	NAVAI	NAVAI
		COBIL	ZH) /	9	z		SUB		Z	Þ	Þ	Þ	Þ	Þ	<b>•</b>	Þ	Þ
		RES !	UENC	20	z					ę			٠,	9			92
	URE	JAMMER SYSTEM RES MOBIL	FREO	DC 50 60 400	<b>&gt;</b>				MODEL	r-150	J-4412	-4410	-1165	M-729	-4411	P-337	VRA-6092
	CLAT	R SY			•				Ī	3	'n	ņ	Ú	Z I	ני	S.	
	NOMEN	JAMME		MANUFACTURER					RE	R REC	CTING	TIND	Ħ	MPI	CTING	RIC P	ANTENNA MATCHING
				NUFA	RACAL				NOMENCLATURE	ITTE	SONNE	ACE	75 SA	FREO	CONNE	MOME	Š
		38-33		Ž	2				MENC	RANSK	TERC	TER	ONTRO	DIO	TERC	LPHA	TEN
		01-16			5613	i											
	NSN	5865-01-188-3309	REPERENCE	DOCUMENT	58652				LINE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
			REFE	DOCC	1111				ODE	_	_						
CONTROL NUMBER FUCO619 SYSTEM	LINE	315776		<b>E</b> GT	ı				SYS	AC049	AC050	AC051	AC052	AC053	AC054	AC055	AC056
N 201 W				3													
CONTROL FU00619 SYSTEM	CODE	AC048		×													

			_			<b>&gt;</b>	-	-	-
	DATE		90261			r S			
TER T	OPRS		<b>-</b>			SRCVAL OTY	S	S	S
Shelter Type N/A		HIO	z			COOL	٠	•	ı
	PHASE	3 DC OTH	z		BTC	HEAT	•	•	•
GEN SYSCD G-60-4	Z.	۳ :	*			•			
ب د م		S	z			00/0	ŭ	ŭ	ပ္ခ
PRM MVR MODEL	!	418	<b>&gt;</b>	 		AMPS WATTS AC/DC	•	-	1
		240	z			MA			
PRIME MOVER N/A	62	220	z			AMPS	•	•	•
AZZ	POLTAG	28 110 120 208 220 240 418	Z			OLTS	16.0	16.0	416.0
		120	z	ENTS		Š			
MODEL XM-19211		110	Z	NOMBON			15-764	1-695	1440-00-138-4026
<b>X</b> X		58	Z	E			00-74	00-54	00-13
	(2	100	*	SUB SYSTEM COMPONENTS		NSN	1440-	4320-	1440-
	X (H	9	×	DS		-			
	UENC	20	z						
TURE 2L	FREGUENCY (HZ)	2	z			MODEL			
NOMENCLATURE LAUNCHER ZL						RE	OOLER		ASSEMBLY POWER R
		MANUPA	RAYTHEON	Je-7-5-5-6-6-5-5-5-6-6-6-6-6-6-6-6-6-6-6-6		ENCLATO	EMBLY C	HVD	DIBLY P
-805-						NON	ASSI	ענע	ASSI
NSN 1440-00-805-3012	PENCE	DOCUMENT	PLATE			LINE	MONE	HON	NONE
57 11	REFEE	500	DATA			ODE			
LINE L45757	-		2662			SYS	AC010	AC011	AC012
FUUUSIA SYSTEM CODE AC013		KW							

		DATE	91215			Ę	֚֚֓֞֞֜֞֜֜֓֓֓֓֓֓֓֓֓֓֓֓֡֓֜֓֓֓֡֓֡֓֡֓֡֓֓֓֡֓֡֡֡֓֡֓֡֡֡֡֓֡֓֡֡֡֡֡֡	-	-	-	-	_	_	- ۱	٠,-	٠,-	-
	SHELTER FYPE JNSHELTER	OPRS	~			VTO INDICATOR	S	S	v	S	S	ď	ď	ď	, v.	ı v	ι (A
	SHELTER TYPE Unshelti		E z		ı	D COOL	}	1	•	ı	ı	•	1	•	1	ı	•
	۵	PHASE	z z			BTU	۱ ا	1	ı	•	,	•	ı	,	•	•	ı
i	GEN SYSCD G-10-6D	E E	1 ×			=	•										
		10	n z		1	AC/DC	, O	ပ္	Ų	<b>A</b> C	ñ	Ş	Ş	ပ္	õ	õ	ပ္
	MODEL XM1061E		Z			WATTS		•		1492						3452 J	250
		240	Z														•
5	MOVER 5 TON	E	Z			AMPS	14.30	•	7.10	7.10	5.0	4.70	5.10	•	4.20	17.60	2.5
•	7 Z 10	VOLTAGE	2			LTS	208.0	0.	8.0	9.0	0.0	9.0	0.0	9.0	9.0	3.0	0.0
		2   5	<b>2</b> >	. !	ENTS	O <sub>V</sub>	20	Õ	<u> </u>	20 20	23	20 20	23	20	5 5 7	50 50	20
	EL 9T	011	Z		NOAMC		ы	E)	ы	ea ea	6a	6a)	6-3	6e3	61	6-1	(c)
	Model	28	z		TEM C		MAVAILABLE	NAVAILABLE	NAVAILABLE	NAVAILABLE	NAVAILABLE	NAVAILABLE	MAVAILABLE	NAVAILABLE	MAVAILABLE	NAVAILABLE	NAVAILABLE
		2)	z		SUB SYSTEM COMPONENTS	NSN	UNAVA	NAVA	NAVA	SNAVA	NAVA	NAVA	MAVA	MAVA	MAVA	JNAVA	JNAVA
	MTD	FREQUENCY (HZ) C 50 60 4	*		SU		- ·				- '			_	_	_	_
	TRL	EQUEN 50	z	1 1		ı,	5K43HG1230	5K36FG288		3	aro	4	>		0	<b>.</b>	2
	ENCLATURE IDRY UNIT TRL MTD	E N	z			_		•			MERCOID		_	N	11800	11801	SYE-13
	NOMENCLATURE LAUNDRY UNIT	CTURER	TOOELE DEPOT	1	٠	RE	PUMP, WATER MOTO	K REAT	NEK	D HELE	AKM AL	בא בא	WATER	K, HEA	ER	KACTOR	SSOR
	NSN 3510-01-197-6742	MANUFA	TOOELE	1		NOMENCLATURE	P, WATE	A WALE	A, BUK	JR, TUR	מינים של אינים של אינים של היינים של היינים של היינים של היינים של היינים של היינים של היינים של היינים של היינים	A TURB	JEF LOW	SFORME	MOTOR WASHER	K, EXT	IIK COMPRESSOR
	1-197			į		NOM							5	K			AIR
	SN 510-0	REFERENCE DOCUMENT	PLATE	į		LINE	NONE							COL	NON E	NON E	
		REFERENCE DOCUMENT	DATA			DDE											
NUMBER	LINE L48315	WGT				SYS CODE	BD111	1112	1417	20114	Philip	001100	007700	67100	55130	20121	7CT00
CONTROL NUMBER FU00629 SYSTEM	CODE BD110		10.														

		DATE	21200				L OTY	9	15	25	100	200
SER.		OPRS	-	•			SRCVA	T 60	<b>[-</b>	Ħ	F	H
SHEL	TYPE N/A		E Z	i		_	1000	١	١	•	•	•
	0.5	PHASE	1	2		BTC	HEAT	ı	i		•	ı
Na S	SYSCD G-15-6U	ቯ	m 2	:			ļ					
25	MODEL		w >	•	 		AC/D	V	¥	<b>N</b> C	Ŋ	<b>V</b> C
PRM	MODE		220 240 418	:			WATTS	9009	900	5000	2500	2000
6.7	~		24(	•								41.60
PRIMI	MOVER N/A	\GE	25 25 8	•								
		VOLT	8 2 10	•	S		VOLTS	130.0	120.0	120.0	120.0	120.0
			0 12	•	ONENT			119	071	059	124	153
	MODEL 15KW		28 110 120 208 220		COM			-143 - 3	-143-3	-143-3	-143 - 3	-143-3
				•	SUB SYSTEM COMPONENTS		z	6240-00-143-3119	40-00	6240-00-143-3059	40-00	6240-00-143-3153
		(HZ)	00 4 00 N		SUB		NSN	62	62	62	62	
		QUENC	ν Ο Ζ	:				01	I-L-101/37	I-L-101/31	J-L-101/1T	W-L-101/25AT
	ATURE	FRE	<u> </u>  2	•			MODEL	W-L-101	W-L-1	W-L-1	W-L-1	W-L-1
	NOMENCLATURE 0 LIGHT SET		MANUFACTURER GE				ATURE	CANDESCEN	CANDESCEN	CANDESCEN	CANDESCEN	LAMP INCANDESCEN
	9108						MENCI	ži de	A A	ři de	ŽI de	ŽI de
	NSN 6230-00-299-7080		CLE02									
	NSN 6230-	REFERENCE	DOCUMENT SC6230-97CLE02							NONE		
á	LINE L63857	REFE	90CG				CODE	4	5	91	17	81
			WGT 1275				SXS	AA0.	AA0.	AAO	AAO.	AA018
FU00549 SYSTEM	CODE AA013		ΚW 19.									
FUO	<b>X</b> 00		X 61									

		DATE		91234				OTY.	~	~	7	4	m	9	~	7	7	4	~	7	7	
ĝ	LTER	OPRS D		4				SRCVAL QTY	S	ဟ	S	ß	S	S	S	S	S	S	S	တ	S	S
Gar. Taks	TYPE UNSHELTER	0	132	z			_	1000	•	1	•	ı	•	1	•	•	1	1	1	1	•	1
	-6-3	PHASE	2	z			BTU	HEAT	ı	•	•	,	•	•	ı	•	ı	•	1	•	ı	ı
Na.	SYSCD ST-10-6-3	ቪ	~	<b>&gt;</b>				ļ	٠,													
	4		S	<b>&gt;</b>				AC/DC	AC/DO	ŊĊ	AC	¥C	<b>A</b> C	<b>A</b> C	¥	¥	<b>Y</b> C	¥C	¥Ç	AC	¥Ç	<b>y</b> C
AVA MAG	MODEL N35A2		418	z				ATTS	350	18000	3600	920	0081	4476	880	345	598	1	2882	50	1	483
	TON		240	Z									•	•						17	ı	20
AMLGO	MOVER 2 1/2	S.	220	z				AMPS	2.0	81.80	30.00	8.00	40.00	40.60	8.00	3.00	5.20		26.20	•		4.20
Ī		VOLTAGE	208	>				OLTS	120.0	220.0	120.0	15.0	120.0	110.0	10.01	15.0	120.0	15.0	10.0	15.0	115.0	115.0
	7		120	<b>&gt;</b>		NENTS		×						_								
	MODEL MIL STAN		911	z		OMPO			6515-01-173-2053	6530-00-926-2151	84-89	6530-00-937-2204	6545-01-117-3894	6518-00-782-2625	6515-01-510-8020	6525-00-601-0600	13-83	6515-00-935-9763	6640-00-418-8010	6650-01-019-0423	6525-00-823-8144	6525-00-604-0000
	S E	•	28	z		STEM			-01-1	6-00-	-01-0	6-00-	-01-1	-00-	-01-5	9-00-	-00-	6-00-	4-00-	-01-0	-00-	9-00-
		(21		Z	1	SUB SYSTEM COMPONENTS		NSN	6515	6530	6525	6530	6545	6513	6515	6525	4110	6515	6640	6650	6525	6525
	LION	ICX CI	.09	<b>&gt;</b>		S									_		_					
	INCLATURE CLEARING STATION	FREQUENCY (HZ)	20	z	1			EL		7X-1636	111	C-4	OOTAIM	0	BUNN-3001	PICKER	BBC-1-MOD	æ	.05739	SHT-BHTU		7-1
	LATUR EARIN	E	10	Z				MODEL	EEG	_	J		_	1200	_		BBC	732A	_	-		1417-1
	NOMENCLATURE MES CLEARING		TURER					ы	DR, M	SURG	ATUS	ICAL	SURG	MACH SURG SUCTIO	ENTRA	DIOG	œ	ICAL	ပ ပ	MICROSCOPE, OPTI	MACHI	X B
			MANUFACTUR	<b>≥</b>				LATUR	ILLAT	IZER,	APPAR	SURG	UNIT,	URG S	CONCO	TE RA	ERATO	OSURG	R BLO	COPE,	SING	NATOR
	MSN 6545-01-102-6790		Ž					NOMENCLATURE	DEFIBRILLATOR,	TERIL	RAY	IGHT,	INK,	ACH S	XXGEN	ASSET	REFRIGERATOR	<b>ELECTROSURGIC</b>	COUNTER BLOOD	ICROS	ROCES	ILLUMINATOR X
	-01-1	p.	i	11 11 11	1				D86072 D													
	MSN 6545	REFERENCE	DOCUMENT	A PLA	i			LINE	D86	NON	NON	NON	NON	NONE	NON	NON	NON	NONE	NON	NON	NONE	NONE
ă	LINE M52524	REF	8	DAT		-		SYS CODE		34	35	36	37	03	38	39	56	40	41	42	43	44
	35		WGT	•				SYS	ည္ထ	BD134	BDI	BD1	BDI	<b>BB</b> 003	BDI	BD1	AG026	BD140	BD141	BD142	BD143	BD144
CONTROL NUMBER FUO0632 SYSTEM	CODE BD133		M.	10.																		

	DATE 90330		2	S VII				יאו	-	7	. ~		7	-	4	. υ	•	•	~	~	· ~	۱ ۸	•	•	•	-
TER	OPRS 8			S	S)	S	S	(S)	co	S	S	(C)	S	S	w	S	S	V2	S	v.	503	S	C)	(0)	v.	S
SHELTER TYPE N/A	E N	,	D.	3 '	١		1	1	1	•	ı	1	•	1	1	1	1	١	•	١	1	١	•	1	•	1
n9-	PHASE DC N	!	BTU	5	•	١	٠	•	ı	•	٠	•	١	ı	•	1	•	•	•	1	1	1	•	•	ſ	•
GEN SYSCD ST-30-6U	E >		ł																							
H W	w z		00/04	ACA ACA	V	Ş	¥	AC	YC.	¥	YC.	N V	Ş	Ş	Y	AC	AC	Ŋ.	Ş	Ş	Ş	¥	V	Ä	AC.	AC
PRM MVR MODEL M931	418 N			800	•	ı	•	1	ı	1000	•	1650	550	1000	750	200	1200	300	•	١	2600	•	1	1	1	ı
83 e4 tm	N N		N DON'S			1	ı	•	ı	8.60	1	70	4.70	8.30	6.50	4.30	90	2.60	1	ı	9			•	1	1
PRIME MOVER 5 TON	NGE 3 220 N	]	7	9						80		13.70	4	æ	9	4	10.90	5			22.60					
	VCLTAGE 0 208 N	S	ST-TON	120.0	115.0	120.0	120.0	115.0	115.0	115.0	115.0	120.0	115.0	120.0	115.0	115.0	110.0	115.0	110.0	115.0	115.0	115.0	110.0	110.0	110.0	115.0
	0 120 Y	ONENT											•	•										•		
MODEL N/A	28 110 N Y	COMP		359-9	359-9	BLE	BLE	298-7	359-9	895-1	359-9	358-9	BLE	BLE	359-9	290-6	359-9	359-9	267-5	494-3	171-4	310-8	BLE	BLE	377-9	359-9
	10	SUB SYSTEM COMPONENTS	*=	6630-00-359-9626	6640-00-359-9708	UNAVAILABLE	UNAVAILABLE	6630-00-298-7253	6635-00-359-9827	6630-00-895-1259	6630-00-359-9122	6640-00-358-9635	UNAVAILABLE	UNAVATLABLE	6640-00-359-9840	6640-00-290-6707	6640-00-359-9863	6640-00-359-9880	4310-00-267-5645	6640-00-494-3774	6640-00-171-4407	6640-00-310-8558	UNAVAILABLE	UNAVAILABLE	6640-00-377-9383	6630-00-359-9984
M BAS	(HZ) 60 4 Y	SUB	NSX	99	99	3	3	99	99	99	99	99	5	25	99	99	99	99	43	99	99	99	3	AND CAN	99	99
ROLEU	UENCY 50 N																		001				3-4	37		
NOMENCLATURE LABORATORY PETROLEUM BASE	FREQUENCY (HZ) DC 50 60 40 N N Y N		MODEL	73748	67310	74518	13-449	74731	73455	74801	69-140	74944	69-910	96999	61600	13-580	6171-8	31540	91105-001	14-502	92230	14-335	232-1-3-4	5-14-337	67-985	69-018
ENCLATURE ORATORY P	RER		•	ZIS	ដ្ឋ	300	•	-				> >	DE	BA	_		Ę	•			•	3				HE
	MANUFACTURER N/A		TURE	S ANI	GR EL	SCLO	TER	S DIS	ROPPII	ASOLII	DVAPO	EMATI	WATER	WATER	<u> </u>	MERS	X.	LITY	<b>1</b>	ELECT	S DIS	MICAL	OR AII	ATOR 1	SFRE	SUL
NSN 6640-00-303-4940	MANU N/A	j   	NOMENCLATURE	APPARATUS AND	CENTRIFUGE EL	APPARATUS CLOI	COLORIMETER	APPARATUS DISTIL	GREASE DROPPI	TESTER GASOLI	BATH REIDVAPOR P	BATH KINEMATI	APPARAT WATER	UTILITY WATER	HEATER FUL-KO	HEATER IMMERSION	HOT PLATE CIN	OVEN UTILITY	PUMP VACUUM	STIRRER ELECT	APPARATUS DISTIL	HOOD CHEMICAL	COMPRESSOR AI	REFRIGERATOR	APPARATUS FREEZI	APPARATUS
-00-30	E 144	1		-		•	_	•	_	_			-	_	_	_	_	-	•			_	•			_
NSN 6640	REFERENCE DOCUMENT TM566402144	}	LINE	NONE	NONE	NON	NONE	NONE	NON	NON	NON	NON	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NON	NONE	NONE	NONE	NONE
MBER Line N83275	REP DOC TMS		SYS CODE	16	17	18	19	20	21	22	23	24	<b>1</b>	9 1	27	28	67	90	31	32	33	34	35	36	37	38
2	WGT 23181		SYS	BH116	BH117	BH118	BH119	BH120	BH121	BH122	BH123	BH124	BH	BH126	BH127	BH128	BH129	BH130	BH131	BH132	BH133	BH134	BH135	BH136	BH137	BH138
CONTROL FU00593 SYSTEM CODE BH115	KN 60.																									

	œ	DATE		91112				SRCVAL OTY	1	T	T.
LTER	type Unshelter	OPRS		m					-		_
SHE	TYP		HIO	z	!	ļ.	5	1000	1	•	•
	SYSCD ST-10-4-1	PHASE	얼	z			BTO	HEAT	•	•	ı
ZE S	SYSCD ST-10	,,,,	٣	<b>&gt;</b>				ļ			
<b>X</b>	MODEL		w	Z				AC/D	Y	Ä	<b>V</b> C
PRM	MODE		418	N N N N N				WATTS AC/DC	2121	2350	4097
	Ę		240	Z				M Sd	02	30	0,
RIME	MOVER TRL, MTD	Ħ	220	z				W	10.7	11.3	19.70
<u>α</u> ,	z F	OLTAG	208	<b>&gt;</b>				LTS	0.8	0.8	208.0
	•	>	120	×		ENTS					
	MODEL AN/MPQ-4A		110	Z		MPON			3-053	6-773	3-053
	MOD NA		28	z		S			00-54	00-58	00-54
		FREQUENCY (HZ)	100	>		SUB SYSTEM COMPONENTS		NSN	5840-(	5840-(	5840-00-543-0538
		X (H2	9	z		SG		_	•,	•.	ω,
		OUENC	20	Z					58	57	26
	TURE	FRE	ည	Z				MODEL	OA-12	OA-12	0A-1256
	NOMENCLATURE RADAR SET		MANUPACTURER					URE	ROUP	TRANSMI	CONTROL INDICATO
	0759		MANUE	J-E-C				NCLAT	NNA G	IVER	ROL 1
	-543-							NOME	ANTE	RECE	CONT
	NSN 5840-00-543-0759	ERENCE	UMENT	TM11584020810				LINE	NONE	NONE	NONE
ă	LINE Q15414	REF	00	THE				CODE	6,	0	AC031
L NUMB	EI.		WGT	6633				SYS	ACO.	ACO	ACO.
CONTROL NUMBER FU00616 SYSTEM	CODE AC028		KW	10.							

	DATE 90247		OTY 1
X	OPRS D		SRCVAL QTY S 1 S 1
SHELTER TYPE N/A		Bru	1000 1000
GEN SYSCD G-60-4	PHASE S 3 DC OTH N Y N N	1	HEAT
S S G	w z		AC/DC AC AC
PRM MVR MODEL	418 Y	! ! !	WATTS AC/DC - AC
<b>61</b> CC	0 240 N		AMPS W
PRIME MOVER N/A	TAGE 22		
10	VOI 120 2 N	ENTS	VOLTS 416.0 416.0
MODEL AN/MPQ 55	VOLTAGE 28 110 120 208 220 240 418 M N N N N Y	COMPON	BLE
<b>*</b> *	,,,,	SUB SYSTEM COMPONENTS	NSN UNAVA: ABLE INA: (*) APTE
NCLATURE R SET ICWAR	FREQUENCY (HZ)  DC 50 60 400  N N Y	SUB SYSTEM COMPONENTS	MODEL
NOFE	MANUPACTURER RAYTHEON		NOMENCLATURE PRECEIVER TRANSMI
NSN 1430-01-042-4907	•	; ; ;	NOMENC! RECEIV!
NSN 1430-01	REFERENCE DOCUMENT DATA PLATES		LINE
4			SYS CODE LINE ACOOS NONE
10 10	WGT 4900		SX
SYSTEM CODE ACOO4 Q1604	Ж. 6.		

		DATE		90318			SRCVAL OTY	<u>-</u>	~	_	7	_	-
	TEX.	OPRS		-			SRCV	S	S	S	S	S	S
	SHELTER TYPE N/A		HIO	z	•	Đ	COOL	1	•	•	•	ŧ	1
		PHASE	2	z		BTU	HEAT	ı	•	ı	ı	ì	•
	GEN SYSCD G-60-4	<u>a</u>	m	<b>&gt;</b>	1		i						
	£	1	S	z			AC/D	YC	AC	¥Ç	¥C	¥	γc
	PRM	VOLTAGE	418	<b>&gt;</b>			AMPS WATTS AC/DC	•	,	•	*	•	1
			240	Z			M Sdi	,	,	,	,	,	
	PRIME MOVER N/A	EE	220	z			¥						
		VOLTA	208	<b>Z</b>			70LTS	116.0	116.0	416.0	116.0	116.0	116.0
	20		12(	Z	NENT		_	•	•	•	•	•	•
	MODEL AN/MPQ 50		28 110	Z	SUB SYSTEM COMPONENTS			BLE	BLE	BLE	BLE	BLE	BLE
•	¥Z				STEM			NAVAILABLE	MAVAILABLE	NAVAILABLE	MAVAILABLE	<b>NAVAILABLE</b>	MAVAILABLE
		(HZ)_	400	<b>&gt;</b>	SUB S		NSN	CNA	CINA	CNA	SNA.	UNA	UNA
	_	ENCY	۰ ص	Z									
	RE (HAWK	FREQUENCY (HZ)	က် : ည	z			MODEL						
	CLATU	١		Z			S.	H		œ			
	NOMENCLATURE RADAR SET (HAWK)		CTURER	ž Õ	-		RE	RANSMI		COOLER	ŢĶ	R SET	NNA
			MANUFACTU	RAYTHEON			NOMENCLATURE	VER T	ATOR	FIER	SUPP	RADA	ANTE
	.042-4	i	<b>2</b>	<b>2</b> ,			NOMEN	RECEI	MODOL	AMPLI	POWER	GROUP	GROUP
	NSN 1430-01-042-4908	CE	E	ATE			LINE						
		REFERENCE	COME	IL VIN	i								
(BER	LINE Q16048						SYS CODE	3016	017	3018	010	020	3021
10 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	H O		E SE	820			S	¥	¥	¥	¥	¥	¥
CONTRC	SYSTER CODE LINE ACOO3 Q1604	i	¥ ,	• •									

	DATE 91216	r otr	46
Shelter Type Unshelter	OPRS I	SRCVAL QTY T 1 T T 1	H #
SHEL	E Z	1000 C00[	1 1
	PHASE DC N	; [2]	1 1
GEN Syscd	7	1	
	lu z	AC/DC AC DC	N N
PRM MVR MODEL M105A2	418 X	WATTS 373	1119
PRIME MOVER 1 1/2 TON	VOLTAGE 110 120 208 220 240 418 N Y Y N N N	L. 79	5.37 7.537
PRIME MOVER 1 1/2	GE 220	¥ ; ;	ກໍ <b>ເ</b> ດີ
	VOLTA 208 Y	S VOLTS 208.0 24.0	20.0
	120	NENTS (	N 01 -1
MODEL M-51	1		
Ž X	2 Z	SYSTEM COINSMINANTIABLE UNAVAILABLE UNAVAILABLE UNAVAILABLE UNAVAILABLE	navailable navailable mavailable
IVE	FREQUENCY (HZ)  DC 50 60 400 7  N N Y N N	SUB SYSTEM COMPONENTS NSN UNAVALLABLE UNAVAILABLE UNAVAILABLE	UNAV
LLECT	CX (1	150	CENT
8	EQUES 50 X		Incandescent
NCLATURE TER SYSTI		MODEL	INC
nomenclature Shelter system collective	MANUFACTURER LIPANI MPG	JRE PLY IT FAN	R FAN &
NSN 4240-00-854-4144		LINE NOMENCIATURE NONE POWER SUPPLY NONE FILTER UNIT FAN NONE EVACUATION FAN	APORATOI ADENSER SHT
0~854	112	NO BOO	
fSN 1240-0	ZENCE TENT 240264	NON KE	NONE NONE
4	, and other	CODE	
NUMBER LINE TODA74	WGT 5405	SYS CODE BD118 BD119 BD120	8012 AA00
CONTROL NUMBER FUGGESO SYSTEM CODE LINE RD117 TOOA7	7. 5		

NOMENCIATURE						ANL SO	Maa	O OAN MOO	a a a	006-1000	9	
A		ក្ខខា	7 <u>T</u> O	MODEL GETS100(	•	MOVER N/A	MODEL N/A	•	SYSCD	TYPE N/A	1	
LINE	M	FREQUE	ACY (HZ)	- (	TOA	FAGE	- 1	·	PHASE		OPRS	DATE
LINE NOMENCIATURE HODEL NSM VOLTS  NONE COMPUTER 2113B UNAVALIABLE 110.0  NONE PROGRAMER POWER 59501A UNAVALIABLE 110.0  NONE ATTENUATOR SWITC 11713A UNAVALIABLE 110.0  NONE GENERATOR SYNTHE 33.25A UNAVALIABLE 120.0  NONE DRIVE DISK 436A UNAVALIABLE 120.0  NONE DRIVE DISK 7900A UNAVALIABLE 120.0  NONE DRIVE DISK 7900A UNAVALIABLE 120.0  NONE COUNTER THE INT 5370A UNAVALIABLE 120.0  NONE COUNTER THE INT 5370A UNAVALIABLE 120.0  NONE OSCILLOSCOPE DIG 111A UNAVALIABLE 120.0  NONE POWER SUPPLY 65294A UNAVALIABLE 120.0  NONE POWER SUPPLY 6294B UNAVALIABLE 120.0  NONE POWER SUPPLY 6294B UNAVALIABLE 120.0  NONE POWER SUPPLY 6133A UNAVALIABLE 120.0  NONE POWER SUPPLY 6130A UNAVALIABLE 120.0  NONE POWER SUPPLY 6120A UNAVALIABLE 120.0  NONE POWER SUPPLY 6120A UNAVALIABLE 120.0  NONE POWER SUPPLY 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0  NONE TERMINAL 6120A UNAVALIABLE 120.0		S N	Z ×			0 X	240 418 N N	ν >-	) Z	E N	7	90310
LINE NOMENCLATURE  NONE PAN BLOWER  NONE PROGRAMER POWER 2113B UNAVAILABLE 110.0  NONE ATTENUATOR SWITC 11713A UNAVAILABLE 110.0  NONE GENERATOR SYNTHE 3125A UNAVAILABLE 120.0  NONE GENERATOR SYNTHE 3125A UNAVAILABLE 120.0  NONE METTER POWER 1325A UNAVAILABLE 120.0  NONE DRIVE PLEXIBLE D 9885H UNAVAILABLE 120.0  NONE DRIVE DISK 7900A UNAVAILABLE 120.0  NONE VOLTMETER POWER 13215A UNAVAILABLE 120.0  NONE COUNTER TIME 1115 UNAVAILABLE 120.0  NONE MULTIPROGRAMER 6940B UNAVAILABLE 120.0  NONE POWER SUPPLY 6294A UNAVAILABLE 120.0  NONE POWER SUPPLY 6294B UNAVAILABLE 120.0  NONE POWER SUPPLY 6294B UNAVAILABLE 120.0  NONE POWER SUPPLY 6294B UNAVAILABLE 120.0  NONE SOURCE PROGRAMAB 8165A UNAVAILABLE 120.0  NONE TERMINAL 22645A UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 6294B UNAVAILABLE 120.0  NONE TERMINAL 7204B TANTANATANATANATANATANATANATANATANATANA				1	j 1 1					!		
LINE NOMENCLATURE MODEL NSW  NONE PAN BLOWER  NONE COMPUTER  NONE ATTENUATOR SWITC 11713A UNAVAILABLE 110.0  NONE ATTENUATOR SWITC 11713A UNAVAILABLE 110.0  NONE GENERATOR SYNTHE 3125A UNAVAILABLE 120.0  NONE METER POWER 1325A UNAVAILABLE 120.0  NONE DRIVE PLEXIBLE D 9885M UNAVAILABLE 120.0  NONE DRIVE DISK 7900A UNAVAILABLE 120.0  NONE VOLTWETER TIME INT 515A UNAVAILABLE 120.0  NONE VOLTWETER TIME INT 515A UNAVAILABLE 120.0  NONE WITTIPROGRAMER 6940B UNAVAILABLE 120.0  NONE MULTIPROGRAMER 6940B UNAVAILABLE 120.0  NONE POWER SUPPLY 6294A UNAVAILABLE 120.0  NONE POWER SUPPLY 6294B UNAVAILABLE 120.0  NONE POWER SUPPLY 6294B UNAVAILABLE 120.0  NONE SOURCE PROGRAMAB 8165A UNAVAILABLE 120.0  NONE TERMINAL 120.0  NONE TERMINAL 120.0  NONE TERMINAL 120.0  NONE TERMINAL 120.0  NONE TERMINAL 120.0  NONE TERMINAL 120.0  NONE TERMINAL 120.0		•	SUB SYST	EM COMPO	FINTS							
FAN BLOWER         UNAVAILABLE         110.0           COMPUTER         2113B         UNAVAILABLE         115.0           PROGRAMER         59501A         UNAVAILABLE         110.0           ATTENDATOR SWITC         1713A         UNAVAILABLE         120.0           METER POWER         436A         UNAVAILABLE         120.0           DRIVE PLEXIBLE         1325A         UNAVAILABLE         120.0           DRIVE PLEX         13215A         UNAVAILABLE         120.0           VOLTHETER DIGITA         3455A         UNAVAILABLE         120.0           VOLTHETER DIGITA         3455A         UNAVAILABLE         120.0           COUNTER TIME INT         5370A         UNAVAILABLE         120.0           OSCILLOSCOPE DIG         111A         UNAVAILABLE         120.0           NUTTIPROGRAMER         6940B         UNAVAILABLE         120.0           POWER SUPPLY         6294A         UNAVAILABLE         120.0           POWER SUPPLY         6204B         UNAVAILABLE         120.0           POWER SUPPLY         6204B         UNAVAILABLE         120.0           POWER SUPPLY         6204A         UNAVAILABLE         120.0           SOURCE PROGRAMAB         8165A	_	MODEL	NSN		VOLT	SAMPS	WATTS	AC/DC	HEAT	BTU	SECVAL OTY	<u> </u>
COMPUTER  COMPUTER  PROGRAMER POWER  PROGRAMER POWER  ATTENUATOR SWITC  11713A UNAVAILABLE  110.0  GENERATOR SYNTHE  436A UNAVAILABLE  120.0  DRIVE FLEXIBLE D  9885M UNAVAILABLE  120.0  POWER SUPPLY  13215A UNAVAILABLE  120.0  VOLTHETER DIGITA  4455A UNAVAILABLE  120.0  VOLTHETER DIGITA  59500A UNAVAILABLE  120.0  HONTER THE INT  1310A UNAVAILABLE  120.0  POWER SUPPLY  6294B UNAVAILABLE  120.0  POWER SUPPLY  6294B UNAVAILABLE  120.0  POWER SUPPLY  6294B UNAVAILABLE  120.0  POWER SUPPLY  6294B UNAVAILABLE  120.0  POWER SUPPLY  6113A UNAVAILABLE  120.0  GENERATOR PULSE  8015A UNAVAILABLE  120.0  GENERATOR PULSE  SOUTH ONAVAILABLE  120.0  GENERATOR PULSE  SOUTH ONAVAILABLE  120.0  GENERATOR PULSE  SOUTH ONAVAILABLE  120.0  TERMINAL  TERMINAL  TERMINAL  TANAVAILABLE  120.0	_		UNAVAI	LABLE	110.			Ç	•	•	S	, en
PROGRAMER POWER   59501A   UNAVAILABLE   110.0	•	•	UNAVAI	LABLE	115.	_	1150	Ş	1	1	va	. ~
ATTENUATOR SWITC 11713A UNAVAILABLE 110.0 GENERATOR SYNTHE 3325A UNAVAILABLE 120.0 METER POWER 436A UNAVAILABLE 120.0 DRIVE DISK 7900A UNAVAILABLE 120.0 DRIVE DISK 7900A UNAVAILABLE 120.0 VOLTWETER THE 112 3325A UNAVAILABLE 120.0 VOLTWETER THE 112 3370A UNAVAILABLE 120.0 OSCILLOSCOPE DIG 111A UNAVAILABLE 120.0 MUTIPROGRAMER 6940B UNAVAILABLE 120.0 POWER SUPPLY 6294B UNAVAILABLE 120.0 POWER SUPPLY 6209B UNAVAILABLE 120.0 POWER SUPPLY 6209B UNAVAILABLE 120.0 POWER SUPPLY 6133A UNAVAILABLE 120.0 SCURCE PROGRAMAB 8165A UNAVAILABLE 120.0 TERMINAL 120.0 TERMINAL 120.0 TERMINAL 120.0	_		UNAVAI	LABLE	110.			<b>Y</b> C	f	•	W	-
CEMERATOR SYNTHE 3325A UNAVAILABLE 120.0	•	ဥ	UNAVAI	LABLE	110.	0 2.50		Ų	•	1	S	~
NETER POWER	•	黑	UNAVAI	LABLE	120.			Ş	ſ	•	S	-
DRIVE PLEXIBLE D         9885M         UNAVAILABLE D         120.0           DRIVE DISK TOOM         7900A         UNAVAILABLE D         120.0           POWER SUPPLY TOOM         13215A         UNAVAILABLE D         120.0           VOLTHER RE DIGITA TOOM         113         UNAVAILABLE DO.0         120.0           COUNTER TIME INT 5370A         UNAVAILABLE DO.0         120.0         120.0           OSCILLOSCOPE DIG TOOM         UNAVAILABLE DO.0         120.0         120.0           POWER SUPPLY GOOD UNAVAILABLE DO.0         COOD UNAVAILABLE DO.0         120.0           POWER SUPPLY GOOD UNAVAILABLE DO.0         GOOD UNAVAILABLE DO.0         120.0           SOURCE PROGRAMAB BLESA UNAVAILABLE DO.0         120.0         120.0           SOURCE PROGRAMAB BLESA UNAVAILABLE DO.0         120.0         120.0           TERMINAL DO.WED DO.WED TO.0         TONAVAILABLE DO.0         120.0	_		UNAVAI	LABLE	120.			¥	•	•	S	-
DRIVE DISK         7900A         UNAVAILABLE         120.0           POWER SUPPLY         13215A         UNAVAILABLE         120.0           VOLTHETER DIGITA         3455A         UNAVAILABLE         120.0           COUNTER TIME INT         5370A         UNAVAILABLE         120.0           OSCILLOSCOPE DIG         111A         UNAVAILABLE         120.0           MULTIPROGRAMER         6940B         UNAVAILABLE         120.0           POWER SUPPLY         6294A         UNAVAILABLE         120.0           POWER SUPPLY         6133A         UNAVAILABLE         120.0           SOURCE PROGRAMAB         8165A         UNAVAILABLE         120.0           SURVER SUPPLY         6133A         UNAVAILABLE         120.0           SURVER SUPPLY         6133A         UNAVAILABLE         120.0           SCHERATOR PULSE         8015A         UNAVAILABLE         120.0           TERMINAL         2645A         UNAVAILABLE         120.0	_	۵	UNAVAI	LABLE	120.			¥C	ſ	•	S	-
POWER SUPPLY   13215A   UNAVAILABLE   120.0		7900¥	UNAVAI	LABLE	120.	1.00		¥C	•	1	S	-
VOLTWETER DIGITA         3455A         UNAVAILABLE         120.0           COUNTER TIME INT         5370A         UNAVAILABLE         120.0           OSCILLOSCOPE DIG         111A         UNAVAILABLE         120.0           INTERFACE MULTIP         59500A         UNAVAILABLE         120.0           POWER SUPPLY         6294A         UNAVAILABLE         120.0           POWER SUPPLY         6209B         UNAVAILABLE         120.0           POWER SUPPLY         613A         UNAVAILABLE         120.0           GENERATOR PULSE         8015A         UNAVAILABLE         120.0           TERMINAL         2645A         UNAVAILABLE         120.0           TERMINAL         2645A         UNAVAILABLE         120.0	_	~	UNAVAI	LABLE	120.			<b>Y</b> C	•	•	S	7
COUNTER TIME INT 5370A UNAVAILABLE 120.0 0SCILLOSCOPE DIG 111A UNAVAILABLE 120.0 INTERPACE MULTIP 5950A UNAVAILABLE 120.0 MULTIPROGRAMER 6940B UNAVAILABLE 120.0 POWER SUPPLY 6294A UNAVAILABLE 120.0 POWER SUPPLY 6209B UNAVAILABLE 120.0 GENERATOR PULSE 8015A UNAVAILABLE 120.0 SCOURCE PROGRAMAB 8165A UNAVAILABLE 120.0 TERMINAL 120.0 TERMINAL 120.0	-	Z,	UNAVAI	LABLE	120.	05.0		¥	•	•	S	-
OSCILLOSCOPE DIG 111A UNAVAILABLE 120.0 INTERFACE MULTIP 59500A UNAVAILABLE 120.0 MULTIPROGRAMER 6940B UNAVAILABLE 120.0 POWER SUPPLY 6299A UNAVAILABLE 120.0 POWER SUPPLY 6299B UNAVAILABLE 120.0 FOWER SUPPLY 6113A UNAVAILABLE 120.0 GENERATOR PULSE 8015A UNAVAILABLE 120.0 SCOUNCE PROGRAMAB 8165A UNAVAILABLE 120.0 TERMINAL 2645A UNAVAILABLE 120.0	-	Ę	UNAVAI	LABLE	120.	0 2.50	••	¥C	•	•	S	_
INTERPACE MULTIP 59500A UNAVAILABLE 120.0	_	2	UNAVAI	LABLE	120.			¥C	•	•	S	7
MUATIPROGRAMER 6940B		6	UNAVAI	LABLE	120.	05.	9	¥C	•	•	S	-
POWER SUPPLY         6294A         UNAVAILABLE         120.0           POWER SUPPLY         6209B         UNAVAILABLE         120.0           POWER SUPPLY         6113A         UNAVAILABLE         120.0           GENERATOR PULSE         8015A         UNAVAILABLE         120.0           SOURCE PROGRAMAB         8165A         UNAVAILABLE         120.0           TERMINAL         2645A         UNAVAILABLE         120.0	_	_	UNAVAI	LABLE	120.	4.00	480	¥C	•	•	S	-
POWER SUPPLY         6209B         UNAVAILABLE           POWER SUPPLY         6113A         UNAVAILABLE           GENERATOR PULSE         8015A         UNAVAILABLE           SOURCE PROGRAMAB         8165A         UNAVAILABLE           TERMINAL         2645A         UNAVAILABLE           CONVIEDTUP DOMED         7004A		6294A	UNAVAI	LABLE	120.	_	_	¥	•	•	S	-
POWER SUPPLY 6113A UNAVAILABLE GENERATOR PULSE 8015A UNAVAILABLE SOURCE PROGRAMAB 8165A UNAVAILABLE TERMINAL 2645A UNAVAILABLE CONTIBETED DOWED FOOD 7		6209B	UNAVAI	LABLE	120.			¥	•	•	S	-
GENERATOR PULSE 8015A UNAVAILABLE SOURCE PROGRAMAB 8165A UNAVAILABLE TERMINAL POMPE CONTREME DOMP CODA TO THAN 13 21 2	_		UNAVAI	LABLE	120.			<b>Y</b> C	•	•	S	-
SOURCE PROGRAMAB 8165A UNAVAILABLE TERMINAL 2645A UNAVAILABLE CONTREMED OF THE TOTAL THROUGHT	•	ė.	UNAVAI	LABLE	120.	2.00		¥C	•	1	S	<b>H</b>
TERMINAL 2645A UNAVALLABLE CONVEDEND DOMED TODAY	-	9	UNAVAI	LABLE	120.	_		¥	•	•	S	· ~
CONVENTED BOARD GODD 9	•	2645A	UNAVAI	LABLE	120.			Ş	•	•	S	-
CONVENTED FOREN TOPAS UNAVALLABLE	E CONVERTER POWER	TOPAZ TOPAZ	UNAVAI	LABLE	120.0	3.66	440	¥	,	•	S	_

HODEL HOVER N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A	VOLTAGE N/2 N/2 208 N/2 200 0 220 0 0 220 0 0 220 0 0 220 0 0 220 0 0 220 0 0 220 0 0 220 0 0 220 0 0 0 220 0 0 0 0 220 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
PRINE NOVER N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A	PRIME PRM MVR GEN N/A N/A N/A  VOLTAGE S20 240 418 S 3 N Y N N Y Y N Y Y N N Y Y S20 200 10 10 2238 AC 15.0 4.17 480 AC 15.0 4.17 480 AC 15.0 3.30 380 AC 20.0 10.10 2238 AC 15.0 3.30 373 AC 20.0 10.10 2238 AC 15.0 3.30 373 AC 20.0 10.10 2238 AC 20.0 10.10 2238 AC 20.0 3.30 373 AC 20.0 3.30 373 AC 20.0 3.30 373 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 3.30 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 20.0 AC 2
	MVR GEN  IL SYSCD  I S 3  V Y  AC DC HE  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC AC  AC

SYSTEM  THE NOTE THE NOTE THE NOTE THE FELSE THY BY IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HIGH STANDARD IN HI		DATE	90330			1	; ;		• -	' ~	-	-	· ~	-	•		٠-	-	• ~	' ^	ı ~	
Time   NSW   NOWENCLATURE   HODEL   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINE   PRINCE   PRINE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRINCE   PRIN	TER	OPRS	7				7 J	y c	S CS	S)	y y	v2	S	S	<b>U</b> 2	<b>(</b> 2	<b>(</b> 2	· C	· 0	1 60	S	
Time   NSN	SHEL TYPE N/A	ļ	Ēz		!		3 '	•	•	ı	1		•	1	1	1	•	•	٠	١	•	
Time   NSN	M SCD 60-60	PHASE	~ ×		! ! ! ! !	Banan	1	•	1	•	1	1	•	t	•	•	•	•		•	•	
TIME   NSN	Æ	e	o >-		i   	24/24	) } }	· ·	ပ္	ŭ	ပ္	2	Ş	ည	ပ္	2	۲	ပ္	۷	2	Ş	
TIME   NSN   NOMENCIATURE   FIRECT   FW-BAS   2 1/2 TON	PRN M MODEL M109		2				-	805	805			-	_		_		_	1				
Table   NSN		07.0	2 ×			-	_	8	8	<b>•</b>	.20	.20	00.	<del>0</del>	90		20	,	•		10	
TIME   NSN	PRIM MOVE 2 1/3	FAGE	, z				-		•	7	,	ř						_				
LINE   NSN		VOL.			rrs	VOLTE	28.0	115.0	115.0	115.0	115.0	120.0	115.0	115.0	115.0	115.0	120.0	115.0	240.0	120.0	120.0	
LINE   NSN	MODEL PM-BAS	ſ			I COMPONE		-940-7866	-063-7375	-542-4111	-449-6684	-204-2718	-204-2728	-729-9259	-460-7198	-465-1649	-460-7211	-542-0396	-238-1459	-767-0218	-392-2939	-221-0607	
LINE   NSN					B SYSTE	NSN	6130-00	4310-00	4310-00	4940-00	5130-00	5130-00	6230-00	3439-00	3439-00	3439-00-	3439-00-	6625-00	4910-00-	4910-00-	5130-00-	
EINE NSN NOMEN  TIO414 4940-00-754-0714 SHOP  REFERENCE  WGT DOCUMENT  SC491095CLA01 MIL STANDAR  SYS CODE LINE NOMENCLATURE AB N54691 CHARGER BATTERY AH043 NONE COMPRESSOR UNIT AH045 F86209 DEGREASER PORTA AH045 F86209 DEGREASER PORTA AH045 NONE LIGHT EXECTRICA AH046 NONE LIGHT EXTENSION AH049 NONE SOLDERING & DES AH051 NONE SOLDERING & DES AH051 NONE GUN SOLDERING AH052 NONE GUN SOLDERING AH053 V64052 TEST SET ARMATU AH054 V99843 STAND TEST AUTOI AH055 W02707 TESTER ENGINE DI AH056 W02707 TESTER ENGINE DI	FUEL &	EMCY (F			S		v												500 A			
EINE NSN NOMEN  TIO414 4940-00-754-0714 SHOP  REFERENCE  WGT DOCUMENT  SC491095CLA01 MIL STANDAR  SYS CODE LINE NOMENCLATURE AB N54691 CHARGER BATTERY AH043 NONE COMPRESSOR UNIT AH045 F86209 DEGREASER PORTA AH045 F86209 DEGREASER PORTA AH045 NONE LIGHT EXECTRICA AH046 NONE LIGHT EXTENSION AH049 NONE SOLDERING & DES AH051 NONE SOLDERING & DES AH051 NONE GUN SOLDERING AH052 NONE GUN SOLDERING AH053 V64052 TEST SET ARMATU AH054 V99843 STAND TEST AUTOI AH055 W02707 TESTER ENGINE DI AH056 W02707 TESTER ENGINE DI	ature UI Phent	FREQUE		1 1 1		MODEL	12/24VD	1.5 CFM	_	<b>∀</b> /¤		K/N	X/X	< <u>&gt;</u>	K/N	<b>4/</b> 2	N/A	A/V IND	FL MTD			
ENS.  LINE NSN  T30414 4940-00-754-  T30414 4940-00-754-  REFERENCE  WGT DOCUMENT  SYS CODE LINE NONE  AH043 NONE COMP  AH044 E67735 COMP  AH045 F86209 DEGR  AH046 NONE DRILL  AH046 NONE LIGH  AH047 NONE COMP  AH048 NONE LIGH  AH051 NONE GUD  AH051 NONE GUD  AH051 NONE GUD  AH053 V64052 TEST  AH054 V99843 STANI  AH055 W02707 TEST]  AH055 W02707 TEST	22	CTURER	PANDARD	j 		RE	TTERY	WILT CAN'T	C UNIT	PORTAB	TRICAL	TRICAL	NOISH	E DESO	RING E	Œ	LING	RMATOR	AUTOM			
SES	54-0714	MANUE	MIL S			MENCLATI	ARGER BA	MPRESSOF	MPRESSOF	GREASER	TIL ELEC	TIL ELEC	GHT EXT	LDERING	ON SOLD	SE TRANS	N SOLDER	ST SET	AND TEST	STER ENG		
SES NUMBER   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES   SES	3N 540-00-7!	NCE	95CLA01			. •	-			3						-					_	
	<b>*</b>	REFERE	SC491(	1						- •												
FUGOSES SYSTEM CODE AH042 KW 22.		WGT	ı			SYS	8	AHO	AHO	AHO	ANO	AMO	Ano	100	AHOO	AHOD	AHOD	CONV	AHOS	AHOD	AHCO	
	CONTROL FU00585 SYSTEM CODE AH042	K	22.																			

Prime Prm mvr gen shelfer Mover Model syscd type N/A N/A	PHASE	1 220 240 418 5 3 DC OTH N N N Y N N 3 91052	DLE	AMPS WATTS AC/DC HEAT	12.50	8.30 1000	18.30	16.66 2000	8.30 1000	. 80 100	4.16 500 AC - S 1	,,,
HODEL NAVUSM-410(V)1 N	SOLT-TOV	28 110 120 208 N N Y N	SUB SYSTEM COMPONENTS	STION	MAVATTARTE 120.0						NAVAILABLE 120.0	
STATION ELECT EQPT	(6H) AURENCE	DC 50 60 400	SUB SYST	NON	MODEL T	74-17	201123	Catino	087-100		, _	•
NSW NOMENCLA 6625-01-070-3658 TEST STA		MANUFACTURER RCA			NOMENCLATURE	OPERATOR CONTROL	MAGNETT TAFF OF	TOWER BOLLES GNO	THIPPOORUPIT THE	TEST SINITES OF	CAMPAIGN BALL	DINE PRINTER
CONTROL NUMBER \$100607 \$95TEM LINE NSN COOR LINE NSN AHOGS T49896 6625-01		MGT DOCUMENT - DATA SHEET									AHO74 HORE	
CONTROL FU00607 SYSTEM CODE AH068		K										

		DATE		91052				SRCVAL OTY		-	٠-	• ~	-	-	7
o e	TYPE Unshelter	OPRS		М				SRCVA	v	· C	· ca	o o	S	, ca	S
i de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de la companya de l	TYPI		Ę	z		•	Đ	100	1	1	1	•	1	1	1
		PHASE	ا ک	z		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	BTU	HEAT	•	ı	•	•	•	•	1
	SYSCD	Ā	٣	<b>&gt;</b>				l							
5	٠.		Ø	Z				AC/DC	Ŋ,	¥C	Ş	YC.	¥	¥C	<b>y</b> c
PRM	MODEL N/A		418	z				WATTS			200	000	000	100	200
			240	Z											
PRIME	MOVER N/A	20	220	z				7	12.5	8.3	18.3	16.66	8.3	Φ.	4.16
_	 E	VOLTAGE	208	Z				ILTS	0.0	0.0	0.0	120.0	0.0	0.0	0.0
	110 (V)		120	<b>&gt;</b>		TENTS		×	=	1	7	7	7	7	7
	MODEL AN/USM-410(V)3		110	Z		OHLO:			ьí	뻑	뻑	삑	삑	편	ń
	N N		58	Z	-	STEM			MAVAILABLE	ILLABI	NAVAILABLE	MAVAILABLE	NAVAILABLE	MAVAILABLE	WAVAILABLE
	<b>5</b> .	PREQUENCY (HZ)	400	Z		SUB SYSTEM COMPONENTS		NSN.	ZAYS 5		CNAV	SAND		CNAV	CNAVA
	OM ES	CX (1	9 :	<b>&gt;</b>		S									
	ata N	REQUE	20	Ž,	į			u !	117	46	123	80	49		
	Latur Fatio			z			1	MODEL		•					
	NOMENCLATURE TEST STATION ELECT EQPT		MANUFACTURER						TKOL	PE GR	GRO		d C	W.	~
			NUFAC	2				NOMENCLATURE	3 *	LC	SUPPL	INTERCONNECT	FATIO	ERMI	ZINIZ
	77-54		NAN C	Į				SEE SEE	T Y	CONET	WER	TERC	EST S	0101	
	NSN 6625-01-077-5452	De2	£	1			•								
	NSN 6625	REFERENCE	DOCUMENT	900	į	٠						NONE			
<b>E</b>	LINE T99998	REF					9	SIS CODE	<u>.</u>	2 :	<b>.</b>	2 :	າ :	4	ū
NUMB	16 16	5					5	O TO				V C		210	
CONTROL NUMBER FU00608 SYSTEM	AH077	Š	B Y												

		DATE		91246				L OTY		• -	• -	• ~	٠-	4	4 0	
	Shelitek Type Unshelter	OPRS		4				COOL SECVAL OFF			2 4	) U	) V	) U	ט נ	1
	TYPE		E	z				1000 0000			٠	•	•	•	•	
	5	PHASE		z			BTO	HEAT	•		•		ı			
2	SYSCD G-30-6U	PH	۳	>				E								
į	8 YS(		S	z				20/20		<b>V</b>	, c	2	. U	, U	2	•
3	MODEL		418	Z								3120 A				
•	TRE		240	z												
D. K.	MOVER 5 TON	VOLTAGE	220	Z				ARPS	56.90	3.40	3.40	15.00	6.20	26.50	11.60	
٥	4 X 10	OLTAG	208	<b>&gt;</b>		1		LTS	0.0	8.0	0.8	208.0	0.0	8.0	0.0	
	10	2	120	<b>&gt;</b>		ENTS		8	22	70	70	20	11	7	23	
	MODEL 0996109001		110	z		NOLINO			र्ष	ej	ei ei	<b>6</b> 4	M	N	e e	
	10M	ļ	<b>58</b>	Z		TE C			MAVAILABLE	ILABI	MAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	MAVAILABLE	
	Ħ	FREQUENCY (HZ)	<b>4</b> 00	Z		SUB SYSTEM COMPONENTS		NSN	UNAVA	UNAVA	UNAVA	UNAVA	UNAVA	UNAVA	UNAVA	
	<u> </u>	) XOX	8	<b>&gt;</b>		S			125	221	222	ı				
	E ICATI	REQUE	20	Z				딞	36BL3	3002K371221	1002K371222			E	92	
	PURIF		<b>.</b>	<b>Z</b> ,				_						215JM		
	NOMENCLATURE WATER PURIFICATION UNIT		MANUFACTURER	Z C			٠.	M	H	BOOST	DIST	TIMER BACKWASH	CAL F	ASH P	WATER	
			NUFAC	CHANI				LATUR	ELEC	PURE	PUMP	BACKW	CHEMI	BACKW	MAN	
	NSN 4610-01-234-2196		2	N.				OMENO	OTOR,	OTOR	OTOR	IMER	OTOR	OTOR	OTOR,	
	-01-2	Ħ.	. (	3												
		REFERENCE	UMENT	3	,							NONE				
ĺ	LINE W35417	REF	3 2	DA				1000 s	97	27	28	AZ029	30	31	35	
	38		3 6	7300				SYS	AZC	AZO	AZO	AZO	<b>A</b> 20	AZO	AZO	
FU00633 SYSTEM	CODE AZ025	ì	N C	, 10.												

PRIME PRM MVR GEN SHELTER MOVER MODEL SYSCD TYPE 2 1/2 TON M35A2 G-10-6D 21/2T BOX	VOLTAGE OPRS DATE	220 240 418 S 3 DC OTH N N N Y N N 3		3TC	AMPS WATTS AC/DC HEAT	0 7.10 1492 AC S 1	1.80 373	1.80 373	4.40 932	. 90 186	2.70	86 08.	6.40 746	1.50	. 80 100	15.00	7.00	
MODEL EMC-1500S	AOL	28 110 120 20 N N N	SITE SYSTEM COMPONENTS		MOLT	LABLE 208.0								-3071				
ENCLATURE ER PURIFICATION UNIT	FREOURNCY (HZ)	DC 50 60 400	TSAS MIS		MODEL	N/A UNAVAILABLE	N/N	N/A	N/N	7	N/N		_	W-L-101/37	N/A UNAVAILABLE	_	UH-68F	
NSN NOMENCLATURE 4610-00-202-6925 WATER PURIFI		MANUFACTURER EMC INDUSTRI			NOMENCLATURE	MOTOR SLURRY FEE	PUMP DIATOMITE F	MOTOR ERDLATOR D	MOTOR ERDLATOR S	MOTOR SLURRY DRI	MOTOR SLURRY FEE	PUMP CHEMICAL SO	STARTER MAGNETIC	LAMP INCANDESCEN	BULB LOW WATER W	SWITCH LOW WATER	HEATER	
NUMBER LINE Y35486	REFERENCE	NGT DOCUMENT 19060 DATA PLATE	1 0 0 0		SYS CODE LINE					AZ010 NONE	AZ011 NONE		AZ013 NONE			AZ015 NONE		
CONTROL FU00583 SYSTEM CODE AZ005		KW 10.																

	DATE			AL OTY	•	n	-	~	9	m	-	ri	~	m	~	-	~	~	n	~	-	S	7
SHELTER TYPE Unshelter	OPRS	<b>v</b>		SRCVAL	E	Z	×	X	×	Z	X	X	I	E	E	×	X	X	×	X	X	E	×
SHELTER TYPE UNSHELT	H.		! ;	1000	•	•	•	1	•	•	•	•	1	1	1	•	•	•	•	•	•	•	•
	PHASE	E .	à	HEAT	1	1	•	•	١	•	١	•	•	•	•	٠		•	•	•	•	•	•
GEN SYSCD	A  m >	<b>.</b>		1																			
PRM MVR MODEL	ko z	E .		AC/DC	V	¥	¥C	¥	¥Ç	¥	¥C	¥	¥C	¥C	¥	Ş	¥	¥C	¥	¥C	¥	¥	¥C
PRM M MODEL	418	E,		WATTS	1	•	•	1	•	1	•	•	1	•	•	•	•	1	•	•	•	f	ı
	240	E		AMPS W		•	•	•	1	•	ŧ	•		•	•	,	•	•		•	•	,	
PRIME MOVER N/A	GE 220	<b>.</b>		Ž																			
Ħ	VOLTAGE	E		VOLTS	1	•	•	•	•	1	•	•	ŧ	•	•	•	•	•	ı	•	•	ł	1
MODEL AN/GSC-62 (V) 1	120	-	SUB SYSTEM COMPONENTS	>																			
MODEL AN/GSC-	110	E .	COMBO		LE	i.	Į.	LE	Ę	Ľ	<u> </u>	Ľ	LE	LE	I.E	Ę	LE	LE	LE	CE CE	LE	LE E	I.E
Ş.Ş	. 58	E .	STEM		UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	MAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	UNAVAILABLE	NAVAILABLE
	(Z) 400	E	JB SY	NSN	UNAV	CNAV	CNAV	UNAV	UNAV	CNAV	UNAV	CNAV	CNAV	CNAV	CNAV	CNAV	CNAV	CNAV	CNAV	CANA	CNAV	CNAV	UNAV
PATION	FREQUENCY (HZ)	•	S									7											
	2002 2002 2003	E		닖	1210	234		GRID 386	224	000	MODEL 86	X 2177	190	031	AN/PSC-3					œ			TW100ACT
ATORE OP BA	E <sub>O</sub> ,	E.		MODEL	RF-3210	RF-3234	PSU	GRIC	RF-3224	RF-5000	MODE	CODEX	RF-5051	RF-5031	AN/E	5461				MRS-8			TWI
NOMENCLATURE TABLE TOP BASE STATION	MANUFACTURER			NOMENCLATURE	POWER AMP	POWER DIST PANEL	PORT SELECTOR UN	UTER	POWER SUPPLY	RECEIVER TRANSMI	WIRELESS MODEM	WIRELINE MODEM	POWER SUPPLY	POWER SUPPLY	RECEIVER TRANSMI	CASSETTE RECORDE	ASSY	MORRIS CODE DEMO	STER	CARD CAGE	ANTENNA MULTICOU	MESSAGE KEY	PRINTER DOT MATR
ABLE				NOME	POWE	POWE	PORT	COMPUTER	POWE	RECE	WIRE	WIRE	POWE	POWE	RECE	CASS	ICU ASSY	MORR	COMPUTER	CARD	ANTE	MESS	PRIN
nsn Unavailable	REFERENCE DOCUMENT	31414		E LINE	_	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE	NONE
MBER LINE NONE	282	\$		SYS CODE	AT025	AT026	AT027	AT028	AT029	AT030	331	AT032	AT033	AT034	AT035	AT036	AT037	AT038	AT039	AT040	AT041	AT042	AT043
2	WGT			SY	AT	¥	AŢ	AT	Ä	AŢ	AT031	AT	AT	AT(	AT	AT	AŢ	Į	AT(	AT	AT	AŢ	AT
CONTROL NUMBER FUGGES SYSTEM CODE LINE ATGE NONE	Z.		-																				

# Appendix Sets, Kits, and Outfits (SKOs) by Line Item Number

킠	NABICATIAL	WALAGE/PHASE	Materia	<b>121</b>	Ħ	뜅	XX.	<b>Shi</b>	<b>E</b> i
A20246	ADBIRISTRATIVE CONTROL CENTRAL: AAVTSG-79	120 VAC, 1 PH	ZH 09	3.88	25.000	=	=	2. <b>8</b>	8.
	HOTE: FOWER EXCLUDES 1-18000 BTV A/C.								
A2888	AIR DEFENSE SYSTEM GUIDED MISSILE: AN/150-73 BATTALION	120/208 VAC, 3 PH	400 HZ	20.000	<b>8</b> 2.	>	=	2.8	8
	MOTE: PRIMARY POWER CONSUMER 15 56/06 VZ MOTOR GENERATOR SET.	INCLUDES 6.5 KW A/C. NSN 1425-01-023-6141 DELETED PER SB 700-20 APPENDIX E 88246	R 58 700-20 APPENDIX E 88245.						
A28874	A28674 AIR DEFENSE SYSTEM QUIDED MISSILE: AN/TSG-73 GAOUP	120/208 VAC, 3 PH	400 HZ	20.000	<b>82</b> .	>	=	2.900	8.2
	NOTE: SEE LIN A20000. NSN 1425-01-130-2230 DELETED PER SB 700-20 APPENDIX E 08245.	IO APPENDIX E 00245.							
A100	INDIA SET: ANTPO-37(V)1	120/206 VAC, 3 PH	400 HZ	<b>46</b> .000	133.400	*	*	2.000	8.
	HOTE: 115/200 VAC. POWER EXCLUDES 6000 8TU A/C. A 60 KM GEN S	A 80 KW GEN SET AUTHORIZED SEPERATELY.							
911796	BOTTLE CLEANING-CHANGING STATION: ANJTAN-4	120/208 VAC, 3 PH	60 HZ, 50 HZ	7.200	32.200	*	=	2.900	8.
	MOTE: POWER EXCLUDES 2-18080 BTV A/C (ONE FOR SHELTER, ONE TO C LISTED, RAW 1 AT A THEE) (5 KB, 3 PA), AIR PURIFICATION U PER PANSE COMBINES 3 PM LOND AND LANGEST 1 PM LOND. AND	(ONE FOR SHELTER, ONE TO COOL COMPRESSOR). POWER HICLUDES COMBINATION OF SELECTED COMPONENTS: 5 HP COMPRESSOR (2 3 Ph), air purification unit (.3 km compressor). 5 km blomer), lights (.24 km), sonic generator (1.15 km). Amps D langest 7 Ph load. Add Poc-John McKenny, Wicchi, (205)887-1075.	TED COMPONENTS: 5 MP COMPMESSI , Somic Generator (1.15 kg).	22 K2					
200	BIBGAB BAKERY PLANT TRAILER WOMITED: LESS POWER	120/208 VAC, 3 PH; 120 VAC, 1 PH; 240 VAC, 1 PH	50 HZ	37.650	108.400	=	=	2.000	8
	NOTE: POURS DOWN BY DISTRIBUTION PAREL ON MIXING TRAILER AND THEN DISTRIBUTED TO SUBELENENTS. POURS INCLUDES COMPINATION OF SELECTED COMPONENTS: LIGHTS (1.4 KBT), BACERY OPEN (22.5 KB, 3 PM), MIXING TRUR (7.5 KB), SIFTEN (.25 KBT), PROOFING CARNIENT (6 KBT). SOUNCES: MIKE SONDAM (SIFTER FAMBLELL-NDSS, (219)424-3434; TOWY MAKSON (ALL OTHER COMPONENTS), CAM HOUSTRIES, (206)251-4310.	EL CHI BIXING TRALLER AND THEN DISTRIBUTED TO SUBELENENTS. PONEN INCLUDES COMBINATION OF SELECTED CONFORENTS: 2.6 kg, 3 pm), bixing trar (7.5 kg), sifter (.25 kg), proofing cabinent (6 kg). Sources: bixe scandan (sifter), It wason (all other components), can industries, (206)251-0310.	NATION OF SELECTED CONFONENTS Sources: Nike Schimma (Siff)	<b>£</b>					
23023	BATH UNIT POSTABLE: GED & SH LESS POWER	120/208 VAC, 3 PH	50 HZ	0.850	2.640	=	=	2.900	8
	MOTE: FORMER HICLORGS COMBINATION OF SELECTED CONTONENTS: BLOWER AND FIEL PARP ELECTRIC MOTOR - 120/2004, ADVZ, 3PH., 33MP; 120/2004, ADVZ, 3PH., 130MP; AND CONVERSION FACTOR OF 756 MP PER KR.	I AND FUEL FUAMP ELECTRIC MOTOR - 120/2004,6042,3PH,) Di conversion factor of 756 MP Per Kri.	ISHP; MATER MARP ELECTRIC MOTOR	<b>5</b>					
19884	DATTENY CONTROL CENTRAL: 60/1060 BISSILE SENITRALLEN BTO (PII)	120/208 VAC, 3 PH	80 MZ, 50 MZ	25.600	<b>8</b> .90	=		2.98	8.
	NOTE: POWER INCLNOES 3-18,000 BTU A/C, POWER SUPPLY (PP6224A/V)	FOUEN SUPPLY (PPG224A/V), AND COMBINATION OF SELECTED COMPONENTS.							
36178	BLOWER ELECTRIC PORTABLE: AC OC 115 V 60 CY 1 PH WANDBER NOZZLE 129 VAC, 1 PH, 28 VOC		80 HZ, DC	0.466	5.00	-	=	2.80	8.
	NOTE: NAJOR FONER CONSUMER IS 1/2 MP ELECTRIC NOTOR. ALTERNATE	ALTERNATE SOURCE: BILL GASTON, POLAN WEED EATER, (316)607-0100.							
21.000	BOOTH SPRAYING: BEICH TYPE	120 W.C. 1 PN; 120/200 W.C. 3 PN; 240/416 W.C. 3 PN 00 HZ, 50 HZ		0.230	2.000	=	*	7.000	8
	WITE: 115 WIC OR 238/460 WIC. INMERACIUMEN INDICATED 1/4 HP INDION FOR SPINY BOOTH.	OR FOR STANY BOOTH.							

3	MANAGE	VOLTAGE/PHAGE	ABBILLY.	21		¥	WE!	썲	<b>X</b>
C17869	CENTRAL OFFICE TELEPHONE AUTOMATIC: MA/TTC-29 300 LINE	120/206 VAC, 3 PH	60 HZ, 50 HZ, 400 HZ	13.30	38.500	=	~	2.000	8
	MITE: FORER EXCLUDES 2-18000 STV A/C. FORER HICLIDES CHIBINATION OF SELECTED CHIPONERTS. ASSUMES 3 PM PALANCHIS DUT TO A/CS.	ION OF SELECTED CONFONENTS. ASSUMES 3 PH PALANCIA	16 DUT TO A/Ca.						
C17867	CENTINAL OFFICE TELEPHONE AUTOMATIC: ANJTIC-39 600 LINE	120/208 VAC, 3 PH; 120 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	<b>38</b> .700	300	=	-	2.88	8
	NOTE: 115 OR 208 VIC. POWER EXCLIDES 4-18000 BTU A/C AUTHORIZED SEPARATELY. POWER INCLUDES 2-18464 BTV A/C. ASSUMES 3 PH BALANCING DUE TO A/Cs.	ED SEPARATELY. POWER INCLUDES 2-18456: 9TV A/C. /	ISSUMES 3 PH BALANCING DUE TO A/C	<b>ni</b>					
C3	COUNTENEASURE SET SP: AN/TLO-17A(V):	120/208 VAC, 3 PH	60 HZ, 400 HZ	3.000	8.300	=	2	2.000	8
	MOTE	•							
C32871	C22871 CLEMER ULTNASONIC: 120/230V 50/80 CY KZ 23.75X17.75X31 IN 18 GAL	23.75K17.75K31 IN 18 GAL 120 VAC, 1 PH; 240 VAC, 1 PH	80 HZ, 50 HZ	1.800	15.000	=	7	2.000	8.
	HOTE: LIK 215166 CHANGED PER SB 700-20 APPENDIX E 88245.								
2000	CA1061 CENTRAL MESSAGE SHITCHING AUTOMATIC: ANJTYC-39 25/50 LINE	120/208 VAC, 3 PH; 120 VAC, 1 PH	60 HZ, 50 HZ	20.800	300	=	-	2.990	8.
	HOTE: POWER EXCLUDES 4-18000 BTV A/Cs (A24463).								
280164	COMBUNICATIONS CENTRAL: MI/TSC-99	120/208 VAC, 3 PH; 120 VAC, 1 PH; 240 VAC, 1 PH	60 KZ, 50 HZ	37.400	104.000	=	~	2.000	8
	NOTE: 41-63 HZ. AND'S SUMED FROM TRANSMIT (88 AND'S) AND RECEIVE (36 AND'S) SHELTERS.	/E (36 AMPS) SHELTERS.							
C90363	COMMENICATION RELAY GROUP: GUIDED MISSILE SYS TRUCK MOUNTED	120/208 VAC, 3 PH	2H 007	19.000	52.800	<b>&gt;</b>	2	2.000	8
	HOTE: POWER INCLUDES 1-18000 BTU A/C (A34870) AUTH WITH SET.								
CB0572	C80572 COMMUNICATIONS TERMINAL: AN/TSC-87 LESS POWER	120 VAC, 1 PH; 240 VAC, 1 PH	80 HZ, 50 HZ	3.300	30.000	=	2	2.000	8
	HOTE: 110 OR 220 VAC. ADD SOURCE-GORDON BUCKNER, ESL INC., (408)738-2888.	38) 738-2888.							
C80754	COMBUNICATIONS TERMINAL: AN/TSC-108	120/208 VAC, 3 PH	50 HZ, 50 HZ	27.000	75.000	=	~	2.000	8.
	HOTE: FOWER INCLUDES 2-18,000 STV A/C.								
C78592	CENTRAL OFFICE TELEPHONE AUTOMATIC: ANYTIC-41(V)1 LESS POWER	120 VAC, 1 PH	80 HZ	5.100	44.300	*	~	2.000	8
	MOTE: 115 VAC. POWER INCLUDES 1-8000 BTU A/C (A23887) AUTH WITH SET.	TH SET.							
C78660	C78660 CENTRAL OFFICE TELEPHONE AUTOMATIC: ANVITC-41(V)5 LESS POWER	120 VAC, 1 PH	S0 H2	2.100	17.500	=	7	2.06	8.
	NOTE: 115 VAC.								

		18/21/21							
3	KORECATINE	WA IMELINASE	PROJECT			E	I I	<b>36</b> 1	<b>X</b> I
C78728	CENTRAL OFFICE TELEPHONE AUTOMATIC: ANVITC-41(V)6 LESS POWER	120 VAC, 1 PH	ZH 09	1.136	9.80	*	=	2.000	8.
	NOTE: 115 VAC.								
C7879S	CENTRAL OFFICE TELEPHONE AUTOMATIC: ANVITC-41(V)2 LESS PONER	120 VAC, 1 PH	60 HZ	6.200	45.200	*	=	2.900	8.
	115 W.C.								
C78796	CENTINAL OFFICE TELEPHONE AUTOMATIC: AN/TTC-41(V)? LESS PONER	120 VAC, 1 PH	ZH 99	25	9.900	*	=	2.000	8.
	101E: 115 W.C.								
C78861	CENTINAL OFFICE TELEPHONE AUTOMATIC: ANVITC-41(V)3 LESS PONER	120 VAC, 1 PH; 240 VAC, 1 PH	ZH 09	1.880	23.300	*	=	2.000	0.70
	HOTE: 115 W.C.: POWER EXCLUDES 1-6000 STU A/C (A23867). POWER OPENATION OF POWER SUPPLY.	000 BTU AJC (A2367), POWER INCLUDES THREE SB-3614 (.57 KW EACH). POWER CALCULATION INCLUDED 10% FACTOR FOR	ITION INCLUDED 10% FACTOR FOR						
C78829	CYBECO CENTRAL OFFICE TELEPHONE AUTOMATIC: ANVITC-41(V)4 LESS POWER	120 VAC, 1 PH	60 HZ	4.400	36.700	=		2.000 1.00	8.
	HOTE: 115 MAC. POWER EXCLUDES 1-8000 STU A/C (A23887).								
C78000	COLLECTIVE PROTECTION EQUIPMENT: NOC SINPLIFIED NZO	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	1.500	12.500	*	=	2.000	98.0
	HOTE: POWER HACLIDES 2 VACUUM PAMPS, AND 6 THERMISTORS ADDED TO DELAY HARISH.	DELAY INNUSA.							
CESSIS	CHIEDA SECTION TOPOGRAPHIC REPRODUCTION SET: SENITRAILER MOUNTED 120/208 VAC, 3 PH	120/208 VAC, 3 PH	80 HZ, 50 HZ	0.200	18.800	*	-	2.000	0.85
	HOTE: POREN EXCLUDES 2 A/Co ANTH SEP. POREN INCLIDES COMBINATION OF SELECTED COMPONENTS: LITHO COPYING CANERA (6,72 KM) AND 12 FLUORESCENT LIGHTS (.48 KM).	ON OF SELECTED COMPONENTS: LITHO COPYING CANERA (6.	.72 KW) AND 12 FLUONESCENT LIGH	5					
002464	DETECTION SYSTEM SPECIAL PURPOSE: AN/TSO-114	120/200 VAC, 3 PH	400 HZ	83.100	231.000	=	=	2.000	8
	WITE: POURS EXAMPLES 5-3000 BTV AVCs, ONE FOR EACH OF THE 5 SKELTERS. POURS INCLUDES COMBINATION OF SELECTED COMPONENTS: 2-ANVTSQ 138 (18.3 AM EACH) AND 3-ANVTSQ 139 (18.5 AM EACH).	ELTERS, POWER INCLUDES COMBINATION OF SELECTED COMP.	MENTS: 2-AN/TSQ 138 (18.3 KW E	(HOM					
151920	DES GENERAL DENTISTRY FIELD:	120 VAC, 1 PH	60 HZ	1.36	11.700	=	=	2.000	8.
	MITE: FOWER INCLUDES COMBINATION OF SELECTED COMPONENTS: COMPRESSION/DEPTORATION (1.1 KB), LIGHTS (.15 KB), AND ANALGAMATOR (.1 KB).	RESSION/DEHTDRATION (1.1 KB), LIGHTS (.15 KB), AND A	INLEMENTOR (.1 KD).						
822880	DES DENTAL MINIEUST FIELD:	120 VAC, 1 PH	50 HZ	1.650	15.400	₹.	*	2.000	8.
	THE STREET STREET STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STREET, STRE	TE. CHIEDERSON MENYBATTIO (1 2 KM) AND 1 (RM SET (15 KM)	15 100).						

3	MARICATIVE	VC, TAEL PHASE	CHERENCY		1	Z VE		Shi	<b>E</b> i
077682	077682 DATA AMALYSIS CENTRAL: AK/TYK-10A	120 VAC, 1 PH	5H 45	0.80	7.300	=	=	2.800	8
	NOTE: 110 VAC.								
217770	077712 DATA AMALYSIS CENTRAL: AN/TYG-5/V/3	120/206 VAC, 3 PH	<b>6</b> 0 HZ	9.500	4.500	*	*	2.000	8
	NOTE: 110/208 VAC. POWER EXCLUDES 18000 8TU A/C (LIN A24465) AUTHORIZED SEPARATELY.	WINCRIZED SEPNATELY.							
011780	DATA AMALYSIS CENTRAL: AN/TYG-5/V/4	120/208 VAC, 3 PH	50 HZ	0.500	4.500	=	=	2.600	8.
	NOTE: 110/208 VAC. POWER EXCLUDES 18000 BTV A/C (LIN A24455).								
077886	CENTER COMMUNICATIONS PATCHING: AN/TSC-76 LESS POWER	120 VAC, 1 PH	60 HZ, 50 HZ	0.740	6.200	*	*	2.000	8.
	NOTE: 115 VAC. POWER EXCLUDES 1-6000 BTU A/C (A23701-1.4 KM) AUTH SEP.	WTH SEP.							
078075	DATA PROCESSING SYSTEM AUTOMATED: AN/MYO-4	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	9.30	61.800	=	=	2.000	9.0
	MOTE: 110 GR-220 VAC. POWER EXCLUDES 4-18000 BTU A/Cs.								
078271	CENTER MESSAGE: ANJOSO-BO LESS POWER	120 VAC, 1 PH	50 HZ, 50 HZ	2.000	17.400	*	*	2.000	8
	MOTE: 115 VAC.								
078325	DATA PROCESSING SYSTEM: AN/MYG-4A	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	10.500	103.400	=	~	2.000	98.0
	NOTE: 110 OR 220 VAC. POWER EXCLUDES 4-18006 BTV A/Cs. POWER INCLUDES COMBINATION Equip, and 6 disk drives. Add Source-Tom Maxinley, PM CTASC, (703)664-1881.	N OF SELECTED COMPONENTS:	COMPUTER, TAPE DRIVE, PRINTERS, COMIC						
078523	CENTRAL OFFICE TELEPHONE AUTOMATIC: AM/TTC-38(V): LESS POWER	120/208 VAC, 3 PH	60 HZ, 50 HZ, 400 HZ	2.400	9.600	*	=	2.000	8
	NOTE: 115 VAC. PCYER EXCLUDES 18000 BTU A/C AUTH SEPARATELY. Assumes 3 PH Ballancing due to A/C.	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS THAT ARE ALL SINGLE PHASE CONSUMERS	WT ARE ALL SINGLE PHASE CONSUM	S.					
D78524	CENTRAL OFFICE TELEPHONE AUTOMATIC: AN/TTC-38(V)2 LESS POWER	120/208 VAC, 3 PH	60 HZ, 50 HZ, 400 HZ	2.800	7.600	=	<b>2</b>	2.000	8.
	NOTE: POWER EXCLUDES 18000 BTV A/C AUTH SEP.	,							
D78907	DJ8907 CENTRAL OFFICE TELEPHONE MANUAL: ANVINTC-1 LESS POWER	120 VAC, 1 PH	60 HZ, 50 HZ	9.20	44.800	*		2.000	8.1
	NOTE: 115 VAC. POWER EXCLEDES 9000 BTU A/C AUTH SEP.								

3		VOLTARE/PMSE	REWIE		<b>N</b>	뾝	WEI	wi	<b>t</b> ti
079818	D78518 CENTRAL OFFICE TELEMONE MANUAL: ANATIC-8 LESS POWER	120/208 VAC, 3 PH	90 MZ, 50 MZ	9.100	28.30	=	=	2.80	8
	MOTE: 115 W.C. POURR EXCLUDES 2-18000 BTU A/Cs (A24044). ASSUMES 3 PH BALANCING DUE TO A/C.	SSUIES 3 PH BALANCING DUE TO A/C.							
244	CENTRAL OFFICE TELEPHONE MANUAL: AN/TTC-23 LESS FORER	120 VAC, 1 PH	60 HZ, 50 HZ	2.700	23.700	=	-	2.800	8
	MOTE: 115 VAC. POWER EXCLUDES 8000 BTU A/C AUTH SEP.								
24 A	CENTRAL OFFICE TREEPHONE IMMINAL: ANVTTC-29 LESS POWER	120 VAC, 1 PH	50 HZ, 50 HZ	3.78	27.300	#	#	2.000	8
	MOTE: 115 W.C.								
194610	CENTRAL OFFICE TELEPHONE MANUAL: AN/TTC-36(V) 1 LESS PONER	120 VAC, 1 PH	60 HZ, 50 HZ	2.100	16.300	=	=	2.000	8
	1011 116 WC.								
	CENTINL OFFICE TELETIFERITER: ANTIC-30 LESS FOURS	120 VAC, 1 PH	50 KZ	2.900	25.200	*	=	2.000	8.
	MOTE: 115 VAC. POWER EXCLUDES 1-6,000 BTU A/C (A23647).								
D88676	DOOFTS CHANGER RECOMPRESSION DIVERS: 100 PS!	240 VAC, 1 PH, 28 VDC	90 HZ, DC	2.300	14.200	=	*	2.900	8.
	MITE: 220 W.C. OR 24 VOC. POMER INCLUDES HEATER/COOLER UNIT (10 AMPS), CO2 SCRUBBER (3.7 AMPS) AND COMMUNICATIONS/LIGHTING (.5 AMPS) GEAR. ADD SOURCE-COD JOHN VIEW, ENDS SCHOOL, (703) 844-4585.	(10 AMPS), COZ SCRIBBER (3.7 AMPS) AND COMMUNICATIONS	S/LIGHTING (.5 AMPS) GEAR. ADD						
006343	DEHTAL EBUINDENT SET DEHTAL SUPPORT:	120 VAC, 1 PH; 240 VAC, 1 PH	90 HZ	1.350	11.250	=	=	2.000	8.
	NOTE: 120 OR 230 W.C. POWER BASED ON STRBLE LANGE CONSUMER (STERILIZER, 1.36 KB)	(STERILIZER, 1.36 KM).							
280283	ELECTROPIC SHOP SENITRALLER HOURTED: ANVALIN-153	120/208 VAC, 3 PH	80 HZ	31.300	87.000	=	-	35	8
	MOTE: THIS SIND PULLS AN AVENUE OF 89 ANTS (INIX 87 ANTS) PER PHASE.	PHASE.							
E0000	ELECT PROCESSING AND DISSEMENTION SYS: AN/150-184 (V) 1	120/208 VAC, 3 PM	SO HZ	190.000	100.000 278.000	=	=	2.000	8.
		,							
E00407	ENEMBEERT CONTROL STATION GH: TRUCK INTO ANAISO-104 (PATRIOT)	120/208 VAC, 3 PM	400 HZ	35.000	97.300	<b>-</b>	=	2.000	8.
	WITE: FUNEN INCLUDES 2-18000 BTV A/Ca (A34670) AUTH WITH SET.								

3	STATE AT VE	VALTAEL/PAGE	FEMELT	21	<b>2</b>				<b>W</b> .
E2 1880	BRECTON LANCHER GAIDED MISSILE SEATTMILER ATD: (PERSHING 11)	120/208 VAC, 3 PH	90 HZ, 60 HZ		<b>8</b>	=	~	2.000	8.
	MITE: FORER HICLIDES CONTINUTION OF SELECTED CONFORENTS: EN	ERECTOR/LAWCHER POWER SUPPLY, MISSILE POWER SUPPLY, MISSILE, LCA, AND PCA PANEL	SILE, LCA, AND PCA PAMEL						
E4081	CLOTHING REPAIR SKOP: TRLA BTD 2 WAL LESS POWER	120 VAC, 1 PH	2H 99	<b>8</b>	3.5	-	2	2.88	8.
	METE: 116 VIC. FORER HICLIDES COMPINATION OF SELECTED COMPONENTS: SERVING MICHINE (. 33 HP). AND NEAVY DATY SERVING MICHINE (. 33 HP).	EOTS: SERVING MACKVINE (.25 HP), DARWING MACKVINE (.26 MP), TEXTVLE SESTVING INCOVINE (.25 MP). Bring wichine (.30 HP).	HP), TEXTILE SESPING INCHINE (.	<b>\$</b> 2					
ESAZSA	COMMUNICATIONS CENTRAL: ANVIRC-30 LESS PONER	240/416 VAC, 3 PH	2H 00	88.	<b>36</b> .000	-	-	2.000 1	8
	NOTE: EXCLUDES POWER FIRD MEATERS AND A IR CONDITIONERS. 3 - 180,000 BT 310-34. A/C POWER 8.000 (3.2 PER A/C UNIT). HEATER POWER 6 KM.	AND AIR CONDITIONERS. 3 - 180,000 BTU AIR CONDITIONERS (LIN AZ4044) ANE AUTHORIZED SEPERATELY ACCORDING TO AN .2 per a/c unit). Heater power 6 km.	ED SEPERATELY ACCORDING TO AR						
E69631	EBASSI COMMUNICATIONS CENTRAL: AN/TSC-38 LESS POWER	120/208 VAC, 3 PH; 120 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	90.09	214.000	=	7	2.000 0	35
	NOTE: FOWER INCLIDES 2-18000 BTV A/Cs (A24682) (1 A/C FOR EACH OF TWD SHELTERS).	H OF TWO SHELTERS).							
E00194	COMMUNICATION TECHNICAL CONTROL CENTER: AN/NSQ-73	120/208 VAC, 3 PH	2H 08	2.400	6.700	*	2	2.000	8
	NOTE: POWER EXCLUDES 2-18000 8TU A/Cs AUTH SEP.								
E8018)	COMMUNICATIONS TECHNICAL CONTROL CHITER: AN/158-64 LESS POWER	120 VAC, 1 PH; 240 VAC, 1 PH	2H 98	9. 18	70.400	=	7	2.000 1	8
	NOTE: 116 OR 230 VAC. POWER HICLUDES 2-9000 BTU A/Ca (A23988)								
E06325	CONTROL CENTRAL OPERATIONS: AN/TSO-78	120 W.C. 1 PH	60 HZ, 50 HZ	.8	10.000	=	7	2.000.1	8
	HOTE: 110-180 W.C.								
EB1476	E87476 CONTROL-TEST-4M INTERNANCE GROUP: CK-287/TTC-38	120/208 VAC, 3 PH	60 NZ, 50 NZ, 400 NZ	2.000	9.800	*	2	2.000	8
	MOTE: 115 VAC. POWER EXCLUDES 1-4000 BTU A/C AUTH SEP. ASSUMES 3 PH BALLANCING DUE TO A/C.	NES 3 PH BALANCING DUE TO A/C.							
F20404	COUNTERMEASURES SET: AN/61.0-3 LESS POWER	120/208 VAC, 3 PH	400 HZ	8.400	23.300	=	2 H	2.000	8
	HOTE: POWER EXCLUDES 6000 BTV A/C AUTH SEP. MAJOR POWER CONS	MAJOR FOWER CONSUMER IS RADIO FREQUENCY CONTROLLER-TRANSMITTER.							
F21088	COUNTERIEASINES SET: AN/TLA-15 LESS POWER	120/208 VAC, 3 PH	ZH 907	10.000	27.800	=	2	2.000	8
	MUTE: POWER INCLUDES 1-60000 BTU A/C.								

MEN COMPANIED DATABASE (Pertial Data) 12/12/41

=			WOLTARE/PAGE	Residency	•	1	¥	<b>%</b>	*	¥
F2198		COUNTEMEASURES SET: AV/TLG-17	120/206 VAC, 3 PH	ZH 900	3.00	35	=	=	28	8
	Ë	115 W.C. THIS SET CONSUMES APPROXIMATELY SAME POWER AS AN/TLG-17A.	AVTLG-17A.							
74000		CHUSH AND SCREEN PLANT: DOL AND ELEC DRAW WAL HTD 76 TPH (AMEN')	240/416 VAC, 3 PH; 120/206 VAC, 3 PH	ZH 00	190.90	131.000	=	-	2.900	6.70
		220/440 VAC. FORER INCLUDES HP MOTORS).	COMBINATION OF SELECTED COMPONENTS: PRIMARY CRUSHER (10 HP MOTORS, 8 EA), SECONDARY CRUSHER (15 MP, 10 MP, AND 5	DIDARY CRUSKER (15 MP, 10 MP, A	<u>.</u>					
F49673	26 HSH 50	F48673 CNUSH SCREEN AND WISH PLANT: DSL/ELEC DRAW WHL WTD 2251794	120/206 VAC, 3 PH; 246/416 VAC, 3 PH	90 HZ	73.006	238.000	=	=	2.000	38
	Ë	NATED FOUER IS DERIVED FROM	SC 3829-98-CL-E04 FOR THE CRUSHER'S POWER DISTRIBUTION PANEL.							
13.00E	CNUSIER	F51064 CNUSHER RING TYPE: CAP TPN 2-1/2-8-1/2 HP 56/75 900APH 57	120/208 VAC, 3 PH; 240/416 VAC, 3 FH	5H 99	98.000	228.000	=	*	2.000	35
		POWER BASED ON SELCTING LANGEST ELECTRIC NOTOR (75 MP).								
F56700	FIRE DIA	FINE DIRECTION CENTER ARTILLERY: OA-4380/656-10V LESS POWER	120/208 VAC, 3 PH, 28 VDC	400 HZ, DC	18.700	90.00	=	*	2.000	8.
	ij	POWER INCLUDES 2-18000 8TV A/Cs (A24578).								
F78771	FLIGHT L	F76771 FLIGHT LINE TEST SET: ANVARM-163(V)3	120/208 VAC, 3 PH	ZH 98	3.200	26.700	*	-	2.000	8.
	110									
F77627	DATA ABA	DATA AMALYSIS CHITIMA: AM/TYK-11	120 VAC, 1 PN	80 HZ, 50 HZ	7.500	<b>3</b>	=	=	2.86	8.
FB3826	FIRE DIR	FB3828 FINE DINECTION CENTER ANTILLENY: OA-6300/0556-10V LESS POWER	120/208 VAC, 3 PH	400 HZ	15.000	41.700	=	=	2.800	8
	ä	POWER INCLUDES 18000 BTU A/C (A24675) AUTH SEP.								
F96604		obital instrument and supply set brencency theathent field:	240 VAC, 1 PH; 120 VAC, 1 PH	60 HZ, 50 HZ	43.000	188.000	=	=	2.60	8.
		116 OR 230 MG. SURGE FACTOR FOR X-NAY INCHINE CAN DE AS HIGH AS 100, BUT, DNE TO SHORT DUNATION, IS REGARDED AS HISTMITANCOUS. COMBINATION OF SELECTED COMPONENTS: FOUR COMPRESSON BUTIONS (1.1 KM (8 EA) AND 1.7 KM), X-RAY INCHINE (38 KM), AND LIGHTS (1.15 KM	IS HIGH AS 100, BUT, DUE TO SNORT DURATION, 1S REGARD ONS (1.1 FOR (8 EA) AND 1.7 FOR), X-RAY INACHINE (38 FOR	REGARDED AS INSTANTAMEDUS. PONER INCLUDES (38 KB), AND LIGHTS (.15 KB).	SOUTH					
112/09		807211 GIB-SUPLY OFFICE AND PACKAGINS/PRESERVATION SINP: (PERSHING)	120/200 VAC, 3 PH	2H 96	3.820	10.900 · M	=	=	2.000 1.00	8

POWEN EXCLUSES 2-18000 BTU AVEA AUTH SEP. POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: OVEN/FAN (1.2 KW), SVC OUTLETS (2.1 KW), AND LIGHTS (.42 KW). Ë

		18/21/21							
3		WATAELTHAR	FEBRUAY.		Ħ		W.	Wei	點
<b>6466</b> 22	GEDIDED BHSSILE PLATODN CONTROL CENTRAL: (MEISHING 11)	128/208 WC, 3 FH	2N 909	12.600	# T	*	=	2.600	8.
	NOTE: POWER INCLUDES 2-18000 BTV A/CS (0.6 KW). POWER INCLUDES POWER SUPPLY, AND RADIOS.	POWER HICLIDES COMBINATION OF SELECTED CONTOUGHTS: CILL AGENT ALANI, MENDTE LAUNCH CONTROL UNIT,	III, MENDTE LAUNCH CONTROL UNIT,						
986786	GUIDED BISSILE SYS: NEPAIR PARTS SKOP SEBITIALLER WITD (PERSKING) 120/206 VAC, 3 PK	20/208 VAC, 3 PK	60 HZ, 50 HZ	14.400	90.00	=	=	2. 86.	8
<b>3</b>	ELECTRONIC ENVIRABRIT CALIBRATION STANDANDS SET SECONDARY REF:	129/200 VAC, 3 PH	ZH 98	18.500	137.000	=	=	2.000	8
	WITE: MOVER EXCLIDES 30000 BTV A/C AUTH SEP. MOVER NEGLINBHENT	AUTH SEP. POWER REQUIREMENT DERIVED FROM BITCOM POWER SURVEY.							
201	ELECTRORIC SHOP SERITTALLER MOURTED: AN/ASM-100 LESS POUER	120/206 MAC, 3 PM	2H 08	18.200	200.20	=	=	2.86	8
	NOTE: POWER EXCLUDES 2-18000 BTV A/Cs (A24181).								
101857	ELECTRONIC SIND SENITRALLER MOUNTED: ANVASH-190 LESS PONER	120/208 VAC, 3 PH	5H 69	20.800	76.400	=	-	2.00	8.
	WITE: POUGH EXCLUDES 18000 BTV A/C (4.8 KB). FOUR? INCLUDES COMPINATION OF SELECTED CONFOURITS: EDWAY FLOOR, IGHTS (.66 KB), AND INTERNITIENT USE OF POUGH SUPPLY, NOTON GENERATOR, AND HEATERS (5 KB). OFFISET BY THE A/C REQUIREMENT.)			õ					
HD198	ELECTRONIC SNOP SNELFER: AN/TSN-126 LESS POWER	120 VAC, ? FR	2H 08	0.930	<b>8</b> . 100	*	*	2.000	8.
	MITE: POWER EXCLUDES 18600 BTV A/C (A2465). POWER INCLUDES CO. (.48 NW).	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: ANVANCE 44 (.25 KB), ANVIPICED (.2 KB), AND LIGHTS	), AN/TPX-50 (.2 KB), AND LIGHT	χ.					
<b>10190</b> 7	HO1907 ELECTRONIC SHOP SHELTER HOUNTED AVIONICS: ANJASH-146 LESS POMER :	120/208 VAC, 3 PH	ZH 09	5.50	16.700	-	*	2.000	8
	NOTE: POWER HIGHDES CHRIMATION OF SELECTED CHIPOLENTS: 9000 B)	SELECTED COMPONENTS: 9000 BTU A/C (A23907) (1.8 KM), AN/GAC-106 (2.5 KM), 2 PU PAD10S (.56 KM), AND LIGHTS (.6	MADIOS (.56 KB), AND LIGHTS (.8						
H01912	HOIDIZ ELECTRONIC SHOP SHELTER NOUNTED AVIONICS: ANJASH-147 LESS POWER 1	120 VAC, 1 PH	ZH 99	3.710	32.300	=	=	2.900	8.
	MOTE: 116 W.C. POWER INCLUDES 1 DEMONICIFIER AND LIGHTS, PLUS TINCE USED IN THE SET, NO A/C.	DE USED III THE SET, NO JAC.							
760201	ELECTRONIC SIGN TRANSPORTABLE: AU/659-44 LESS POWER	120 VAC, 1 PM	<b>50</b> H2	3.86	8.8	#	-	2.000	8
	HOTE: 115 VAC.								
H02173	ELECTRONIC SHOP THANSPORTABLE: AN/6SH-236	120 VAC, 1 PH	24 98	5.99	25.50	=	-	2.000	8.
	<u>WIE:</u> 115 MC.								

3		WINETOWN	<b>ERRECT</b>				W		<b>E</b>
M14262	: ENECTION OUTFIT HIGH BOLTED STORMEE TANKS: STEEL STORMEE TANKS	120 WC, 1 PH	Z+ 09	9.80	6.670	#	-	7. 8	8.
	MILE								
##0CE	FACSIBILE RECEIVING CENTRAL: ANTXR-3	240 VAC, 1 PH	90 HZ	2.600	7.280	=	-	<b>3</b>	8
	NOTE: 208 VAC.								
J68150	INMERIY INTERPRETATION SYSTEM: ANJTYG-11(V)4 LESS POWER	120/206 VAC, 3 PH	SH 95	7.820	22.000	-	=	8	8.
	NOTE: POWER EXCLUSES 2-30000 BTV A/CA (A24000). POWER INCLUDES COMBINATION OF SELECTED COMMUNICATIONS EQUIPMENT LOCATED IN THD SPELTERS (ONE INTERPRETATION, ONE AUXILLARY).	COMBINATION OF SELECTED COMMUNICATIONS EQUIPMENT LO	CATED IN TWO SPELTERS (ONE						
362250	JAZZEG INFORMATION AND COORD CENTRAL: 6 SYSTEM MAJEG-116 (PATRIOT)	120/206 W.C. 3 PH	400 HZ	# . # . # . # . # . # . # . # . # . # .	<b>3</b> .700	<b>&gt;</b>	-	2.86	8:
	HOTE: POWER INCLUDES 2-18000 BTU A/C (ASA470) AUTH 21TH SET.								
K26215	. WIR HOT OIL TRUM MOUNTED: ELECTRIC POWERED 21000000TU CUTPUT	120/206 VAC, 3 PH; 240/416 VAC, 3 PH	60 HZ, 50 HZ	12.500	70.900	=	-	2.8	9.8
	HOTE: EFFICIENCY FACTOR FOR CALCULATION OF NATED POWER (RP) ASSUMED TO BE 0.7. RP = {10HP (BLOWER, PLUP AND CONTINUL)/1.74.85)}x.746 = 12.59 NB	NAMED TO BE 0.7. RP = [10HP (BLOWER, PLAIP AND CONTING	L)/(.)x.85)}x.746 = 12.53 tm.						
KB2206	I INFORMATION AND COORDINATION: CENTRAL QUIDED MISSILE SYSTEM WHAT 240/416 W.C., 3 PM	240/416 W.C. 3 PM	400 HZ	22.000	38.86 8	<b>&gt;</b>	=	2.900	8.
	HOTE: POWER INCLUDES 1-1000 BTV A/C (AZAGAZ) ANTH WITH SET. ASSOCIATED WITH WHIK SYSTEM	SSOCIATED WITH WHAT SYSTEM.							
101326	DEBINERALIZATION EQUIP SET WATER ION EXCHANGE: TRLA NETD 2000 GAL 120/200 WC, 3 PH	126/200 VMC, 3 PM	7: 3	3.	11.400	*	#	2. 80	9.0
	MOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 2 PU	JF SELECTED COMPONENTS: 2 POMPS (2 HP), 1 POMP (1 HP), 1 POMP (0,5 HP), AND NEXTER.	<u>.</u>						
181	LISSIDA LABONATORY AIR HOBILE: AVIATION FUEL	120/208 VIC, 3 PH	50 HZ, 50 HZ	15.000	41.70	=	=	2. \$	8.
	MOTE: POWER INCLUDES 2-6000 BTV A/Ca.								
7380	LABONATORY PETROLEIM SENITMALER MOUNTED:	120/206 VAC, 3 PH	50 HZ, 50 HZ	5. 8	13.80	=	-	2. 8	8.
	HOTE: FOURE EXCLUDES 1-40000 BTU A/C (A25651).								
146757	LAMICHER ZERO LENGTH: QUIDED MISSILE (WMK)	240/416 WC, 3 PH	ZH 909	10.50	¥.	~	-	<b>3</b>	8
	WIE:								
£887	LAMINCHING STATION ON: SENI TRAILER MID (PATRIOT))	120/208 W.C. 3 PH	490 KZ	8	£.78	>	#	<b>8</b>	8

POWER COMMENTS DATABLES (Parties Data)

		12/12/91							
3		VICTARE PRIME					Z,		<b>a</b> ti
746318	I LANGORY WHIT TRAILER INDUSTED: SINGLE TRAILER 60 LS CAP	120/208 VAC, 3 PH	211 08	. E	3.8	=	=	 #	
	MILE PUREN HICLORS COMPINATION OF SELECTED COMPONENTS: COR. SESSON (2.6 AP), AND HYDRO-SHEME (1.6 MP).	IMANETIC VALVE (.064 KIT), 6 NOTONS (2 ANY, EACK), 1 NOTOR (1 MP), 1 NOTOR (12.8 ANY), AIR	OR (1 HP), 1 MOTOR (12.8 AMP), A	=					
	MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-670/ASM	28 VDC	8	9.124	\$	-	=	*	8
	WIE:								
<b>#</b>	MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-673/MPG-4	120/206 W.C. 3 PH	400 KZ	16.00	3.	=	=	2.8	8
	MOTE: FOWER INCLIDES COMMINATION OF SELECTED CONTONENTS: A KIT (16.7 AND), AND FOWER SUPPLY (7.1 AN).	ANTERNA POSITION SIBULATOR (.037 KM), 2 NOTOR GENERATORS (1 Nº AND 4 Nº), TEST FACILITIES	S (1 NP AND 4 NP), TEST FACILITI	83					
M01374	NO1374 INNINTENANCE KIT ELECTRONIC EQUIPMENT: INC-722/UNC	120 VAC, 1 PH	400 HZ	8	32.	=	-		8
	WIE:								
#81 <b>0#</b>	MOISTY MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-731/ANC-61X	28 VDC	8	. <del>.</del>	13.606	*	=	2.880	8
	MIE:								
3	MD1848 INNINFERNANCE KIT ELECTRONIC EQUIPMENT: INC-733/ARC-54	28 VDC	8	0.200	3.18	=	=	2.86	8.
	WOTE:								
ED1622	MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-774/APN-158	120 VAC, 1 PH	ZH 907	0.400	3.330	*	=	2.000	8
	NOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: D	SELECTED COMPONENTS: DEMANIET1ZER, LAMPS, PONER SUPPLY AND NETERS.							
M02013	UNINTENANCE KIT ELECTRONIC EGUIPMENT: MK-1004/ARC	28 VDC	2	0.112	4.000	=	=	2.000	8.
	<u>MOTE:</u> MAY CONSUME 3 TO 9 AMPS FOR RUMING. MAY CAUSE INTER Generator; therefore no v/Fi.	INV CONSIDE 3 TO 9 ANTS FOR PLANTING. INV CAUSE INTERFERENCE DUE TO RF SIGNAL. SINCE THIS IS MAINTENANCE ITEM, IT WOULD NOT REQUIRE SEPARATE GENERATOR), THEREFORE NO VFI.	BR, IT WOULD NOT REQUIRE SEPARAT	w					
MD2038	MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-1035/ARC-131	28 VDC	្ន	0.140	5.000	=	=	2.000	8
	WOTE:								
MD2108	MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-1961/U	120 VAC, 1 PH	2H 99	0.850	7.000	*	=	2.80	8.
	MOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DI	DEMACHITIZER, ELECTRIC (GIN-TYPE) HEATER, AND WIRE-WARPING POWER TOOL	ING PONEN TOOL.						

3	MARKETATUME	VALIME/PAME	<b>FREMENT</b>		Ħ	<b>#</b>	WEI E		
1120	MAINTENANCE KIT ELECTRONIC EQUIPMENT: MK-1962/U	120 VAC, 1 PH	5H 09	6.13	1.460	=	2.98	8	8
	NOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: SOLDE	SOLDERING 190M, DESOLDERING 180M, AND LIGHTS.							
90520	MAINTENANCE KIT ELECTRONIC MK-1902/NSQ-103:	120 VAC, 1 PH	400 HZ, 60 HZ	6.30	2.500	*	2.980		8
	NOTE: ONE ITEM 400 HZ; ONE ITEM 60 OR 400 HZ.								
MD3035	IM.INTEHANCE SHOP (ARF): AN/ARM-185	120/208 VAC, 3 PH	\$9 KZ	16.200	78.990	_	2.000		8
	WOTE:	•							
MD4268	NOOE INAVGEMENT SWELTER:	120 VAC, 1 PH, 28 VDC	80 HZ, DC	3.280	23.50	_	1 2.000		8
	MOTE: 115 VAC. TYPE CLASSIFIED FROM 246789.								
MD6138	MD8136 MAP LAYOUT SECTION: TOPO REPRODUCTION SET SENITRAILER MTD	120 VAC, 1 PH	40 HZ, 50 HZ	0.50	5.040	<b>=</b>	N 2.000		8
	NOTE: 115 VAC. POWER EXCLUDES A/CA AUTH SEP. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: EXWALST BLOWER (.1 KW) AND LIGHTING (.48)	MIBINATION OF SELECTED COMPONENTS: EXMANST BLOWER (.	1 KE) AND LIGHTING (.48).						
M20273	IZO273 IMINTEMNICE KIT ANALYTICAL PROGRAM POSTNG SYSTEM: INC2023/UNC-48 120 VAC, 1 PH	120 VAC, 1 PH	54 0 <del>8</del>	<b>X</b>	3.000	-	M 2.000		8.
	HOTE: POWER INCLUDES CONBINATION OF SELECTED COMPONENTS: TEST	OF SELECTED COMPONENTS: TEST CONNECTOR, 1/0 EXTENDER BOARD, AND TEST CONNECTOR ASSEMBLY.	SEMBLY.						
1782	NEDICAL EQUIPMENT SET CLEARING STATION:	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	7.20	37.700	**	2.6	2.000 1.00	8
	WITE: 115 VAC. POWER INCLUDES COMMINATION OF SELECTED COMPONENTS: REPRIGERATOR (.066 KM), X-RAY APPARATUS (8 KM), AND SIMK UNIT (1.266 KM).	KTS: REFRIGERATOR (.066 KM), X-RAY APPARATUS (3 KM)	AID SIKK UNIT (1.296 KB).						
24983	MEDICAL EQUIPMENT SET EPIDEMIOLOGY SERVICE FIELD	120 W.C. 1 PH	80 HZ, 50 HZ	9.6	<b>80</b> .400	-	5.0	2.000 1.	8.
	HOTE: POUR INCLUDES COMBINATION OF SELECTED COMPONENTS: REFRI	OF SELECTED COMPONENTS: REFRIGERATOR (.66 KM) AND STERILIZER (8 KM).							
129451	MEDICAL EQUIPMENT SET PHYSICAL EXMINATION FLIGHT SUNGEON:	120 W.C., 1 PH, 28 VDC	90 HZ, DC	9. 180	0.130	=		2.900 1.	8.
	MOTE. 116 VAC. POWER INCLUDES CHABINATION OF SELECTED COMPONENTS: PROJECTOR (.06 KB) AND ELECTROCARDIOGRAPH (.046 KB).	hts: projector (.06 kg) and electrocardiograph (.04)	5 (4).						
M29633	MEDICAL EQUIPMENT SET PATIENT HOLDING SQUAD FIELD LIGHTWEIGHT:	120 VAC, 1 PH; 240 VAC, 1 PH	80 NZ. S0 NZ	0.900	5.000		2.	2.000 1.	8
	HOTE: LIN 220633 WANDED PER SB 700-20 APPENDIX E 87244.								
<b>867003</b>	HEDICAL EQUIPMENT SET TRAINA FIELD (2):	120 W.C., 1 PH; 240 W.C., 1 PN	60 HZ, 50 HZ	9.00	<b>9</b> .000	=	~ =	2.000	8.
	NOTE: LIN 242360 CHANGED PER SB 706-20 APPENDIX E 64061.								

=

3			VALUE COME	PROBERTY.	Đi			A/Fi	<b>X</b>	
M46477		NEDICAL EQUIPMENT SET: IMMANUGY/SEROLOGY AUGMENTATION	120 W.C. 1 PH	60 HZ, 50 HZ	2.925	23.468	-	2.8	8	
		115 W.C. POWER REFLECTS C CERTRIFUCE (1.725 KW).	OMBINATION OF SELECTED COMPONENTS: 2 REPRIEDRATORS (.15 KW EACH), LIGHTS (.2 KW), 2 WATER MATHS (.25 KW EACH), AND	RATER BATHS (.35 KB EACH), A	ş					
846546		MEDICAL EQUIPMENT SET: LABORATORY VETERIUMRY AUGMENTATION	120 VAC, 1 PH	2H 08	<u></u>	17.280	*	2.600	8	
		WIE. 116 WG. FOWER REFLECTS COMPINATION OF SELECTED COMPONENTS: VACUUM FAMP (.06 KB), CENTRIFINGE (1.725 KB), AND LIGHTS (.2 KB)	IBITS: WICHUM PUMP (.08 KW), CENTRIFUCE (1.726 KW), AM	) LIGHTS (.2 td).						
1847187		MAINTENANCE KIT GROUP ELECTRONICEGUIPMENT: CA-0161/GRC-213	28 VDC	8	0.020	9.78	*	2.900	8	
		MOTE: 22-30 VOC.								
M17255		MAINTENANCE KIT GROUP ELECTRONICEQUIPMENT: OA-9183/GRC-192A	28 VDC	8	1.120	<b>40</b> .000	-	2.800	8. - 8	_
		22-30 VDC.								
M52524		MES CLEARING STAFION:	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	10.000	87.000	=	2.900	8.	_
		MOTE: POWEN WEVECTS GENERATOR SIZE. EQUIPMENT REQUIREMENTS EXCED GENERATOR CAPACITY. (EXAMPLE: 4 STENLIZERS 19 KM, 2 EACH; 1.4 KM, 2 EACH), X-RAY APPARATUS (2.3 KM), 3 SARGICAL SINKS (1.283 KM EACH), REFRIGERATOR (.345 KM).) CAMDIDATE FOR POWEN ASSESSMENT.	28. EQUIPMENT REQUIREMENTS EXCED GENERATOR CAPACITY. (EXAMPLE: 4 STERILIZERS 19 KM, 2   SYRGICAL SINGS (1,283 KM EACH), REFRIGERATOR (.345 KM).) CANDIGNTE FOR PRUER ASSESSMENT	I KNI, 2 EACH; 1.4 KNI, 2 EACH), ESSMENT.						
M52774		NES BNEHGENCY TREATMENT NEDICAL DETACNMENT:	120 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	3.015	26.200	-	M 2.000	8.	_
	E I	NOTE: 115 VAC. POWER REFLECTS COMBINATION OF SELECTED COMPONENTS: STERILIZER (1.4 KM), SURGIDAL SINK (1.265 KM), REFRIGERATOR (.15 KM), AND LIGHTS (.2 KM).	EHTS: STERLIZER (1.4 KB), SUNGICAL SINK (1.265 KB), R	EFRIGERATOR (.15 KB), AND 1.1GH	HTS					
ME 7460	HOB! LE	MOBILE AUDIO VISUAL UNIT: ANAISA-85 LESS POWER	120 VAC, 1 PH; 240 VAC, 1 PH	ZH 99	4.000	41.700	=	N 2.000	08.0	_
M79412		NES GEN CLINIC COMO TYPE 1:	120/208 VAC, 3 PH; 240/416 VAC, 3 PH.	60 NZ, 50 HZ, 400 NZ	12.320	34.000	=	R 2.000	90 -	_
	::	116 VAC. POWER REFLECTS CO (.15 KW EACH), AND LIGHTS (	MBINATION OF SELECTED CONFOMENTS: 2 STERILIZENS (9 KM AND 1.4 KM), 2 SANGICAL SINKS (1.266 KM EACH), 2 REFRIGENATORS .5 km). Assumes 3 Probalancing due to large 1 Proper Requirement. Candidate for poner assessment.	SURGICAL SINCS (1.285 KB EACH), 2 REFRIGERA CANDIDATE FOR FOLER ASSESSIBIT.	NTORS					
M79662		NES GEN CLINIC CONNY TYPE 2:	120/208 VAC, 3 PH; 240/416 VAC, 3 PH	60 HZ, 50 HZ, 408 HZ	17.530	13.200	=	2.000	8	_
		POWER REFLECTS COMBINATION OF SELECTED COMPONENTS: STERILIZER (9 KM), REFRIGERATOR (.15 KM), X-RAY APPARATUS (5 KM), X-RAY TANK (.7 KM), AND 1 SURGICAL SINK (2.63 KM), ASSUME 3 PH BALANCING DUE TO LARGE 1 PH POWER REQUIREMENT. CANDIDATE FOR POWER ASSESSMENT.	IILIZER (9 KM), REFRIGERATOR (.15 KM), X-RAY APPARATUS Jage 1 pr pouer reguirbient. Candidate for pouer asse;	(5 KB), X-RAY TAMK (.7 KB), A Sment.	- -					

2

3	SWILL COMPANY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY	VOLTAGE / PAINE	Maughty	<b>D</b> I	*		VFI E	<b>E</b> i	
799	INVINTENNICE FACILITY ELECTRONIC EQUIPMENT: AN/TSM-141	120/208 VAC; 3 PH; 120 VAC, 1 PH	5H D9	19.710	91.100	=	2.0	2.000 1.	8.
	MOTE: POWER HICLADES COMBINATION OF SELECTED COMPONENTS: 2-1 EACH), AND POWER SIPPLY (5.4 KB). ASSMES 3 PH BALANCI	JF SELECTED CHAPONENTS: 2-18000 BTU A/Cs (9.2 KW), LIGHTS (1.96 KW), EXHAUST FAN (1.15 KW), 2 NOTON GENERATONS I KW). ASSANES 3 PH BALANCING DUE TO A/Cs AND LANGE 1 PH LOAD.	. 16 KW), 2 MOTOR GENERATORS (4	2					
	MAINTENANCE FACILITY (MSE):	120 VAC, 1 PH	60 HZ	10.000	83.300	*	2.0	2.900 1.	8.
	NOTE: 115 W.C. POWER INCLUDES 2-8000 BTV A/Ce (A29828). TYPE CLASSIFIED FROM ZADRES.	PE CLASSIFIED FROM 240653.							
R19077	OPERATIONS CENTER COMMUNICATIONS: MANISC-26 LESS POWER	120 VAC, 1 PH	60 HZ, 50 HZ	7.852	99.500	*	5.(	2.000 1.	8
	HOTE: 115 VAC. POWER EXCLUDES A/C.								
\$11021	OPERATIONS CENTER COMMUNICATIONS: ANJNSC-31 LESS POWER	120 VAC, 1 PH	80 HZ, 50 HZ	3.500	29.200	-	.; =	2.000 1.	8.
	MOTE: 116 VAC. POWER EXCLUDES A/C.								
12063	OPERATIONS CENTRAL: MANISC-32 LESS PONER	120 VAC. 1 PH	80 HZ, 50 HZ	5. 150	44.B00	-	 	2.800	8
	MOTE: 116 VAC.								
N22073	OPTICAL FABRICATION UNIT: PORTABLE FIELD	120 VAC, 1 PN	5H 09	1.930	16.800	=	); #	2.000 1.	8.
	MITE: 110-116 VAC. PURER INCLUDES COMBINATION OF SELECTED COMPONENTS: KR), AND OPTIVALBIC MARKEN (.01 KR).	OMPONENTS: EDGING (.4 KM), HEAT TREATING UNIT (1.6 KM), LENS NEASURING INSTRUMENT (.02	), Lens Neasuring instrument (.	70					
R23712	OPTOMERY EQUIPMENT SET FIELD COMBAT:	120 VAC, 1 PH	80 HZ	0.100	0.670	*	2.	2.600	8
	MOTE: 115 W.C.								
MB3275	PETROLEUM BASE LABORATORY ASSEMBLY:	120/208 VAC, 3 PH	80 HZ, 50 HZ	90.00	167.000	#	 =	2.000	8
	MOTE: POWER BASED ON 60 KW GEN SET THAT IS AUTH SEPARATELY FROM SET.	NOM SET. NO OTHER DATA AVAILABLE.							
1	PHOTOGRAPHIC DARKGOOM GROUP: ES-38 LESS POWER	120 VAC, 1 PH	ZH 08	1.830	16.000	*	 =	2.000	8.
	MOTE: 115 W.C. POWER EXCLUDES 9,000 BTV A/C (A2828). POWER INCLUDES COMPINATION OF SELECTED COMPONENTS: PROTOPROCESSOR AND HEAT COIL (.8 KM) CONTACT PRINTER (.8 KM), PRINTER (.8 KM), PRINTER (.8 KM), AND LIGHTS (.18 KM). AND SOURCE-COM NOLTA, BRDEC, (783) 644-4796.	A INCLUGES COMBINATION OF SELECTED COMPONENTS: PHOTOPY ND LIGHTS (.18 KD). ADD SQURCE-COM ND.TA, BRDEC, (703)	NOCESSOR AND HEAT COIL (.8 KB), 1884–4796.						
# S S S S S S S S S S S S S S S S S S S	INDG14 PHOTOGNAPHIC DANKGIOCH TRANSPORTABLE: ES-82 LESS POWER	120 VAC, 1 PM	2H 00	9.500	90.000	=	2.	2.000 1	8.
	NOTE: 110 VAC. POWER EXCLUDES 2-8000 BTV A/Ca. POWER HACLUDES COMBINATION OF SELECTED CONTONERTS: HAMERSION NEATER (1.0 KM) AND WATER NEATER (4.5	DES COMBINATION OF SELECTED CONPONENTS: INNERSSION NEAT	TER (1.0 KW) AND WATER HEATER (	<b>4.5</b>					

# Portial Data)

CHECATURE	VOLTAGE/PWGE	PERFECT				WEI SE		<b>I</b>
LANGE EXTENSION SHITCH OPERATIONS SPELTER:	120 VAC, 1 PH, 28 VOC	60 HZ, DC	6.200	3. 88.	=	-		8
WIEL 116 VAC. POWER PROVIDED BY ASSOCIATED MODE INMAGEMENT S	ELTER (LIN 248788). TYPE CLASSIFIED FROM 237888.							
PLATOON COMMAND POST: GUIDED BISSILE ANAMSW 11 (NAMK)	240/416 VAC, 3 PH	400 HZ	22.000	30.500	>	2		8
MOTE: POWER INCLUDES 1-18000 BTU A/C (A24692) AUTH WITH SET.								
PLATE PROCESS SECTION: TOPO REPRODUCTION SET STLA MTD	120/208 VAC, 3 PH .	60 HZ	3.130	12.830	=	2		38.
NOTE: POWER EXCLUDES 2-18000 A/Cs AJTH SEP. POWER INCLUDES CO.	BINATION OF SELECTED COMPONENTS: PNOTOLITHOGRAPHIC I	MCHINE (2.65 KB) AND LIGHTS (	<b>9</b>					
OTONECIAMICAL PROCESS SECTION: TOPO REPRODUCTION SET STLA INTO	120/208 VAC, 3 PH	BO HZ, SO HZ	3.600	14.400	*	.2		0.85
MOTE: 115 VAC. POWER EXCLUDES 2-18000 A/Cs AUTH SEP. POWER 11 AND LIGHTS (.48 KW).	CLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAM	HIC PROCESSING MICHINE (3.12	â					
PBO164 PRESS SECTION TOPOGRAPHIC REPRO SET: SEMI TRAILER WOUNTED	129/208 VAC, 3 PH	<b>60</b> HZ	11.400	36.400	=	<b>~</b> <b>≈</b>		0.85 85
<u>zie.</u> Power Excludes a/ce auth sep. Power includes combinatio	OF SELECTED COMPONENTS: OFFSET PRINTING PRESS (10.0	KW) AND LIGHTS (.48 KW).						
PRINT PRESS OFFSET: AC 220V 3PH BOCY 15-1/2 IN X 9-7/6 IN MAX	120/208 VAC, 3 PH	80 HZ	10.900	27.000	*			8
<u>MOTE:</u> 220 VAC. NO INFO AVAILABLE ON P56830 WHICH IS BEING REP	ACED BY C/O OF TSS PRESS SECTION (LIN PS0154). DATA	IS FROM REPLACEMENT LIN.						
PRINTING PLANT SPECIAL WARFARE TRANSPORTABLE: LIGHT WT (ARMY)	120 VAC, 1 PH	80 HZ	3.16	27.400	=			8
MOTE: 115 VAC. POWER EXCLUDES A/Ca. POWER DERIVED FROM LANGE: LIGHTS.	f power consumers on each of the two subsystems (e.g.	PLATBINKER & PAPERCUTTER) AND						ļ
NODE CENTER SWITCH OPERATIONS SWELTER:	120 VAC, 1 PH, 28 VDC	60 HZ, DC	9.670	90.600	=			8
HOTE: 116 VAC. POWER PROVIDED BY ASSOCIATED WODE CENTER SWITCH	FACILITY (LIN 246766). TYPE CLASSIFIED FROM 246768.							
PHOTO KIT PROCESSING AND PRINTING PORTABLE: EH-94A		80 HZ	0.100	0.830	=			8
MOTE:								
RADAR ANTENNA DRIVE REPAIR SYOP TRUCK INDUNTED: DS/65 (VADS)	120 VAC, 1 PH; 240 VAC, 1 PH			37.500				9 6
NOTE: 116 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONEN	'S: UPPIGHT DRILLING MACHINE (3.73 KM) AND EXTENSION							
				SELENT: 120 WK, 1 PH, 24 VDC ASSOCIATED MODE IMMAGRIENT SHELTER (L.IH. 244748). THYE CLASSIFIED FROM 227448.  ANYWENT II (NAME) 240/418 VAC, 3 PH 240/418 VAC, 3 PH 3 00 MZ 3 1.300 AUTH SET STLM mTD 120/208 VAC, 3 PH 3 00 MZ 3 1.300 AUTH SEP. POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOCLITHOGRAPHIC WACHINE (2.65 KB) AND LIGHTS (1.48 3 1.600 AUTH SEP. POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGLITHOGRAPHIC PROCESSINE WACHINE (3.12 KB) 100 A/Cs ANTH SEP. POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAPHIC PROCESSINE WACHINE (3.12 KB) 11.400 A.P. POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAPHIC PROCESSINE WACHINE (4.8 KB). 15-1/2 IM X 9-7/8 IN MAX 120/208 VAC, 3 PH 60 MZ 61 POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAPHIC PROCESSINE WACHINE (4.8 KB). 15-1/2 IM X 9-7/8 IN MAX 120/208 VAC, 3 PH 60 MZ 61 POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAPHIC PROCESSINE WACHINE (4.8 KB). 16-1/2 IM X 9-7/8 IN MAX 120/208 VAC, 3 PH 60 MZ 61 POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAPHIC (4.8 KB). 16-1/2 IM X 9-7/8 IN MAX 120/208 VAC, 1 PH 60 MZ 61 POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: PROTOGRAPHIC (4.8 KB). 178 MEE: EH-MAX 120 VAC, 1 PH 60 MZ 61 POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: SON MAD EXTENSION LIGHT (1 KB). 189 MAXION OF SELECTED COMPONENTS: WARRING DIRECTED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS: WARRING DEPLICED COMPONENTS:	SECURISE MODE WANGEDERT SHELTER (LIN 248788). THE CLASSIFIED FROM 237888.  ANYWERT II (WANC)  240/418 VAC, 3 PH  440 NZ  22.000  ACC (424682) ANTH WITH SET.  120/208 VAC, 3 PH  440 NZ  3.130  AUTH SEP. POREN INCLUDES CARBINATION OF SELECTED COMPONENTS: PROTOCLITHOGRAPHIC WACHINE (2.65 KW) AND LIGHTS (.48  3.600  110/208 VAC, 3 PH  90 NZ, 50 NZ, 50 NZ, 50 NZ  110.400  90 NZ  110.400  90 NZ  110.400  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ  90 NZ	ELIDE: 120 VIC, 1 PH, 28 VIC  400 HZ  400 HZ  400 HZ  22 100 30 800 Y  400 HZ  400 HZ  22 100 30 800 Y  400 HZ  22 100 30 800 Y  400 HZ  400 HZ  22 100 30 800 Y  400 HZ  22 100 30 800 Y  400 HZ  23 100 12 800 W  400 HZ  400 HZ  23 100 12 800 W  400 HZ  400 HZ  3 100 NZ  3 100 NZ  400 HZ  3 100 NZ  400 HZ  400 HZ  3 100 NZ  400 HZ  400 HZ  3 100 NZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ  400 HZ	400 NZ, 100 WZ, 101, 2407M3, TPTE CLASSIFED FINDL 2278M4,  400 NZ  400 NZ  22.000 30.500 Y N  400 NZ  22.000 30.500 Y N  400 NZ  22.000 30.500 Y N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 30.500 W N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  22.000 N N  400 NZ  23.000 Z Z Z Z  400 NZ  23.000 Z Z Z  400 NZ  23.000 Z Z Z  400 NZ  23.000 Z Z Z  400 NZ  23.000 Z Z Z  400 NZ  23.000 N N  400 NZ  23.000 Z Z Z  400 NZ  23.000 N N  400 NZ  23.000 N N  400 NZ  23.000 N N  400 NZ  23.000 N N  400 NZ  23.000 Z Z Z  400 NZ  23.000 Z Z Z  400 NZ  23.000 N N  400 NZ  23.000 Z Z Z  400 NZ  23.000 N N  400 NZ  23.000 Z Z Z  400 NZ  23.000 N N  400 NZ  23.000 N N  400 NZ  23.000 N N  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  400 NZ  40	AND SET THE SET OF SELECTED COMPONENTS: PROTECTION SET STANDARY STANDARY STANDARY STANDARY SET SET STANDARY SET SET SET SET SET SET SET SET SET SET

킠	MERCANE	VOLIME/PWEE	FREMENT		Ħ	¥	Z.		對
013817	613817 NADAR DATA GROUND RECEIVING SET: AN/TKG-2 LESS POWER	120/208 VAC, 3 PH	400 HZ	9.000	20.000	=	*	2.8	8:
	HOTE:								
915414	GIS414 PADAR SET: AN/MPG-4 LESS POWER	120/208 VAC, 3 PH	400 HZ	7.090	19.700	=	=	2.8	8.
	NOTE:	•							
016040	RADA; SET: HIPIR ANVIROG-57 (HAMK)	240/416 VAC, 3 PH	400 HZ	29.000	40.300	<b>&gt;</b>	=	2.80	8
	HOTE:								
9	018044 RADAR SET: CHAR AN/MPG-56 (WANK)	240/416 VAC, 3 PH	400 HZ	<b>3</b>	. 80	-	=	2.000	8.
	MOTE								
970910	PADAR SET: MAZIFO-48 (FAAR)	120/208 VAC, 3 PH	400 HZ	4.900	13.600	-	=	2.000	8.
	IOTE								
970010	GIGOGE PADAR SET: (NAMK)	240/416 VAC, 3 PH	400 HZ	16.000	22.200	>	=	2.8	8.
	MOTE.								
6/1910	RADAR SET: AN/PPS-15 LESS POWER	28 VDC	8	910.0	0.600	æ	=	2.000	8.
	HOTE: NUMS OFF POWER SUPPLY PP-7500/PPS 158 OR BATTERY 24 VDC	O/PPS 158 OM BATTERY 24 VOC (VENICLE) REBULATED TO 12 VOC BY EXTENNAL POWER CABLE.	:						
017332	017332 NADAR SET: AN/TPS- 25 LESS POWER	120 VAC, 1 PH	\$100 HZ	1.515	13.706	=	=	\$	98.0
	HOTE: 116 VAC.								
918702	RADAR SURVEILLANCE CENTRAL: AN/855-1 LESS POWER	120 VAC, 1 PH, 28 VCC	400 HZ, DC	7.820	66.200	=	=	2.000	8.
	NOTE: 115 VAC.								
623623	PADIO MAINTENANCE CENTRAL: AN/THM-18	240 VAC, 1 PH	<b>6</b> 0 HZ	2.400	6.700	=	*	2.000	8.
<b>198</b> 29	PADIO RECEIVING CENTRAL: ANTTRR-27	120 VAC, 1 PH	<b>\$</b> 0 H2	3.80	25.000	=	=	2.900	8.
	HOTE: POWER EXCLUDES 1-18000 BTW A/C.								

**=** 

# CONSTITUTES DATABASE (Partie) Deta)

		18/17/81							
3		VOLTABL/PAUSE	FRENERCY		1	뵘	WFI	bi	¥i
2	8 MOIO TELEPRINTER SET: AL/TGR-2	120 VAC, 1 PH	50 HZ	3.000	25.000	=	*	2.000	
	HOTE: POWER EXCLUDES 1-18000 BTV A/C.								
80100	NADIO TELETYPENRITER SET: AAVGRC-122	120 VAC, 1 PH	ZH 09	3.350	29.100	=	=	2.000	8.
	HOTE: 116 VAC. POWER EXCLUDES 1-6000 BTU A/C (A23701). REPLACEMENT 1TBM FOR AN/GRO-260.	REPLACEMENT ITEM FOR AN/GRC-260.							
080120	MOIO TELETYPEURITER SET: AA/GRC-142	120 VAC, 1 PH, 28 VDC	60 HZ, DC	3.350	45.000	=	=	2.000	8.
	HOTE: POWER EXCLUDES 1-6000 6TU (A23701) A/C AUTH SEP. RI 620 Authorized Separately.	RTT SET INCLUCES THE SHELTER AND AN IMPERTER THAT WILL TAKE 28 VOC AND CONVERTS TO 110 VAC. PU	E 28 VDC AND CONVERTS TO 110 VA	<b>æ</b>					
8	081301 RADIO TELETYPERITER SET: MA/YSC-2	28 VDC	8	2.500	69.300	=	-	2.000	8
	NOTE:	-							
091302	ANDIO TELETYPEIRITER SET: ANVSC-3	120 VAC, 1 PH	60 HZ	3.350	28.100	#	#	2.900	8.
	NOTE: POWER REQUIREMENT SAME AS AN/GRC-122.								
092197	PADIO TERRITAL SET: AN/ARC-127 LESS POWER	120 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	1.750	14.600	=	=	2.000	9.
	MOTE: 115 VAC. 47-420 HZ.								
092848	RADIO TERNINAL SET: ANTRC-112 LESS POWER	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	9.345	77.900	*	=	2.000	8.
	NOTE: 1 36-60000 BTU A/C POWERED BY 204P ENGINE.								
092899	RADIO TERNINAL SET: AN/TRC-151 LESS PONER	120/208 VAC, 3 PH	60 HZ, 50 HZ, 400 HZ	3.50	10.100	=	=	2.000	8.
	NOTE: 115 VAC. 47-420 HZ. POWER EXCLUDES 18000 BTU A/C (A20271). ASSUMES 3 PH BALANCING DUE TO A/C.	A28271). ASSUMES 3 PH BALANCING DUE TO A/C.							
104101	REFERENCE SCENE GENERATION FACILITY: RSGF (PERSHING 11)	120/208 VAC, 3 PH	400 HZ	18.250	50.700	#	*	2.900	0. 80.
	NOTE: FOWER INCLUDES 2-18000 BTU A/Cs. FOWER INCLUDES COMBIS (3). Add Sounce-bay Hoffaker, Goodyfear, (16)799-4829	FOWER INCLIDES 2-18000 BTV A/Cs. POWER INCLIDES COMBINATION OF SELECTED COMPONENTS: CÓMPUTER EQUIPMENT (7.5 KW), CB (1.3 KW), AND LIGHTS (.15 KM). ADD SOUNCE-RAY HOFFAKER, GOODPEAR, (216)796-1829.	(13), CB (1.3 KB), AND LIGHTS (	<u> 5</u>					
814148	RI4148 RADAR SET: AW/TRQ-38(V)1	120/208 VAC, 3 PH	400 HZ	10.000	27.800	=	=	2.000	8.
	NOTE: 115/200 VAC.								

=	NAVOR AN	VOLTAGE/PHASE	REVIEW		*	<b>E</b>	WE!		¥1
A16476	RABIN SET: AN/GAD-1	120 VAC, 1 PM	60 HZ, 50 HZ	1.000	9.300	*	* *	2.000	8
	HOTE: 105-129 VAC.								
R18815	INDAR SET SEHITMILER WOUNTED: ANVIROG-53 (PATRIOT)	120/208 VAC; 3 PH	400 HZ	125.000	347.000	>	~ =	2.900	8.
	MOTE: ACTUAL KIP IS CLASSIFIED SINCE IT CAN BE USED TO ESTIMATE	NCE IT CAN DE USED TO ESTINATE NAMBE. ALLOWABLE KAI LIBITS ARE 100-200 KM. ASSUMED TO REQUIRE 125 KM GENERATOR	TO REQUIRE 125 KM GENERATOR.						
R33561	RADIO ACCESS UNIT (MAU) (MSE):	120 VAC, 1 PH, 28 VDC	60 HZ, DC	2.770	24.100	=	~	2.900	8
	HOTE: 115 VAC. TYPE CLASSIFIED FROM 253757.								
R\$5664	RECEIVING CENTRAL TELETYPEURITER: AN/TGR-1	120/208 VAC, 3 PH	50 HZ	2.500	20.800		2	2.000	8.
	MOTE	-							
R38590	RECEIVING SET PADIO: AN/MRR-8 LESS POWER	120 VAC, 1 PH	ZH 09	5.640	46.700	=	2	2.900	8
	NOTE: 115 VAC.								
R38668	RECEIVING SET PADIO: AN/TPR-18 LESS POWER	120 VAC, 1 PH	2H 09	2.280	19.800	=	-2	2.000	8
	MOTE: POWER EXCLUDES 2-9000 BTU AVCA AUTH SEP. FOWER HICLUDES 2-90 W, 2 WIDHTORS (18 W EACH), INTERCOLARCEIVER (10 W)	AVGA ANTH SEP. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 4 RECEIVERS (40 W EACH), 4 AMPLIFIERS (2-25 W, Each), intercollineceiver (10 W), 2 Tape Michines (650 W Each), and Lights (240 W).	W EACH), 4 AMPLIFIERS (2-25 W	_•					
R39452	NADIO TERBINAL SET: ANJTRC-173	120 VAC, 1 PH	60 HZ, 50 HZ	9.447	<b>62</b> .100	=	2	2.000	8.
	NOTE: 115 VAC.								
R39520	REPEATER SET INDIO: AN/TRC-174	120/208 VAC, 3 PH	60 HZ, 50 HZ	1.212	23.000	=	7	2.000	8
	MOTE: 115 VAC. POWER HICLUDES 9000 BTV A/C (A22965) PER BOIP. ASSUMES 3 PH BALANCINS DUE TO A/C.	ASSUMES 3 PH BALANCING DUE TO A/C.							
R39588	PADIO TERNINAL SET: ANJTRC-176	120/208 VAC, 3 PH	80 HZ, S0 HZ	9.179	26.500	=	7	2.000	8
	MOTE: 115 VAC. POURS HICLUDES 9000 BTV A/C (A22965) PER BOLP. ASSUMES 3 PH BALANCHING DUE TO A/C.	ASSUMES 3 PH BALANCING DUE TO A/C.							
F159663	RECEIVING SET SPECIAL PURPOSE: AKANSA-103	120/208 VAC, 3 PH; 240/416 VAC, 9 PH	2H 907	10.00	27.700	=	2	2.88	8
	HOTE: POWER INCLUDES 1-18000 BTU A/C (A24562) (4.8 KM).								
P40073	RECEIVER SET COURTERIESSURE SPECIAL PURPOSE: AN/ALQ-34	120/208 VAC, 3 PH	ZH 909	<b>56.40</b> 0	208.200	*	7	2.606	9.9
	HOTE: POWER EXCLUSES 1-34000 BTU A/C, 400M2.								

			12/12/91							
3			WATAKITHME	PROMERY			삠	X/E	<b>W</b>	
R73630		REPAIR PARTS STUBAGE FACILITY: ALVUSH-379	120/206 VAC, 3 PH	90 HZ	9.16	0.440	=	=	2. 80.	8.
		POWER EXCLUDES 18000 BTU A/	C (A24456). PRIMARY POWER REQUIREMENT IS LIGHTS.							
R78627		REPEATER SET INDIO: ANTIRC-113(V)2 LESS POWER	120/208 VAC, 3 PH	60 HZ	2.065	9.90	*	-	% %	8
	Ë		POWER EXCLUDES 18000 8TU A/C (A26271, 3 PH, 3 KM) AUTH SEP. HEATER REQUIREMENT OFFSET BY A/C REQUIREMENT. ASSUMES 3 PH BALANCHIG DUE TO A/C.	IT. ASSUMES 3 PH BALANCING DUE TO						
N78028		REPEATEN SET PADIO: AN/TRC-113(V)3 LESS PONER	120/206 VAC, 3 PH	2H 09	2.065	9.800	=	=	2.900	8
			POWEN EXCLUDES 18000 BTV A/C (A26271, 3 PH, 3 KM) AUTH SEP. HEATEN REQUINEMENT OFFSET BY A/C REQUINEMENT. ASSUMES 3 PH BALANCING DUE TO A/C.	IT. ASSUMES 3 PH DALANCING DUE TO						
87,0048		NEPEATEN SET NACIO: AN/THC-138 LESS POVER	120/208 VAC, 3 PH	60 HZ, 50 HZ	5.509	16.300	=	=	2.000	8
	ä	POWER EXCLUDES 3 A/Co AUTH SEP. ASSUMES 3 PH BALANCING DUE TO A/C.	ES 3 PH BALANCING DUE TO A/C.							
R78067		NEPEATER SET INDIO: ANVINC-162 LESS PONER	120/208 VAC, 3 PH	60 HZ, 50 HZ, 400 HZ	3.560	10.300	=	=	2.000	8
	MATE:	INTE: 115 VAC. 47-420 HZ. POUER EXCLUDES 16	EKCLUDES 18000 BTV A/C (A28271,3 PH, 3 KM). ASSUMES 3 PH BALANCING DUE TO A/C.	VC.						
R78130		REPEATER SET ANDIO: AN/TRC-113(V)! LESS POWER	120/208 VAC, 3 PH	80 HZ, 50 HZ, 400 HZ	5.075	14.700	=	=	2.000	8
	ETE:	NOTE: 115 VAC. 47-420 HZ. POWER EXCLUDES 18	EICLUDES 18000 BTU A/C (A26271, 3 PH, 3 AB). ASSUMES 3 PH BALANCING DUE TO A/C.	A/C.						
P64689		REPRODUCTION SET DIAZO PROCESS: 10 CONFONENTS	120 VAC, 1 PH	50 HZ	1.200	12.300	=	=	5.00 2.00	9.6
	NOTE:	MOTE: 115 VAC. TSS POWER SURVEY PAGE 11, ITEM 5.	<b>19</b> 5.							
R92962		PADIO TERNINAL SET: AWTRC-145(V)2 LESS POWER	120/208 VAC, 3 PH	60 HZ, 50 HZ	3.000	8.300	=	=	2.900	8.
			110 VAC. POWER EXCLUDES 18000 BTU A/C (A2027), 3 PH, 3 KM7 AUTH SEP. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 2 AM/GRC-103 (1.11 KM) EACH), TSEC/KG-27 (.1 KM7, CV/1648/G (.2 KM), ELECTRIC LATTERN (.1 KM7, POWER DISTRIBUTION PANEL (.2 KM7, AND LIGHTS (.4 KM7). ASSAMES 3 PH Balancing due to a/C.	LECTED COMPONENTS: 2 AN/GRC-103 (1), AND LIGHTS (.4 KM). ASSUMES 3 PA	Ē					
R92996		RADIO TERMINAL SET: AN/TRC-145(V)1 LESS POWER	120/206 VAC, 3 PH	60 HZ, 50 HZ	3.00	8.300	=	=	2.000	8
	E E	115 VAC. POWER EXCLUDES 18000 BTU A/C	INTE: 115 VAC. POWER EXCLUDES 18000 BTU A/C (A26271, 3 PM, 3 KW). ASSUMES 3 PM BALANCING DUE TO A/C.							
R\$3030		RADIO TERMINAL SET: AN/TRC-145(V)3 LESS POWER	120/208 VAC, 3 PH	60 HZ, 50 HZ	3.000	8.30	= .	=	2.000	8
	ij	115 VAC. POWER EXCLUDES 18000 BTU A/C	MOTE; 115 VAC. POWER EXCLUDES 18000 BTV A/C (A28271, 3 PH, 3 KB) AUTH SEP. ASSMES 3 PH BALANCING DUE TO A/C.							

3	MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MATERIAL MAT	VOLTABE/PHASE	The second	<b>D</b> i	활	¥1	S S		
\$10034	I SHOP EQUIPMENT DATTERY SERVICING SHELTER MOUNTED: ANVISH-133 L/P 120/200 VAC, 3 PH		60 HZ, 50 HZ	17.500	100.000	=		2.000	8.
	MITE: POWER EXCLIDES 2-9000 BTU A/Co. POWER INCLIDES COMPINATION OF SELECTED COMPONENTS: 4-BATTERY ANALYZER-CHARGERS; AN/USH-432 (26-30) EACH).	PF SELECTED CONFORENTS: 4-BATTERY ANALYZER-CHARGE	ERS: AN/USM-432 (25-30 AMPS						
\$10325	SHOP EQUIPMENT NIGHT SIGHT MAINTENANCE FACILITY: (HSMF)	120/206 VAC, 3 PH	60 HZ, 50 HZ	10.300	35.300	-	=	2.88	8
	HOTE: POWER INCLUDES COMBINATION OF SELECTED CONFORENTS: 2-18000 3 PM SALMETING DUE TO A.C.	OF SELECTED COMPONENTS: 2-18000 BTV A/Ca (4.8 KW EACH), OSCILLOSCOPE (.24 KW), AND UPAGON TEST SET (.1 KW). ASSUMES	D DANGON TEST SET (.1 KM). A	SSUMES					
\$10535	SNOP EQUIPMENT ELECTRICAL NEPAINSENITRAILER NTD: PERSHING II	120/208 W.C., 3 PH	60 HZ	8.400	23.300	**	-	2.000	8
	MOTE: POWER EXCLUDES 3-18000 BTV AVCs. POWER INCLUDES COMBINATION OF SELE- IND), AND SERVICE OUTLETS (6 NM). ASSAMES 3 PV GALANCING DUE TO AVC.	A/Ca. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: POWER SUPPLY (.2 KM), LIGHTS (.86 KM), AIR COMPRESSON (1.6 KM). ASSURES 3 PH BALANCING ONE TO A/C.	.IGHTS (.06 KB), AIR COMPRESSO	9.1) #					
S14500	SHOP EQUIPMENT ON SYSTEM: AN/TON-1 (PATRIOT)	120/208 VAC, 3 PN	400 112	3.800	10.800	=	=	2.600	8
	MOTE: POWER EXCUDES 18000 BTU A/C. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: OSCILLOSCOPE (2.4 KB) AND POWER COMPENTER (1.4 KB). 3 PH SALANCING DUE TO A/CA.	SELECTED COMPONENTS: OSCILLOSCOPE (2.4 KM) AND I		ASSIDES					
\$14637	SKOP EQUIPMENT ON SYSTEM: AN/TSM-176 (PATRIOT)	120/208 VAC, 3 PH	400 HZ	3.700	10.300	=		2.000	8
	MOTE: FOURTH EXCLUDES 18000 BTU A/C (ASAR70). FOURTH HICLIDES COMBINATION OF SELECTED COMPONENTS: FOURTH SUPPLY (2.3 KM) AND POURTH SUPPLY FOR AMORICE-106 (1.4 KM). ASSUMES 3 PN BALANCHING DUE TO A/C.	NATION OF SELECTED COMPONENTS: POWER SUPPLY (2.3	I KIT) AND POWER SUPPLY FOR						
\$15457	SHOP EQUIPMENT GUIDED MISSILE SYSTEM: AN/TSM-164 (PATRIOT)	120/206 VAC, 3 PH	400 HZ	2.00	9. 600	=	=	2.000	8.
	MOTE: POWER EXCLUDES 18000 BTV A/C (ASA786). POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: OSCILLOSCOPE, MALTINETERS, AND LIGHTS. ASSUMES 3 PM BALANCINE DUE TO A/C.	MATION OF SELECTED COMPONENTS: OSCILLOSCOPE, MAI:	TIMETERS, AND LIGHTS. ASSUME	£ 55					
S17120	SHOP EQUIPMENT: GUIDED MISSILE SYSTEM	120/208 VAC, 3 PH	400 HZ	12.000	23.26 26.20	-	<del></del>	2.000	8.
	NOTE: FOWER INCLUDES 18000 BTV A/C (ASA870) AUTH WITH SET.								
\$24750	LANGE EXTENSION SWITCH SWITCHING FACILITY (MSE):	120 VAC, 1 PH	24 08	83.	71.900	=	=	2.000	8
	HOTE: 115 VAC. TYPE CLASSIFIED FROM 228434.								
524818	NODE CENTER SWITCH (NCS) SWITCHING FACILITY (NGE):	120 VAC, 1 PH, 28 VDC	90 HZ, DC	7.000	90.90	#	=	2.000	8.
	MOTE: 116 W.C. TYPE CLASSIFIED FROM 246776.								

		10/2//21							
3		VOLTABELPHASE	FEMERY		*		WE E	¥.	16.1
\$26379	S26379 SMALL EXTENSION SHITCH V2:	120 VAC, 1 PH, 28 VDC	80 NZ, DC	4.310	37.500	=	2.80		8
	HOTE: 115 VAC. TYPE CLASSIFIED FROM 274369.	,							
525447	SHALL EXTENSION SWITCH VI (MSE):	120 VAC, 1 PH	<b>60</b> HZ	4.310	37.500	=	H 2.000		8
	MOTE: 116 VAC. TYPE CLASSIFIED FROM 228437.								
S26335	SHOP SET AVIN ANNAMENT REPAIR SHELTER NTD: NON DIV	120/206 VAC, 3 PH	<b>80</b> HZ	4.200	11.700	=	II 2.000		8.
	<u>NOTE:</u> FOWER EXCLUDES 2-10000 BTV A/Cs (3 PH). POWER INCLUDES (BALANCHIS DUE TO A/Cs.	A/Ca (3 PH). POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: HEAT GUN (1.4 KM) AND DRILL (.5 KM). ASSUMES 3 PH	AND DRILL (.5 KM). ASSUMES	£					
S28635	SHOP SET AVIB FIRE CONTROL REPAIR SHELTER BTD: NON-DIV	120/208 VAC, 3 PH	ZH 09	4.200	11.700	*	2.000		8
	HOTE: POWER EXCLUDES 2-18000 BTU A/Ca. POWER BASED ON SINGLE I	I A/Ca. POWER BASED ON SINGLE LANGEST CONSUMER: HEAT GIM (1.4 KM). ASSUMES 3 PH BALANCING DUE TO A/Ca.	WAICHIG DUE TO A/Cs.						
S29688	SNOP SET ENGINE TUNBINE APPR. AVIB NON-DIV SMLT MTD	120/206 VAC, 3 PH	2H 08	3.000	9.300	=	N 2.000		8
	NOTE: 115 VAC. PONER EXCLUSES 2-18000 BTV A/Cs. PONER INCLUSES CONBINATION OF SELECTED COMPONENTS: GRINDER (1.5 KB), DRILL (1 KB) AND LIGHTS (1.48 KB). ASSUMES 8 PH BALLMCING DUE TO A/Cs.	ES COMBINATION OF SELECTED CONPONENTS: GRUNDER (.S.K.	II), CAILL (1 KB) AND LIGHTS (	2					
23064	SNOP EQUIPMENT GENERAL PURPOSE REPAIR SENITRAILER UTD: PERSH 11	120/206 VAC, 3 PH	ZH 09	10.500	29.200	*	N 2.900		8
	NOTE: POWER EXCLUDES 3-10000 BTU A/Cs., POWER INCLUDES COMBINN' OUTLETS (6 KB), ASSUMES 3 PH BALANCINE DUE TO A/Cs.	A/Cs. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: AIR COMPRESSOR (1.5 KM), JACK TEST SET (3 KM) AND SERVICE Ph balancing due to A/Cs.	. Jack Test set (3 kg) and sen	AICE VICE					
<b>531897</b>	SHOP SET INSTRUMENT/ELECTRICAL; AVIA NON-DIV SALT NTD	120/208 VAC, 3 PH	60 HZ	3.000	9.300	=	1 2.000		0.85
	NOTE: FOURS EXCLUDES 2-18000 BTU A/C4 (A24483, 6.2 KW EACH, 3 PH) AUTH SEP. POURS INCLUDES COMBINATION OF SELECTED COMPONENTS: ORTLL (.33 KW), GRINDER (.5 KW), HEAT GAM (1 KW), AND LIGHTS (.48 KW), ASSUMES 3 PH BALANCING DAE TO A/C4.	A/Cs (A24483, 6.2 KW EACH, 3 PH) AUTH SEP. POWER INCLUDES COMBINATION OF SELECTED (1 KW), AND LIGHTS (.48 KW). ASSUMES 3 PH BALANCING DUE TO A/Cs.	COUPONENTS: ORILL (.33 KW),						
532719	S32719 SHOP SET INCHINE/WELDING: AVIB NON-DIV SALT NTO	120/208 VAC, 3 PH; 120 VAC, 1 PH	80 HZ	4.200	11.700	=	2.000		8.
	NOTE: POWER EXCLUDES 2-18000 8TU A/Cs. POWER INCLUDES COMBINATION (AP). ASSUMES 3 PH BALANCING, DUE TO 3 PH LONGS.	A/Cs. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: LATHE (1.5 KM, 3 PH), WELDER (1.726 KW), AND LIGHTS (.44 NG, DUE TO 3 PH LOAGS.		₹					
533441	SHOP SET PHEUDNAULIC: AVIII HON-DIV SHLT INTO	120/208 VAC, 3 PH	ZH 98	3.480	9.90	-	2.000	8:	8
	MOTE: POWER EXCLUDES 2-18000 BTU A/Cs. POWER INCLUDES COMBINATION LIGHTS (.48 KW). ASSUMES 3 PH BALARCING DUE TO A/Cs.	A/Cs. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: MOSE CUTOFF NACHINE (2 KW, 230 VAC), DRILL (1 KW), AND 3 PM BALANCING DUE TO A/Cs.	JR, 230 VAC), DRILL (1 KB), AM	۵					

3		VOLTAGE / PWASE	FROMENCY	21		E	Ī	104	<b>X</b> i
534774	S SHOP SET PORERTRAINE: AVIA NON-DIV SHLT NTO	120/208 VAC, 3 PH	<b>2</b> 0 H2	4.200	11.600	*	-	2.900	8
	HOTE: FOWER EXCLUSES 2-18000 BTV A/CA. FOWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL (.8 KW), GRINDER (.5 KW), HEAT GAM (1.4 KW), AND	MTION OF SELECTED COMPONENTS: DRILL (.8 KW), GRINDER	(.5 KB), HEAT GUN (1.4 KB), A	9					
534963	SAMMS SATELLITE COMBUNICATIONS TERMINAL: ANJ/ISC-02A	120/208 VAC, 3 PH; 240/418 VAC, 3 PH	BO HZ, 50 HZ	7.600	21.100	=		2.000	8
	MOTE: 116 OR 230 VAC. POWER EXCLUDES 1-9000 BTV A/C (A23865) AVTH SEP. POWER INCLUDES COMPINATION OF SELECTED COMPONENTS. ASSUMES 3 PH BALANCING DUE TO A/C.	I ANTH SEP. POWER INCLUDES COMBINATION OF SELECTED COM	POMENTS. ASSUMES 3 PH BALANCI	14G DUE					
526146	SSE145 SATEL/ ITE COMBUNICATIONS TERNINAL: ANAMSC-44(V)2	120 W.C. 1 PH, 28 VDC	80 HZ, 50 HZ, DC, 50 HZ	19.000	87.800	*	-	2.000	8.
	MOTE: 115 OR 230 VAC.								
3961962	5 SHOP SET PRODUCTION/QUALITY CONTROL: AVIR MON-DIV SHLT MTD	120/208 VAC, 3 PH	2H 00	0.480	 8	=	=	2.000	8.
	MOTE: POWER EXCLUDES 2-18000 BTV A/CE (A24483) AUTH SEP. P. BALANCHINS DVE TO A/CE.	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: LIGHTS (.48 KM). ASSUMES 3 PM	NTS (.48 KM). ASSUMES 3 PH						
S35436	6 SHOP SET PROP/ROTOR: AVIII MON-DIV SHLT BITD	120/208 VAC, 3 PH	50 HZ	4.200	11.700	=	=	2.000	8
	MOTE: POWER EXCLUSES 2-18000 BTV A/Ca. POWER INCLUSES COMBIN	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: ORILL (.35 KM), GRINDER (.5 KM), HEAT GUN (1.4 KM), Lancing due to avgs.	R (.5 KB), HEAT GUN (1.4 KB),	9					
235500	SHOP SET SHEET METAL/PAINT: AVINDOM-DIV SHLT INTO	120/208 VAC, 3 PH; 120 VAC, 1 PH	90 HZ	6.250	14.500	#	=	2.000	8
	MOTE: POURS DICLUDES 2-16000 BTU A/Ca. POURS INCLIDES COMBINATION OF SELECTED COMPONENTS: BAND SAW (.76 KB), GRINDER (.6 KB), AND COMPRESSOR (3 KB), 3 KB), 3 FM),	INTION OF SELECTED COMPONENTS: BAND SAW (.76 KM), GRI	HOER (.6 KB), AND COMPRESSOR	E					
78475	4 SYSTEM CONTROL PLANNING CENTER (SCPC) (MSE):	120 VAC, 1 PH, 28 VDC	60 HZ, DC	3.	11.400	*	*	2.000	8.
	MOTE: 115 W.C. TYPE CLASSIFIED FIRM 278886.								
24/12	2 SYSTEM CONTROL CENTER COMMAND SYELTEN:	120 VAC, 1 PH, 28 VDC	90 HZ, DC	<b>9</b> .	<b>2</b>	•	-	<b>38</b>	8.
	NOTE: 116 VAC. TYPE CLASSIFIED FIRM 270606.								
\$44814	4 SYSTEM CONTROL CENTER TECHNICAL SHELTER:	120 W.C., 1 PH, 28 VCC	80 HZ, DC	4.946	42.00	=	*	2.000	<u>.</u>
	METE: 116 W.C. TYPE CLASSIFIED FROM 278000.								
X6709A	4 SKOP SET: LAWDIER LONGER MODINE DIRECT SUPPORT (MLIS)	120 W.C. 1 PH	ZH 08	0.675	<b>2.8</b>	=	=	2. 88	8.
	HOTE: 106-120 VAC. FOWER INCLUDES COMPINATION OF SELECTED C	COMMINATION OF SELECTED COMPONENTS: DESOLUCINES TOOL (.575 KM) AND EXTENSION LIGHT (.1 KM)	.1947 (.1 KB).						

3		WALARL/THIRE	HOMEN.		Ħ	H	WE!		
367162	SHOP EQUIPMENT: ORGANIZATION MAINTENANCE (ROLAND)	120 MC, 1 PH	80 KZ, 50 KZ	8	. X	=	~	2.8	=
	101E: 116 W.C.								
790365	SUMELLLANCE INFORMATION PROCESSING CENTER: ANVISO-106(V)3 LP	120/208 W.C. 3 PH	80 HZ, 50 HZ	170.00	179.800 472.000	-	7	2.86	8
	METE: FOUR HICLIGES 6-9000 BTV A/Cs (A2400). FOUR IS CONSTANT TAFE RECORDERS, SATELLITE DISHES AND DISK STONNEE.	POURS IS COMBOLIDATION OF REQUIREMENTS FOR 6-40 FT WARS (I MAXILLARY, 2 SHOP, AND 3 SEALAND) HOUSING STORME.	FM, 2 SHOP, AND 3 SEALAND) HOU	55. 58. 58.					
874480	SENITRALLER WAI: EXPANSIBLE 6 TOH 4 WHEEL (ANNY)	120/208 VAC, 3 PM	66 HZ, 56 HZ	99.	32.19	=	.;	2.000	3
	MOTE:	•							
S78486	SATELLITE COMMUNICATIONS TERMINAL: AN/TSC-85A	120/208 VAC, 3 PH; 240/418 VAC, 3 PH	90 NZ, 50 NZ	7.200	20.000	-	2.	2.990	8
	MOTE: 116 W.C. FOWER EXCLUDES 2-8000 BTU A/CA (A23866) AUTH SEP. ASSUMES 3 PH BALANCING DUE TO A/CA.	. ASSUMES 3 PH BALANCING DUE TO A/Cs.							
100172	T00172 TEST SUPPORT SYSTEM: (TSS) ON 500	120/208 VAC. 3 PH	24: 00	25.200	70.900		 =	2.000	8
	MOTE: FOURS INCLIDES 2 A/Ca.								
106474	SHELTER SYSTEM COLLECTIVE PROTECTION CHEMICAL-BIOLOGICAL: 10-MM 120/200 VAC, 3 PM	20/206 VAC, 3 PH	2H 08	7.250	20.100	=	.2	2.000	8
	WITE.								
100837	TEST STATION GUIDED BISSILE SYSTEM: SYS COMPONENTS (PERSHING II) 120/200 VAC, 3 PM	20/208 VAC, 3 PH	ZH 98	14.500	90.300	=	~	2.000	8
	MITE: FOURT EXCLUDES 8-18000 6TV A/CA. FOURT INCLUDES COMBINATION OF SELECTED CONFONENTS: AUTO TEST EQUIPMENT CONSISTS OF FOURT SUPPLIES, DTS-70 COMPUTENS, ETC., 14 KW, 1 PH, WHICH CAN BE BALANCED ANDIG 8 PH POURT INPUT) AND LIGHTS (.5 KW). ASSUMES 8 PH DALANCING DUE TO A/CA.	DII OF SELECTED COMPONENTS: AUTO TEST EGUIPMENT COME 3 pm ponen input) and lights (.5 km). Assumes 8 pm	SISTS OF POWER SUPPLIES, 015-70 Dalancing due to A/Cs.	90					
T01973	TOPOGRAPH	120/206 VAC, 3 PH	50 HZ	8	22.100	=	~	2.000 0.	9.
	MOTE: 115 VAC. POWER EXCLUDES 2-19000 BTU A/CA AUTH SEP. POWER BASED ON SINGLE LANGEST CONSUMER (PHOTOGRAMETRIC POSITIONING SYSTEM, 2.65 KM, 1 PH). ASSUMES 3 PH BALANCING DUE TO A/CA) WILL ACCOMMODATE OTHER COMPONERTS.	BASED ON SINGLE LANGEST CONSUMER (PHOTOGRAMETRIC PA R COMPONENTS.	ASITIONING SYSTEM, 2.65 KM, 1 F	Ė					
T02041	TOPOGRAPHIC SUPPORT SET: COLLECTION SECTION SENITRAILER NOUNTED 120/206 VAC, 3 PM	20/206 VAC, 3 PM	80 HZ	.56	4.200	*	~	2.000	8
	MOTE: POWER EXCLUDES 2-18000 BTU AVCA AUTH SEP. POWER BASED ON WILL ACCOMPOSATE COMPONENTS.	POWER BASED ON SINGLE LANGEST CONSUMER (VACUUM CLEANER, .S KM). AS	ASSUMES 3 PH BALANCING (DUE TO A/Cs)	N/Ca)					
T02109	TOPGRAPHIC SUPPORT SET: DIVISION DINECT SUPPORT SEC TRK WAN WITD 120/208 VAC, 3 PH	10/208 VAC, 3 PH	ZH 98	3.600	10.000	*	3.0	2.000 0.80	8
	HOTE: 116 VAC. POWER EXCLUDES 2-18000 BTU A/Cs AUTH SEP. POWER BALANCING CONFORMERTS.	FOURTH EXCLUDES 2-18000 8TU A/CA AUTH SEP. FOURTH BASED ON SINGLE LANGEST CONSUMER (DIAZO COPY BACKLINE, 1,2 KD). ( (DAE TO A/CA) WILL ACCUMINANTE OTHER COMPONENTS.	E, 1.2 KM). ASSURES 3 PH						

# POUEN CONDUMEN DATABASE (Partial Data) 12/12/91

3	MARKETATAR	VOLTAGE/PHASE	FREMERCY	•	•	£	WE W	¥	
,				n :	1				, ;
2	102245 TOPOGRAPHIC REPRODUCTION SET: FIRESPIRE SEC SENTRALLER WITH	120/200 VAC. 3 PM	~ S	<u>.</u>	<b>R</b>	=	~i =	6 8 8 8 7	2
	<u>INTE:</u> 220 VAC. POWEN EXCLUDES 2-18000 BTU A/CG AUTH SEP. POWEI BALANCING (DUE TO A/CG) WILL ACCOMMODATE DINEN COMPONENTS	POWER BASED ON STHELE LARGEST CONSUMER (SHRTHK WARP SYSTEM, 2.2 KB, 1 PH). ASSUMES 3 PH HEHTS.	P SYSTEM, 2.2 KB, 1 PM). ASSUMES 3	Ē					
102313	TOPOGRAPHIC REPRODUCTION SET: PAPER CONDITIONING SEC SENITLA MID 120/208 VAC, 3 PM	ID 120/208 VAC, 3 PH	60 HZ	0.600	<b>8</b> .80	#	~	2.000	8
	<u>NOTE:</u> 115 W.C. FOWER EXCLUDES 2-18000 BTU A/Cs AUTH SEP. PI BALMACING DUE TO A/Cs.	POWER CONSISTS OF EXAMIST BLOWER (.) AND LIGHTS (.48 KM, 40 W PER BULD). ASSUMES 3 PH	S (.48 KW, 40 W PER BULD). ASSUMES	Ē					
T03166	TOPOGRAPHIC SUPPORT SET: DISTRIBUTION SECTION SENITRAILER INTO	240/416 VAC, 3 PH; 120/208 VAC, 3 PH	60 HZ	12.400	% . 466	=	~	2.000	8
	<u>HOTE:</u> 220 VIC. POWER EXCLUDES 2-18000 BTV A/C& AUTH SEP. POW ASSUMES 3 PH BALANCING WILL ACCOMMODATE OTHER COMPONENTS	POWER BASED ON SINGLE LARGEST CONSUMER (SHNEDDER/COMPACTER, 8.26 KM, 220 VAC, 1 PH). Ents.	DMPNCTER, 8.25 KM, 220 VAC, 1 PH).						
100233	TOPOGRAPHIC SUPPORT SET: COMPILATION SECTION SENITRALLER MOUNTED 120/208 VAC, 3 PH	ED 120/208 VAC, 3 PH	60 HZ, 50 HZ	4.50	6.600	=	~i	2.000	8
	NOTE: 115 VAC. POWER EXCLUDES 2-18000 BTV A/CA AUTH SEP. POWER DASED ON SINGLE LARGEST CONSUMER (STEREO PLOTTER, 1.5 KM). ASSUMES 3 PH BALANCING (DAE TO A/CA) BILL ACCIDINDANTE OTHER COMPONIENTS.	YOUER DASED ON SINGLE LANGEST CONSUMER (STEREO PLO	TTER, 1.5 KW). ASSUMES 3 PH DALANCO	<b>9</b>					
T03673	TOPOGRAPHIC SUPPORT SET: INFORMATION SECTION SENITRAILER MOUNTED 120/206 VAC, 3 PH	ED 120/208 VAC, 3 PH	60 HZ, 50 HZ	3.600	10.400	=		2.000	8
	HOTE: 115 VAC. FORER EXCLIDES 2-18000 BTU A/Ca AUTH SEP. FOWER BASED ON SINGLE LANGEST CONSUMER (DIAZO COPY MACHINE, 1.2 KM). ASSUMES 8 PH. BALANCING (DUE TO A/Ca) WILL ACCOMMONTE OTHER COMPONENTS.	TOWER BASED ON SINGLE LANGEST CONSUMER (DIAZO COPY BATS.	INCHINE, 1.2 KM). ASSUMES 8 PH						
103801	TOPOGRAPHIC SUPPORT SET: DRAFTING SUPPORT SECTION SENITRAILER ND 120/206 VAC, 3 PM	ID 120/208 VAC, 3 PH	50 HZ	3.450	10.000	=		2.000 1	8
	<u>HOTE:</u> 116 VAC. POWER EXCLUDES 2-18000 BTU A/CA AUTH SEP. POWER BALLACINED COMPONERTS.	POWER BASED ON SINGLE LANGEST CONSUMER (COMPOSING WACHINE, 1.16 KB). ASSUMES 3 PHINENTS.	MCHINE, 1.15 (D). ASSUMES 3 PH						
106613	TOPOGRAPHIC SUPPORT SET: MAINTENANCE/STORNGE SEC SENITRALLER INTO 120/206 VAC, 3 PM	TD 129/208 VAC, 3 PH	50 HZ	3.88	<b>8</b> . 700	=	= 5.	2.000 0	8
	INTE: 115 VAC. POWEN EXCLUDES 2-18000 BTV A/C4 AUTH SEP. POWEN BASED ON SINGLE LANGEST CONSUMEN (GRINDEN, 1 KD). ASSUMES 3 PH BALANCING (DUE TO A/C4) WILL ACCOMMONTE OTHER CONFORENTS.	ROWER BASED ON STRELE LANGEST CONSUMER (GRINDER, )	KIP). ASSINTES 3 PH BALLNICHIG (DUE 1	9					
ā	TOGGG TOPOGRAPHIC SUPPORT SET: OPERATIONS SECTION SENITRAILER MOUNTED 120/204 VAC, 3 PH	0 120/206 VAC, 8 PH	2H 98	.50	7.30	*	1 2.	2.000	8
	<u>HOTE:</u> 115 VAC. POWER EXCLUDES 2-18000 BTU A/Ca AUTH SEP. POWER BASED ON SINGLE LARGEST CONSUMER (VACUUM CLEANER), .5 KW). (DUE TO A/Ca) WILL ACCOMMODATE OTHER COMPUNENTS.	POWER BASED ON STRGLE LARGEST CONSUMER (VACUUM CLE	MER, .6 KP). ASSURES 3 PH BALANCING	<b>©</b>					
ş	106749 TOPOGRAPHIC SUPPORT SET: RECTIFIER II SECTION SENITRAILER NTO	120/208 VAC, 3 PH	50 HZ	7.950	22.100	*	.2	2.000 1	<b>8</b> .
	INTE: 115 VAC. POWER EXCLUDES 2-18000 BTV A/Cs AUTH SEP. POWER BASED ON SINGLE LANGEST CONSUMER (PROTOGNAMETRIC POSITIONING SYSTEM, 2.65 KB) ASSIMES 3 PH BALANCING (DUE TO A/Cs) WILL ACCOMMODATE OTHER COMPONENTS.	POWER BASED ON SUMBLE LANGEST CONSUMER (PAOTOGRAME) OTHER CONFORENTS.	TAIC POSITIONING SYSTEM, 2.65 KD).						

# FORTH COMMENT DATABLE (Partie) Deta)

3	MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MANUAL MA	WI TARLTHEE	FEBRUARY		¥		W.		
<b>7188</b> 17	TOPOGRAPHIC SUPPORT SET: STORAGE RETRIEVAL SECTION SCHITILE BTD.	120/288 W.C. 3 PH	22 <b>88</b>	3.	2.78	=	~	2.88	8
	<u>INTE:</u> 115 W.C. FOURT EXCLUGE 2-1880 BTV A/CA AUTH SEP. FOURT ( A/Ca) WILL ACCOMMONTE OTHER COMPONENTS.	POWER DASED ON SIMPLE LANDEST CONSUMER (WICHMA, .6 ICM).	ASSURES 3 PH BALANCING (DUE TO	_					
100 IS	TOBIGO TEST SET COMMITEMENSMES SET: TS-2006()/ALG-156(V)	120 WC, 1 PH	2H 000	9.50	4.30	=	-2	2.00	8
	MITE: 116 WC.								
T04623	TOPOGRAPHIC SUPPORT SET: MOSALCKHIS/DNAFTING SEHITN, MOUNTED	120/208 VAC, 8 PH	<b>22 08</b>	- <b>36</b>	<b>6</b> . <b>4</b> 0	=	H 2.000		8
	HOTE: 115 W.C. POIER EXCLUDES 2-18000 BTU A/CA AITH SEP. POIER BASED ON SHIGLE LANGEST CONSLIER (SEALING INCHINE, 1880). ASSURES 3 PH BALANCING (DUE TO A/CA) 911, ACCOMPODATE OTHER CONFORDINS.	ASED ON SINGLE LARGEST CONSUMER ISEALING INCHINE,	. BERT). ASSURES 3 PH BALAKCH	•					
700025	TOPOSAMMIC SUPPORT SET: RECTIFIER I SECTION SENITMILEN HOURTED 120/200 UAC, 3 PH	/208 UAC, 3 PH	5H 05, 50 HZ	11.700	22.500	-	**	2.000	8
	MOTE: 115 W.C. FOREN EXCLUDES 2-14000 BTU A/Cs. AUTH SEP. FOUEN INCLUDES COMINATION OF SELECTED COMPONENTS: ID, 240 W.C.). CENTRIFUSAL FURP. (2 KM). AND PHOTOGRAPHIC SHIK. (1.75 KM). ASSUES 8 PH BALANCHIG.	18000 BTU AVGA ANTH SEP. FOURTH INCLUDES COMMINATION OF SCLECTED COMPONENTS: PHOTO UMP (2 ND), AND PHOTOGRAPHIC SHEK (1,75 ND). ASSUMES 8 PH BALANCHING.	PHOTOGRAPHIC FILLI PROCESS INCHINE (4.3	4.3					
T08642	TOBBES TACT PADAR THEST GENERATOR: ANJTPG-T4	120 VAC, 1 PN; 240 VAC, 1 PN, 28 VDC	60 HZ, 400 HZ, DC	3.000	25.98	=	2.	2.000	8
	1011 115 OR 200 VAC.								
10 <b>9</b> 751	100751 TEST SET MONITOR ASSY: GAS TURBLINE ENGINE GT404	28 VDC		0.030	.8	=	-2	2.000	8
	MIL.								
- 10 <b>98</b>	SHOP EQUIPMENT ARTILLERY NEPAIR SHELTER MOUNTED:	120 VAC, 1 PH	80 HZ	90.0	6.700	-	2	2.800	8
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL (.7 KM), BONE SCOPE (.1 KM), AND LIGHTS (.1 KM)	DRILL (.7 KB), BORE SCOPE (.1 KB), AND LISHTS (.	.1 (8).						
10906	SNOP EQUIPMENT BATTERY SERVICING SHELTER MOUNTED;	120 VAC, 1 PH	60 HZ	46	13.000	724	.2	2.000 1	8
	MOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: BATTERY CHARGER (1.39 KB) AND LIGHTS (.1 KB)	BATTERY CHARGER (1.38 KB) AND LIGHTS (.1 KB).							
110038	SHOP EQUIPMENT CAMMAS AND GLASS SHOP SHELTER INDURITED:	120 VAC, 1 PH	60 HZ	8	9.16	=	~:	2.000	8
	MOTE: 115 VAC. POWER HICLUDES COMBINATION OF SELECTED COMPONENTS: BELT SANDER (1 KW) AND LIGHTS (.1 KW).	BELT SAIDER (1 KW) AND LIGHTS (.1 KW).							
110275	SHOP EQUIP ELEC NEP SENITHLA UTD: ANNY	120/208 VAC, 3 PH	60 HZ, 50 HZ	9.500	<b>99</b> . 99	=	<b>=</b> 2.	2.000 0	3.0
	MOTE: 10 KM GEN SET IS AUTHORIZED SEPARATELY. POWER INCLUDES 24000 BTV A/C (NSN 4120-00-902-2548).	9 BTU A/C (NSH 4120-00-902-2548).							

3		W.T. S. C. C. C. C. C. C. C. C. C. C. C. C. C.	FREMENT		1	2			
110429	TIBAZO SKIOP EQUIP ELECTRONIC TESTING AND NEPAIR SKELT NTD: DS/65(VADS)	120/208 VAC, 3 PM; 120 VAC, 1 PH	400 HZ	12.700	67.000	=	= 2	2.000	8
	MOTE: POWER HACLUDES 2-18000 BTU A/Cs. (A24592).								
11044	SHOP EQUIPMENT ENGINE FUEL AND ELECT SYSTEM NEPR SHELTER WITD:	120 MC, 1 PM	2H 09	1.240	26. <b>36</b>	=	- 3	2.900	8
	MOTE: POWER INCLUDES COMPINATION OF SELECTED COMPONENTS: HAP-	HIPACT WRENCH (.44 KB) AND LIGHTS (.8 KB).							
110800	SIOP EQUIPMENT QUIDED MISSILE: AUX EQUIPMENT MAINT (CHAPMANA)	120 VAC, 1 PH	90 HZ, 50 HZ	0.200	 60 1.	=	=	2.000	8.
	BOTE: 115 VAC.								
11081	TEST EQUIPMENT: AUTOMATIC (ATE) (WANK)	120 VAC, 1 PH; 240 VAC, 1 PH	50 HZ, 50 HZ	10.000	2 X	<b>=</b> .	-	2.000	8
	LOTE	-							
113346	T13346 TACTICAL COMP TEMBRIAL: ANUMO-30	120 VAC, 1 PH; 240 VAC, 1 PH, 28 VDC	60 MZ, 50 MZ, 400 MZ, DC	1.725	14.380	=	<b>2</b>	2.900	8
	NOTE:								
113595	TACTICAL COMPUTOR TERMINAL: ANJUND-30A	120 VAC, 1 PH, 28 VDC	60 HZ, 50 HZ, 400 HZ, DC	0.045	9.48	=	-	2.000	8.
	HOTE: 115 VAC. LIN 277026 CAMBED PER SB 700-20 APPENDIX E 80061.	1061.							
113751	T13751 TEST SET AIRBORNE LASER TRACKER: MAJANN-65	120 VAC, 1 PH, 28 VDC	400 HZ, DC	0.240	2.000	=	~	2.000	8.
	100E: 115 VAC.								
114441	SHOP EQUIPMENT GUIDED MISSILE SYSTEM: AN/TSM-86 (CHAPMENL)	120/208 VAC. 3 PH	2H 00+	<b>36</b> .000	128.100	<b>&gt;</b>	=	2.000	38
	101E: POWER INCLUDES 2-18000 BTV A/CA (A246A2) AND WAS A 30 KM 400 HZ GEN SET.	1 400 HZ GEN SET.							
114486	SHOP EQUIPMENT: QUIDED BISSILE SYSTEM AN/TSM 94 (LCSS)	120/208 W.C. 3 PH; 120 VAC, 1 PH	400 HZ	24.500	<b>\$</b> 2.000	=	*	2.000	8.
	MOTE: MUST DE USED WITH AN/TSM-82. POWER INCLUDES COMBINATION SUPPLIED TA AND ELECTRICAL OU	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 2-18000 BTV A/Cs (6.5 KM EACH), AUXILLARY WEATER (TO KM, 3PM), AND ELECTRICAL OUTLETS (2.5 KM), SELECTRICAL OUTLETS (2.5 KM), SELECTRICAL OUTLETS (2.5 KM), SELECTRICAL OUTLETS (2.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SET INCLUDES OF KM, 3 CM, SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL OUTLETS (3.5 KM), SELECTRICAL O	JOH), AUXILLARY HEATER (TO NO NZ BEN.						
T15581	TIESOT SKOP EQUIPMENT HISTRADERT AND FIRE CONTROL REPAIR SKELTER HTD: 120 VMC, 1 PH	120 VAC, 1 PH	50 HZ	0.00	6.700	=	=	2.000	8
	MOTE: 115 VAC. POWER HYCLUGES COMPTINATION OF SELECTED COMPO	BLINATION OF SELECTED COMPONENTS: URLLL (.7 KM) AND LIGHTS (.1 KM).							
115040	SHOP EQUIPMENT UNCHINE SHOP: FILHEAVY LESS POWER	120/208 VAC, 3 PH	2H 00	5.18	18.900	=	-	2.000	8.
	HOTE: POWEN INCLUDES COMBINATION OF SELECTED COMPONENTS: LAT	SELECTED COMPONENTS: LATHE (5 NS) AND LIGHTS (.1 NS).							
		*							

3	WALLARGE THANKS		Property	21	N		WE SE	<b>X</b> tl	
73643	TISSAI SNOP EQUIPMENT MACHINE SNOP: FIR HEARY SUPPL NO 1 LESS POWER 246/416 VAC, 3 PH; 120/206 VAC, 3 PH	108 VAC, 3 PH	211 03	9.900	15.200	=	2.800	98.0	10
	HOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: MILLING MACHINE (1.5 KM, 240/416 VAC, 3 PH), BAND SAW (1.5 KM, 120/200 VAC, 3 PH), AND DRILL (1 KM, 120 VAC, 1 PH).	1416 VAC, 3 PH), BAND SAW (1.	6 KM, 120/208 VAC, 3 PH), AMD	111186					
115644	SHOP EQUIPMENT MACHINE SHOP: FIE DASIC LESS POWER		24 08	1.600	13.300	#	1.900	8	2
	INTE: 116 VAC. POWER HICLUDES COMBINATION OF SELECTED COMPONENTS: LATHE (1.5 KB), AND LIGHTS (.1 KB).	LIGHTS (.1 KB).							
T:6666	S SHOP EQUIPMENT MACHINE SHOP SHELTER MOUNTED: 120 VAC, 1 PH; 240 VAC, 1 PH	Ξ.	60 HZ	1.600	13.300	=	A 2.000	8	2
	HOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: LATHE (1.5 Kg) AND LIGHTS (.1 Kg)	. (4)							
T15675	SHOP EQUIPMENT MECHANICAL MAINTENANCE SHELTER MOUNTED: 120 VAC, 1 PH		2H 09	9.80	9.400	*	1 2.000	8.	2
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL (.99 KM) AND LIGHTS (.2 KM)	LIGHTS (.2 KM).							
1,600	T18000 SNOP EQUIPMENT PADIATOR TEST AND REPAIR; DA MGS AND SERVICE NO 4 120 VAC, 1 PH		60 KZ	000.1	6.300	-	¥ 2.000	96.0	2
	HOTE: POWER BASED ON SINGLE LARGEST CONSUMER (LOAD TEST MACHINE, 1 KB).								
116006	SHOP SET AVIATION INTERNED MAIN: ELECTRICAL INSTRUMENT AINDIGELLE 120/208 VAC, 3 PH		80 HZ, 50 HZ	1.770	4.900	=	N 2.900	9.1	2
	NOTE: 116 VAC. POWER EXCLUDES 2-18000 BTU A/C. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: SOLDERING IRON (.1 KM), SOLDERING GAM (.11 KM), AND POWER SUPPLY PP-1104 (1.58 KM). ASSUMES 3 PH BALANCING DUE TO A/Cs.	COMPONENTS: SOLDERING IRON	I (.1 KIN), SOLDERING GUN (.11 K	8					
116007	SHOP SET AVIATION HATERMEDIATE MAINT: MACHINE SHOP AIRMOBILE 120/208 VAC, 3 PH		50 KZ	2.250	6.250	=	N 2.000	8	9
	NOTE: 115 VAC. POWER EXCLUDES 2-18000 8TV A/CS. POWER BASED ON SINGLE LARGEST CONSUMER (BAND SAW, .75 KW). ASSUMES 3 PH BALANCING DUE TO A/CS.	ir (band saw, .75 km). Assum	ES 3 PH BALANCING DUE TO A/Cs.						
T16008	SHOP SET AVIATION INTERNEDIATE NAINT: POWER TRAIN AIRNOBILE 120/208 VAC, 3 PH		60 HZ	4.320	12.000	=	N 2.000	8:-	9
	HOTE: POWER EXCLUDES 2-18000 BTU A/C. POWER BASED ON SINGLE LARGEST CONSUMER (HEAT GUM, 1.44 KM). ASSUMES 3 PH BALANCING DUE TO A/Cs.	I, 1.44 KW). ASSUMES 3 PH BA	JANCING DUE TO A/Cs.						
T16009	SHOP SET AVIATION INTERMEDIATE MAINT: ROTOR AIRMOBILE 120/208 VAC, 3 PH		60 HZ	1.500	4.200	=	N 2.000	1.90	9
	MOTE: 116 VAC. POWER EXCLUDES 2-18000 8TU A/Ca. ASSUMES 3 PH BALANCING DUE TO A/Ca.								
T16010	TIBOIO SHOP SET AVIATION INTERNEDIATE MAINT: SHEET METAL AIRMOBILE 120/208 VAC, 3 PH		60 HZ	4.320	12.000	_	N 2.000	8	9
	MOTE: 115 VAC. POWER EXCLUDES 2-18000 BTU A/Cs. POWER BASED ON SINGLE LARGEST CONSUMER (HEAT GIM, 1.44 KM).	SR (MEAT GUN, 1.44 KM).							

=	<b>MERCATUR</b>		VALIME/THATE			Ħ		KE I	<b>W</b>	<b>X</b> i
200		SHOP SET AVIATION INTERMEDIATE MAINT: TOOL CRIB AINNOBILE	120/206 VAC, 3 PH	60 HZ, 50 HZ	12.100	33.60	=	7	2.000	8
		115 VAC. POWER EXCLUDES 2-18000 6TU A/C (A24463). KW, 1 PH). ASSINES 3 PH BALANCING. ADD SOURCE-BOB	FOURTH HICLUDES COMBINATION OF SELECTED CONPONENTS: COMPRESSOR (10 KB), 3 PH), AND DRILL 1.7 LUCKER, ANSOM, (817)287-6006.	PRESSOR (19 KD), 3 PH), AND DRILL	1.7					
116012	35 25 35	FIGO12 SHOP SET AVIATION INTERNEDIATE MAINT: TURBINE ENGINE AIRWOBILE	120/208 VAC, 3 PH	SH 15	5.800	5.300	=	7	2.990	8
	E E	POWER EXCLUDES 2-18000 BTU A/Cs. ASSUMES 3 PH BALANCING DUE TO A/Cs.	S DUE TO A/Ca.							
18687		SHOP EQUIPMENT SMALL ARMS REPAIR SKELTER INDUNTED:	120 VAC, 1 PV	50 HZ	0.600	9.600	*	~	2.900	8.
		POWER INCLUDES COMPINATION	OF SELECTED COMPONENTS: GRINDER (.6 KM) AND LIGHTS (.1 KM).							
718617	SHOP EG	F16617 SWOP EQUIPMENT SMALL EQUIPMENT REPAIR SWELTER LOADED:	120 W.C., 1 PH	ZH 99	0.590	4.900	=	-	2.000	8.
		HOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL (.46 KB) AND LIGHTS (.13 KB).	BITS: DRILL (.46 KB) AND LIGHTS (.13 KB).							
118714	SHOP ED	SNOP EQUIPMENT WELDING: FIELD INVITTEMNICE	120 VAC, 1 PH	B0 H2	 8	9.200	=	=	2.000	98.0
	E E	NOTE: 116 VAC. POWER HICLUDES COMBINATION OF SELECTED COMPONERTS: BAND SAW (1 KM) AND LIGHTS (.1 KM).	BIFS: BAND SAW (1 KM) AND LIGHTS (.1 KM).							
11668	SHOP EG	SHOP EQUIPMENT WELDING SHELTER MOUNTED:	120 VAC, 1 PH	\$0 KZ	0.800	6.700	-	-	2.000	8.
		NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL (.76 KM) AND LIGHTS (.1 KM).	BATS: DRILL (.76 KB) AND LIGHTS (.1 KB).							
188 188 1	SHOP EQ	SHOP EQUIP WOODWORK BASE MAINT: TRLR INTO (APPr)	240/416 VAC, 3 PH	60 HZ	2.990	13.000	-	۲ 2	2.900	99.
•										
716495		SHOP SET ACFT MAINT GRAD HANDLG AND SERVING: SET C AVIN NON DIV	28 VDC	R	8.800	314.000	*	2	2.900	8
		POWER INCLUDES COMBINATION	OF SELECTED COMPONENTS: CHANES (2), DILER AND PICKLER. SET NAS AC POWER REQUINGMENT LISTED SEPARATELY.	ENENT LISTED SEPARATELY.						
10486	33 908	SHOP SET ACFT MAINT GRUD HANDLG AND SERVING: SET C AVIN NON DIV	120 VAC, 1 PH	80 HZ	.600	13.900	=	7	2.000	8
		INS VAC. SHOP SET MAS DC POWER REQUIREMENT LISTED SEPARATELY	MTELY.							
T20701	TAMESE	720701 TRANSMITTER: T-1373/TRQ-36(V)	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	.500	13.000	=	7	2.900	8.
		MOTE: 115 OR 230 VAC. 47-440 HZ.								
720881	<b>TEST 96</b>	720861 TEST SET HISTRIMENT DISPLAY SYSTEM BENCH:	28 VDC	8	0.065	3.000	=	-	1.180	8
	NOTE:	SET INCLUDES AC POWER REQUIREMENT LISTED SEPARATELY.								

3	MINISTALIA	VOLTABE/PINSE	FIREMENT	<b>3</b> 1	<b>3</b>		Ĩ,		<b>k</b> i
120061	TEST SET HISTRIMENT DISPLAY SYSTEM BENCH:	120 W.C., 1 PH	400 HZ	9.00	0.5	=	=	81.1	8.
	HOTE: SET INCUTES OC POWER REQUIREMENT LISTED SEPNANTELY.			,					
122331	SHOP SET ACFT IMMIRT STUR BITO: C-2 ELEC SHOP AVIR HON-DIV	120 VAC, 1 PH	60 HZ, 50 HZ	5.280	45.900	=	=	2.000	8.
	NOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 2-6A (CD).	SELECTED COMPONENTS: 2-BATTERY CHARGER (.69 KM EACH), COMPRESSOR (2 KM), GRINDER (.5 KM), AND HEAT GUN (1.4	ER (.5 KB), AND HEAT GUN (1.4						
T22468	SHOP SET ACFT INNINT STLR NTD: C-3 FLAW DETECTION AVIN HON-DIV	240 VAC, 1 PH; 120 VAC, 1 PH; 120/206 VAC, 3 PH	60 HZ, 50 HZ	14.200	90.900	=	=	2.000	8
	MOTE: SET REQUIRES 14.2 KW 1 PM FOR MAGNETIC INSPECTION UNIT AN	INMANETIC INSPECTION UNIT AND 3 PH POWER FOR 2 COMPRESSORS. SELECTIVE USE OF EQUIPMENT IS SATISFIED BY 10 KM, 1-3 UKER, ANSCOM, (817)287-6006.	UIPNENT IS SATISFIED BY 10 KB.	<u>.</u>					
122805	SHOP SET ACFT IMAINT STLR HTD: C-4 SHEET HETAL AVIH HON-DIV	120/208 VAC, 3 PH; 120 VAC, 1 PH	80 HZ, 50 HZ	3.500	9.700	=	=	2.000	8
	MOTE: 116 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONE	INATION OF SELECTED COMPONENTS: COMPRESSOR (2 KM, 3 PH) AND GRINDER (.5 KM, 1 PH). ASSUMES 3 PH BALANCING	H). ASSUMES 3 PH BALANCING.						
122742	SHOP SET ACFT MAINT STLR BTD: C-6 WELDING AVIN HON-DIV	120 VAC, 1 PH	60 HZ, 50 HZ	7.250	63.900	=	=	2.000	8.
	MOTE: 115 VAC. POWER EXCLUDES 200 AMP ARC WELDER AUTH SEP. P. TREATING FURWACE (5 KM), AND CRILLE (1 KM).	AMP AND WELDER AUTH SEP. POWER INCLIDES COMBINATION OF SELECTED COMPONENTS: 69 Drill (1 kg).	GRINDER (.5 KB), SAB (.75 KB), HEAT	3					
122879	SHOP SET ACFT MAINT STLR MTD: C-6 MACH SHOP AVIB HON-DIV	120 VAC, 1 PH	60 HZ, 50 HZ	2.600	22.600	=	-	2.000	8.
	MOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONE	INATION OF SELECTED COMPONENTS: LATHE (.75 KM), BAND SAN (.75 KM), DRILL (.8 KM), AND.LIGHTS (.2 KM).	), AND.LIGHTS (.2 KB).						
123016	723016 SHOP SET ACFT MAINT STUR MTD: C-7 ENG AND HYD AVIN NON-DIV	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ	3.200	27.800	*	2	2.000	8.1
	HOTE: 116 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONE	INNTION OF SELECTED COMPONENTS: COMPRESSOR (2 NW), 2-DRILL (.6 NW EACH), AND LIGHTS (.2 NW).	GHTS (.2 KW).						
723153	SHOP SET ACFT BAINT STLR HTD: C-8 INSTRUMENT SHOP AVIN HON-DIV	120/208 JAC, 3 PH	2H 09	3.600	10.000	=	~	2.000	8.
	NOTE: 115 VAC. POWER EXCLUDES A/Cs (2 PH) AUTH SEP. POWER INCLUDES COMBINAT (.8 KW) AND 6-LIGHTS (.1 KW EACH). ASSUMES 3 PH BALANCING DUE TO A/Cs.	POWER INCLUCES COMBINATION OF SELECTED COMPONENTS: SOLDERING GUN (1 KW), LATNE (1 KW), DRILL 1 Balancing due to A/Cs.	GUN (1 KIN), LATHE (1 KIN), DRI	<b>ಪ</b>					
123290	123280 SHOP SET ACFT MAINT STLR MTD: C-9 PROP AND ROTOR AVIM NON-DIV	240/416 VAC, 3 PH; 120/208 VAC, 3 PH; 120 VAC, 1 PH 60 HZ	60 HZ	6.200	14.300	=	<b>2</b>	2.000	8.
	HOTE: 115 VAC. POWER HICLUDES COMBINATION OF SELECTED COMPONE	HINATION OF SELECTED COMPONENTS: COMPRESSOR (2 KM, 240/416 VAC, 3 PH) AND HEAT GUN (1.4 KM, 1 PH). ASSURES 3 PH	UN (1.4 KM, 1 PM). ASSUMES 3	Æ					

		18/21/21							
=	A SWINT TO SHOW	YA, TARE PAUSE	FREGUENCY	큠	<b>9</b>	뜀	ZZ.	184	<b>I</b>
123427	SHOP SET ACIT MAINT STLR WID: C-11 POWERTRAIN AVIM NON-DIV	240/416 VAC, 3 PH; 120/206 VAC, 3 PH; 120 VAC, 1 PH 60 HZ	50 HZ	3.500	7.000	#	=	2.000	8.
	<u>NOTE:</u> 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENT BALANCING.	BINATION OF SELECTED COMPONENTS: COMPRESSOR (2 KM, 240/418 VAC, 3 PH) AND GRINDER (.5 KM, 1 PH). ASSUMES 3 PH	ER (.6 KM, 1 PH). ASSUMES 3 PH						
724523	I SHOP EQUIPMENT ARTILLERY MAINTEMANTE: FIELD MAINT SET IN LESS PUR 120 VAC, 1 PH	120 VAC, 1 PH	24 09	1.866	14.00	*	=	2.000	8.
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENT	BINATION OF SELECTED COMPONENTS: HEAT GAN (1.6 KM) AND LIGHTS 1.006 KM).							
124880	SHOP EQUIPMENT AUTOMOTIVE MAINT AND REPAIR: FM BASIC LESS POWER 120 VAC, 1 PH; 240 VAC, 1 PH	120 VAC, 1 PH; 240 VAC, 1 PH	ZH 09	1.900	16.500	=	=	2.000	8
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENT	BINATION OF SELECTED COMPONENTS: DRILL (1.16 KM) AND GRINDER (.75 KM).							
125619	725619 SWOP EQUIPMENT AUTO MAINT AND REPAIR; FIN SUPPLIND I LESS POWER 120 VAC, 1 PH; 240 VAC, 1 PH	20 VAC, 1 PH; 240 VAC, 1 PH	60 HZ	1.065	8.200	₩.	=	2.000	0.85
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENT	BINATION OF SELECTED COMPONENTS: GRINDER (1 KR) AND LIGHTS (.065 KR).							
125756	SHOP EQUIPMENT AUTO MAINT AND REPAIR:	FIL SUPPL NO 2 LESS POWER 120/208 VAC, 3 PH; 240/416 VAC, 3 PH	2H 09	5.300	14.700	=	*	2.000	0.85
	MOTE: POWER BASED ON SINGLE LARGEST CONSUMER (RADIAL SAW, 5 KW, 120/208 VAC, 3 PH) AND LIGHT (.1 KW, 1 PH).	120/208 VAC, 3 PH; AND LIGHT (.1 KW, 1 PH).							
125961	SHOP SET ANY INTILED MAINT DIV: ARMANDIT REPAIR	120/208 VAC, 3 PH	50 HZ	4.200	11.700	=	=	2.000	8.
	NOTE: POWER EXCLUDES 2-18000 BTV A/Cs. POWER BASED ON SINGLE LARGEST CONSUMER (HEAT GIN 1.4 KM). ASSUMES 3 PH BALLANCING DUE TO A/Cs.	rest consumer (heat gun 1.4 km). Assumes 3 PH Balla	UNCING DUE TO A/Cs.						
125981	SHOP SET AVIATION INTERNEDIATE MAINT: DIV FIRE CONT RPR SALT NTD 120/208 VAC, 3 PH	20/208 VAC, 3 PH	50 HZ	3.400	9.400	=	=	2.000	8.
	NOTE: POWER EXCLUDES 2-18000 A/Cs (A24483); ASSUMES 3 PH BALANCING DUE TO A/Cs.	ING DUE TO A/Cs.							
126030	SHOP SET CONTACT AND EMERGENCY REPAIR: FIL LESS FOWER	120 VAC, 1 PH	80 HZ	0.89.0	2.48	=	=	2.000	8.
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED CONFONENT	HIMATION OF SELECTED COMPONENTS: DRILL (.89 KM) AND LIGHTS (.2 KM).							
128261	TEST SYS AUTO DEP MAINT AMALOG/DIGITAL: TSEC/ST-61	120/208 VAC, 3 PH	80 HZ, 50 HZ	98.900	300.000	*	=	2.800	8.
	MOTE: 112-128 VAC. 57-63 NZ.								
130377	180377 TOOL OUTFIT HYDRAILIC SYSTEM: TEST AND REPAIR 3/4 TON TLR MTD 1	120 VAC, 1 PH	50 HZ	0.46	88.7	=	_	2.000	98.0
	HOTE: 115 VAC.								
130414	730414 SHOP EQUIPMENT FUEL AND ELECT SYSTEM ENGINE: FIN BAS LESS POWER 2	28 VDC	8	2.800	.08	=	=	2.80 2.80	8
	INTE: SET MS AC POWER PROVINCIENT SEPARATELY LISTED.								

3	HOMENCLATURE		YO, TAGE / PLASE	FRENERCY			¥.	V/FI	썲	M:
130414	130414 SKOP EQUIPMENT FUEL AND ELECT SYSTEM ENGINE: FIN BAS LESS POWER	YSTEN ENGINE: FIN BAS LESS POWER	120/208 VAC, 3 PH	60 HZ	22.500	73.500	*	-	2.000	99.0
	NOTE: 115 VAC. POWER BASED	ON SINGLE LANGEST CONSUMER (AUTO (	<u>note:</u> 116 vac.  Power based on single largest consumer (auto generator test stand, 22.5 kW, 3 PH).							
T31784	131784 SHOP EQUIP INSTR AND FIRE CONT SYS REPAIR: FILBASIC LESS PONER	SYS REPAIR: FIL BASIC LESS POILER	120 VAC, 1 PM	60 HZ	0.765	9.400	=	-	2.000	8.
	HOTE: 115 VAC. POWER INCLUD	ES COMBINATION OF SELECTED CONFON	HOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL (.7 KM) AND LIGHT (.065 KM).							
133017	133017 SHOP SET MECHANICAL EMERGENCY REPAIR:	ERAIR: BASIC	120 VAC, 1 PH	60 HZ	1.350	11.250	=	-	2.000	0.85
	NOTE: 115 VAC. POWER INCLUD	ES COMBINATION OF SELECTED CONPONE	INTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: DRILL, GRINDING MACHINE, "AND LIGHTS.							
135651	735651 TEST SET RECEIVER: AN/ARM-180()		120 VAC, 1 PH	60 HZ, 50 HZ	0.270	2.600	=	=	2.000	0.90
	NOTE: 115 VAC.									
T4203	142031 TEST SET PROCESSOR: AN/APH-415		120 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	0.290	2.500	*	*	2.000	8.
	NOTE: 115 VAC. 50-420 HZ.									
14866	148686 TEST SET: TOP SUBSYSTEM (TOP 2)		28 VDC	8	0.170	9.000	*	*	2.000	8.
	NOTE:									
148861	148861 TEST SET MAGNETIC TAPE TRANSPORT: TS-4002/UTH-5	T: TS-4002/UYH-5	120 VAC, 1 PH	60 HZ	0.600	9.000	=	=	2.000	8.
	NOTE:									
149324	149324 TEST SET TRANSPONDER: AN/APH-378	•	120 VAC, 1 PH, 28 VDC	60 HZ, 50 HZ, 400 HZ, DC	0.048	0.400	*	=	2.000	8.
	NOTE: 103-127 VAC. 50-420 HZ.	Z. 25-31 VDC.								
149392	149392 TEST SET TRANSPONDER: AN/APN-421	_	120 VAC, 1 PH, 28 VDC	400 HZ, DC	0.360	3.000	=	=	2.000	8
	MOTE: 103-127 VAC. 380-420	MOTE: 103-127 VAC. 380-420 HZ. 16-36 VDC. CONSUMES .086 KM FOR DC.	FOR DC.							
149696	TEST STATION ELECTRONIC EQUIPMENT: AN/USH-410(V)	NT: AN/USH-410(V)1	120/208 VAC, 3 PH	60 HZ	900.09	167.000	*	*	2.000	1.00
	NOTE:									
152849	152849 TEST SET ELECTRONIC SYSTEMS: DIRECT SUPPORT (DSESTS)	RECT SUPPORT (DSESTS)	28 VDC	8	1.200	90.00	*	#	2.000	8
	NOTE: 18-30 VDC.									

# ONER CONSUMER DATABASE (Partial Data) 12/12/81

		18/21/21							
릐	MOBICATIVE	VOLTAGE/PLASE	PREMERCY		활		WFI SF	<b>E</b> i	
153471	TS3471 TEST SET AVIATORS NIGHT VISION INAGING SYSTEM: TS-3895/UV	120 VAC, 1 PH; 240 VAC, 1 PH, 28 VDC	60 HZ, 50 HZ, DC	9.014	0.130	=	2.(	2.000 1.	8
	MOTE: 110 OR 220 VAC.								
158130	SHIBULATOR SET: AM/USH-393	120/208 VAC, 3 PM	2н 09	17.200	47.800	=	2.(	2.000 1.	8
	HOTE: POWER EXCLUDES 4-18000 BTU A/Cs (A24455). AR 310-34 STATE	AR 310-34 STATES THAT A/C IS AUTHORIZED WHEN CLIMATIC CONDITIONS DICTATE IAN TOE AUGMENTATION TABLE.	ICTATE IAN TOE AUGMENTATION TA	BLE.					
158491	SIBULATOR STATION: PADAR SIGNAL ON SYSTEM (HANK)	240/416 VAC, 3 PH	400 HZ	18.000	25.000	<b>&gt;</b>	3.(	2.000 1.	8.
	NOTE: POWER INCLUDES 38000 BTU, 3PH, 240/416 VAC, A/C (A25277, 9.8 KM)	.8 KOU).							
160337	TEST SET ELECTRICAL ASSY SIMULATOR: 150KH GAS TURB GEN SET	120 VAC, 1 PH	60 HZ, 50 HZ, 400 HZ	0.600	5.000	=	7.(	2.000 1.	8
	WTE:								
161973	181973 TEST FACILITY ELECTRONIC EQUIPMENT: 00-290(V)1/NEM	120/208 VAC, 3 PH	60 HZ, 50 HZ	1.510	4.200	=	<b>3</b> .(	2.000 1.	8.
	NOTE: 115 VAC. POWER EXCLUDES 4-1800C 8TV A/Cs (A24455, 3 PH). POWER INCLUDES COMB (.15 KW EACH) AND 82-LIGHTS (.02 KW EACH). ASSUMES 3 PN BALANCING DUE TO A/Cs	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 3-DIAGNOSTIC TEST INSTRUMENTS Klancing due to a/C4.	3-DIAGNOSTIC TEST INSTRUMENT	رم د					
167961	T87881 TOPOGRAPHIC SUPPORT SET: SURVEY SECTION SENTRALLER MOUNTED	120/208 VAC, 3 PH	60 HZ, 50 HZ	4.090	11.400	*	<b>3</b> 2.6	2.000 1.	8.
	NOTE: 115 VAC. POWER EXCLUDES 2-18009 BTV A/Cs AUTH SEP. POWER AND LIGHTS (.48 KM, 1 PH). ASSUMES 3 PH BALANCING.	POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: PHOTOPOSITIONING SYSTEM (2.65 KM,	PPOSITIONING SYSTEM (2.65 KM, )	£					
T68049	186049 TOPOGRAPHIC SUPPORT SET: SYNTHESIS SECTION SENITRAILER MOUNTED	120/208 VAC, 3 PH	50 HZ	1.800	5.000	=	2.(	2.000 1.	8
	NOTE: 115 VAC. POWER EXCLUDES 2-18000 A/Ca AUTH SEP. POWER BASED ON SINGLE LARBEST CONSUMER (VERTICAL REFLECTING PROJECTOR, .8 KW). ASSUMES 3 PH. BALANCING DUE TO A/Ca.	ED ON SINGLE LANGEST CONSUMER (VERTICAL MEFLECTING P	PROJECTOR, .6 KW). ASSUMES 3	ŧ					
169689	TEST SET BENCH: ADVANCED FLIGHT CONTROL SYSTEM CH-470	120 VAC, 1 PH	400 HZ	0.600	9.00	=	2.0	2.000 1.	8.
	NOTE: 116 VAC. 18PUT REQUIREMENTS DO NOT INCLUDE POWER FOR EQUIRMENT UNDER TEST. SET NAS DC POWER REQUIREMENT LISTED SEPARATELY.	MENT UNDER TEST. SET HAS DC POWER REQUIREMENT LIST	TED SEPARATELY,						
189689	TEST SET BENCH: ADVANCED FLIGHT CONTINOL SYSTEM CH-47D	28 VDC	8	0.140	9.000	*	2.(	2.000 1.	8.
	MOTE: INPUT REQUIREMENTS DO NOT INCLUDE POWER FOR EQUIPMENT UNDER TEST. SET NAS AC POWER REQUIREMENT LISTED SEPARATELY.	1 TEST. SET MAS AC POWER REQUIREMENT LISTED SEPARATE	ELY.						
169694	TEST SET BENCH: INTEGRATED LOWER CONTROL ACTUATOR CH-470	120 VAC, 1 PH	50 HZ	0.840	7.000	=	». «	2.000 1.	8
	NOTE: 115 VAC. INPUT REQUIREMENTS DO NOT INCLUDE POWER FOR EQUIPMENT UNDER TEST.	MENT UNDER TEST.			•				

3	MATERIAL ATTACK	W. 1766/PWS	Residu		Ħ	¥	WE E	
172621	1720ai Test set countemeasures set: Anvala-104a	120/208 VAC, 3 PH	400 HZ	9.400	15.000	-	<del>-</del>	4.000 1.00
	<b>EDTE:</b>							
1798QA	WORSE TACTICAL IMMEENT INTERPRETATION FACILITY: ANTSO-43 LESS POWER	120/206 VAC, 3 PH	60 HZ	938.0	2.500	=	-2	2.000 1.00
	HOTE: FOWER EXCLUDES 30000 BTU ACC (A24000). AR 310-34 STATES THAT ANC IS AUTHORIZEDHEN CLIMATIC CONDITIONS DICTATE IAN TOE AUGUSTIANTION TABLE. POWER INCLUDES CONDINCION OF SELECTED COMPONENTS: TT-76 AND NGC-4. ASSAMES 3 PH BALANCING DUE TO ACC.	TNAT AVC IS AUTHORIZEDINES CLIBATIC CONDITIONS DICTA' 6 AND UGC-4. ASSURES 3 PH BALANCING OUE TO AVC.	TE IAW TOE AUGMENTATION TABLE.					
V28144	VZ8144 TENRINAL TELEPHONE: AN/TOC-66 1.35 PROFIS	120/208 VAC, 3 PM	60 HZ, 50 HZ	4.090	12.000		<b>.</b> 2.	2.000 1.00
	MOTE: 115V AC. POWER EXCLUDES 18008 8TU A/C (A25271, 3KW, 3 P	8000 BTU A/C (A25271, 3KW, 3 PH). ASSUMES 3 PH BALANCING DUE TO A/C.						
V31417	V31417 TEHNINAL TELEPHONE: AN/TOC-40 LESS POWER	120/208 VAC, 3 PH	60 HZ, 50 HZ	2.700	7.500	=	2.	2.000 1.00
	NOTE: 115V AC. POWER EXCLUDES 18000 BTU A/C (A28271, 3KW, 3 P	8000 BTU A/C (A26271, 310), 3 PH). ASSUMES 3 PH BALANCING DUE TO A/C.						
V31419	V31419 TERBINAL TELEPHONE: ANJTOC-61 LESS POWER	120/208 VAC, 3 PM	60 HZ, 50 HZ	6.500	19.900	*	. 2.	2.000 1.00
	HOTE: 1189 AC POWER EXCLUDES 18000 BTU A/C (A26271), ASSUMES 3 PH BALANCING DUE TO A/C.	3 PH BALANCING DUE TO A/C.						
V31422	V31422 TERBINAL TELEPHONE: AN/TCC-62 LESS POWER	120 VAC, 1 FH	60 HZ, 50 HZ	4.	40.800	=	.2	2.000 1.00
	MOTE: 110 VAC.							
V31462	V31462 TERRIBAL TELEPHONE: AN/TCC-73(V)2 LESS PONER	120/208 VAC, 3 PH	80.HZ, 50 HZ	5.172	16.000		-2	2.000 1.00
	NOTE: POWER EXCLUDES 18000 BTU A/C (A28271) AUTH SEP. ASSUMES 3 PH BALANCING DUE TO A/C.	9 PH BALANCING DUE TO A/C.						
V35727	TELETYPE MAINTENANCE CENTRAL: AN/TOH-2	120/208 VAC, 3 PH	60 HZ, 50 HZ	2.400		*	<b>*</b>	2.000 1.00
	MOTE:							
V57504	V67504 TEMINAL TELEGRAPH: AN/TSC-58 LESS POWER	120 VAC, 1 PH	ZH 09	7.176	62.400	*	# 2.	2.000 1.00
	MOTE: 115 VAC.							
V58627	TEMBINAL TELEPHONE: AN/TCC-72 LESS POWER	120/208 VAC, 3 PH	60 HZ, 50 HZ	4.122	11.500	=	2.	2.000 1.00
	MOTE: 115 VAC. POWER EXCLUDES 18000 BTU A/C (A26271, 30M, 3P)	18000 BTU A/C (A26271, 3KM, 3PM). ASSUMES 3 PH BALANCING DUE TO A/C.						
V64463	VB4463 TEST SET ASPIVALT: (ARBY)	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	2.950	64.000	=	<u>-</u>	1.900 1.90
	NOTE: POWER BASED ON SINGLE LARGEST CONSUMER (HOT PLATE, 2.94 NW)							

3	NOTE THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPE	VOLTABLI PHASE	PREMENCY	<b>2</b> 1	<b>9</b> i	¥	Ĭ,	yai	<b>X</b> :I
V77628	V77628 TEST SET FLIGHT LINE: ANJALM-164	120 VAC, 1 PH	60 HZ	26.000	125.000	=	=	2.000	8.
	MOTE: 115KM.	,							
V63986	TEST SET ROOM: ALVIETH-67 FHTS (FAAR)	120/208 VAC, 3 PH; 120 VAC, 1 PH	400 HZ	30.000	128.000	>	=	2.000	0.65
	WOTE: POWER HICLIDES 2-18000 A/CS (AZASAZ) AUTHORIZED WITH THE RADAR. TEST SET HAS TWO GEN SETS: 30 KM, 400 HZ AMD 1.5 KM, 60 HZ.	HADAR. TEST SET HAS TWO GEN SETS: 30 KM, 400 HZ AND	1 1.5 KW, 60 HZ.						
VR2958	TEST SET SOIL: (ARINY)	120 VAC, 1 PH	60 HZ, 50 HZ	. 18	9.200	=	=	. 60	8.
	NOTE: POWER INCLUDES COMPINATION OF SELECTED COMPONENTS: LABOR	SELECTED COMPONENTS: LABORATORY OVEN (1 KM) AND STIRRER (.1 KM).							
V93301	VOZZO 17E5, ZET STABILIZATION EQUIPMENT: TS-1864/ASM	120 VAC, 1 PH	400 HZ	0.360	3.000	=	=	2.000	8.
	NOTE: 115 VAC. IMPUT REQUIREMENTS DO NOT INCLUDE POWER FOR EQUIPMENT UNDER TEST.	WITHERT UNDER TEST.							
V93951	VB3861 TEST SET TELEGRAPH: AN/OGH-15(V)?	120 VAC, 1 PH; 240 VAC, 1 PH	80 HZ, 50 HZ	0.105	0.875	*	=	2.000	8.
	115 OR 230 VAC. POWER INCLUDES COMBINATION ™ SELECTED COMPONENTS: TS-2862/GGH-15 (.045 KM), OS-206/GGH-15 (.030 KM), AND SG-860/GGH-15 (.030 KM), AND SG-860/GGH-15 (.030 KM).	COMPONENTS: TS-2882/GGM-16 (.045 KW), OS-206/GGM-16	(.030 KM), AND SG-860/GGH-15 (	.030					
69800M	WOODS TEST STATION: GUIDED MISSILE SYSTEM AN/TSM 83 (LCSS)	120/200 VAC, 3 PH; 120 VAC, 1 PH	400 HZ	26.300	59.600	*	=	2.000	9.0
	MOTE: FOURTH HICLORES COMBINATION OF SELECTED COMPONENTS: 2-18000 BTU A/CS (A24652) (4.8 KD EKTENNI, 3 PH), TEST EQUIPMENT (5.5 KD, 1 PH), AND EXTENNI, OUTLETS (1.2 KD, 1 PH). ASSUMES 3 PH BALANCING (TEST EQUIPMENT CONSISTS OF SEVERAL SMALLER ITEMS) DUE TO A/CS.	0000 BTU A/Cs (A24662) (4.8 KW EACH, 3 PK), TEST EQUIF Number consists of Sevenal Smaller Items) due to a/C	PAENT (5.5 KM, 1 PK), AND EXTERN 36.	N N					
MS2593	WEZSSS SHOP EQUIPMENT AUTO MAINT AND REPAIR: ON COMBON NO 1 LESS POWER	120 VAC, 1 PH	60 HZ	0.900	7.000	=	#	2.000	0.85
	NOTE: 115 WAC. POWER BASED ON SINGLE LARGEST CONSUMER (1/2" DRILL, .805 KM).	JAILL, .805 KW).							
W32730	SHOP EQUIPMENT AUTO MAINT AND REPAIR: ON COMICM NO 2 LESS POWER	120 VAC, 1 PH	60 HZ	0.500	5.760	#	*	2.000	9.0
	MOTE: 115 VAC. POWER IS BASED ON SINGLE LARGEST POWER CONSUMER (1/2 HP GRINDER, .5 KW)	ER (1/2 HP GRINDER, .5 KM).							
1955	SHOP EQUIPMENT AUTO MAINT AND REPAIR: ORG SUPPL NO 1 LESS POWER	120 VAC, 1 PH	60 HZ	0.370	3.200	=	=	2.000	9.65
	NOTE: 116 VAC. FOWER BASED ON SINGLE LARGEST CONSUMER (DISK SANDER), .6 KW).	SAIDER, .6 KP).							
<b>18</b> 7251	187251 TOOL KIT ELECTRONIC EQUIPMENT: TK-100/6	120 W.C. I PH	80 HZ	0.810	4,400	=	=	2.000	8.
	HOTTE: POWER CONSMETS: SOLDERING IRON 60W, SOLDERING GUN 150W, DRILL 120V, 3.5A.	, DRILL 120V, 3.5A.							

3	HOLESCATURE	VOLTABE/PHASE	<b>4</b>	REGIERT					WE	St.	<b>E</b> i
<b>23</b> /463	TOOL KIT ELECTRIC EQUPPENT: TK-101/659	120 VAC, 1 PH	æ	24 00		9.150	1.250	-	=	2.900	8.
	MOTE: POWER BASED ON SINGLE LARGEST CONSUMER (ELECTRIC SOLDERING GAM, .16 KM).	TING BUN, .15	. (2)								
<b>20</b> 77 <b>06</b>	TOOL KIT ELECTRONIC EQUIPMENT SHELTER: TK-144/G	120 VAC, 1 PH	æ	2¥ 26		2.300	11.500	-	-	2.000	8.
	MOTE: POWER CONSUMERS: DRILL, 116V, 3.5A; RECIPHOCATING SAW, 115V, 4A; CIRCULAR SAW 115V, 4A.	115V, 4A; CII	RCULAR SAW 115V, 4A.								
146197	TOOL KIT MEDICAL EQUIPMENT MAINTENANCE AND REPAIR: ORG MAINT	120 VAC, 1 PH	æ	<b>2</b> 4 <b>2</b> 5	60 HZ, 50 HZ	0.150	.300	=	_	2.000	8.
	NOTE: POWER BASED ON SINGLE LANGEST CONSUMER (OSCILLOSCOPE, .15 KM).	.15 (38).	•								
<b>M</b> 6534	TOOL KIT MEDICAL EQUIPMENT MAINTENANCE AND REPAIR: REPAIRMANS	120 VAC, 1 PH	æ	<b>8</b> 0 KZ.	80 HZ, 50 HZ	0.045	0.390	*	=	2.000	8.
	NOTE: POWER BASED ON SINGLE LARGEST CONSUMER (SOLDERING GUM, .15 KM).	.15 (0).									
<b>35</b> 1499	SHOP SET SHALL ARMS: FIELD MAINTENANCE BASIC LESS POWER	120 VAC, 1 PH	æ	2H 09		1.000	8.300	*	=	2.000	8.
	MOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: GRINDER (.5 KW) AND DRILL (.5 KW).	ENTS: GRIND	ER (.5 KW) AND DRILL (.5 KW).								
<b>W664</b> 72	TOOL KIT SPECIAL WEAPONS: SUPPORT DEPOT LESS POWER	120 VAC, 1	120 VAC, 1 PH; 240 VAC, 1 PH	2 2		2.100	17.500	=	=	2.000	0.85
	INTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: PORTABLE SAW (2 KM) AND LIGHTS (.1 KM).	TABLE SAW (2	KNY AND LIGHTS (.1 KN).								
<b>#58486</b>	TOOL OUTFIT PLONEER PORTABLE ELECTRIC TOOLS: ARMY	120 VAC, 1	120 VAC, 1 PH, 28 VDC	60 HZ, DC	8	1.450	10.900	=	=	2.000	9.65
	NOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: 6.6 TOOL OUTFITS CONTAINING INDUCTIVE INCTORS.	AMP, 115V HA	SELECTED COMPONENTS: 6.6 AMP, 115V HANNER (LARGEST CONSUMER) AND FLOOD LIGHT (.5 KB). PF CONSISTENT WITH OTHER IVE WOTORS.	(. <b>S</b> RB).	PF CONSISTENT WITH OTI	\$					
<b>#5958</b> 2	TOOL SET AMBUNITION: FILORD AMBO CO LESS POWER	120 VAC, 1 PH	æ	2¥ 04		1.590	13.300	-	<b>-</b>	2.000	8.
	NOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPON	ENTS: SAW (1	MATION OF SELECTED COMPONENTS: SAW (1.5 KW) AND LIGHTS (.1 KW).								
<b>W</b> 1226	TOOL SET FIELD ORDMANCE PARK COMPANY: LESS POWER	120/208 VAC, 3 PH	E	ZH 09		3.450	9.500	=	#	2.000	8.
	NOTE: POWER BASED ON SINGLE LARGEST CONSUMER (STEAM CLEAMER, 3.45 KM).	3.45 (0).									
1363	TOOL SET FIELD ORDMANCE SUPPLY OR DEPOT COMPANY: LESS POWER	120 VAC, 1 PH	æ	ZH 09		2.100	17.500	=	<u>-</u>	2.000	1.8
	NOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: SAN	(2 KW) AND L	SAW (2 KW) AND LIGHTS (.1 KW).								
119291	W82611 TOOL SET AVIATION UNIT MAINTENANCE: SET NO 1 AIRMOBILE	120 VAC, 1 PH	æ	2¥ 2\$		0.350	2.900	=	=	2.000	9.
	NOTE: POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: VACUUM SWEEPER (.26 KW) AND LIGHTS (.1 KW).	UUM SWEEPER (	.25 KW) AND LIGHTS (.1 KM).								

3	MARKILLINE YOLDER PROPERTY.	FREQUENT				WFI		<b>k</b> i
W6747	WEG747 TOOL SET VEHICLE FULL TRACKED: ONG MAINT SUPPL NO 2 LESS POWER 120 VAC, 1 PH	2H 09	7.600	13.900	*	-	2.900	9.6
	HOTE: POWER REQUIREMENT DERIVED BY AUCCOM BY ADDING ALL POWER CONSUMERS. CANDIDATE FOR POWER REDUCTION	POWER REDUCTION.						
X17831	1 TRANSHITTER SET RADIO: AN/TRT-22 (ESS POWER	60 HZ, 50 HZ	134.000	186.900	=	-	2.880	8.
	IDITE: 460 VAC.							
Y35496	B WATER PURIF EQUIP SET: TRK MTD DIATONITE FILTER 1500 GPH (ARMY) 120/208 VAC, 3 PH	96 H2	5.900	13.900	=	=	2. <b>8</b>	<b>8</b> .
	NOTE. POWER INCLUDES COMBINATION OF SELECTED CONPONENTS: 2 POWES (2 KM EACH, 3 PH), POWE (1 KM, 1 PK), AND AGITATOR (.5 KM, 1 PK). ASSUMES 3 PH BALANCING.	IP (1 KW, 1 PK), AND AGITATOR (.5 KW, 1 PK). ASSUNES A	ŧ					
147707	7 WELDING IMACHINE AND: TRANSFORMER 300 AMP AC DC ARC 240 VAC, 1 PH	24 09	18.000	<b>36</b> .000	=	-	2.000	0.62
	MOTE: AND SOUNCE-BILLER ELECTRIC, (414)734-9021.							
191975	5 X-RAY EQUIPMENT SET DENTAL FIELD:	ZH 09	0. 15v	340	=	=	2.900	8.
	MOTE: 115 VAC. POWER INCLUDES COMBINATION OF SELECTED COMPONENTS: X-RAY (.06 KM), PROCESSING MACHINE (.06 KM), AND FILM VIEWER (.014 KM).	CESSING MACHINE (.06 KM), AND FILM VIEWER (.014 KM).						
201161	201151 AIR BATTLE IMART OPS COMMIND AND CONTROL STATION: (FAAD C21) 120 VAC, 1 PH	50 HZ	3.00	2.500	=	=	2.000	8.
	MOTE: EQUIPMENT WILL REQUIRE SHELTER AND ENVIRONMENTAL CONTROL (A/C & HTR); MAYBE 10-15 KD GENERATOR FOR TOTAL SYSTEM. POWER ASSUMES A/C& EXCLUDED.	KW GENERATOR FOR TOTAL SYSTEM. POWER ASSUMES A/Co						
208328	S BAKERY PLANT: FIELD 120/208 VAC, 3 PH	60 HZ	25.200	70.000	=	=	2.000	8.
	107E; CONSISTS OF TWO ISO SHELTERS (1-60 AMP, 1-20 AMP).							
213343	13 CMITELEVER ELEVATED CAUSEBAY SYSTEM: CANTELCAS	2H 95 HZ, 80 HZ	20.000	99.99 99.99	=	=	2.000	8
	MOTE: INCLUDES FLOODLIGHT SET, WELDING MACHINE. ADD SOUNCE-LESLEY SCOTT, FAIREY MARINE, 'IMITED, (717) 397-6066	;, 'IMITED, (717)397-6066.						
215773	13 COLLECTION AND PROCESSING GROUP: 0L-279/TSG-134 120/208 VAC, 3 PH	2H 00	13.000	<b>38</b> .00	=	=	2.000	8.
	MOTE: POWER EXCLUDES 2-36000 BTV A/Ca.							
\$15849	IS SURVEILLANCE INFORMATION PROCESSING FACILITY: V-XX3/TSQ-105(V)4 120/208 VAC, 3 PH	80 HZ, 50 HZ	11.400	31.700	=	=	2.98	8.
	MOTE: POWER EXCLUDES 2-40000 8TU, 120/208 VAC, 3 PH, A/Cs. POWER DATA FROM FIELD POWER SURVEY.	1 SURVEY.						

		10/21/21							
3		WA TARE FRAME	PROPERTY		*	K	ZZ.	<b>34</b>	
718917	216017 SURVEILLANCE HIFORMATION PROCESSING FACILITY: V-XXA/TSG-106(V)4 120/206 VAC, 8 PH	120/206 VAC, 3 PH	60 HZ, 50 HZ	8.8	13.800	=	=	2.000	8
	NOTE: POWER EXCLUSES 2-60000 BTU, 120/200 VAC, 3 PH A/CA. FOWER DATA FROM FIELD FOWER SURVEY.	DUER DATA FROM FIELD FOWER SURVEY.							
219830	COMMUNDERS TACTICAL TERMINAL (CTT): AN/TSC-XXX	120 VAC, 1 PH; 240 VAC, 1 PH, 28 VDC	90 HZ, 50 HZ, DC		8.30	=	=	2.000	<u>.</u>
	MITE: 120 OR 220 VAC.								
216333	COMMUNICATION CENTRAL: AN/TSCAO(V)?	120/208 VAC, 3 PH	60 HZ, 50 HZ, 400 HZ	8.	22.200	=	*	2.000	8
	<b>WITE</b> :								
21810	Z18109 TC3 CENTRAL PROCESSOR: AN/TYG-30V)2	120/208 VAC, 3 R.1	80 HZ, 50 HZ	36.00	83.468	=	=	2.000	8
	HOTE: POWER INCLUDES A/Ca.					•			
22022	220726 DATA ABALYSIS CENTRAL (DAC): AN/TSO-KKK	120/208 VAC, 3 PH; 120 VAC, 1 PH	80 HZ, 50 HZ	9.500	15.400	*	~	2.800	8
	NOTE: POWER EXCLUDES 2-18000 BTV A/Ca.								
221096	221006 DECEPTION SYSTEM: CRITICAL NODE MECHANIZED	120 VAC, 1 PH	ZH 09	3.000	25.000	*	~ æ	2.900	8
	MOTE: POWER COULD PANCE FINA 1 KM TO 3 KM.								
221164	DECEPTION SYSTEM: LOGISTICAL BASE (OSLB)	120 VAC, 1 PH	60 HZ	3.80	25.000	=	*	2.000	8
	MOTE: POWER COULD PANCE FROM 1 KM TO 3 KM.								
225240	ELECTRONIC EQUIPMENT TEST FACILITY: 00-290 (V) 2/NEW	120/208 VAC, 3 PH	60 HZ, 50 HZ	9.000	41.700	=	*	2.000	8
	MOTE: POWER EXCLUDES 2-18000 BTU A/Ca.								
225526	CENTINAL PROCESSOR GROUP (CTASC): 01-332/MYG-5	120/208 VAC, 3 PH; 240/416 VAC; 3 PH	60 HZ, 50 HZ	34.410	<b>92</b> . <b>80</b> 0	=	~	2.000	8
	MOTE: POWER EXCLUDES 2-40000 BTV A/C& (A2500). COMPONENT OF	A/Ca (A25860). COMPONENT OF 236206, 1TASC. ASSUME 3 PH BALANCING. ADD SOUNCE-PH CTASC, (703)664-1881.	W CTASC, (703)664-1881.						
226048	228048 ELECTRONIC SWOP SWELTER MOUNTED: AM/MSM-108	120/208 VAC, 3 PM	90 HZ	1.50	31.900	=	**	2.000	8.
	MATERIAL STREET HET HAT TON OF SELECTED CHARACTER. COM	COMMENT (ME I WE I WE I WE I WE I WE I WE I WE I	TO CAME THE TANK OFFEE TO SHE SHE	9					

POWER INCLIDES COMBINATION OF SELECTED CONFONENTS: COMPRESSOR (8 KM; 3 PH), VACUAR CLEARER (1536 KM; 1 PH), LIGHTS (165 KM; 1 PH), AND POWER RECEPTACLES (12.3 KM; 1 PH). ASSUKES 3 PH BALANCING. ä

			12/12/61							
3	MUNICIPALINE		VALTARE/THANK	Person.		<b>2</b>		WEI E		<b>X</b> I
228128		FLIGHT LINE TEST SET: AN/ARM-163(V)4	120/208 VAC, 3 PH	60 HZ	12.500	24.78	=	7	2.000	8.
		1788 CONTAINS BIOSTLY COMBENCIAL EQUIPMENT SUCH AS COMPUTENS, PLOTTENS AND PRINTERS. POWER INCLUDES 24000 BTV A/C, 120 VAC, 1 PH. ASSUMES 3 PH. BALANCING DNE TO S1ZE OF TOTAL REQUIRENCIN.	IS, PLOTTERS AND PRINTERS. POWER INCLUDES 24000 BTU	A/C, 120 VAC, 1 PH. ASSUMES 3	£					
232106		SURVEILLANCE INFORMATION PROCESSING FACILITY: V-XX1/TSG-105(V)5 120/200 VAC, 3 PH		80 MZ, 50 MZ	2.900	8.18	=	.;	2.980	8.
	E E	POWER EXCLUDES 2-60000 BTV A/Cs., 120/206 VAC, 3 PH, 50/60 ASSURES 3 PH BALANCING DUE TO A/Cs.	JUCA, 120/208 VAC, 3 PH, 50/80 NZ. CECON NEP RECOMBINS USE OF SAME PONEN DATA AS LIN 277087, V-XXI/TSG-106 (V) 4. To A/Ca.	LIN 277007, V-XX1/750-106 (V)	ų.					
232118	SUPPEIL	SURVEILLANCE INFORMATION PROCESSING FACILITY: V-XXZ/TSG-106(V)5	120/206 VAC, 3 PH	80 MZ, 50 MZ	7.100	19.700	-		2.000	8
	ä	POWER EXCLUDES 2-40000 BTV A/Cs., 12/206 VAC, 3 PH, 50/40 I ASSINES 3 PH BALANCING DUE TO A/Cs.	UCS, 12/206 VAC, 3 PH, 56/40 HZ. · CECCH NEP NECCHNIENCS USE OF SAME PONEN DATA AS LIN 277106 V-XX2/TS0-105(V)4. 10 A/Cs.	.IR 277186 V-XX2/TSQ-105(V)4.						
232119	SURVEIL	232119 SURVEILLANCE INFORMATION PROCESSING FACILITY: V-XXA/15G-106(V)5 120/208 VAC, 3 PH	-	80 KZ, 50 KZ	9.000	13.900	=		2.000	8.
		POWER EXCLUDES 2-60000 87U / ASSUMES 3 PH BALANCING DUE 1	L/Cs. 120/208 VAC, 3 PH, 50/10 NZ. CECOM REP RECOMBINGS USE OF SAME POWER DATA AS LIN 215917, V-XXA/TSS-106(V)4. To A/Cs.	LIN 215817, V-XXA/TSQ-106(V)4.						
232120		SURVEILLANCE INFORMATION PROCESSING FACILITY: V-XX3/TSG-106(V)5 120/206 VAC, 3 PH		80 NZ, S0 NZ	11.400	31.700	*		2.888	8.
		POWER EXCLUSES 2-80000 BTV AVCA., 120/208 VAC, 3 PH, 50/80 ASSUMES 3 PH BALANCING DUE TO AVCA.	JUCE, 120/208 VAC, 3 PH, 50/80 MZ. CECOM REP RECOMMENDS USE OF SAME PONER DATA AS LIN 215848, V-XX3/TSG-106(V)A. To AJCs.	LIN 215848, V-XX3/TSG-105(V)4.						
23568		COMMUNICATIONS TERMINAL: AN/TRC-179(V)1	120/208 VAC, 3 PH; 240 VAC, 1 PH	80 HZ	14.400	40.900	=	~;	2.906	8.
		POWER EXCLUDES 2-18000 87V A/Ca.								
234088		HIGH FREQUENCY COMMUNICATION CENTRAL: AN/TSC-118	120/208 VAC, 3 PH	60 HZ	31.800	300	=	.2	2.000	8.
	Ë	POWER EXCLUDES 1-30000 BTU A/C. ASSUMES 3 PH BALANCING DUE TO A/C.	UE TO A/C.							
236206		HITCHIN THEATER ADPE SERVICE CENTER (17ASC):	120/208 VAC, 3 PH; 240/416 VAC, 3 PH	60 HZ, 50 HZ	77.200	214.000	-	-2	2.986	8.
		POWER EXCLUSES 6-80000 BTV A/Ca AUTH SEP. POWER HICLUDES A/Ca. Add Sounce-Jim Bloom, PH CTASC, (705)644-1661.	POWER HUCLUDES WARIETY OF ADP COMPONENTS (236206, 225626, 242837). ASSUMES 3 PH BALANCHIG DUE TO 31864-1881.	ASSURES 2 PI BALANCING DUE TO						
236208		INTEROPENALE DATA LINK (IDL) TRACKING ANTENDA; ANVUNG-38	120/208 VAC, 3 PH	ZH 98	9.0	31.30	-	-i	2.000	8.0

		12/12/91							
3		VO.TARE/PROFE	<b>HERIOC</b>		*		X/E	<b>W</b>	
238288	LIBRARY BROUP SENI (CTASC): 0A-9160/NYG-5	120 W.C., 1 PH; 240 W.C., 1 PH	60 HZ, 50 HZ	2.800	10.00	-	=	2.880	8
	WITE: FOWER EXCLIDES 2-40000 BTV AVGA (AZSABA). COMPONENT OF 256206, CTASC.	3F 286206, CTASC.							
240002	UNINTERNICE FACILITY WAS INDUSTED: ANJOSH-271A	120/208 W.C. 3 PH	80 HZ	16.900	47.500	=	=	2.00	8
	NOTE: FORER INCLUDES CORBINATION OF SELECTED COMPONENTS: 2 To stant an aimplane, 600A).	SELECTED CHIPOMENTS: 2-18080 BTV A/Cs, ELECTRONIC EQUIPMENT, LARGE AIR CHIPPESSOR, AND LARGE POWER SUPPLY (ENDUGH	SSOR, AND LANGE POWER SUPPLY (E	MONE					
241346	INLINTENANCE FACILITY WAN INDUNTED: AN/659-2710	120/206 VAC, 3 PH	3 3	16.900	2.50	*	=	2.8	8.
	NOTE: POWER INCLUDES COMMINATION OF SELECTED CONTOURNES: 2 Assures 3 PH DALARCING.	SELECTED COMPONENTS: 2-18000 BTV A/Ca, ELECTRONIC EQUIPMENT, AIR COMPRESSOR, AND LANGE FOURN SUPPLY (500 AMPS).	WD LANGE FOIER SUPPLY (500 AMP	<u>.</u>					
241406	IN INTERNICE SHOP SENTINALLER NOUNTED: ANJARN-185A	120 WC, 1 PH	24 8	3.000	28.000	=	=	2.000	8.
	MOTE: POWER EXCLUDES A/Cs. POWER HICLUDES TEST EQUIPMENT AND LIGHTS.	O LIGHTS.							
241556	MAINTENANCE SHOP SEMITMAILER MOUNTED: AM/ANN-1868	120/206 VAC, 3 PH	<b>50 HZ</b>	98. 98.	13.900	=	=	2.000	8
	HOTE: FOWER EXCLUDES 2 A/C+ WHICH REQUIRE 14 KM.								
241585	MAINTENANCE 690UP SEMI (CTASC): 0A-9107/MYG-5	120/208 VAC, 3 PN; 240/416 VAC, 3 PH	60 HZ, 50 HZ	9.0	22.400	=	_	2.000	8.1
	MOTE: ASSIMES 3 PH BALANCING.								
242943	MICROTOME-CHYOSTAT:	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	1.20	10.000	=	-	2.000	8
	NOTE:								
243422	243422 MIS OPHTMALMOLOGICAL SUNG SPECIAL AUGMENTATION:	120 VAC, 1 PH; 240 VAC, 1 PH	60 HZ, 50 HZ	2.100	17.500	=	=	2.000	8.
	WOTE:								
243432	MAIS VITREOUS SURG SPECIAL ANG:	120 VAC, 1 PN; 240 VAC, 1 PH	80 HZ, 50 HZ	4.200	36.900	*	**	2.000	8.
	MOTE:								
243439	NAS PADIOLOGY COMPUTERIZED TOMOGRAPHY SPEC AUGMENTATION:	120/206 VAC, 3 PH; 240/416 VAC, 3 PH	60 KZ, 50 KZ	25.900	72.000	**	-	2.000	8.
	WOTE:								

FOUEN COMMUNER DATABASE (Partiel Data) 12/12/81

=	MARIE VANCE	VA.TAKE PHANE	FREEERICY		¥		KE		¥۱
747637	INS ANGIOGRAPHY SPEC AUGNERT:	120/208 VAC, 3 PH; 240/416 VAC, 3 PH	60 HZ, 50 HZ	16.600	98.000	=	2	2.800	8.
	MOTE								
743854	249824 MOBILE RELAY FACILITY: OA-9171A/TSG-144	240 VAC, 1 PH	SH 88	89.	18.200	=	-	1.256	8
	MOTE: 220 VAC.								
147327	247327 OPERATING AND THEATHERT UNIT DENTAL FIELD;	120 VAC, 1 PH; 240 VAC, 1,PH	60 HZ, 50 HZ	1.46	12.000	=	7	2.000	8
	MOTE								
248645	GROUND PROCESSOR INTERFACE: 01-336/159-144	120 VAC, 1 PH	<b>2</b> 4 <b>03</b>	89.	40.000	=	7	2.000	8.
	MOTE: 110 VAC.								
762937	BASS STORAGE GROUP (CTASC):	120/208 UAC, 3 PH; 240/416 VAC, 3 PH	80 1/2, 50 1/2	31.800	132.000	=	7	2.000	8
	INTE: POWER EXCLUDES 2-60000 BTV A/Ca (A25000). COMPONENT OF	A/Cs. (A25860). CONFONENT OF 235205, CTASC. ASSIMES 3 PR BALABCHIS DUE TO A/Cs.							
273906	SINGLE CHANNEL OBJECTIVE TACTICLE TENNINAL (SCOTT):	120 UMC, 1 PM; 248 UMC, 1 PM, 28 UDC	80 NZ, 50 NZ, 400 NZ, DC	2.800	27.000	=	2	2.000	8
	HOTE: 115 OR 230 VAC. 45-440KZ. INDURTED IN S-250 SKELTER.								
276007	PRESS SECTION: (MPS)	120/208 VAC, 8 PH	\$ \$2	70.800	207.000	*	-	1.060	8.
	HOTE: POWER INCLUDES COMERCIAL A/CA FOR THE FIVE MODULES OF THE SECTION. ADD SCHACE-LOWN DAMPHERTY, SAIC, FOWER SAMPEY OF MPS, (785) 221-4347.	E SECTION. ADD SOUNCE-JOHN DAUGHENTY, SAIC, FORER SA	MEY OF MPS, (765) 621-4347.						
181912	SURV TANGET ATTACK RADAR SUBSYSTEM (JOINT STANS): AN/TSG-132	120/208 VAC, 3 PH	80 KZ, 50 KZ	25.200	70.300	*	2	2.000	8
	HOTE: POWER EXCLUDES 18000 8TV A/C. ASSUMES 3 PH BALANCING DUE TO A/C.	E 10 A/C.							
270772	TACTICAL CIED CONTROL AND COMB CENTRAL PROCESSOR: AI/TYG-30(V)1	120/208 VAC, 3 PH	60 HZ, 50 HZ	30.000	63.400	=	1 2	2.900	8.
	HOTE: FOWER INCLUDES A/C.								
\$20172	277024 TACTICAL CHID CONTROL AND COMM WODAL PROCESSOR: AN/TYG-51()	120/206 VAC, 3 PH	60 HZ, 50 HZ	30.000	83.400	=	2	2.000	8
	HOTE: POWER HICLUDES A/C.								
277025	277025 TACTICAL COMPUTER PROCESSOR: AN/UYG-43	120 VAC, 1 PH; 240 VAC, 1 PH, 28 VDC	60 HZ, 50 HZ, 400 HZ, DC	0.600	5.500	=	2	2.300	8
	MOTE: BUIS OF MICANS WEN VEHICLE SUTS DOWN OF NO TAC PORER I	FISHER DOWN OF HE POWER IS ANALLABLE. CAN DEPARTE ON ALL MARIETIES OF TACTICAL POWER. THE ANALLABLES IS A	POWER THE ANYIND-42 IS A						

RUNS ON NICADS WHEN VEHICLE SUTS DOWN OR NO TAC POWER IS AVAILABLE. CAN OPERATE ON ALL WANTETIES OF TACTICAL POWER. THE NALVYO-43 IS A COMMENCIAL SURGATE FOR THE TOT ANLYYO SO & SOA (TOT"-GREATER STORAGE THAN TOT) (27)7028). ADD SOUNCE-SAL LAFORTIA, PW OPTADS, (20)1532-2048. IOLE:

A-39

3	MARKELATURE	VOLTAGE/PHASE	REMERCY	함			THE VIE	161	
217087	SURVEILLANCE INFORMATION PROCESSING	FACILITY: V-XXI/TSQ-105(V)4 120/208 VAC, 3 PH	90 HZ, 50 HZ	2.900	 8	=	=	2.000	8.
	NOTE: POWER EXCLUDES 2-80000 BTU A/Cs., 121	N/Ca, 120/208 VAC, 3 PH. POWER DATA FROM FIELD SURVEY. ASSUMES 3 PH BALANCING DUE TO A/Cs.	EY. ASSUMES 3 PH BALANCING DUE TO A/Cs.						
991772	SURVEILLANCE INFORMATION PROCESSING	FACILITY: V-XX2/TSQ-105(V)4 120/208 VAC, 3 PH	60 HZ, 50 HZ	7.100	19.700	=	=	2.000 1.00	8.
	HOTE: POWER EXCLUDES 2-60000 BTV A/Ca, 120	N/Ca, 120/208 VAC, 3 PH. POWER DATA FROM FIELD SURVEY. ASSUMES 3 PH BALANCING DUE TO A/Ca.	EY. ASSUMES 3 PH BALANCING DUE TO A/Cs.						
280487	280487 TERBINAL GROUP TACTICAL USER ENAMICED: DW-108/150-134	1/150-134 120/208 VAC, 3 PH	60 HZ, 50 MZ	48.800	48.800 136.080 N N 2.800 1.00	*	**	8	8.
	HOTE: POWER EXCLUDES 2-46500 BTU AVCA. AS	LICA. ASSUMES 3 PH BALANCING DUE TO A/CA.							
280737	TERMINAL GROUP TACTICAL USER: 08-95/TSG-134	120/208 VAC, 3 PH	50 HZ	11.300	11.300 31.400 N N 2.600 1.00	#	-	8	8.
	HOTE: POWER EXCLUDES 2-46500 BTV A/Cs. AS	VCs. ASSUMES 3 PH BALANCING DUE TO AVCs.	_						
281740	281740 TEST FACILITY BASE SHOP: (BSTF)	120/208 VAC, 3 PH	80 HZ, 50 HZ	6.000	16.700 N N 2.000	=	=	8	8.

MOTE: POWER EXCLUDES 38000 BTU A/C. ASSUMES 3 PH BALANCING DUE TO A/C. ITEM ALSO BEING DEVELOPED IN 400 HZ VERSION.

# NOTES:

- 1. Values listed for KW (fifth column) and AMP (sixth column) are inaccurate in many instances.
- 2. Information shown in PRE (seventh column), V/FI (eighth column), SF (ninth column), and PF (last column) are default values which may be inaccurate.

# **DISTRIBUTION FOR REPORT NO. 2518**

### DEPARTMENT OF DEFENSE

- Director, Technical Information
   Defense Advanced Research Projects Agency
   1400 Wilson Blvd.
   Arlington, VA 22209
- Director
   Defense Nuclear Agency
   ATTN: TTTL
   Washington, DC 20305
- Defense Technical Information Center Cameron Station
   ATTN: DTIC-FDAC
   Alexandria, VA 22304-6145
- 3 DOD Project Manager Mobile Electric Power 7500 Backlick Road Springfield, VA 22150

# DEPARTMENT OF THE ARMY

- 1 HQDA (DAMA-AOA-M) Washington, DC 20310
- 1 HQDA (DALO-TSM) Washington, DC 20310
- 1 HQDA (DAEN-RDL) Washington, DC 20314
- 1 HQDA (DAEN-MPE-T) Washington, DC 20314
- Commander
   US Army Missile Research and Development Command
   ATTN: AMSMI-PR
   Redstone Arsenal, AL 35809
- Director
   Army Materials and Mechanics Research
   Command
   ATTN: AMXMR-RL (Technical Library)
   Watertown, MA 02172-0001

- Commander
   Chemical Research R&D Center
   ATTN: SMCCR-SPS (Technical Library)
   Aberdeen Proving Ground, MD 21005
- Commander
   US Army Aberdeen Proving Ground
   ATTN: STEAP-MT-U (GE Branch)
- Director
   US Army Materiel System Analysis Agency
   ATTN: AMXSY-MP
   Aberdeen Proving Ground, MD 21005-5071
- Director
   US Ballistics Research Laboratory
   ATTN: AMXBR-OD-ST (STINFO)
   Aberdeen Proving Ground, MD 21005-5066
- Commander
   US Army Armament Research and
   Development Command
   ATTN: SMCAR-TSS
   Dover, NJ 07801-5001
- Commander
   US Army Troop Support and Aviation Materiel
   Readiness Command
   4300 Goodfellow Blvd.
   St. Louis, MO 63120
- 1 US Army Tank Automotive Command ATTN: DRSTA-TSL Warren, MI 48090

US Army Laboratory Command

ATTN: SLCMT-MN

Materials Technology Laboratory
Watertown, MA 02172-0001

#### 1 Commander

US Army Electronics Research and Development Command ATTN: DELSD-L

Fort Monmouth, NJ 07703-5301

#### 1 President

US Army Aviation Test Board

ATTN: STEBG-PO Fort Rucker, AL 36360

# 1 US Army Aviation School Library

PO Drawer O

Fort Rucker, AL 36360

#### 1 Commander

Rock Island Arsenal ATTN: SARRI-LPL

Rock Island, IL 61299-7300

# 1 HQDA

**ODCSLOG** 

**DALO-TSE** 

Room 1E588, Pentagon

Washington, DC 20310-0561

#### 1 Commandant

US Army Engineer School

ATZA-CDD

Fort Leonardwood, MO 65473

### 1 US Army AMCCOM

ATTN: Joseph Menke

1032 N. Thornwood

Davenport, IA 52804

### 1 Commander

Headquarters, 39th Engineer Bn (Cbt)

Fort Devens, MA 01433

#### 1 President

US Army Airborne, Communications, and

Electronics

ATTN: STEBF-ABTD

Fort Bragg, NC 28307

# 1 President

US Army Armor and Engineer Board

ATTN: ATZK-AE-PD-E Fort Knox, KY 40121-5470

## 1 Director

ATTN: STSTO-TPP Tobyhanna Army Depot Tobyhanna, PA 18466-5097 1 Commander and Director

**USA FESA** 

ATTN: FESA-TS

Fort Belvoir, VA 22060

# 1 HQ, USAEUR & Seventh Army

Deputy Chief of Staff, Engineer

ATTN: AEAEN-MT-P

APO New York 09403

# 1 Director

**US Army TRADOC** 

Systems Analysis Activity

ATTN: ATAA-SL (Technical Library)

White Sands Missile Range, NM 88002

#### Director

US Army LABCOM/Ballistic Research Lab

- 12 ATTN: SLCBR-IB-B
- 10 Charles Leveritt
- 1 Jody Wojciechowski
- 1 Madeline M. Decker

Aberdeen Proving Ground, MD 21005-5066

## Product Manager, PEO, Air Defense

- 1 ATTN: SFAE-AD-GSL
- 1 ATTN: SFAE-AD-LU
- 1 ATTN: SFAE-AD-FM
- 1 ATTN: SFAE-AD-PA
- 1 ATTN: SFAE-AD-AUG
- 1 ATTN: SFAE-CC-AD

Redstone Arsenal, AL 35898-5796

# Project Manager, PEO, Armored Systems Modernization

1 ATTN: SFAE-ASM-BV

1 ATTN: SFAE-ASM-CV

1 ATTN: SFAE-ASM-SS

Warren, MI 48397-5000

# Project Manager, PEO, Command Control

Systems

- 1 ATTN: SFAE-CC-CHS
- 1 ATTN: SFAE-CC-FS
- 1 ATTN: SFAE-CC-MVR

Fort Monmouth, NJ 07703-5000

#### Project Manager, PEO, Communication Systems

- 1 ATTN: SFAE-CM-ADD
- 1 ATTN: SFAE-CM-EP
- 1 ATTN: SFAE-CM-MSE
- 1 ATTN: SFAE-CM-MSC
- 1 ATTN: SFAE-CM-SC

Fort Monmouth, NJ 07703-5000

Project Manager, PEO, Intelligence and Electronic Warfare

1 ATTN: SFAE-IEU-EU

1 ATTN: SFAE-IEU-JS

1 ATTN: SFAE-IEU-RD

Fort Monmouth, NJ 07703-5000

Project Manager, PEO, Intelligence and Electronic Warfare

1 ATTN: SFAE-IEU-SG Vint Hill Farms Station Warrenton, VA 22186-5116

Commander, Ordnance Center & School

ATTN: ATSL-CD
Aberdeen Proving Ground, MD 21005-5201

1 HQDA, FARD-TT Washington, DC 20310-0103

# BELVOIR RD&E CENTER

#### Circulate

- 1 Commander STRBE-Z
  Deputy Commander STRBE-ZD
  Technical Director STRBE-ZT
  Assoc Tech Dir (E&A) STRBE-ZTE
  Assoc Tech Dir (R&D) STRBE-ZTR
  Executive Officer STRBE-ZX
  Sergeant Major STRBE-ZM
  Advanced Systems Concept Dir STRBE-H
  Program Planning Div STRBE-HP
  Foreign Intelligence Div STRBE-HF
  Systems and Concepts Div STRBE-HC
- 5 STRBE-F
- 25 STRPE FEA
- 3 Tech Reports Ofc ASQNK-BVP-G
- 3 Security Ofc (for liaison officers) STRBE-S
- 2 Technical Library STRBE-BT
- 1 Public Affairs Ofc STRBE-I
- 1 Ofc of Chief Counsel STRBE-L

## DEPARTMENT OF THE NAVY

- Library (Code L08A)
   Civil Engineering Laboratory
   Naval Construction Battalion Center
   Port Hueneme, CA 93043
- Naval Training Equipment Center ATTN: Technical Library Orlando, FL 32813

# DEPARTMENT OF THE AIR FORCE

- HQ USAF/RDPT ATTN: Commander Washington, DC 20330
- 1 HQ USAF/PREEU Chief, Utilities Branch Washington, DC 20330
- HQ Air Force Engineering & Services Center Technical Library FL7050
   Tyndall AFB, FL 32403
- US Air Force
   Warner Robins Air Logistics Center
   WR-ALC/MMEM
   Warner-Robins AFB, GA 31098
- Chief, Lubricants Branch
  Fuels and Lubrications Division
  ATTN: AFWAL/POSL
  Wright-Patterson AFB, OH 45433
- HQ Air Force Civil Engineering Support AGency, RAAE ATTN: C. Calobrisi Tyndall AFB, FL 32403-6001